

Where Every Slice is a Taste of Perfection

WELCOME TO PIZZA RESTO

Start Your Slide

ORDER
NOW



HELLO !

My Name is Aniket Sanjay Mistry



In this project i have used SQL queries to solve questions related to pizza sales

QUERIES TO BE SOLVED IN THIS PROJECT ...



1. Retrieve the total number of orders placed.
2. Calculate the total revenue generated from pizza sales.
3. Identify the highest-priced pizza.
4. Identify the most common pizza size ordered.
5. List the top 5 most ordered pizza types along with their quantities.

Intermediate:

6. Join the necessary tables to find the total quantity of each pizza category ordered.
7. Determine the distribution of orders by hour of the day.
8. Join relevant tables to find the category-wise distribution of pizzas.
9. Group the orders by date and calculate the average number of pizzas ordered per day.
10. Determine the top 3 most ordered pizza types based on revenue.

Advanced:

11. Calculate the percentage contribution of each pizza type to total revenue.
12. Analyze the cumulative revenue generated over time.
13. Determine the top 3 most ordered pizza types based on revenue for each pizza category.

RETRIEVE THE TOTAL NUMBER OF ORDERS PLACED.



```
SELECT  
    COUNT(order_id) AS total_orders  
FROM  
    orders;
```

OUTPUT :

Result Grid	
	total_orders
▶	21350

CALCULATE THE TOTAL REVENUE GENERATED FROM PIZZA SALES



SELECT

ROUND(SUM(order_details.quantity * pizzas.price),
2) **AS** Total_Sales

FROM

order_details

JOIN

pizzas **ON** pizzas.pizza_id = order_details.pizza_id

OUTPUT :



Result Grid	
	Total_Sales
▶	817860.05

IDENTIFY THE HIGHEST-PRICED PIZZA.



```
SELECT
    pizza_types.name, pizzas.price
FROM
    pizza_types
    JOIN
        pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
ORDER BY pizzas.price DESC
LIMIT 1;
```

OUTPUT :

Result Grid				 Filter Rows
	name	price		
▶	The Greek Pizza	35.95		

IDENTIFY THE MOST COMMON PIZZA SIZE ORDERED.



```
SELECT
    pizzas.size,
    COUNT(order_details.order_details_id) AS order_count
FROM
    pizzas
    JOIN
    order_details ON pizzas.pizza_id = order_details.pizza_id
GROUP BY pizzas.size
ORDER BY order_count DESC;
```

OUTPUT :

Result Grid			Filter
	size	order_count	
▶	L	18526	
	M	15385	
	S	14137	
	XL	544	
	XXL	28	

LIST THE TOP 5 MOST ORDERED PIZZA TYPES ALONG WITH THEIR QUANTITIES.

```
SELECT
    pizza_types.name, SUM(order_details.quantity) AS quantity
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY quantity DESC
LIMIT 5;
```

OUTPUT :

Result Grid			Filter Rows:
	name	quantity	
▶	The Classic Deluxe Pizza	2453	
	The Barbecue Chicken Pizza	2432	
	The Hawaiian Pizza	2422	
	The Pepperoni Pizza	2418	
	The Thai Chicken Pizza	2371	

JOIN THE NECESSARY TABLES TO FIND THE TOTAL QUANTITY OF EACH PIZZA CATEGORY ORDERED.



```
SELECT
    pizza_types.category,
    SUM(order_details.quantity) AS quantity
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY quantity DESC;
```

OUTPUT :

Result Grid			Filter
	category	quantity	
▶	Classic	14888	
	Supreme	11987	
	Veggie	11649	
	Chicken	11050	

DETERMINE THE DISTRIBUTION OF ORDERS BY HOUR OF THE DAY.

```
SELECT
    HOUR(order_time) AS hour, COUNT(order_id) AS order_count
FROM
    orders
GROUP BY HOUR(order_time);
```

OUTPUT :

Result Grid					File
	hour	order_count			
▶	11	1231			
	12	2520			
	13	2455			
	14	1472			
	15	1468			
	16	1920			
	17	2336			
	18	2399			
	19	2009			
	20	1642			
	21	1198			
	22	663			
	23	28			
	10	8			
	9	1			

JOIN RELEVANT TABLES TO FIND THE CATEGORY-WISE DISTRIBUTION OF PIZZAS.

```
SELECT
    category, COUNT(name)
FROM
    pizza_types
GROUP BY category;
```

OUTPUT :

Result Grid			Filter Rows
	category	COUNT(name)	
▶	Chicken	6	
	Classic	8	
	Supreme	9	
	Veggie	9	

GROUP THE ORDERS BY DATE AND CALCULATE THE AVERAGE NUMBER OF PIZZAS ORDERED PER DAY.

```
SELECT
    ROUND(AVG(quantity), 0) as avg_pizzas_ordered_per_day
FROM
    (SELECT
        orders.order_date, SUM(order_details.quantity) AS quantity
    FROM
        orders
    JOIN order_details ON orders.order_id = order_details.order_id
    GROUP BY orders.order_date) AS ordered_quantity;
```

OUTPUT :

Result Grid		Filter Rows:
	avg_pizzas_ordered_per_day	
▶	138	

DETERMINE THE TOP 3 MOST ORDERED PIZZA TYPES BASED ON REVENUE.

```
SELECT
    pizza_types.name,
    SUM(order_details.quantity * pizzas.price) AS revenue
FROM
    pizza_types
    JOIN
    pizzas ON pizzas.pizza_type_id = pizza_types.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY revenue DESC
LIMIT 3;
```

OUTPUT :

Result Grid			Filter Rows:
	name	revenue	
▶	The Thai Chicken Pizza	43434.25	
	The Barbecue Chicken Pizza	42768	
	The California Chicken Pizza	41409.5	

CALCULATE THE PERCENTAGE CONTRIBUTION OF EACH PIZZA TYPE TO TOTAL REVENUE.

```
SELECT
    pizza_types.category,
    ROUND((SUM(order_details.quantity * pizzas.price) / (SELECT
        SUM(order_details.quantity * pizzas.price)
        FROM
            order_details
            JOIN
                pizzas ON pizzas.pizza_id = order_details.pizza_id) * 100),
        2) AS revenue
FROM
    pizza_types
    JOIN
        pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
        order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY revenue DESC;
```

OUTPUT :

	category	revenue
▶	Classic	26.91
	Supreme	25.46
	Chicken	23.96
	Veggie	23.68

ANALYZE THE CUMULATIVE REVENUE GENERATED OVER TIME.



```
select order_date,  
sum(revenue) over(order by order_date) as cum_revenue  
from  
(select orders.order_date,  
sum(order_details.quantity*pizzas.price) as revenue  
from order_details join pizzas  
on order_details.pizza_id=pizzas.pizza_id  
join orders  
on orders.order_id=order_details.order_id  
group by orders.order_date) as sales;
```

OUTPUT :

Result Grid			Filter Rows:
	order_date	cum_revenue	
▶	2015-01-01	2713.8500000000004	
	2015-01-02	5445.75	
	2015-01-03	8108.15	
	2015-01-04	9863.6	
	2015-01-05	11929.55	
	2015-01-06	14358.5	
	2015-01-07	16560.7	
	2015-01-08	19399.05	
	2015-01-09	21526.4	
	2015-01-10	23990.350000000002	
	2015-01-11	25862.65	
	2015-01-12	27781.7	
	2015-01-13	29831.300000000003	
	2015-01-14	32358.700000000004	
	2015-01-15	34343.50000000001	



Pizza Resto Presentation

THANK YOU
FOR ATTENTION

See You Next

www.reallygreatsite.com