Assignment 1

MySQL 8.0 Command Line Cli

```
mysql> show databases;
+--------------------+
| Database           |
+--------------------+
| cdac_lecture       |
| classroom          |
| codingwallah       |
| college            |
| databaseforjdbc2   |
| db                 |
| information_schema |
| jdbc_demo          |
| my_db              |
| my_db2             |
| my_db22            |
| mydatabase         |
| mysql              |
| performance_schema |
| sakila             |
| student            |
| student_db         |
| sys                |
| temp2              |
| testdb             |
| world              |
| xyz                |
+--------------------+
22 rows in set (0.04 sec)

mysql> create database cdac_kharghar
    -> ;
Query OK, 1 row affected (0.01 sec)

mysql> USE cdac_kharghar;
Database changed
mysql> CREATE TABLE a1_salespeople(
    ->     snum INT,
    ->     sname VARCHAR(10),
    ->     city VARCHAR(10),
    ->     comm FLOAT(3,2)
    -> );
```

MySQL 8.0 Command Line Cli

```
mysql> CREATE TABLE a1_customers(
    ->     cnum INT,
    ->     cname VARCHAR(10),
    ->     city VARCHAR(10),
    ->     rating INT,
    ->     snum INT
    -> );
Query OK, 0 rows affected (0.06 sec)

mysql> CREATE TABLE a1_orders(
    ->     onum INT,
    ->     amt FLOAT(7,2),
    ->     odate DATE,
    ->     cnum INT,
    ->     snum INT
    -> );
Query OK, 0 rows affected, 1 warning (0.06 sec)

mysql> INSERT INTO a1_salespeople VALUES
    -> (1001,'Peel','London',0.12),
    -> (1002,'Serres','San Jose',0.13),
    -> (1004,'Motika','London',0.11),
    -> (1007,'Rifkin','Barcelona',0.15),
    -> (1003,'Axelrod','New York',0.10)
    -> ;
Query OK, 5 rows affected (0.07 sec)
Records: 5  Duplicates: 0  Warnings: 0

mysql> select * from a1_salespeople
    -> ;
+------+---------+-----------+------+
| snum | sname   | city      | comm |
+------+---------+-----------+------+
| 1001 | Peel    | London    | 0.12 |
| 1002 | Serres  | San Jose  | 0.13 |
| 1004 | Motika  | London    | 0.11 |
| 1007 | Rifkin  | Barcelona | 0.15 |
| 1003 | Axelrod | New York  | 0.10 |
+------+---------+-----------+------+
5 rows in set (0.02 sec)
```

MySQL 8.0 Command Line Cli

```
mysql> INSERT INTO a1_customers VALUES
    -> (2001,'Hoffman','London',100,1001),
    -> (2002,'Giovanni','Rome',200,1003),
    -> (2003,'Liu','San Jose',200,1002),
    -> (2004,'Grass','Berlin',300,1002),
    -> (2006,'Clemens','London',100,1001),
    -> (2008,'Cisneros','San Jose',300,1007),
    -> (2007,'Pereira','Rome',100,1004);
Query OK, 7 rows affected (0.04 sec)
Records: 7  Duplicates: 0  Warnings: 0

mysql> INSERT INTO a1_orders VALUES
    -> (3001,18.69,'1990-10-03',2008,1007),
    -> (3003,767.19,'1990-10-03',2001,1001),
    -> (3002,1900.10,'1990-10-03',2007,1004),
    -> (3005,5160.45,'1990-10-03',2003,1002),
    -> (3006,1098.16,'1990-10-03',2008,1007),
    -> (3009,1713.23,'1990-10-04',2002,1003),
    -> (3007,75.75,'1990-10-04',2004,1002),
    -> (3008,4723.00,'1990-10-05',2006,1001),
    -> (3010,1309.95,'1990-10-06',2004,1002),
    -> (3011,9891.88,'1990-10-06',2006,1001);
Query OK, 10 rows affected (0.03 sec)
Records: 10  Duplicates: 0  Warnings: 0

mysql> SHOW TABLES;
+-------------------------+
| Tables_in_cdac_kharghar |
+-------------------------+
| a1_customers            |
| a1_orders               |
| a1_salespeople          |
+-------------------------+
3 rows in set (0.08 sec)

mysql> SELECT * FROM a1_salespeople;
+------+---------+-----------+------+
| snum | sname   | city      | comm |
+------+---------+-----------+------+
| 1001 | Peel    | London    | 0.12 |
| 1002 | Serres  | San Jose  | 0.13 |
| 1004 | Motika  | London    | 0.11 |
| 1007 | Rifkin  | Barcelona | 0.15 |
| 1003 | Axelrod | New York  | 0.10 |
+------+---------+-----------+------+
5 rows in set (0.00 sec)
```

MySQL 8.0 Command Line Cli

```
+------+---------+-----------+------+
| 1001 | Peel    | London    | 0.12 |
| 1002 | Serres  | San Jose  | 0.13 |
| 1004 | Motika  | London    | 0.11 |
| 1007 | Rifkin  | Barcelona | 0.15 |
| 1003 | Axelrod | New York  | 0.10 |
+------+---------+-----------+------+
5 rows in set (0.00 sec)

mysql> SELECT * FROM a1_customers;
+------+----------+----------+--------+------+
| cnum | cname    | city     | rating | snum |
+------+----------+----------+--------+------+
| 2001 | Hoffman  | London   |    100 | 1001 |
| 2002 | Giovanni | Rome     |    200 | 1003 |
| 2003 | Liu      | San Jose |    200 | 1002 |
| 2004 | Grass    | Berlin   |    300 | 1002 |
| 2006 | Clemens  | London   |    100 | 1001 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
| 2007 | Pereira  | Rome     |    100 | 1004 |
+------+----------+----------+--------+------+
7 rows in set (0.00 sec)

mysql> SELECT * FROM a1_orders;
+------+---------+------------+------+------+
| onum | amt     | odate      | cnum | snum |
+------+---------+------------+------+------+
| 3001 |   18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 |  767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 |   75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-05 | 2006 | 1001 |
| 3010 | 1309.95 | 1990-10-06 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-06 | 2006 | 1001 |
+------+---------+------------+------+------+
10 rows in set (0.00 sec)
```