


# DRL, generalization, and DQN



THE UNIVERSITY OF  
SOUTHERN MISSISSIPPI®

# Deep Reinforcement Learning (DRL)

- Originates from the combination of:
  - RL using a value-based technique: Q-Learning
  - A deep neural network
- It can be defined as:
  - Implementation of deep neural networks to approximate the components in RL, such as Q-values.



# DRL

- With DRL:
  - Q-learning:
    - Learning is done through the approximation of Q-values instead of prediction


$$Q(S_t, A_t) \leftarrow Q(S_t, A_t) + \alpha \left[ R_{t+1} + \gamma \max_a Q(S_{t+1}, a) \right]$$

Approximated through NN

- Now, the RL agent queries the NN for Q-values so that an action can be executed
- Output of the NN are indexed


# DRL

- Indexed NN output:
  - The output with the highest output value is passed to the RL agent



# DRL -> DQN

- With NN approximation, a Q-table can be disregarded
  - Everything is now coming from the NN
  - **This is a Deep Q-network**
- However, a “warm-up” period is or can be needed to discard unnecessary experience



# DQN

- Some cautions with DQN:
  - Since we are working with large state spaces:
    - Dimensionality: the number of states is very large
- To address this:
  - Use Experience Replay
    - Prioritized experience replay
    - Importance factor



# DRL

- Generalization:
  - Two definitions:
    - The “problem” of generalization
    - A generalized model
  - The “problem” of generalization:
    - When a model is not able to approximate (or classify) because of **overfitted** values:
    - Overfitted values:
      - False values for Accuracy and Loss:
        - Very high accuracy reached, very fast
        - Very low loss reached, very fast


# DRL

- A generalized model:
  - A single model that can be implemented in different environments:
    - This means:
      - No overfitting
      - Good accuracy and loss
    - A generalized model can still output good values even when the input state was never seen before (or during training)
- The main goal of a DRL model is to be able to generalize





# DQN flowchart simplified with ER





THE UNIVERSITY OF  
**SOUTHERN MISSISSIPPI.**

