

Bootstrap / jQuery Navbars

Links for Navbars:

1. <https://colorlib.com/wp/bootstrap-navbar/>
2. <https://www.mockplus.com/blog/post/bootstrap-navbar-template>
3. <https://colorlib.com/wp/jquery-navigation-menu-bar-plugins/>

Audio/Video Tags

- Audio and video tags are used to place audio files and video files on the websites
- `<audio></audio>`
- `<video></video>`

Example on Video Tag

```
<!DOCTYPE html>
<html>
  <head>
    <title>Video Tag Example</title>
  </head>
  <body>
    <video height="420" width="650" controls>
      <source src="Sample_Videos.mp4" type="video/mp4"/>
    </video>
  </body>
</html>
```

Example to place the Youtube video in Webpage:

Goto the video - Open the video - down the video you will find the option called “share” - select the option as “Embed” and it will produce the Html with iframe tag
Copy that iframe and paste in the website

```

<!DOCTYPE html>
<html>
  <head>
    <title>Video Tag Example</title>
  </head>
  <body>
    <iframe width="560" height="315" src="https://www.youtube.com/embed/iAIsG_orac8"
      frameborder="0"
      allow="accelerometer; autoplay; encrypted-media; gyroscope; picture-in-picture" allowfullscreen></iframe>
  </body>
</html>

```

Example on Audio Tag;

```

<!DOCTYPE html>
<html>
  <head>
    <title>Audio Example</title>
  </head>
  <body>
    <audio controls="controls" autoplay loop>
      <source src="file_example_MP3_2MG.mp3" type="audio/mp3" />
    </audio>
  </body>
</html>

```

Example of Audio using JS

```
<!doctype html>
<html>
  <head>
    <title>Audio tag with Js</title>
    <script type="text/javascript">
      var audio_info = document.getElementById("audio1");
      document.getElementById('play').addEventListener('click',function(){
        audio_info.play();
      },false);
      document.getElementById('stop').addEventListener('click',function(){
        audio_info.pause();
      },false);
    </script>
  </head>
  <body>
    <audio id="audio1">
      <source src="file_example_MP3_2MG.mp3" />
    </audio>
    <button id="play" >Play</button>
    <button id="stop">Stop</button>
  </body>
</html>
```

```
<!DOCTYPE html>
<html>
  <body>
    <audio id="myAudio">
      <source src="file_example_MP3_2MG.mp3" type="audio/mp3" />
    </audio>

    <p>Click the buttons to play or pause the audio.</p>

    <button onclick="playAudio()" type="button">Play Audio</button>
    <button onclick="pauseAudio()" type="button">Pause Audio</button>

    <script>
      var x = document.getElementById("myAudio");

      function playAudio() {
        x.play();
      }

      function pauseAudio() {
        x.pause();
      }
    </script>
  </body>
</html>
```

GeoLocation

```
<!DOCTYPE html>
<HTML>
  <head>
    <title>GeoLocations</title>
  </head>
  <body>
    <button onclick="getLocation()">Get Location</button>
    <script>
      function getLocation(){
        debugger
        if(navigator.geolocation){
          navigator.geolocation.getCurrentPosition(showPosition);
        }
        else{
          window.alert('Error Message');
        }
      }
      function showPosition(position){
        window.alert(position.coords.latitude+ " " + position.coords.longitude);
      }
    </script>
  </body>
</HTML>
```