

Lesson 01 Demo 06

Implementing Transaction Management

Objective: To implement transaction management to execute all the SQL statements together, ensuring data integrity and consistency within the database

Tool required: Eclipse IDE


Prerequisites: None

Steps to be followed:

1. Create new table name orders
2. Create the executionTransaction method
3. Call the created method and checking the output
4. Use the auto-commit feature
5. Use insert and update operations
6. Use the delete operation


Step 1: Create new table name orders

1.1 Open the Terminal Emulator




1.2 Login to MySQL using the command:

mysql -u john -p



Note: A user named john has already been created for the database.

1.3 Enter the command **use estore;** to change the database



1.4 Run the **show tables;** command to list the tables in the **estore** database

```

erishantgmail@ip-172-31-17-157: ~
File Edit View Search Terminal Help
owners.
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.
mysql> use estore;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
mysql> show table;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that
corresponds to your MySQL server version for the right syntax to use near '' at
line 1
mysql> show tables;
+-----+
| Tables_in_estore |
+-----+
| Customer          |
| Employees         |
| User              |
+-----+
3 rows in set (0.00 sec)

mysql>
  
```

1.5 Write **create table Orders** to create a new table in the **estore** database

```

erishantgmail@ip-172-31-17-157: ~
File Edit View Search Terminal Help
owners.
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.
mysql> use estore;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
mysql> show table;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that
corresponds to your MySQL server version for the right syntax to use near '' at
line 1
mysql> show tables;
+-----+
| Tables_in_estore |
+-----+
| Customer          |
| Employees         |
| User              |
+-----+
3 rows in set (0.00 sec)

mysql> create table Orders
  
```

1.6 Define **attributes** for the table Orders

```

mysql> use estore;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
mysql> show table;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that
corresponds to your MySQL server version for the right syntax to use near '' at
line 1
mysql> show tables;
+-----+
| Tables_in_estore |
+-----+
| Customer          |
| Employees         |
| User              |
+-----+
3 rows in set (0.00 sec)

mysql> create table Orders(
-> orderId int primary key auto_increment,
-> userId int,
-> orderDate date,
-> orderAmount int

```

1.7 Run the **show tables;** command

```

mysql> show table;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that
corresponds to your MySQL server version for the right syntax to use near '' at
line 1
mysql> show tables;
+-----+
| Tables_in_estore |
+-----+
| Customer          |
| Employees         |
| User              |
+-----+
3 rows in set (0.00 sec)

mysql> create table Orders(
-> orderId int primary key auto_increment,
-> userId int,
-> orderDate date,
-> orderAmount int
-> );
Query OK, 0 rows affected (0.03 sec)

mysql> show tables;

```

You can see the **Orders** table created.

```

erishantgmail@ip-172-31-17-157: ~
File Edit View Search Terminal Help

| User |
+-----+
3 rows in set (0.00 sec)

mysql> create table Orders(
-> orderId int primary key auto_increment,
-> userId int,
-> orderDate date,
-> orderAmount int
-> );
Query OK, 0 rows affected (0.03 sec)

mysql> show tables;
+-----+
| Tables_in_estore |
+-----+
| Customer         |
| Employee         |
| Orders          |
| User             |
+-----+
4 rows in set (0.00 sec)

mysql>
  
```

1.8 Run the **select * from Orders;** command to see the empty set in the Orders table

```

erishantgmail@ip-172-31-17-157: ~
File Edit View Search Terminal Help

mysql> create table Orders(
-> orderId int primary key auto_increment,
-> userId int,
-> orderDate date,
-> orderAmount int
-> );
Query OK, 0 rows affected (0.03 sec)


mysql> show tables;
+-----+
| Tables_in_estore |
+-----+
| Customer         |
| Employee         |
| Orders          |
| User             |
+-----+
4 rows in set (0.00 sec)

mysql> select * from Orders;
Empty set (0.00 sec)


mysql>
  
```

Step 2: Create the executionTransaction method

2.1 Open Eclipse IDE



2.2 Open the DB.java file



2.3 Create an **executeTransaction** method to write transaction management code

```

259      statement.addBatch(sql1);
260      statement.addBatch(sql2);
261      statement.addBatch(sql3);
262      //statement.addBatch(sql4);
263      //statement.addBatch(sql5);
264
265      int[] results = statement.executeBatch();
266
267      /*String sql = "insert into Employees values(null, ?, ?, ?)";
268      preparedStatement = connection.prepareStatement(sql);
269
270      preparedStatement.setString(1, "George");
271      preparedStatement.setString(2, "george@example.com");
272      preparedStatement.setInt(3, 30000);
273      preparedStatement.addBatch();
274
275      preparedStatement.setString(1, "Harry");
276      preparedStatement.setString(2, "harry@example.com");
277      preparedStatement.setInt(3, 34000);
278      preparedStatement.addBatch();
279
280      preparedStatement.setString(1, "Sia");
281      preparedStatement.setString(2, "sia@example.com");
282      preparedStatement.setInt(3, 40000);
283      preparedStatement.addBatch();
284
285      int[] results = preparedStatement.executeBatch();*/
286
287      System.out.println("Batch Executed");
288
289      } catch (Exception e) {
290          System.out.println("Exception Occurred: "+e);
291      }
292  }
293
294  public void executeTransaction() {
295
296

```


2.4 Write a **try-catch** block to manage all potential errors during code execution

```

263      //statement.addBatch(sql5);
264
265      int[] results = statement.executeBatch();
266
267      /*String sql = "insert into Employees values(null, ?, ?, ?)";
268      preparedStatement = connection.prepareStatement(sql);
269
270      preparedStatement.setString(1, "George");
271      preparedStatement.setString(2, "george@example.com");
272      preparedStatement.setInt(3, 30000);
273      preparedStatement.addBatch();
274
275      preparedStatement.setString(1, "Harry");
276      preparedStatement.setString(2, "harry@example.com");
277      preparedStatement.setInt(3, 34000);
278      preparedStatement.addBatch();
279
280      preparedStatement.setString(1, "Sia");
281      preparedStatement.setString(2, "sia@example.com");
282      preparedStatement.setInt(3, 40000);
283      preparedStatement.addBatch();
284
285      int[] results = preparedStatement.executeBatch();*/
286
287      System.out.println("Batch Executed");
288
289      } catch (Exception e) {
290          System.out.println("Exception Occurred: "+e);
291      }
292  }
293
294  public void executeTransaction() {
295      try {
296
297      } catch (Exception e) {
298          // TODO: handle exception
299      }
300  }


```

2.5 Create two SQL statements to perform the insert operation



```
267 /*String sql = "insert into Employees values(null, ?, ?, ?)";
268 preparedStatement = connection.prepareStatement(sql);
269
270 preparedStatement.setString(1, "George");
271 preparedStatement.setString(2, "george@example.com");
272 preparedStatement.setInt(3, 30000);
273 preparedStatement.addBatch();
274
275 preparedStatement.setString(1, "Harry");
276 preparedStatement.setString(2, "harry@example.com");
277 preparedStatement.setInt(3, 34000);
278 preparedStatement.addBatch();
279
280 preparedStatement.setString(1, "Sia");
281 preparedStatement.setString(2, "sia@example.com");
282 preparedStatement.setInt(3, 40000);
283 preparedStatement.addBatch();
284
285 int[] results = preparedStatement.executeBatch();*/
286
287 System.out.println("Batch Executed");
288
289 } catch (Exception e) {
290     System.out.println("Exception Occurred: "+e);
291 }
292 }
293
294 public void executeTransaction() {
295     try {
296         String sql1 = "insert into Orders values(null, 2, '2022-01-08', 3000)";
297         String sql2 = "insert into Orders values(null, 4, '2022-01-09', 4500)";
298
299     } catch (Exception e) {
300     }
301     } catch (Exception e) {
302         System.out.println("Exception Occurred: "+e);
303     }
304 }
```


2.6 Create a batch and execute the batch statement to run the SQL statements created above




```
275 preparedStatement.setString(1, "Harry");
276 preparedStatement.setString(2, "harry@example.com");
277 preparedStatement.setInt(3, 34000);
278 preparedStatement.addBatch();
279
280 preparedStatement.setString(1, "Sia");
281 preparedStatement.setString(2, "sia@example.com");
282 preparedStatement.setInt(3, 40000);
283 preparedStatement.addBatch();
284
285 int[] results = preparedStatement.executeBatch();*/
286
287 System.out.println("Batch Executed");
288
289 } catch (Exception e) {
290     System.out.println("Exception Occurred: "+e);
291 }
292 }
293
294 public void executeTransaction() {
295     try {
296         String sql1 = "insert into Orders values(null, 2, '2022-01-08', 3000)";
297         String sql2 = "insert into Orders values(null, 4, '2022-01-09', 4500)";
298
299         statement.addBatch(sql1);
300         statement.addBatch(sql2);
301
302         statement.executeBatch();
303         System.out.println("Batch Executed");
304     } catch (Exception e) {
305         System.out.println("Exception Occurred: "+e);
306     }
307 }
308
309 }
310 }
```


Step 3: Call the created method and checking the output

3.1 Open the **App.java** file



3.2 Write **db.executeTransaction();** to call the created method



3.3 Run the code, and you will see the output **Batch Executed :)** with no errors

```

jdbcpjrojects - CMS/src/...  gmail@ip-172-31-17-157: ~
jdbcpjrojects - CMS/src/main/java/com/example/cms/App.java - Eclipse IDE
File Edit Source Refactor Navigate Search Project Run Window Help
App.java Run App
//db.createCustomer(customer);
//db.updateCustomer(customer);
//db.deleteCustomer(3);
//System.out.println();
ArrayList<Customer> customers = db.getAllCustomers();
customers.forEach( cRef -> System.out.println(cRef));
db.closeConnection();*/
//Scanner scanner = new Scanner(System.in);
//System.out.println("Enter Name: ");
//String name = scanner.nextLine();
//System.out.println("Enter Password: ");
//String password = scanner.nextLine();
//System.out.println("Enter Customer ID:");
//int cid = scanner.nextInt();
//scanner.close();
DB db = new DB();
db.createConnection();
//db.executeProcedure(name, password);
//db.executeProcedure(cid);
//db.executeSQLStatementsInBatch();
db.executeTransaction();
db.closeConnection();
Problems Javadoc Declaration Console x
<terminated> App [Java Application] /usr/eclipse/plugins/org.eclipse.justi.openjdk.hotspot.jre.full/bin/linux.x86_64/java:
[DB] Driver Loaded
[DB] Connection Created
Batch Executed :)
[DB] Connection Closed. Close Status: true

```

3.4 Return to the Terminal Emulator and run the **select * from Orders;** command

```

Applications jdbcpjrojects - CMS/src/...  gmail@ip-172-31-17-157: ~
jdbcpjrojects - CMS/src/main/java/com/example/cms/App.java - Eclipse IDE
File Edit Source Refactor Navigate Search Project Run Window Help
DB.java App.java x
30
31 //db.createCustomer(customer);
32 //db.updateCustomer(customer);
33
34 //db.deleteCustomer(3);
35
36 //System.out.println();
37
38 ArrayList<Customer> customers
39 customers.forEach( cRef -> Sys
40
41 db.closeConnection();*/
42
43 //Scanner scanner = new Scanne
44 //System.out.println("Enter Na
45 //String name = scanner.nextLi
46
47 //System.out.println("Enter Pa
48 //String password = scanner.no
49
50 //System.out.println("Enter Cu
51 //int cid = scanner.nextInt();
52
53 //scanner.close();
54
55 DB db = new DB();
56 db.createConnection();
57 //db.executeProcedure(name, pa
58 //db.executeProcedure(cid);
59
60 //db.executeSQLStatementsInBatch();
61
62 db.executeTransaction();
63
64 db.closeConnection();
65
66
67
Terminal
erishant@gmail@ip-172-31-17-157: ~
File Edit View Search Terminal Help
mysql> create table Orders(
-> orderId int primary key auto_increment,
-> userId int,
-> orderDate date,
-> orderAmount int
-> );
Query OK, 0 rows affected (0.03 sec)
mysql> show tables;
+-----+
| Tables_in_estore |
+-----+
| Customer          |
| Employees         |
| Orders            |
| User              |
+-----+
4 rows in set (0.00 sec)
mysql> select * from Orders;
Empty set (0.00 sec)
mysql> select * from Orders;

```

The screenshot shows the Eclipse IDE interface. The main editor displays a Java file named `App.java` with the following code:

```

30
31 //db.createCustomer(customer);
32 //db.updateCustomer(customer);
33
34 //db.deleteCustomer(3);
35
36 //System.out.println();
37
38 ArrayList<Customer> customers
39 customers.forEach( cRef -> Sys
40
41 db.closeConnection();*/
42
43 //Scanner scanner = new Scanner
44 //System.out.println("Enter Na
45 //String name = scanner.nextLi
46
47 //System.out.println("Enter Pa
48 //String password = scanner.ne
49
50 //System.out.println("Enter Cu
51 //int cid = scanner.nextInt();
52
53 //scanner.close();
54
55 DB db = new DB();
56 db.createConnection();
57 //db.executeProcedure(name, pa
58 //db.executeProcedure(cid);
59
60 //db.executeSQLStatementsInBatch();
61
62 db.executeTransaction();
63
64 db.closeConnection();
65
66
67 }

```

A terminal window is open in the foreground, showing the output of MySQL commands:

```

erishant@gmail@ip:172-31-17-157: ~
File Edit View Search Terminal Help

mysql> show tables;
+-----+
| Tables_in_estore |
+-----+
| Customer          |
| Employees         |
| Orders            |
| User              |
+-----+
4 rows in set (0.00 sec)

mysql> select * from Orders;
Empty set (0.00 sec)


mysql> select * from Orders;
+-----+
| orderId | userId | orderDate | orderAmount |
+-----+
| 1       | 2     | 2022-01-08 | 3000        |
| 2       | 4     | 2022-01-09 | 4500        |
+-----+
2 rows in set (0.00 sec)

mysql>

```

Step 4: Use the auto-commit feature

4.1 Return to the **DB.java** file and change it to insert two more orders



```
jdbcprojects - C:\MSI\src\main\java\com\example\ms\src\DB.java - Eclipse IDE
File Edit Source Refactor Navigate Search Project Run Window Help
DB.java x App.java
273 preparedStatement.addBatch();
274
275 preparedStatement.setString(1, "Harry");
276 preparedStatement.setString(2, "harry@example.com");
277 preparedStatement.setInt(3, 34000);
278 preparedStatement.addBatch();
279
280 preparedStatement.setString(1, "Sia");
281 preparedStatement.setString(2, "sia@example.com");
282 preparedStatement.setInt(3, 40000);
283 preparedStatement.addBatch();
284
285 int[] results = preparedStatement.executeBatch();
286
287 System.out.println("Batch Executed");
288
289 } catch (Exception e) {
290     System.out.println("Exception Occurred: "+e);
291 }
292
293 }
294
295 public void executeTransaction() {
296     try {
297
298         String sql1 = "insert into Orders values(null, 2, '2022-01-09', 6700)";
299         String sql2 = "insert into Orders values(null, 4, '2022-01-11', 7600)";
300
301         statement.addBatch(sql1);
302         statement.addBatch(sql2);
303
304         statement.executeBatch();
305         System.out.println("Batch Executed :");
306
307     } catch (Exception e) {
```

4.2 Add the auto-commit feature in a **try-catch** block to disable auto-commit and add **commit()**

```

279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
    preparedStatement.setString(1, "Sia");
    preparedStatement.setString(2, "sia@example.com");
    preparedStatement.setInt(3, 40000);
    preparedStatement.addBatch();

    int[] results = preparedStatement.executeBatch();/*
    System.out.println("Batch Executed");

} catch (Exception e) {
    System.out.println("Exception Occurred: "+e);
}

}

public void executeTransaction() {
    try {
        connection.setAutoCommit(false);

        String sql1 = "insert into Orders values(null, 2, '2022-01-09', 6700)";
        String sql2 = "insert into Orders values(null, 4, '2022-01-11', 7600)";

        statement.addBatch(sql1);
        statement.addBatch(sql2);

        statement.executeBatch();
        connection.commit(); // We will ourselves do the commit
        System.out.println("Batch Executed and Transaction Committed :)");
    } catch (Exception e) {
        System.out.println("Exception Occurred: "+e);
    }
}
}
}

```

4.3 Add a **rollback** method within the catch block for any errors that may occur during execution

```

285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
    int[] results = preparedStatement.executeBatch();/*
    System.out.println("Batch Executed");

} catch (Exception e) {
    System.out.println("Exception Occurred: "+e);
}

}

public void executeTransaction() {
    try {
        connection.setAutoCommit(false);

        String sql1 = "insert into Orders values(null, 2, '2022-01-09', 6700)";
        String sql2 = "insert into Orders values(null, 4, '2022-01-11', 7600)";

        statement.addBatch(sql1);
        statement.addBatch(sql2);

        statement.executeBatch();
        connection.commit(); // We will ourselves do the commit
        System.out.println("Batch Executed and Transaction Committed :)");
    } catch (Exception e) {
        System.out.println("Exception Occurred: "+e);
        try {
            System.out.println("Rolling Back the Transaction");
            connection.rollback();
        } catch (SQLException e1) {
            e1.printStackTrace();
        }
    }
}
}
}

```

4.4 Re-run this code, and you will see **Batch Executed and Transaction committed :)** in the output without error

```
//db.createCustomer(customer);
//db.updateCustomer(customer);

//db.deleteCustomer(3);
//System.out.println();

ArrayList<Customer> customers = db.getAllCustomers();
customers.forEach( cRef -> System.out.println(cRef));

db.closeConnection();*/

//Scanner scanner = new Scanner(System.in);
//System.out.println("Enter Name: ");
//String name = scanner.nextLine();

//System.out.println("Enter Password: ");
//String password = scanner.nextLine();

//System.out.println("Enter Customer ID:");
//int cid = scanner.nextInt();

//scanner.close();

DB db = new DB();
db.createConnection();
//db.executeProcedure(name, password);
//db.executeProcedure(cid);

//db.executeSQLStatementsInBatch();

db.executeTransaction();

db.closeConnection();
```

```
<terminated> App [Java Application] /usr/eclipse/plugins/org.eclipse.justi.openjdk.hotspot.jre.full/bin/linux64/
[DB] Driver Loaded
[DB] Connection Created
Batch Executed and Transaction Committed :)
[DB] Connection Closed. Close Status: true
```

4.5 Go back to the **Terminal Emulator** and run the **select * from Orders;** command. You will see two more orders inserted in the Orders table.

```
mysql> select * from Orders;
Empty set (0.00 sec)


mysql> select * from Orders;
+----+-----+-----+-----+
| orderId | userId | orderDate | orderAmount |
+----+-----+-----+-----+
| 1 | 2 | 2022-01-08 | 3000 |
| 2 | 4 | 2022-01-09 | 4500 |
+----+-----+-----+-----+
2 rows in set (0.00 sec)

mysql> select * from Orders;
+----+-----+-----+-----+
| orderId | userId | orderDate | orderAmount |
+----+-----+-----+-----+
| 1 | 2 | 2022-01-08 | 3000 |
| 2 | 4 | 2022-01-09 | 4500 |
| 3 | 2 | 2022-01-09 | 6700 |
| 4 | 4 | 2022-01-11 | 7600 |
+----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql>
```



Step 5: Use the insert and update operations

5.1 Write an insert and an update operation. Insert a new order and update the old order with ID 4



```
285     int[] results = preparedStatement.executeBatch();/*
286
287
288     System.out.println("Batch Executed");
289
290
291     } catch (Exception e) {
292         System.out.println("Exception Occurred: "+e);
293     }
294 }
295
296 public void executeTransaction() {
297     try {
298
299         connection.setAutoCommit(false);
300
301         String sql1 = "insert into Orders values(null, 5, '2022-01-09', 7700)";
302         String sql2 = "update Orders set amount = 7600 where orderId = 4";
303
304         statement.addBatch(sql1);
305         statement.addBatch(sql2);
306
307         statement.executeBatch();
308         connection.commit(); // We will ourselves do the commit
309         System.out.println("Batch Executed and Transaction Committed :");
310
311     } catch (Exception e) {
312         System.out.println("Exception Occurred: "+e);
313         try {
314             System.out.println("Rolling Back the Transaction...");
315             connection.rollback();
316         } catch (SQLException e1) {
317             e1.printStackTrace();
318         }
319     }
```

5.2 Re-run the code, and you will see **Exception Occurred** in the console



```
//db.createCustomer(customer);
//db.updateCustomer(customer);

//db.deleteCustomer(3);

//System.out.println();

ArrayList<Customer> customers = db.getAllCustomers();
customers.forEach( cRef -> System.out.println(cRef));

db.closeConnection();*/

//Scanner scanner = new Scanner(System.in);
//System.out.println("Enter Name: ");
//String name = scanner.nextLine();

//System.out.println("Enter Password: ");
//String password = scanner.nextLine();

//System.out.println("Enter Customer ID:");
//int cid = scanner.nextInt();

//scanner.close();

DB db = new DB();
db.createConnection();
//db.executeProcedure(name, password);
//db.executeProcedure(cid);

//db.executeSQLStatementsInBatch();

db.executeTransaction();

db.closeConnection();
```

```
<terminated> App [java Application] /usr/eclipse/plugins/org.eclipse.justi.openjdk.hotspot.j
[DB] Driver Loaded
[DB] Connection Created
Exception Occurred: java.sql.BatchUpdateException: Unknown column 'amount'
Rolling Back the Transaction...
[DB] Connection Closed. Close Status: true
```

5.3 Return to the terminal and run the **select * from Orders;** command. You will see that the new order is not inserted, and the old order is also not updated

The screenshot shows the Eclipse IDE with a terminal window open. The terminal displays the following MySQL commands and results:

```
mysql> select * from Orders;
Empty set (0.00 sec)

mysql> select * from Orders;
+----+-----+-----+-----+
| orderId | userId | orderDate | orderAmount |
+----+-----+-----+-----+
| 1 | 2 | 2022-01-08 | 3000 |
| 2 | 4 | 2022-01-09 | 4500 |
+----+-----+-----+-----+
2 rows in set (0.00 sec)

mysql> select * from Orders;
+----+-----+-----+-----+
| orderId | userId | orderDate | orderAmount |
+----+-----+-----+-----+
| 1 | 2 | 2022-01-08 | 3000 |
| 2 | 4 | 2022-01-09 | 4500 |
| 3 | 2 | 2022-01-09 | 6700 |
| 4 | 4 | 2022-01-11 | 7600 |
+----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> select * from Orders;
```

The screenshot shows the Eclipse IDE with a terminal window open. The terminal displays the following MySQL commands and results:

```
mysql> select * from Orders;
+----+-----+-----+-----+
| orderId | userId | orderDate | orderAmount |
+----+-----+-----+-----+
| 1 | 2 | 2022-01-08 | 3000 |
| 2 | 4 | 2022-01-09 | 4500 |
| 3 | 2 | 2022-01-09 | 6700 |
| 4 | 4 | 2022-01-11 | 7600 |
+----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> select * from Orders;
+----+-----+-----+-----+
| orderId | userId | orderDate | orderAmount |
+----+-----+-----+-----+
| 1 | 2 | 2022-01-08 | 3000 |
| 2 | 4 | 2022-01-09 | 4500 |
| 3 | 2 | 2022-01-09 | 6700 |
| 4 | 4 | 2022-01-11 | 7600 |
+----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql>
```

5.4 Change the column name to **orderamount** in the updated SQL code

```

285
286     int[] results = preparedStatement.executeBatch();
287
288     System.out.println("Batch Executed");
289
290
291     } catch (Exception e) {
292         System.out.println("Exception Occurred: "+e);
293     }
294 }
295
296 public void executeTransaction() {
297     try {
298         connection.setAutoCommit(false);
299
300         String sql1 = "insert into Orders values(null, 5, '2022-01-09', 7700)";
301         String sql2 = "update Orders set orderamount = 4900 where orderId = 4";
302
303         statement.addBatch(sql1);
304         statement.addBatch(sql2);
305
306         statement.executeBatch();
307         connection.commit(); // We will ourselves do the commit
308         System.out.println("Batch Executed and Transaction Committed :)");
309
310     } catch (Exception e) {
311         System.out.println("Exception Occurred: "+e);
312         try {
313             System.out.println("Rolling Back the Transaction...");
314             connection.rollback();
315         } catch (SQLException e1) {
316             e1.printStackTrace();
317         }
318     }
319 }
320 }
321
322
  
```

5.5 Re-run the code, and you will see the code executed without any errors

```

//db.createCustomer(customer);
//db.updateCustomer(customer);

//db.deleteCustomer(3);

//System.out.println();

ArrayList<Customer> customers = db.getAllCustomers();
customers.forEach( cRef -> System.out.println(cRef));

db.closeConnection();

//Scanner scanner = new Scanner(System.in);
//System.out.println("Enter Name: ");
//String name = scanner.nextLine();

//System.out.println("Enter Password: ");
//String password = scanner.nextLine();

//System.out.println("Enter Customer ID:");
//int cid = scanner.nextInt();

//scanner.close();

DB db = new DB();
db.createConnection();
//db.executeProcedure(name, password);
//db.executeProcedure(cid);

//db.executeSQLStatementsInBatch();

db.executeTransaction();
  
```

```

<terminated> App [Java Application] /usr/eclipse/plugin/org.eclipse.justi.openjdk.hotspot...
[DB] Driver Loaded
[DB] Connection Created
Batch Executed and Transaction Committed :)
[DB] Connection Closed. Close Status: true
  
```

5.6 Return to the terminal and run the **select * from Orders** command. You will see a new row added and the **orderamount** of order ID 4 gets updated.

```

//db.createCustomer(customer);
//db.updateCustomer(customer);
//db.deleteCustomer(3);
//System.out.println();
//System.out.println();
ArrayList<Customer> customers
customers.forEach( cRef -> Sys
40
db.closeConnection();*/
41
//Scanner scanner = new Scanner
//System.out.println("Enter Na
//String name = scanner.nextLi
42
//System.out.println("Enter Pa
//String password = scanner.ne
43
//System.out.println("Enter Cu
//int cid = scanner.nextInt();
44
//scanner.close();
45
DB db = new DB();
db.createConnection();
//db.executeProcedure(name, pa
//db.executeProcedure(cid);
46
//db.executeSQLStatementsInBatch();
47
db.executeTransaction();
48
db.closeConnection();
49
}

```

```

mysql> select * from Orders;
+-----+-----+-----+-----+
| orderId | userId | orderDate | orderAmount |
+-----+-----+-----+-----+
| 1 | 2 | 2022-01-08 | 3000 |
| 2 | 4 | 2022-01-09 | 4500 |
| 3 | 2 | 2022-01-09 | 6700 |
| 4 | 4 | 2022-01-11 | 7600 |
+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> select * from Orders;
+-----+-----+-----+-----+
| orderId | userId | orderDate | orderAmount |
+-----+-----+-----+-----+
| 1 | 2 | 2022-01-08 | 3000 |
| 2 | 4 | 2022-01-09 | 4500 |
| 3 | 2 | 2022-01-09 | 6700 |
| 4 | 4 | 2022-01-11 | 7600 |
+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> select * from Orders;

```

```

//db.createCustomer(customer);
//db.updateCustomer(customer);
//db.deleteCustomer(3);
//System.out.println();
//System.out.println();
ArrayList<Customer> customers
customers.forEach( cRef -> Sys
40
db.closeConnection();*/
41
//Scanner scanner = new Scanner
//System.out.println("Enter Na
//String name = scanner.nextLi
42
//System.out.println("Enter Pa
//String password = scanner.ne
43
//System.out.println("Enter Cu
//int cid = scanner.nextInt();
44
//scanner.close();
45
DB db = new DB();
db.createConnection();
//db.executeProcedure(name, pa
//db.executeProcedure(cid);
46
//db.executeSQLStatementsInBatch();
47
db.executeTransaction();
48
db.closeConnection();
49
}

```

```

mysql> select * from Orders;
+-----+-----+-----+-----+
| orderId | userId | orderDate | orderAmount |
+-----+-----+-----+-----+
| 1 | 2 | 2022-01-08 | 3000 |
| 2 | 4 | 2022-01-09 | 4500 |
| 3 | 2 | 2022-01-09 | 6700 |
| 4 | 4 | 2022-01-11 | 7600 |
+-----+-----+-----+-----+
4 rows in set (0.00 sec)


mysql> select * from Orders;
select * from Orders;
^C
mysql> select * from Orders;
+-----+-----+-----+-----+
| orderId | userId | orderDate | orderAmount |
+-----+-----+-----+-----+
| 1 | 2 | 2022-01-08 | 3000 |
| 2 | 4 | 2022-01-09 | 4500 |
| 3 | 2 | 2022-01-09 | 6700 |
| 4 | 4 | 2022-01-11 | 4900 |
| 6 | 5 | 2022-01-09 | 7700 |
+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql>

```

Step 6: Use the delete operation

6.1 Insert another order by changing the values in the insert statement




```

jdbcpjprojects - CMS/src/main/java/com/example/cms/db/DB.java - Eclipse IDE
File Edit Source Refactor Navigate Search Project Run Window Help

DB.java x App.java
285         int[] results = preparedStatement.executeBatch();
286         System.out.println("Batch Executed");
287     } catch (Exception e) {
288         System.out.println("Exception Occurred: "+e);
289     }
290 }
291
292 public void executeTransaction() {
293     try {
294         connection.setAutoCommit(false);
295
296         String sql1 = "insert into Orders values(null, 7, '2022-01-09', 320)";
297         String sql2 = "update Orders set orderAmount = 4900 where orderId = 4";
298         statement.addBatch(sql1);
299         statement.addBatch(sql2);
300         statement.executeBatch();
301         connection.commit(); // We will ourselves do the commit
302         System.out.println("Batch Executed and Transaction Committed :)");
303     } catch (Exception e) {
304         System.out.println("Exception Occurred: "+e);
305         try {
306             System.out.println("Rolling Back the Transaction...");
307             connection.rollback();
308         } catch (SQLException e1) {
309             e1.printStackTrace();
310         }
311     }
312 }
313
314 }
315
316 }
317
318 }
319
320 }
321
322 }

```

6.2 Write the delete statement




```

DB.java x App.java
285         int[] results = preparedStatement.executeBatch();
286         System.out.println("Batch Executed");
287     } catch (Exception e) {
288         System.out.println("Exception Occurred: "+e);
289     }
290 }
291
292 public void executeTransaction() {
293     try {
294         connection.setAutoCommit(false);
295
296         String sql1 = "insert into Orders values(null, 7, '2022-01-09', 3200)";
297         String sql2 = "update Orders set orderAmount = 4900 where orderId = 4";
298         String sql3 = "delete from Orders id = 1";
299         statement.addBatch(sql1);
300         statement.addBatch(sql2);
301         statement.addBatch(sql3);
302         statement.executeBatch();
303         connection.commit(); // We will ourselves do the commit
304         System.out.println("Batch Executed and Transaction Committed :)");
305     } catch (Exception e) {
306         System.out.println("Exception Occurred: "+e);
307         try {
308             System.out.println("Rolling Back the Transaction...");
309             connection.rollback();
310         } catch (SQLException e1) {
311             e1.printStackTrace();
312         }
313     }
314 }
315
316 }
317
318 }
319
320 }
321
322 }

```

6.3 Re-run the code, and you will see the rollback function is called because one or more batches failed during execution



```

App.java Run App
//db.createCustomer(customer);
//db.updateCustomer(customer);
//db.deleteCustomer(3);
//System.out.println();

ArrayList<Customer> customers = db.getAllCustomers();
customers.forEach( cRef -> System.out.println(cRef));
db.closeConnection();*/

//Scanner scanner = new Scanner(System.in);
//System.out.println("Enter Name: ");
//String name = scanner.nextLine();

//System.out.println("Enter Password: ");
//String password = scanner.nextLine();

//System.out.println("Enter Customer ID:");
//int cid = scanner.nextInt();
//scanner.close();

DB db = new DB();
db.createConnection();
//db.executeProcedure(name, password);
//db.executeProcedure(cid);

//db.executeSQLStatementsInBatch();

db.executeTransaction();
db.closeConnection();

```

```

<terminated> App [Java Application] /usr/eclipse/plugins/org.eclipse.justi.openjdk.hotspot.jre.full/bin/linux.x86_64/java
[DB] Driver Loaded
[DB] Connection Created
Exception Occurred: java.sql.BatchUpdateException: You have an error in your SQL syntax; check the
Rolling Back the Transaction...
[DB] Connection Closed, Close Status: true

```


6.4 Run the **select * from Orders;** command in the Terminal Emulator, and you will see that there is no change in the table

```

App.java x
//db.createCustomer(customer);
//db.updateCustomer(customer);
//db.deleteCustomer(3);
//System.out.println();
ArrayList<Customer> customers
customers.forEach( cRef -> Sys
db.closeConnection();*/
//Scanner scanner = new Scanner
//System.out.println("Enter Na
//String name = scanner.nextLi
//System.out.println("Enter Pa
//String password = scanner.ne
//System.out.println("Enter Cu
//int cid = scanner.nextInt();
//scanner.close();
DB db = new DB();
db.createConnection();
//db.executeProcedure(name, pa
//db.executeProcedure(cid);
//db.executeSQLStatementToBatch();

erishantgmail@ip-172-31-17-157: ~
File Edit View Search Terminal Help
+-----+
| orderId | userId | orderDate | orderAmount |
+-----+
| 1 | 2 | 2022-01-08 | 3000 |
| 2 | 4 | 2022-01-09 | 4500 |
| 3 | 2 | 2022-01-09 | 6700 |
| 4 | 4 | 2022-01-11 | 4900 |
| 6 | 5 | 2022-01-09 | 7700 |
+-----+
5 rows in set (0.00 sec)
mysql> select * from Orders;
+-----+
| orderId | userId | orderDate | orderAmount |
+-----+
| 1 | 2 | 2022-01-08 | 3000 |
| 2 | 4 | 2022-01-09 | 4500 |
| 3 | 2 | 2022-01-09 | 6700 |
| 4 | 4 | 2022-01-11 | 4900 |
| 6 | 5 | 2022-01-09 | 7700 |
+-----+
5 rows in set (0.00 sec)
mysql>

```

By following these steps, you have successfully managed transaction execution to perform all SQL statements together, ensuring data integrity and consistency within the database.