

Lesson 03 Demo 02

Creating a Multi-Container Pod

Objective: To create a multi-container pod in a Kubernetes cluster that allows you to run and interact with multiple containers within a single pod

Tools required: kubeadm, kubectl, kubelet, and containerd

Prerequisites: A Kubernetes cluster (refer to Demo 01 from Lesson 01 for setting up a cluster)


Steps to be followed:

1. Create and access a multi-container pod

Step 1: Create and access a multi-container pod

- 1.1 Create a YAML file using the following command:

vi multi-pod.yaml



```
labsuser@master:~$ vi multi-pod.yaml
labsuser@master:~$
```

- 1.2 Enter the following code into the **multi-pod.yaml** file and then save it:

```
apiVersion: v1
kind: Pod
metadata:
  name: multicontainer-pod
spec:
  containers:
    #Container 01
    - name: web
      image: nginx
```

```
ports:
- containerPort: 80
#Container 02
- name: redis
  image: redis
  ports:
  - containerPort: 6379
```

```
apiVersion: v1
kind: Pod
metadata:
  name: multicontainer-pod
spec:
  containers:
    #Container 01
    - name: web
      image: nginx
      ports:
      - containerPort: 80
    #Container 02
    - name: redis
      image: redis
      ports:
      - containerPort: 6379
```

1.3 Create the pod using the following command:

kubectl apply -f multi-pod.yaml

```
labsuser@master:~$ vi multi-pod.yaml
labsuser@master:~$ kubectl apply -f multi-pod.yaml
pod/multicontainer-pod created
labsuser@master:~$
```

- 1.4 Execute the command inside the **web** container of the **multicontainer-pod** to display the date and time:

kubectl exec -it multicontainer-pod -c web -- date

```
labsuser@master:~$ vi multi-pod.yaml
labsuser@master:~$ kubectl apply -f multi-pod.yaml
pod/multicontainer-pod created
labsuser@master:~$ kubectl exec -it multicontainer-pod -c web -- date
Mon Oct 30 15:43:33 UTC 2023
labsuser@master:~$
```

- 1.5 Execute the command inside the **redis** container of the **multicontainer-pod** to display the date and time:

kubectl exec -it multicontainer-pod -c redis -- date

```
labsuser@master:~$ vi multi-pod.yaml
labsuser@master:~$ kubectl apply -f multi-pod.yaml
pod/multicontainer-pod created
labsuser@master:~$ kubectl exec -it multicontainer-pod -c web -- date
Mon Oct 30 15:43:33 UTC 2023
labsuser@master:~$ kubectl exec -it multicontainer-pod -c redis -- date
Mon Oct 30 15:46:11 UTC 2023
labsuser@master:~$
```

- 1.6 To view the logs of the **web** container, use the following command:

kubectl logs multicontainer-pod -c web

```
labsuser@master:~$ kubectl exec -it multicontainer-pod -c redis -- date
Mon Oct 30 15:46:11 UTC 2023
labsuser@master:~$ kubectl logs multicontainer-pod -c web
/docker-entrypoint.sh: /docker-entrypoint.d/ is not empty, will attempt to perform configuration
/docker-entrypoint.sh: Looking for shell scripts in /docker-entrypoint.d/
/docker-entrypoint.sh: Launching /docker-entrypoint.d/10-listen-on-ipv6-by-default.sh
10-listen-on-ipv6-by-default.sh: info: Getting the checksum of /etc/nginx/conf.d/default.conf
10-listen-on-ipv6-by-default.sh: info: Enabled listen on IPv6 in /etc/nginx/conf.d/default.conf
/docker-entrypoint.sh: Sourcing /docker-entrypoint.d/15-local-resolvers.envsh
/docker-entrypoint.sh: Launching /docker-entrypoint.d/20-envsubst-on-templates.sh
/docker-entrypoint.sh: Launching /docker-entrypoint.d/30-tune-worker-processes.sh
/docker-entrypoint.sh: Configuration complete; ready for start up
2023/10/30 15:41:54 [notice] 1#1: using the "epoll" event method
2023/10/30 15:41:54 [notice] 1#1: nginx/1.25.3
2023/10/30 15:41:54 [notice] 1#1: built by gcc 12.2.0 (Debian 12.2.0-14)
2023/10/30 15:41:54 [notice] 1#1: OS: Linux 6.2.0-1013-aws
2023/10/30 15:41:54 [notice] 1#1: getrlimit(RLIMIT_NOFILE): 1024:524288
2023/10/30 15:41:54 [notice] 1#1: start worker processes
2023/10/30 15:41:54 [notice] 1#1: start worker process 28
2023/10/30 15:41:54 [notice] 1#1: start worker process 29
labsuser@master:~$
```

- 1.7 View the logs of the **redis** container using the following command:
kubectl logs multicontainer-pod -c redis

```
Fluentd-Enterprise: configuration complete, ready for start-up
2023/10/30 15:41:54 [notice] 1#1: using the "epoll" event method
2023/10/30 15:41:54 [notice] 1#1: nginx/1.25.3
2023/10/30 15:41:54 [notice] 1#1: built by gcc 12.2.0 (Debian 12.2.0-14)
2023/10/30 15:41:54 [notice] 1#1: OS: Linux 6.2.0-1013-aws
2023/10/30 15:41:54 [notice] 1#1: getrlimit(RLIMIT_NOFILE): 1024:524288
2023/10/30 15:41:54 [notice] 1#1: start worker processes
2023/10/30 15:41:54 [notice] 1#1: start worker process 28
2023/10/30 15:41:54 [notice] 1#1: start worker process 29
labsuser@master:~$ kubectl logs multicontainer-pod -c redis
1:C 30 Oct 2023 15:41:57.208 * 000000000000 Redis is starting 000000000000
1:C 30 Oct 2023 15:41:57.208 * Redis version=7.2.2, bits=64, commit=00000000, modified=0, pid=1, just started
1:C 30 Oct 2023 15:41:57.208 # Warning: no config file specified, using the default config. In order to specify a config file use redis-server /path/to/redis.conf
1:M 30 Oct 2023 15:41:57.208 * Increased maximum number of open files to 10032 (it was originally set to 1024).
1:M 30 Oct 2023 15:41:57.208 * monotonic clock: POSIX clock_gettime
1:M 30 Oct 2023 15:41:57.209 * Running mode=standalone, port=6379.
1:M 30 Oct 2023 15:41:57.209 * Server initialized
1:M 30 Oct 2023 15:41:57.210 * Ready to accept connections tcp
labsuser@master:~$
```

Note: When working with a pod that contains only one container, the **-c** flag is not necessary. However, for multi-container pods, specifying the container is crucial.

By following these steps, you have successfully established a multi-container pod within a Kubernetes cluster.