

Lesson 03 Demo 03 Create a React Program to Implement a Timer

Objective: To create a React program to implement a timer

Tools Required: Node terminal, React app, and Visual Studio Code

Prerequisites: Knowledge of creating a React app and understanding of the folder structure

Steps to be followed:

1. Create a new React app

- 2. Configure the file **src/App.js**
- 3. Create a new file called Timer.js
- 4. Run the app and verify the functionality

Step 1: Create a new React app

1.1. Open your terminal and run the following command to create a new **React** app: npx create-react-app timer-app

```
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

shreemayeebhatt@ip-172-31-22-250:~$ npx create-react-app timer-app
```

This will create a new **React** app in a directory named **timer-app**.

1.2. Navigate to the newly created directory by running the command cd timer-app



Step 2: Configure the file src/App.js

2.1 Open the React project in the Visual Studio code and navigate through the project directory of **timer-app** to open the **src/App.js** file. and replace the code in **App.js** with the following code:

```
JS App.js
                          ×
src > JS App.js > ...
       import React from 'react';
      import Timer from './Timer';
       function App() {
         return (
           <div>
             <h2>Timer App</h2>
             <Timer />
         );
 11
 12
       export default App;
 13
 14
```

This code defines the **App** component that renders the **Timer** component.



Step 3: Create a new file called Timer.js

export default Timer;

- 3.1 In your code editor, create a new file called **Timer.js** inside the **src** directory
- 3.2 Copy and paste the provided code into the **Timer.js** file

```
import React, { Component } from 'react';
class Timer extends Component {
 constructor(props) {
  super(props);
  this.state = {
   seconds: 0
 };
 }
 componentDidMount() {
  this.intervalId = setInterval(() => {
   this.setState(prevState => ({
    seconds: prevState.seconds + 1
   }));
  }, 1000);
 componentWillUnmount() {
  clearInterval(this.intervalId);
 }
 render() {
  return (
   <div>
    <h1>Timer: {this.state.seconds} seconds</h1>
    <button onClick={() => this.setState({ seconds: 0 })}>Reset</button>
   </div>
  );
 }
```



Step 4: Run the App and verify the functionality

- 4.1 Go to the terminal, and execute the command **npm start** within the project directory **timer-app** to run the app
- 4.2 Once the server starts successfully, open http://localhost:3000 in your browser to view and check the functionality of the app





In the browser, you will see the heading **Timer App** and a display of the seconds elapsed in the timer, starting from 0. The timer will increment by 1 every second. You can click on the **Reset** button to set the timer back to 0.

With this, you've implemented a **Timer app** using React.