

PYTHON TECHNICAL ASSESSMENT

Section 1: Output Basics

1. What is the default separator (sep) used in the print() function?

- A) `\n` (newline)
- B) `""` (empty string)
- C) `" "` (single space)
- D) `","` (comma)

2. Which argument determines what is printed at the very end of a print() statement?

- A) `sep`
- B) `end`
- C) `final`
- D) `stop`

3. What is the output of `print("A", "B", sep="->", end="!")`?

- A) `A B -> !`
- B) `A->B!`
- C) `AB->!`
- D) `A->B -> !`

4. How do you print a double newline using only the end parameter?

- A) `end="\n\n"`
- B) `end="2n"`
- C) `end="\n" * 2`
- D) `sep="\n\n"`

Section 2: String Formatting

5. What is the correct syntax for an f-string?

- A) `f("Value: {x}")`
- B) `f"Value: {x}"`
- C) `str(f"Value: x")`
- D) `"{f}Value: {x}"`

6. What do the curly braces {} do inside an f-string?

- A) Create a dictionary
- B) Start a code block
- C) Act as a placeholder to evaluate variables
- D) Print literal braces to the screen

7. What is the result of "{ } is {}".format("Python", "fun")?

- A) `{Python} is {fun}`
- B) `Python is fun`
- C) `fun is Python`
- D) `Python fun`

8. How do you format a float to exactly 2 decimal places in an f-string?

- A) `f"{val:.2f}"`
- B) `f"{val.2f}"`
- C) `f"{val:2}"`
- D) `f"{round(val, 2)}"`

Section 3: Input & Conversion

9. What data type does the `input()` function return by default?

- A) *int*
- B) *float*
- C) *str (string)*
- D) *None*

10. How do you correctly convert a user's input into an integer?

- A) *`x = int(input())`*
- B) *`x = input(int)`*
- C) *`x = input().int()`*
- D) *`int x = input()`*

11. What happens if you run `int(input())` and the user types 25.7?

- A) *It returns 25*
- B) *It returns 26*
- C) *It raises a `ValueError`*
- D) *It raises a `TypeError`*

Section 4: Split & Map

12. If a user inputs "A B C", what does `input().split()` return?

- A) "ABC"
- B) ["A", "B", "C"]
- C) ("A", "B", "C")
- D) ["A B C"]

13. What is the purpose of the `map()` function when taking input?

- A) To create a map or dictionary
- B) To apply a function (like `int`) to all parts of the input
- C) To sort the input data
- D) To remove extra spaces

14. How do you take two integers from one line of input?

- A) `a, b = int(input().split())`
- B) `a, b = map(int, input().split())`
- C) `a, b = input().split().map(int)`
- D) `a, b = map(input().split(), int)`

15. What is the result of `m1, m2 = map(float, ["10", "20"])`?

- A) `m1=10.0, m2=20.0`
- B) `m1="10", m2="20"`
- C) `m1=10, m2=20`
- D) It causes an error

Section 5: Advanced Logic

16. What happens if you set `sep=None` in a `print()` statement?

- A) No space is used
- B) The default single space is used
- C) It raises an error
- D) It prints the word "None"

17. What is the output of `print("Hi", end=" ")` followed by `print("Anil")`?

- A) `Hi\nAnil`
- B) `Hi Anil`
- C) `HiAnil`
- D) `Anil Hi`

18. What is the length of the list returned by `"1,2,3,4".split(",")`?

- A) 1
- B) 4
- C) 7
- D) 3

19. Which escape sequence represents a tab?

- A) `\t`
- B) `\b`
- C) `\n`
- D) `\r`

20. Which code will cause a `TypeError`?

- A) `print("Score: " + "10")`
- B) `print("Score:", 10)`
- C) `print("Score: " + 10)`
- D) `print(f"Score: {10}")`