

Package ‘ASCAT’

September 24, 2015

Type Package

Title Allele-Specific Copy Number Analysis of Tumours

Version 3.0

Date 2015-09-22

Author Peter Van Loo [aut, cre], Gro Nielsen [ctb], Jiqui Cheng [ctb], Stefan Dentre [ctb], Kerstin Haase [ctb]

Maintainer Kerstin Haase <Kerstin.Haase@crick.ac.uk>

Description R package of ASCAT as published in <http://www.ncbi.nlm.nih.gov/pubmed/20837533>

Depends R (>= 2.13.0),
RColorBrewer

License GPL-3

LazyLoad yes

R topics documented:

ascat.aspcf	1
ascat.GCcorrect	2
ascat.loadData	3
ascat.plotAscatProfile	4
ascat.plotNonRounded	5
ascat.plotRawData	6
ascat.plotSegmentedData	6
ascat.predictGermlineGenotypes	7
ascat.runAscat	8
runASCAT	9

Index	11
--------------	-----------

ascat.aspcf	<i>ascat.aspcf</i>
-------------	--------------------

Description

run ASPCF segmentation

Usage

```
ascat.aspcf(ASCATobj, selectsamples = 1:length(ASCATobj$samples),
  ascat.gg = NULL, penalty = 25)
```

Arguments

ASCATobj	an ASCAT object
selectsamples	a vector containing the sample number(s) to PCF. Default = all
ascat.gg	germline genotypes (NULL if germline data is available)
penalty	penalty of introducing an additional ASPCF breakpoint (expert parameter, don't adapt unless you know what you're doing)

Details

This function can be easily parallelised by controlling the selectsamples parameter it saves the results in LogR_PCFed[sample]_[segment].txt and BAF_PCFed[sample]_[segment].txt; if these files exist, the results are read from them. Hence, after parallelisation, copy all the files into the current directory, and run this function to read in the results

Value

output: ascat data structure containing:

1. Tumor_LogR data matrix
2. Tumor_BAF data matrix
3. Tumor_LogR_segmented: matrix of LogR segmented values
4. Tumor_BAF_segmented: list of BAF segmented values; each element in the list is a matrix containing the segmented values for one sample (only for probes that are germline homozygous)
5. Germline_LogR data matrix
6. Germline_BAF data matrix
7. SNPpos: position of all SNPs
8. ch: a list containing vectors with the indices for each chromosome (e.g. Tumor_LogR[ch[[13]],] will output the Tumor_LogR data of chromosome 13)
9. chr: a list containing vectors with the indices for each distinct part that can be segmented separately (e.g. chromosome arm, stretch of DNA between gaps in the array design)

ascat.GCcorrect

ascat.GCcorrect

Description

Corrects logR of the tumour sample(s) with genomic GC content

Usage

```
ascat.GCcorrect(ASCATobj, GCcontentfile = NULL)
```

Arguments

ASCATobj an ASCAT object
 GCcontentfile File containing the GC content around every SNP for increasing window sizes

Details

Note that probes not present in the GCcontentfile will be lost from the results

Value

ASCAT object with corrected tumour logR

ascat.loadData	<i>ascat.loadData</i>
----------------	-----------------------

Description

Function to read in SNP array data

Usage

```
ascat.loadData(Tumor_LogR_file, Tumor_BAF_file, Germline_LogR_file = NULL,
  Germline_BAF_file = NULL, chrs = c(1:22, "X", "Y"), gender = NULL,
  sexchromosomes = c("X", "Y"))
```

Arguments

Tumor_LogR_file file containing logR of tumour sample(s)
 Tumor_BAF_file file containing BAF of tumour sample(s)
 Germline_LogR_file file containing logR of germline sample(s), NULL
 Germline_BAF_file file containing BAF of germline sample(s), NULL
 chrs a vector containing the names for the chromosomes (e.g. c(1:22,"X"))
 gender a vector of gender for each cases ("XX" or "XY"). Default = all female ("XX")
 sexchromosomes a vector containing the names for the sex chromosomes

Details

germline data files can be NULL - in that case these are not read in

Value

ascat data structure containing:

1. Tumor_LogR data matrix
2. Tumor_BAF data matrix
3. Tumor_LogR_segmented: placeholder, NULL
4. Tumor_BAF_segmented: placeholder, NULL
5. Germline_LogR data matrix
6. Germline_BAF data matrix
7. SNPpos: position of all SNPs
8. ch: a list containing vectors with the indices for each chromosome (e.g. Tumor_LogR[ch[[13]],] will output the Tumor_LogR data of chromosome 13)
9. chr: a list containing vectors with the indices for each distinct part that can be segmented separately (e.g. chromosome arm, stretch of DNA between gaps in the array design)
10. gender: a vector of gender for each cases ("XX" or "XY"). Default = NULL: all female ("XX")

ascat.plotAscatProfile

ascat.plotAscatProfile

Description

ascat.plotAscatProfile

Usage

```
ascat.plotAscatProfile(n1all, n2all, heteroprobes, ploidy, rho, goodnessOfFit,
  nonaberrant, y_limit, nAfull, ch, lrr, bafsegmented, chrs, textFlag)
```

Arguments

n1all	copy number major allele
n2all	copy number minor allele
heteroprobes	probes with heterozygous germline
ploidy	ploidy of the sample
rho	purity of the sample
goodnessOfFit	estimated goodness of fit
nonaberrant	
y_limit	Optional parameter determining the size of the y axis in the nonrounded plot and ASCAT profile. Default=5
nAfull	copy number major allele
ch	a list containing c vectors, where c is the number of chromosomes and every vector contains all probe numbers per chromosome
lrr	(unsegmented) log R, in genomic sequence (all probes), with probe IDs
bafsegmented	B Allele Frequency, segmented, in genomic sequence (only probes heterozygous in germline), with probe IDs
chrs	a vector containing the names for the chromosomes (e.g. c(1:22,"X"))
textFlag	Optional flag to add the positions of fragments located outside of the plotting area to the plots. Default=F

Value

plot showing the ASCAT profile of the sample

ascat.plotNonRounded	<i>ascat.plotNonRounded</i>
----------------------	-----------------------------

Description

ascat.plotNonRounded

Usage

```
ascat.plotNonRounded(ploidy, rho, goodnessOfFit, nonaberrant, nAfull, nBfull,
  y_limit, ch, bafsegmented, lrr, chrs, textFlag)
```

Arguments

ploidy	ploidy of the sample
rho	purity of the sample
goodnessOfFit	estimated goodness of fit
nonaberrant	
nAfull	copy number major allele
nBfull	copy number minor allele
y_limit	Optional parameter determining the size of the y axis in the nonrounded plot and ASCAT profile. Default=5
ch	a list containing c vectors, where c is the number of chromosomes and every vector contains all probe numbers per chromosome
bafsegmented	B Allele Frequency, segmented, in genomic sequence (only probes heterozygous in germline), with probe IDs
lrr	(unsegmented) log R, in genomic sequence (all probes), with probe IDs
chrs	a vector containing the names for the chromosomes (e.g. c(1:22,"X"))
textFlag	Optional flag to add the positions of fragments located outside of the plotting area to the plots. Default=F

Value

plot showing the nonrounded copy number profile

ascat.plotRawData	<i>ascat.plotRawData</i>
-------------------	--------------------------

Description

Plots SNP array data

Usage

```
ascat.plotRawData(ASCATobj)
```

Arguments

ASCATobj an ASCAT object (e.g. data structure from ascat.loadData)

Value

Produces png files showing the logR and BAF values for tumour and germline samples

ascat.plotSegmentedData	<i>ascat.plotSegmentedData</i>
-------------------------	--------------------------------

Description

plots the SNP array data before and after segmentation

Usage

```
ascat.plotSegmentedData(ASCATobj)
```

Arguments

ASCATobj an ASCAT object (e.g. from ascat.aspcf)

Value

png files showing raw and segmented tumour logR and BAF

```
ascat.predictGermlineGenotypes
      ascat.predictGermlineGenotypes
```

Description

predicts the germline genotypes of samples for which no matched germline sample is available

Usage

```
ascat.predictGermlineGenotypes(ASCATobj, platform = "AffySNP6")
```

Arguments

ASCATobj	an ASCAT object
platform	used array platform

Details

Currently possible values for platform:

AffySNP6 (default)
 Custom10k
 Illumina109k
 IlluminaCytoSNP
 Illumina610k
 Illumina660k
 Illumina700k
 Illumina1M
 Illumina2.5M
 IlluminaOmni5
 Affy10k
 Affy100k
 Affy250k_sty
 Affy250k_nsp
 AffyOncoScan
 AffyCytoScanHD

Value

predicted germline genotypes

ascat.runAscat	<i>ascat.runAscat</i>
----------------	-----------------------

Description

ASCAT main function, calculating the allele-specific copy numbers

Usage

```
ascat.runAscat(ASCATobj, gamma = 0.55, pdfPlot = F, y_limit = 5,
  textFlag = F, rho_manual = NA, psi_manual = NA)
```

Arguments

ASCATobj	an ASCAT object from ascat.aspcf
gamma	technology parameter, compaction of Log R profiles (expected decrease in case of deletion in diploid sample, 100% aberrant cells; 1 in ideal case, 0.55 of Illumina 109K arrays)
pdfPlot	Optional flag if nonrounded plots and ASCAT profile in pdf format are desired. Default=F
y_limit	Optional parameter determining the size of the y axis in the nonrounded plot and ASCAT profile. Default=5
textFlag	Optional flag to add the positions of fragments located outside of the plotting area to the plots. Default=F
rho_manual	optional argument to override ASCAT optimization and supply rho parameter (not recommended)
psi_manual	optional argument to override ASCAT optimization and supply psi parameter (not recommended)

Details

Note: for copy number only probes, nA contains the copy number value and nB = 0.

Value

an ASCAT output object, containing:

1. nA: copy number of the A allele
2. nB: copy number of the B allele
3. aberrantcellfraction: the aberrant cell fraction of all arrays
4. ploidy: the ploidy of all arrays
5. failedarrays: arrays on which ASCAT analysis failed
6. nonaberrantarrays: arrays on which ASCAT analysis indicates that they show virtually no aberrations
7. segments: an array containing the copy number segments of each sample (not including failed arrays)
8. segments_raw: an array containing the copy number segments of each sample without any rounding applied

runASCAT	<i>runASCAT</i>
----------	-----------------

Description

the ASCAT main function

Usage

```
runASCAT(lrr, baf, lrrsegmented, bafsegmented, gender, SNPpos, chromosomes,
  chrnames, sexchromosomes, failedqualitycheck = F, distancepng = NA,
  copynumberprofilespng = NA, nonroundedprofilepng = NA,
  aberrationreliabilitypng = NA, gamma = 0.55, rho_manual = NA,
  psi_manual = NA, pdfPlot = F, y_limit = 5, textFlag = F)
```

Arguments

lrr	(unsegmented) log R, in genomic sequence (all probes), with probe IDs
baf	(unsegmented) B Allele Frequency, in genomic sequence (all probes), with probe IDs
lrrsegmented	log R, segmented, in genomic sequence (all probes), with probe IDs
bafsegmented	B Allele Frequency, segmented, in genomic sequence (only probes heterozygous in germline), with probe IDs
SNPpos	position of all SNPs
chromosomes	a list containing c vectors, where c is the number of chromosomes and every vector contains all probe numbers per chromosome
chrnames	a vector containing the names for the chromosomes (e.g. c(1:22,"X"))
sexchromosomes	a vector containing the names for the sex chromosomes
failedqualitycheck	did the sample fail any previous quality check or not?
distancepng	if NA: distance is plotted, if filename is given, the plot is written to a .png file
copynumberprofilespng	if NA: possible copy number profiles are plotted, if filename is given, the plot is written to a .png file
nonroundedprofilepng	if NA: copy number profile before rounding is plotted (total copy number as well as the copy number of the minor allele), if filename is given, the plot is written to a .png file
aberrationreliabilitypng	if NA: aberration reliability score is plotted, if filename is given, the plot is written to a .png file
gamma	technology parameter, compaction of Log R profiles (expected decrease in case of deletion in diploid sample, 100% aberrant cells; 1 in ideal case, 0.55 of Illumina 109K arrays)
rho_manual	optional argument to override ASCAT optimization and supply rho parameter (not recommended)

psi_manual	optional argument to override ASCAT optimization and supply psi parameter (not recommended)
pdfPlot	Optional flag if nonrounded plots and ASCAT profile in pdf format are desired. Default=F
y_limit	Optional parameter determining the size of the y axis in the nonrounded plot and ASCAT profile. Default=5
textFlag	Optional flag to add the positions of fragments located outside of the plotting area to the plots. Default=F
gender:	a vector of gender for each cases ("XX" or "XY"). Default = NULL: all female ("XX")

Value

a list containing optimal purity and ploidy

Index

ascat.aspcf, [1](#)
ascat.GCcorrect, [2](#)
ascat.loadData, [3](#)
ascat.plotAscatProfile, [4](#)
ascat.plotNonRounded, [5](#)
ascat.plotRawData, [6](#)
ascat.plotSegmentedData, [6](#)
ascat.predictGermlineGenotypes, [7](#)
ascat.runAscat, [8](#)

runASCAT, [9](#)