REST API

REST STANDS FOR **R**EPRESENTATIONAL **S**TATE **T**RANSFER

REST APIS OPERATE ON A SIMPLE REQUEST/RESPONSE SYSTEM

REQUEST

RESPONSE

CLIENT CAN MAKE A REQUEST USING HTTP METHODS

SERVER RETURNS A RESPONSE WITH AN HTTP STATUS CODE

THESE METHODS ARE:
GET, POST, PUT, PATCH, DELETE, HEAD, TRACE, OPTIONS, CONNECT

POPULAR HTTP STATUS CODE:
EX, 200, 202, 403, 404, 500 ETC

HTTP REQUEST CONTAINS

REQUEST METHOD   HTTP HEADERS   BODY

HTTP RESPONSE CONTAINS

STATUS CODE   HTTP HEADERS   RESPONSE BODY

★ REST API CONSTRAINTS ★

CLIENT-SERVER ARCHITECTURE
- NO THIRD PARTY INTERPRETATION

UNIFORM INTERFACE
- FOLLOW A COMMON PROTOCOL

LAYERING
- MULTIPLE INTERMEDIARIES BETWEEN CLIENT AND SERVER

CACHEABILITY
- RESPONSE CAN BE CACHEABLE

STATELESSNESS
- THERE IS NO STATE. CLIENT AND SERVER ARE COMPLETELY SEPARATED

HTTP HEADERS

CLIENT AND SERVER CAN PASS THE EXTRA BIT OF INFORMATION WITH THE REQUEST AND RESPONSE USING HTTP HEADERS

DIVIDED INTO FOUR PARTS

REQUEST HEADERS
- CLIENT TO SERVER

RESPONSE HEADERS
- SERVER TO CLIENT

REPRESENTATION HEADERS
- INFORMATION ABOUT THE BODY OF THE RESOURCE

PAYLOAD HEADERS
- INFORMATION ABOUT THE PAYLOAD DATA

WIDELY USED HTTP HEADERS

Accept
TYPE OF DATA CLIENT CAN UNDERSTAND

Content-Type
SPECIFIES THE MEDIA TYPE OF THE RESOURCE

Accept-Encoding
WHICH ENCODING METHOD CLIENT CAN UNDERSTAND

Host
SPECIFIES THE DOMAIN NAME

Authorization
USED TO PASS CREDENTIALS SO THAT SERVER CAN AUTHENTICATE

Access-Control-Allow-Origin
WHICH ORIGIN IS ALLOWED TO ACCESS THE RESOURCES

Accept-Language
CLIENT IS EXPECTING THE RESPONSE IN THE MENTIONED LANGUAGE

Access-Control-Allow-Methods
WHICH METHODS ARE ALLOWED TO ACCESS THE CROSS-ORIGIN RESOURCES

HTTP STATUS CODES

REQUEST

GET /POSTS

200 OK

RESPONSE

CLIENT

SERVER

★ SERVER ALWAYS RETURNS HTTP STATUS CODE WITH THE RESPONSE ★

SUCCESSFUL RESPONSES

200 OK
EVERYTHING IS FINE

201 CREATED
NEW RESOURCE WAS CREATED

REDIRECTION MESSAGES

301 MOVED PERMANENTLY
THE RESOURCE HAS BEEN MOVED PERMANENTLY TO THE NEW URL

CLIENT ERROR

400 BAD REQUEST
INVALID SYNTAX

401 UNAUTHORIZED
CREDENTIALS ARE INCORRECT

403 FORBIDDEN
YOU DON'T HAVE PERMISSION TO ACCESS THE RESOURCES

404 NOT FOUND
INVALID URL

429 TOO MANY REQUESTS
USER HAS SENT TOO MANY REQUESTS IN A GIVEN AMOUNT OF TIME

SERVER ERROR

500 INTERNAL SERVER ERROR
SERVER DOES NOT KNOW HOW TO HANDLE THE UNEXPECTED SITUATION

HTTP Request Methods

```
GET /apis
200 OK
```

GET

The GET method is the most common of all these request methods.
It is used to fetch the desired resources from the server.

POST

The POST method is used to submit the information to the server.
As we're submitting data, the POST method often changes the state of the server.

PUT

The PUT method is used whenever you need to change the resource. The resource, which is already a part of resource collection.

PATCH

The PATCH request method is used to modify only the necessary part of the data or response.
The PATCH method doesn't modify the entire response.

DELETE

As the name says, the DELETE request method is used to delete the specified resource. It requests that the origin server delete the resource identified by the Request-URL.

Access Control HTTP Headers

ORIGIN

Request

Origin: https://a.com

a.com

b.com

Browser

IT'S A CROSS-ORIGIN REQUEST. LET ME ADD THE ORIGIN HEADER TO TELL THE SERVER WHERE THE REQUEST IS COMING FROM.

ACCESS-CONTROL-REQUEST-METHOD

I WANT TO MAKE A CROSS-ORIGIN POST REQUEST.

a.com

LET ME ASK THE SERVER.

Access-Control-Request-Method: POST

Browser

b.com

THIS IS A PREFLIGHT REQUEST TO LET THE SERVER KNOW WHICH METHOD WILL BE USED IN THE MAIN REQUEST.

b.com

A.COM ORIGIN IS ALLOWED TO ACCESS RESOURCES FROM B.COM

Access-Control-Allow-Origin: a.com

Access-Control-Allow-Methods: POST

Access-Control-Allow-Credentials: true

THIS IS THE RESPONSE TO THE PREFLIGHT REQUEST INDICATING THAT MAIN REQUEST CAN BE MADE USING CREDENTIALS.

a.com

POST METHOD IS ALLOWED TO ACCESS CROSS-ORIGIN RESOURCES. THIS IS THE RESPONSE TO THE PREFLIGHT REQUEST.

Browser

Browser