



AWK command in Unix/Linux with examples

[Read](#)[Discuss\(20\)](#)

Awk is a scripting language used for manipulating data and generating reports. The awk command programming language requires no compiling and allows the user to use variables, numeric functions, string functions, and logical operators.

Awk is a utility that enables a programmer to write tiny but effective programs in the form of statements that define text patterns that are to be searched for in each line of a document and the action that is to be taken when a match is found within a line. Awk is mostly used for pattern scanning and processing. It searches one or more files to see if they contain lines that matches with the specified patterns and then perform the associated actions.

Awk is abbreviated from the names of the developers – Aho, Weinberger, and Kernighan.

WHAT CAN WE DO WITH AWK?

1. AWK Operations:

- (a) Scans a file line by line
- (b) Splits each input line into fields
- (c) Compares input line/fields to pattern

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

2. Useful For:

- (a) Transform data files
- (b) Produce formatted reports

3. Programming Constructs:

- (a) Format output lines
- (b) Arithmetic and string operations
- (c) Conditionals and loops

Syntax:

```
awk options 'selection _criteria {action }' input-file > output-file
```

Options:

```
-f program-file : Reads the AWK program source from the file  
                  program-file, instead of from the  
                  first command line argument.  
-F fs           : Use fs for the input field separator
```

Sample Commands

Example:

Consider the following text file as the input file for all cases below:

```
$cat > employee.txt  
  
ajay manager account 45000  
sunil clerk account 25000  
varun manager sales 50000  
amit manager account 47000  
tarun peon sales 15000  
deepak clerk sales 23000  
sunil peon sales 13000  
satvik director purchase 80000
```

1. Default behavior of Awk: By default Awk prints every line of data from the specified file.



```
$ awk '{print}' employee.txt
```

Output:

```
ajay manager account 45000
sunil clerk account 25000
varun manager sales 50000
amit manager account 47000
tarun peon sales 15000
deepak clerk sales 23000
sunil peon sales 13000
satvik director purchase 80000
```

In the above example, no pattern is given. So the actions are applicable to all the lines. Action print without any argument prints the whole line by default, so it prints all the lines of the file without failure.

2. Print the lines which match the given pattern.

```
$ awk '/manager/ {print}' employee.txt
```

Output:

```
ajay manager account 45000
varun manager sales 50000
amit manager account 47000
```

In the above example, the awk command prints all the line which matches with the 'manager'.

3. Splitting a Line Into Fields : For each record i.e line, the awk command splits the

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

line has 4 words, it will be stored in \$1, \$2, \$3 and \$4 respectively. Also, \$0 represents the whole line.

```
$ awk '{print $1,$4}' employee.txt
```

Output:

```
ajay 45000
sunil 25000
varun 50000
amit 47000
tarun 15000
deepak 23000
sunil 13000
satvik 80000
```

In the above example, \$1 and \$4 represents Name and Salary fields respectively.

Built-In Variables In Awk

Awk's built-in variables include the field variables—\$1, \$2, \$3, and so on (\$0 is the entire line) — that break a line of text into individual words or pieces called fields.

- **NR:** NR command keeps a current count of the number of input records. Remember that records are usually lines. Awk command performs the pattern/action statements once for each record in a file.
- **NF:** NF command keeps a count of the number of fields within the current input record.
- **FS:** FS command contains the field separator character which is used to divide fields on the input line. The default is “white space”, meaning space and tab characters. FS can be reassigned to another character (typically in BEGIN) to change the field separator.
- **RS:** RS command stores the current record separator character. Since, by default, an input line is the input record, the default record separator character is a newline.
- **OFS:** OFS command stores the output field separator, which separates the fields when Awk prints them. The default is a blank space. Whenever print has several parameters separated with commas, it will print the value of OFS in between each parameter.
- **ORS:** ORS command stores the output record separator, which separates the output lines when Awk prints them. The default is a newline character. print automatically outputs the contents of ORS at the end of whatever it is given to print.

Examples:

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```
$ awk '{print NR,$0}' employee.txt
```

Output:

```
1 ajay manager account 45000
2 sunil clerk account 25000
3 varun manager sales 50000
4 amit manager account 47000
5 tarun peon sales 15000
6 deepak clerk sales 23000
7 sunil peon sales 13000
8 satvik director purchase 80000
```

In the above example, the awk command with NR prints all the lines along with the line number.

Use of NF built-in variables (Display Last Field)

```
$ awk '{print $1,$NF}' employee.txt
```

Output:

```
ajay 45000
sunil 25000
varun 50000
amit 47000
tarun 15000
deepak 23000
sunil 13000
satvik 80000
```

In the above example \$1 represents Name and \$NF represents Salary. We can get the Salary using \$NF , where \$NF represents last field.

Another use of NR built-in variables (Display Line From 3 to 6)

```
$ awk 'NR==3, NR==6 {print NR,$0}' employee.txt
```

Output:

```
3 varun manager sales 50000
. . . . .
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```
5 tarun peon sales 15000
6 deepak clerk sales 23000
```

More Examples

For the given text file:

```
$cat > geeksforgeeks.txt
```

```
A      B      C
Tarun   A12     1
Man     B6      2
Praveen M42     3
```

1) To print the first item along with the row number(NR) separated with " – " from each line in geeksforgeeks.txt:

```
$ awk '{print NR "- " $1 }' geeksforgeeks.txt
```

```
1 - A
2 - Tarun
3 - Manav
4 - Praveen
```

2) To return the second column/item from geeksforgeeks.txt:

The question should be:- To return the second column/item from geeksforgeeks.txt:

```
$ awk '{print $2}' geeksforgeeks.txt
```

```
B
A12
B6
M42
```

3) To print any non empty line if present

```
$ awk 'NF < 0' geeksforgeeks.txt
```

here NF should be 0 not less than and the user have to print the line number also:

```
awk 'NF < 0 {print NR}' geeksforgeeks.txt
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```
awk 'NF <= 0 {print NR}' geeksforgeeks.txt
```

0

4) To find the length of the longest line present in the file:

```
$ awk '{ if (length($0) > max) max = length($0) } END { print max }'  
geeksforgeeks.txt
```

13

5) To count the lines in a file:

```
$ awk 'END { print NR }' geeksforgeeks.txt
```

3

6) Printing lines with more than 10 characters:

```
$ awk 'length($0) > 10' geeksforgeeks.txt
```

```
Tarun    A12    1  
Praveen  M42    3
```

7) To find/check for any string in any specific column:

```
$ awk '{ if($3 == "B6") print $0;}' geeksforgeeks.txt
```

8) To print the squares of first numbers from 1 to n say 6:

```
$ awk 'BEGIN { for(i=1;i<=6;i++) print "square of", i, "is",i*i; }'
```

```
square of 1 is 1  
square of 2 is 4  
square of 3 is 9  
square of 4 is 16  
square of 5 is 25  
square of 6 is 36
```

This article is contributed by **Anshika Goval** and **Praveen Nedi**. If you like GeeksforGeeks

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

or mail your article to review-team@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

Last Updated : 17 Jun, 2022

208

[Previous](#)

[Next](#)

Article Contributed By :



GeeksforGeeks

Vote for difficulty

Current difficulty : [Easy](#)

Easy

Normal

Medium

Hard

Expert

Article Tags : [linux-command](#), [Linux-text-processing-commands](#), [Linux-Unix](#)

[Improve Article](#)

[Report Issue](#)



GeeksforGeeks

A-143, 9th Floor, Sovereign Corporate Tower,
Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Company

[About Us](#)

[Careers](#)

[In Media](#)

Languages

[Python](#)

[Java](#)

[C++](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

[Terms and Conditions](#)[SQL](#)[Privacy Policy](#)[R Language](#)[Copyright Policy](#)[Android Tutorial](#)[Third-Party Copyright Notices](#)[Advertise with us](#)

Data Structures

[Array](#)[String](#)[Linked List](#)[Stack](#)[Queue](#)[Tree](#)[Graph](#)

Algorithms

[Sorting](#)[Searching](#)[Greedy](#)[Dynamic Programming](#)[Pattern Searching](#)[Recursion](#)[Backtracking](#)

Web Development

[HTML](#)[CSS](#)[JavaScript](#)[Bootstrap](#)[ReactJS](#)[AngularJS](#)[NodeJS](#)

Write & Earn

[Write an Article](#)[Improve an Article](#)[Pick Topics to Write](#)[Write Interview Experience](#)[Internships](#)[Video Internship](#)

Computer Science

[GATE CS Notes](#)[Operating Systems](#)[Computer Network](#)[Database Management System](#)[Software Engineering](#)[Digital Logic Design](#)[Engineering Maths](#)

Data Science & ML

[Data Science With Python](#)[Data Science For Beginner](#)[Machine Learning Tutorial](#)[Maths For Machine Learning](#)[Pandas Tutorial](#)[NumPy Tutorial](#)[NLP Tutorial](#)

Interview Corner

[Company Preparation](#)[Preparation for SDE](#)

Python

[Python Tutorial](#)[Python Programming Examples](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

[Experienced Interview](#)[Python Projects](#)[Internship Interview](#)[Python Tkinter](#)[Competitive Programming](#)[OpenCV Python Tutorial](#)[Aptitude](#)

GfG School

[CBSE Notes for Class 8](#)[SSC CGL Syllabus](#)[CBSE Notes for Class 9](#)[SBI PO Syllabus](#)[CBSE Notes for Class 10](#)[IBPS PO Syllabus](#)[CBSE Notes for Class 11](#)[UPSC Ethics Notes](#)[CBSE Notes for Class 12](#)[UPSC Economics Notes](#)[English Grammar](#)[UPSC History Notes](#)

@geeksforgeeks , Some rights reserved