

# Team notebook

ACLimitExceeded (Animesh Sinha, Gaurang Tandon, Arpan Dasgupta)

December 25, 2019

## Contents

1	DisjointSets	1
2	DynamicProgramming	2
3	FastFourier	3
4	FlowAlgorithms	5
5	Geometry	8
6	GraphAlgorithms	8
7	MathematicsTheory	10
7.1	Mobius Inversions	10
7.2	Chinese Remainder Theorem	10
8	MatrixTools	11
9	MergeSortTree	13
10	Miscellaneous	14
11	MobiusSieve	15
12	PalindromicTree	16
13	SegmentTree	16

14	StonglyConnected	18
15	StringAlgorithms	19
16	TreapsIntervals	22
17	TreesCentroids	23

## 1 DisjointSets

---

```
#include "template.hpp"

struct DisjointSetTree {
    ll comp_count; vll parent, comp_size; set<ll> roots;
    DisjointSetTree(int n) {
        comp_count = n; parent.resize(n); comp_size.resize(n, 1);
        iota(parent.begin(), parent.end(), 0);
        for (int i = 0; i < n; i++) roots.insert(i);
    }
    int find(int u) {
        if (parent[u] == u) return parent[u];
        return parent[u] = find(parent[u]);
    }
    bool merge(int u, int v) {
        u = find(u), v = find(v); if (u == v) return false;
        parent[u] = v; comp_size[v] += comp_size[u]; comp_size[u]
            = 0;
        roots.erase(u); comp_count--; return true;
    }
};
```

```

    }
};

class DynamicConnectivity {
    void __dfs(int v, int l, int r, vector<long long>& res) {
        long long last_ans = answer;
        int state = save_ptr;
        for (auto query : tree[v]) merge(query);
        if (l == r - 1) res[l] = answer;
        else {
            int m = (l + r) / 2;
            __dfs(v * 2 + 1, l, m, res);
            __dfs(v * 2 + 2, m, r, res);
        }
        while (save_ptr != state) rollback();
        answer = last_ans;
    };

public:
    int size_nodes, size_query;
    struct Node { long long parent, comp_size = 1; };
    ll answer = 0;
    vector<Node> data;
    vector<long long*> saved_object;
    vector<long long> saved_value;
    int save_ptr = 0;

    struct Query {
        int u, v;
        Query(pair<int, int> p = {0, 0}) { u = p.first, v =
            p.second; }
    };
    vector<vector<Query>> tree;
    DynamicConnectivity(int n = 600000, int q = 300000) {
        size_nodes = n, size_query = q; int tree_size = 1;
        while (tree_size < q) tree_size <= 1;
        data = vector<Node>(n);
        tree = vector<vector<Query>>(2 * tree_size);
        saved_object = vector<long long*>(4 * q);
        saved_value = vector<long long>(4 * q);
        for (int i = 0; i < n; i++)

```

```

        data[i].parent = i;
        answer = n; // Storing the initial answer
    }
    void change(long long& x, long long y) {
        saved_object[save_ptr] = &x; saved_value[save_ptr] = x;
        x = y; save_ptr++;
    }
    void rollback() {
        save_ptr--;
        (*saved_object[save_ptr]) = saved_value[save_ptr];
    }
    int find(int x) {
        if (data[x].parent == x) return x;
        return find(data[x].parent);
    }
    void merge(const Query& q) {
        int x = find(q.u); int y = find(q.v);
        if (x == y) return;
        if (data[x].comp_size < data[y].comp_size) swap(x, y);
        change(data[y].parent, x);
        change(data[x].comp_size, data[x].comp_size +
            data[y].comp_size);
        // Changing the Answer on query
        change(answer, answer - 1);
    }
    void add(int l, int r, Query edge, int node = 0, int x = 0,
        int y = -1) {
        if (y == -1) y = size_query;
        if (l >= r) return;
        if (l == x && r == y) tree[node].push_back(edge);
        else {
            int m = (x + y) / 2;
            add(l, min(r, m), edge, node * 2 + 1, x, m);
            add(max(m, l), r, edge, node * 2 + 2, m, y);
        }
    }
    vector<long long> solve(int v = 0, int l = 0, int r = -1) {
        if (r == -1) r = size_query;
        vector<long long> vec(size_query);
        if (size_query > 0) __dfs(v, l, r, vec);
        return vec;
    }

```

```

}
DynamicConnectivity(int n, vector<Query> queries) :
    DynamicConnectivity(n, queries.size()) {
    map<pair<int, int>, int> last;
    for (int i = 0; i < size_query; i++) {
        pair<int, int> p(queries[i].u, queries[i].v);
        if (last.count(p)) { add(last[p], i, queries[i]);
            last.erase(p); }
        else { last[p] = i; }
    }
    for (auto x : last) add(x.second, size_query, x.first);
};

```

---

## 2 DynamicProgramming

```

#include "template.hpp"

class LineContainer {
private:
    struct Line {
        mutable long long slope, constt, p;
        bool operator<(const Line &o) const { return slope <
            o.slope; }
        bool operator<(long long x) const { return p < x; }
    };
    multiset<Line, less<>> lines;
    // (for doubles, use inf = 1/.0, div(a,b) = a/b)
    bool __is_max_query = false; const long long inf = LLONG_MAX;
    long long __div(long long a, long long b) { return a / b - ((a
        ^ b) < 0 && a % b); } // floored division
    bool __intersect(multiset<Line>::iterator x,
        multiset<Line>::iterator y) {
        if (y == lines.end()) { x->p = inf; return false; }
        if (x->slope == y->slope) x->p = x->constt > y->constt ?
            inf : -inf;
        else x->p = __div(y->constt - x->constt, x->slope -
            y->slope);
        return x->p >= y->p;
    }
};

```

```

}
public:
    LineContainer(bool is_max = false) { this->__is_max_query =
        is_max; }
    void add(long long slope, long long constt) {
        if (!__is_max_query) { slope = -slope; constt = -constt; }
        auto z = lines.insert({slope, constt, 0}), y = z++, x = y;
        while (__intersect(y, z)) z = lines.erase(z);
        if (x != lines.begin() && __intersect(--x, y))
            __intersect(x, y = lines.erase(y));
        while ((y = x) != lines.begin() && (--x)->p >= y->p)
            __intersect(x, lines.erase(y));
    }
    long long query(long long x) {
        assert(!lines.empty());
        auto l = *lines.lower_bound(x);
        return (l.slope * x + l.constt) * (__is_max_query ? 1 :
            -1);
    }
};

void dp_sos(vll &arr) {
    const int bitsize = 20;
    for (int i = 0; i < bitsize; ++i)
        for (int mask = 0; mask < (1 << bitsize); ++mask)
            if (mask & (1 << i)) arr[mask] += arr[mask ^ (1 << i)];
}

```

---

## 3 FastFourier

```

#include "template.hpp"
const double PI = acos(-1);

#ifdef IS_FFT
    using cd = complex<double>;
#else
    using cd = int;
#endif
// use llround(a[i].real()) when printing FFT output

```

```

struct Polynomial {
    static const int root = 565042129;
    static const int root_1 = 950391366;
    static const int root_pw = 1 << 20;
    static const int mod = 998244353;

    static int __mod_pow(int a, int n) {
        int res = 1;
        for (a %= mod; n > 0; n >>= 1) {
            if (n & 1) res = (int)((1LL * res * a) % mod);
            a = (int)((a * 1ll * a) % mod);
        } return res;
    }
    int order;
    vector<cd> coeff;
    explicit Polynomial() : order(0), coeff(vector<cd>(0)) {}
    explicit Polynomial(vector<cd> coefficients)
        : order((int)coefficients.size()), coeff(coefficients) {}
    Polynomial(const Polynomial &copy)
        : order(copy.order), coeff(vector<cd>(copy.coeff)) {}
    void resize(int nOrder) {
        int size = 1 << (1ll)ceil(log2(nOrder));
        coeff.resize(size, 0);
    }

#ifdef IS_FFT
    void fft(bool invert = false) {
        int n = (int)coeff.size();
        for (int i = 1, j = 0; i < n; i++) {
            int bit = n >> 1;
            for (; j & bit; bit >>= 1) j ^= bit;
            j ^= bit;
            if (i < j) swap(coeff[i], coeff[j]);
        }
        for (int len = 2; len <= n; len <= 1) {
            double ang = 2 * PI / len * (invert ? -1 : 1);
            cd wlen(cos(ang), sin(ang));
            for (int i = 0; i < n; i += len) {

```

```

                cd w(1);
                for (int j = 0; j < len / 2; j++) {
                    cd u = coeff[i + j], v = coeff[i + j + len / 2]
                        * w;
                    coeff[i + j] = u + v;
                    coeff[i + j + len / 2] = u - v;
                    w *= wlen;
                }
            }
        }
        if (invert) { for (cd &x : coeff) x /= n; }
    }
#else
    void fft(bool invert = false) {
        int n = (int)coeff.size();
        for (int i = 1, j = 0; i < n; i++) {
            int bit = n >> 1;
            for (; j & bit; bit >>= 1)
                j ^= bit;
            j ^= bit;
            if (i < j)
                swap(coeff[i], coeff[j]);
        }
        for (int len = 2; len <= n; len <= 1) {
            int wlen = invert ? root_1 : root;
            for (int i = len; i < root_pw; i <= 1)
                wlen = (int)(1LL * wlen * wlen % mod);
            for (int i = 0; i < n; i += len) {
                int w = 1;
                for (int j = 0; j < len / 2; j++) {
                    int u = coeff[i + j],
                        v = (int)(1LL * coeff[i + j + len / 2] * w %
                            mod);
                    coeff[i + j] = u + v < mod ? u + v : u + v -
                        mod;
                    coeff[i + j + len / 2] = u - v >= 0 ? u - v : u
                        - v + mod;
                    w = (int)(1LL * w * wlen % mod);
                }
            }
        }
    }

```

```

    if (invert) {
        int n_1 = __mod_pow(n, mod - 2);
        for (auto &x : coeff)
            x = (int)(1LL * x * n_1 % mod);
    }
}
#endif

friend Polynomial operator*(const Polynomial &a, const
    Polynomial &b) {
    Polynomial x(a), y(b);
    int order = a.order + b.order;
    order = 1 << (11)ceil(log2(order));
    x.resize(order), y.resize(order);
    x.fft(), y.fft();

    for (int i = 0; i < order; i++) {
#ifdef IS_FFT
        x.coeff[i] = (x.coeff[i] * y.coeff[i]);
#else
        x.coeff[i] = (int)((1ll * x.coeff[i] * y.coeff[i]) %
            mod);
#endif
    }
    x.fft(true);
    return x;
}

friend Polynomial operator^(const Polynomial &a, int power) {
    Polynomial x(a);
    int order = a.order * power;
    x.resize(order);
    x.fft();
    int size = (int)x.coeff.size();
    vector<cd> poly(size);
    Polynomial res(poly);
#ifdef IS_FFT
    for (int i = 0; i < size; i++)
        poly[i] = pow(x.coeff[i], power);
#else
    for (int i = 0; i < size; i++)
        poly[i] = __mod_pow(x.coeff[i], power);

```

```

#endif
    res.fft(true);
    res.order = order;
    return res;
}
};

// Code for finding closest match by Hamming distance of r in s
// |r| <= |s|
// we reverse polynomial r and multiply with s
// for (11 i = (int)r.size() - 1 - 1; i < s.size(); i++)
//     res[i] += z.coeff[i]; // z is the multiplication result
// answers contained in res[sz(r) - 1] to res[sz(s) - 1]

```

## 4 Flow Algorithms

```

#include "template.hpp"

#define AVG_CASE
#ifdef AVG_CASE
struct Edge {
    11 from, to, cap, flow, index;
    Edge(11 dfrom, 11 dto, 11 dcap, 11 dflow, 11 dindex)
        : from(dfrom), to(dto), cap(dcap), flow(dflow),
            index(dindex) {
    }
};
struct PushRelabel {
    11 N;
    vector<vector<Edge>> G;
    vector<11> excess;
    vector<11> dist, active, count;
    queue<11> Q;
    PushRelabel(11 dN)
        : N(dN), G(N), excess(N), dist(N), active(N), count(2 * N)
        {
    }
    void addEdge(11 from, 11 to, 11 cap) {
        G[from].push_back(Edge(from, to, cap, 0, G[to].size()));
    }

```

```

    if (from == to)
        G[from].back().index++;
    G[to].push_back(Edge(to, from, 0, 0, G[from].size() - 1));
}
void Enqueue(ll v) {
    if (!active[v] && excess[v] > 0) {
        active[v] = true;
        Q.push(v);
    }
}
void Push(Edge &e) {
    ll amt = ll(min(excess[e.from], ll(e.cap - e.flow)));
    if (dist[e.from] <= dist[e.to] || amt == 0)
        return;
    e.flow += amt;
    G[e.to][e.index].flow -= amt;
    excess[e.to] += amt;
    excess[e.from] -= amt;
    Enqueue(e.to);
}
void Gap(ll k) {
    for (ll v = 0; v < N; v++) {
        if (dist[v] < k)
            continue;
        count[dist[v]]--;
        dist[v] = max(dist[v], N + 1);
        count[dist[v]]++;
        Enqueue(v);
    }
}
void Relabel(ll v) {
    count[dist[v]]--;
    dist[v] = 2 * N;
    for (ll i = 0; i < (ll)G[v].size(); i++)
        if (G[v][i].cap - G[v][i].flow > 0)
            dist[v] = min(dist[v], dist[G[v][i].to] + 1);
    count[dist[v]]++;
    Enqueue(v);
}
void Discharge(ll v) {
    for (ll i = 0; excess[v] > 0 && i < (ll)G[v].size(); i++)

```

```

        Push(G[v][i]);
    if (excess[v] > 0) {
        if (count[dist[v]] == 1)
            Gap(dist[v]);
        else
            Relabel(v);
    }
}
ll maxFlow(ll s, ll t) {
    count[0] = N - 1;
    count[N] = 1;
    dist[s] = N;
    active[s] = active[t] = true;
    for (ll i = 0; i < (ll)G[s].size(); i++) {
        excess[s] += G[s][i].cap;
        Push(G[s][i]);
    }
    while (!Q.empty()) {
        ll v = Q.front();
        Q.pop();
        active[v] = false;
        Discharge(v);
    }
    ll totflow = 0;
    for (ll i = 0; i < (ll)G[s].size(); i++)
        totflow += G[s][i].flow;
    return totflow;
}
};
#else
struct Edge {
    int u, v;
    ll cap, flow;
    Edge() : u(0), v(0), cap(0), flow(0) {}
    Edge(int uu, int vv, ll ccap) : u(uu), v(vv), cap(ccap),
        flow(0) {}
};
struct Dinic {
    int N;

```

```

vector<Edge> E;
vector<vector<int>> g;
vector<int> d, pt;
Dinic(int NN) : N(NN), E(0), g(N), d(N), pt(N) {
}
void addEdge(int u, int v, ll cap, ll rcap = 0) {
    if (u != v) {
        E.emplace_back(Edge(u, v, cap));
        g[u].emplace_back(E.size() - 1);
        E.emplace_back(Edge(v, u, rcap));
        g[v].emplace_back(E.size() - 1);
    }
}
bool BFS(int S, int T) {
    queue<int> q({S});
    fill(d.begin(), d.end(), N + 1);
    d[S] = 0;
    while (!q.empty()) {
        int u = q.front();
        q.pop();
        if (u == T)
            break;
        for (int k : g[u]) {
            Edge &e = E[k];
            if (e.flow < e.cap && d[e.v] > d[e.u] + 1) {
                d[e.v] = d[e.u] + 1;
                q.emplace(e.v);
            }
        }
    }
    return d[T] != N + 1;
}

ll DFS(int u, int T, ll flow = -1) {
    if (u == T || flow == 0)
        return flow;
    for (int &i = pt[u]; i < (int)g[u].size(); ++i) {
        Edge &e = E[g[u][i]];
        Edge &oe = E[g[u][i] ^ 1];
        if (d[e.v] == d[e.u] + 1) {
            ll amt = e.cap - e.flow;

```

```

            if (flow != -1 && amt > flow)
                amt = flow;
            if (ll pushed = DFS(e.v, T, amt)) {
                e.flow += pushed;
                oe.flow -= pushed;
                return pushed;
            }
        }
    }
    return 0;
}

ll maxFlow(int S, int T) {
    ll total = 0;
    while (BFS(S, T)) {
        fill(pt.begin(), pt.end(), 0);
        while (ll flow = DFS(S, T))
            total += flow;
    }
    return total;
}

};
#endif
class HopcroftKarp {
public:
    static const int INF = 1e9;
    int U, V, nil;
    vector<int> pairU, pairV, dist;
    vector<vector<int>> adj;
    bool bfs() {
        queue<int> q;
        for (int u = 0; u < U; u++)
            if (pairU[u] == nil)
                dist[u] = 0, q.push(u);
        else
            dist[u] = INF;
        dist[nil] = INF;
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            if (dist[u] >= dist[nil])
                continue;

```

```

        for (int v : adj[u])
            if (dist[pairV[v]] == INF)
                dist[pairV[v]] = dist[u] + 1, q.push(pairV[v]);
    }
    return dist[nil] != INF;
}

bool dfs(int u) {
    if (u == nil)
        return true;
    for (int v : adj[u])
        if (dist[pairV[v]] == dist[u] + 1)
            if (dfs(pairV[v])) {
                pairV[v] = u, pairU[u] = v;
                return true;
            }
    dist[u] = INF;
    return false;
}

public:
HopcroftKarp(int U_, int V_) {
    nil = U = V = max(U_, V_);
    adj.resize(U + 1);
    dist.resize(U + 1);
    pairU.resize(U + 1);
    pairV.resize(V);
}

void addEdge(int u, int v) {
    adj[u].push_back(v);
}

int maxMatch() {
    fill(pairU.begin(), pairU.end(), nil);
    fill(pairV.begin(), pairV.end(), nil);
    int res = 0;
    while (bfs())
        for (int u = 0; u < U; u++)
            if (pairU[u] == nil && dfs(u))
                res++;
    return res;
}
};

```

## 5 Geometry

```
#include "template.hpp"
```

```

class Point {
public:
    typedef long long coord_t; coord_t x, y;
    Point(coord_t coord_x = 0, coord_t coord_y = 0) { this->x =
        coord_x; this->y = coord_y; }
    Point(pair<coord_t, coord_t> coord) { this->x = coord.first;
        this->y = coord.second; }
    friend bool operator<(const Point &a, const Point &b) { return
        (a.x != b.x) ? a.x < b.x : a.y < b.y; }
    friend bool operator==(const Point &a, const Point &b) {
        return (a.x == b.x) && (a.y == b.y); }
    friend istream &operator>>(istream &in, Point &p) { in >> p.x
        >> p.y; return in; }
    friend ostream &operator<<(ostream &out, Point &p) { out <<
        p.x << " " << p.y; return out; }
    static coord_t area(const Point &a, const Point &b, const
        Point &c) { return a.x * (b.y - c.y) + b.x * (c.y - a.y) +
        c.x * (a.y - b.y); }; // Area function: area < 0 =
        clockwise, area > 0 counterclockwise
    static coord_t sq_dist(const Point &a, const Point &b) {
        return (a.x - b.x) * (a.x - b.x) + (a.y - b.y) * (a.y -
        b.y); }
    static coord_t cross(const Point &O, const Point &A, const
        Point &B) { return (A.x - O.x) * (B.y - O.y) - (A.y - O.y)
        * (B.x - O.x); }
    static coord_t dot(const Point &O, const Point &A, const Point
        &B) { return (A.x - O.x) * (B.x - O.x) + (A.y - O.y) *
        (B.y - O.y); }
    static coord_t area(const vector<Point> &polygon) {
        int n = polygon.size();
        coord_t ans = 0;
        for (int i = 0; i < n; i++)
            ans += polygon[i].x * polygon[(i + 1) % n].y -
                polygon[i].y * polygon[(i + 1) % n].x;
    }
    static vector<Point> convex_hull(vector<Point> &a) {
        if (a.size() <= 3) return a;
    }
}

```



```

int n = a.size(), k = 0; sort(a.begin(), a.end());
vector<Point> result(2 * n);
for (int i = 0; i < n; ++i) {
    while (k >= 2 && cross(result[k - 2], result[k - 1],
        a[i]) <= 0) k--;
    result[k++] = a[i];
}
for (int i = n - 1, t = k + 1; i > 0; --i) {
    while (k >= t && cross(result[k - 2], result[k - 1],
        a[i - 1]) <= 0) k--;
    result[k++] = a[i - 1];
}
result.resize(k - 1); return result;
}
};

```

## 6 GraphAlgorithms

```
#include "template.hpp"
```

```

class Graph {
public:
    enum NodeColor { VISITED, VISITING, UNVISITED };
    struct Node { int index; vpl adjacent; NodeColor color =
        UNVISITED; };
    vector<Node> list; int n;
    Graph(int n) {
        list.resize(n);
        for (int i = 0; i < n; i++) list[i].index = i;
        this->n = n;
    }
    void add_edge(int u, int v, long long w = 1) {
        list[u].adjacent.emplace_back(v, w);
        list[v].adjacent.emplace_back(u, w);
    }

    pair<vll, vll> dijkstra(vll from) {
        vll dist(n, INT64_MAX), parent(n, INT32_MAX);
        priority_queue<pll, vpl, greater<>> q;

```

```

        for (auto index : from) dist[index] = 0, q.emplace(0,
            index);
        while (!q.empty()) {
            pll top = q.top(); q.pop();
            if (top.first > dist[top.second]) continue;
            for (auto edge : list[top.second].adjacent)
                if (top.first + edge.second < dist[edge.first])
                    dist[edge.first] = top.first + edge.second,
                    parent[edge.first] = top.second,
                    q.emplace(top.first + edge.second, edge.first);
        } return {dist, parent};
    }

    vector<int> topological_sort() {
        vector<int> in_degree(list.size(), 0), result;
        result.reserve(list.size());
        for (auto node : list) for (auto route : node.adjacent)
            in_degree[route.first - 1]++;
        queue<int> process;
        for (int i = 0; i < list.size(); i++)
            if (in_degree[i] == 0) { process.push(i);
                result.push_back(i); }
        while (!process.empty()) {
            int processing = process.front(); process.pop();
            for (auto route : list[processing].adjacent) {
                in_degree[route.first - 1]--;
                if (in_degree[route.first - 1] == 0) {
                    process.push(route.first - 1);
                    result.push_back(route.first - 1);
                }
            }
        }
        return result;
    }

    mll components() {
        vbl visited(n); mll result(0);
        for (int i = 0; i < n; i++) {
            if (visited[i]) continue;
            vll component; stack<ll> process;
            process.push(list[i].index); component.push_back(i);
            visited[i] = true;
            while (!process.empty()) {

```

```

    ll processing = process.top(); process.pop();
    for (pll neighbor : list[processing].adjacent)
        if (!visited[neighbor.first])
            process.push(neighbor.first),
            component.push_back(neighbor.first),
            visited[neighbor.first] = true;
    } result.push_back(component);
} return result;
}

pair<vll, vll> bellman_ford(vll from) {
    vll distances(n, INT64_MAX);
    vll parent(n, INT32_MAX);
    for (ll &i : from)
        distances[i] = 0;
    for (int i = 0; i < n - 1; i++)
        for (int source = 0; source < n - 1; source++) {
            if (distances[source] == INT64_MAX)
                continue;
            for (const auto &edge : list[source].adjacent) {
                ll sink = edge.first;
                if (distances[source] + edge.second <
                    distances[sink])
                    distances[sink] = distances[source] +
                    edge.second, parent[sink] = source;
            }
        }
    for (ll source = 0; source < n - 1; source++) // -ve cycle
        check
    for (const auto &edge : list[source].adjacent) {
        ll sink = edge.first;
        if (distances[source] + edge.second <
            distances[sink]) {
            for (ll i : from) distances[i] = -1;
            return {distances, parent};
        }
    }
    return {distances, parent};
}

mll floyd_warshall() {
    mll distances(n, vll(n, INT64_MAX));
    for (int i = 0; i < n; i++) distances[i][i] = 0;

```

```

    for (int i = 0; i < n; i++) for (auto route :
        list[i].adjacent)
        distances[i][route.first] = route.second;
    for (int k = 0; k < n; k++) {
        for (int i = 0; i < n; i++) {
            for (int j = 0; j < n; j++) {
                if (distances[i][k] == INT64_MAX ||
                    distances[k][j] == INT64_MAX) continue;
                distances[i][j] = min(distances[i][j],
                    distances[i][k] + distances[k][j]);
            }
        }
    } return distances;
}

pair<ll, vll> prims_mst() {
    priority_queue<pll, vpl, greater<>> routes;
    vll costs(n);
    vbl visited(n, false);
    for (int i = 0; i < n; i++) {
        if (!visited[i]) routes.emplace(INT32_MAX, i);
        while (!routes.empty()) {
            pll best = routes.top(); routes.pop();
            if (!visited[best.second]) costs[best.second] =
                best.first;
            visited[best.second] = false;
            for (const auto &path : list[best.second].adjacent)
                if (!visited[path.second]) routes.push(path);
        }
    }
    return {accumulate(costs.begin(), costs.end(), 0), costs};
};

```

## 7 Mathematics Theory

### 7.1 Mobius Inversions

- $\phi \circ I = \text{id}$  i.e.  $\sum_{d|n} \phi(d) = n$ . Hence,  $\phi = \mu \circ \text{id}$  i.e.  $\phi(d) = \sum_{d|n} \mu(d) \frac{n}{d}$

- Count of numbers coprime to  $n$  and lesser than  $n = \phi(n)$   
Sum of numbers coprime to  $n$  and lesser than  $n$  is  $\frac{n}{2}\phi(n)$   
Proved using the fact that if  $x$  is coprime to  $n$  then so is  $n - x$  coprime to  $n$ . Sum over both and take average
- $\sum_{d|n} \mu(d)f(d) = \prod_{p|n} (1 - f(p))$  ( $p$  are its prime factors)
- $\sum_{d|n} \mu^2(d)f(d) = \prod_{p|n} (1 + f(p))$
- $\phi(mn) = \frac{\phi(m)\phi(n)\gcd(m,n)}{\phi(\gcd(m,n))}$
- $\phi(p^a) = p^{a-1}\phi(p)$

## 7.2 Chinese Remainder Theorem

System  $x \equiv a_i \pmod{m_i}$  for  $i = 1, \dots, n$ , with pairwise relatively prime  $m_i$  has a unique solution modulo  $M = \prod m_i$   $x = \sum_i a_i b_i \frac{M}{m_i} \pmod{M}$  where  $b_i$  is modular inverse of  $\frac{M}{m_i}$  modulo  $m_i$ .

System  $x \equiv a \pmod{m}$ ,  $x \equiv b \pmod{n}$  has solutions iff  $a \equiv b \pmod{g}$ , where  $g = \gcd(m, n)$ . The solution is unique modulo  $L = \frac{mn}{g}$ , and equals:  $x \equiv a + T(ba)m/g \equiv b + S(ab)n/g \pmod{L}$ , where  $S$  and  $T$  are integer solutions of  $mT + nS = \gcd(m, n)$ .

Euler's theorem:  $a^{\phi(n)} \equiv 1 \pmod{n}$ , if  $\gcd(a, n) = 1$  Wilson's theorem:  $p$  is prime iff  $(p-1)! \equiv -1 \pmod{p}$  Primitive Pythagorean triple generator:  $(m^2 - n^2)^2 + (2mn)^2 = (m^2 + n^2)^2$  Postage stamps/McNuggets problem: Let  $a, b$  be coprime integers. There are exactly  $\frac{1}{2}(a-1)(b-1)$  numbers not of form  $ax + by$  ( $x, y \geq 0$ ), and the largest is  $(a-1)(b-1) - 1 = ab - a - b$ .

Fermat's two-squares theorem: Odd prime  $p$  can be represented as a sum of two squares iff  $p \equiv 1 \pmod{4}$ . A product of two sums of two squares is a sum of two squares. Thus,  $n$  is a sum of two squares iff every prime of form  $p = 4k + 3$  occurs an even number of times in  $n$ 's factorization.

Counting Primes Fast: To count number of primes lesser than big  $n$ . Use following recurrence.  $dp[n][j] = dp[n][j+1] + dp[n/p_j][j]$  where  $dp[i][j]$  stores count of numbers lesser than equal to  $i$  having all prime divisors greater than equal to  $p_j$ . Precompute this for all  $i$  less than some small  $k$  and for others use the recurrence to compute in small time.

Compute  $P_N(x)$  in  $T(n) = T(n/2) + \mathcal{O}(n \log n) \approx \mathcal{O}(n \log n)$   
 $P_{2N}(x) = P_N(x)P_N(x+N)$ . using polynomial shifting. Say,  $P_N(x) = \prod_{i=1}^N (x+i) = \sum_{i=0}^N c_i x^i$ . Then,  $P_N(x+N) = \sum_{i=0}^N h_i x^i$ , where,  $h_i = \frac{1}{i!} \cdot (\text{coefficient of } x^{N-i} \text{ in } A(x)B(x))$  where,  $A(x) = \sum_{i=0}^N (c_{N-i} \cdot (N-i)! ) \cdot x^i$ , and  $B(x) = \sum_{i=0}^N \left( \frac{N^i}{i!} \right) \cdot x^i$

```
MUL(N) // computes (x+1)(x+2)...(x+N) in O(NlogN)
    if N==1:
        return (x+1)
    C = MUL(N/2)
    H = convolute(A,B) // use C to obtain A
    ANS = convolute(C,H)
    if N is odd:
        ANS *= (x+N) // naive multiplication will do - O(N)
    return ANS
```

## 8 MatrixTools

---

```
// solving systems of linear equations (AX = B)
// (2) inverting matrices (AX = I)
// (3) computing determinants of square matrices
// O(n^3)
// INPUT : a[][] = an nxn matrix; b[][] = an nxm matrix
// OUTPUT:
// X = an nxm matrix (stored in b[][])
// A {-1} = an nxn matrix (stored in a[][])
// returns determinant of a[][]
```

```
const double EPS = 1e-10;
// T is data type of matrix elements
T GaussJordan(VVT &a, VVT &b) {
    const int n = a.size();
    const int m = b[0].size();
    VI irow(n), icol(n), ipiv(n);
    T det = 1;
```

```

for (int i = 0; i < n; i++) {
    int pj = -1, pk = -1;
    for (int j = 0; j < n; j++)
        if (!ipiv[j])
            for (int k = 0; k < n; k++)
                if (!ipiv[k])
                    if (pj == -1 || fabs(a[j][k]) >
                        fabs(a[pj][pk])) {
                        pj = j;
                        pk = k;
                    }
    if (fabs(a[pj][pk]) < EPS) {
        cerr << "Matrix is singular." << endl;
        exit(0);
    }
    ipiv[pk]++;
    swap(a[pj], a[pk]);

    swap(b[pj], b[pk]);
    if (pj != pk)
        det *= -1;
    irow[i] = pj;
    icol[i] = pk;
    T c = 1.0 / a[pk][pk];
    det *= a[pk][pk];
    a[pk][pk] = 1.0;
    for (int p = 0; p < n; p++)
        a[pk][p] *= c;
    for (int p = 0; p < m; p++)
        b[pk][p] *= c;
    for (int p = 0; p < n; p++)
        if (p != pk) {
            c = a[p][pk];
            a[p][pk] = 0;
            for (int q = 0; q < n; q++)
                a[p][q] -= a[pk][q] * c;
            for (int q = 0; q < m; q++)
                b[p][q] -= b[pk][q] * c;
        }
}
for (int p = n - 1; p >= 0; p--)

```

```

    if (irow[p] != icol[p]) {
        for (int k = 0; k < n; k++)
            swap(a[k][irow[p]], a[k][icol[p]]);
    }
    return det;
} // gets the rank of a matrix.
// Running time: O(n3)
// INPUT: a[] [] = an nxm matrix
// OUTPUT: rref[] [] = an nxm matrix (stored in a[] [])
// returns rank of a[] []

int rref(VV &a) {
    int n = a.size(), m = a[0].size(), r = 0;

    for (int c = 0; c < m && r < n; c++) {
        int j = r;
        for (int i = r + 1; i < n; i++)
            if (fabs(a[i][c]) > fabs(a[j][c]))
                j = i;

        if (fabs(a[j][c]) < EPS)
            continue;
        swap(a[j], a[r]);

        T s = 1.0 / a[r][c];

        for (int j = 0; j < m; j++)
            a[r][j] *= s;

        for (int i = 0; i < n; i++) {
            if (i != r) {
                T t = a[i][c];
                for (int j = 0; j < m; j++) {
                    a[i][j] -= t * a[r][j];
                }
            }
        }

        r++;
    }
}

```

```

    return r;
} // Solves LP with constraints cT x, Ax <= b, x >= 0
// A: m x n matrix
// b: m-dimensional vector
// c: n-dimensional vector
// x: a vector where the optimal solution will be stored
// OUTPUT: value of the optimal solution (infinity if unbounded
// above, nan if infeasible)
// To use this code, create an LPSolver object with A, b, and c as
// arguments. Then, call Solve(x)

struct LPSolver {
    int m, n;
    VI B, N;
    VVD D;
    LPSolver(const VVD &A, const VD &b, const VD &c)
        : m(b.size()), n(c.size()), N(n + 1), B(m), D(m + 2, VD(n
            + 2)) {
        for (int i = 0; i < m; i++)
            for (int j = 0; j < n; j++)
                D[i][j] = A[i][j];
        for (int i = 0; i < m; i++) {
            B[i] = n + i;
            D[i][n] = -1;
            D[i][n + 1] = b[i];
        }
        for (int j = 0; j < n; j++) {
            N[j] = j;
            D[m][j] = -c[j];
        }
        N[n] = -1;
        D[m + 1][n] = 1;
    }
    void Pivot(int r, int s) {
        double inv = 1.0 / D[r][s];
        for (int i = 0; i < m + 2; i++)
            if (i != r)
                for (int j = 0; j < n + 2; j++)
                    if (j != s)
                        D[i][j] -= D[r][j] * D[i][s] * inv;
        for (int j = 0; j < n + 2; j++)

```

```

            if (j != s)
                D[r][j] *= inv;
        for (int i = 0; i < m + 2; i++)
            if (i != r)
                D[i][s] *= -inv;
        D[r][s] = inv;
        swap(B[r], N[s]);
    }
    bool Simplex(int phase) {
        int x = phase == 1 ? m + 1 : m;
        while (true) {
            int s = -1;
            for (int j = 0; j <= n; j++) {
                if (phase == 2 && N[j] == -1)
                    continue;
                if (s == -1 || D[x][j] < D[x][s] ||
                    D[x][j] == D[x][s] && N[j] < N[s])
                    s = j;
            }
            if (D[x][s] > -EPS)
                return true;
            int r = -1;
            for (int i = 0; i < m; i++) {
                if (D[i][s] < EPS)
                    continue;
                if (r == -1 || D[i][n + 1] / D[i][s] < D[r][n + 1] /
                    D[r][s] ||
                    (D[i][n + 1] / D[i][s]) == (D[r][n + 1] /
                    D[r][s]) &&
                    B[i] < B[r])
                    r = i;
            }
            if (r == -1)
                return false;
            Pivot(r, s);
        }
    }
    DOUBLE Solve(VD &x) {
        int r = 0;
        for (int i = 1; i < m; i++)
            if (D[i][n + 1] < D[r][n + 1])

```

```

        r = i;
    if (D[r][n + 1] < -EPS) {
        Pivot(r, n);
        if (!Simplex(1) || D[m + 1][n + 1] < -EPS)
            return -numeric_limits<DOUBLE>::infinity();
        for (int i = 0; i < m; i++)
            if (B[i] == -1) {
                int s = -1;
                for (int j = 0; j <= n; j++)
                    if (s == -1 || D[i][j] < D[i][s] ||
                        D[i][j] == D[i][s] && N[j] < N[s])
                        s = j;
                Pivot(i, s);
            }
    }
    if (!Simplex(2))
        return numeric_limits<DOUBLE>::infinity();
    x = VD(n);
    for (int i = 0; i < m; i++)
        if (B[i] < n)
            x[B[i]] = D[i][n + 1];
    return D[m][n + 1];
}
};

```

## 9 MergeSortTree

```
#include "template.hpp"
```

```

template <typename Type>
struct MergeSortTree {
    int size;
    vector<Type> data;
    vector<vector<int>> tree_idx;
    vector<vector<Type>> tree_val;
    long long inversions;

    template <typename DataType>

```

```

vector<DataType> merge(const vector<DataType> &arr1, const
vector<DataType> &arr2) {
    int n = arr1.size(), m = arr2.size();
    vector<DataType> result; result.reserve(n + m);
    for (int x = 0, y = 0; x < n || y < m; ) {
        if (x < n && (y >= m || arr1[x] <= arr2[y]))
            result.push_back(arr1[x++]);
        else result.push_back(arr2[y++]), inversions += n - x;
    } return move(result);
}

int order_fn(const Type &value, const vector<Type> &arr) {
    return lower_bound(arr.begin(), arr.end(), value) -
        arr.begin();
}

explicit MergeSortTree(const vector<Type> &list) {
    for (size = 1; size < list.size(); size *= 2) ;
    // Make a tree based on the values
    tree_val.resize(2 * size); data = vector<Type>(list);
    for (int i = 0; i < list.size(); i++)
        tree_val[i + size].push_back(i);
    for (int i = size - 1; i > 0; --i)
        tree_val[i] = merge<Type>(tree_val[i << 1], tree_val[i
        << 1 | 1]);
    // Make a tree based on the indices
    tree_idx.resize(2 * size);
    vector<pair<Type, int>> convert(list.size());
    for (int i = 0; i < list.size(); i++)
        convert[i].first = list[i], convert[i].second = i;
    sort(convert.begin(), convert.end());
    for (int i = 0; i < list.size(); i++)
        tree_idx[i + size].push_back(convert[i].second);
    for (int i = size - 1; i > 0; --i)
        tree_idx[i] = merge<int>(tree_idx[i << 1], tree_idx[i
        << 1 | 1]);
}

int order_of_key(int l, int r, Type value) {
    int result = 0;
    for (l = l + size, r = r + size; l < r; l >>= 1, r >>= 1) {
        if (l & 1) result += order_fn(value, tree_val[l++]);
        if (r & 1) result += order_fn(value, tree_val[--r]);
    } return result;
}

```

```

}
int key_of_order(int l, int r, int order, int node = 0, int x
= 0, int y = -1) {
    if (y == -1) y = size;
    if (x + 1 == y) return tree_idx[node][0];
    int m = (upper_bound(tree_idx[2 * node].begin(),
        tree_idx[2 * node].end(), r - 1) - tree_idx[2 *
        node].begin())
        - (lower_bound(tree_idx[2 * node].begin(), tree_idx[2
        * node].end(), l) - tree_idx[2 * node].begin());
    if (m >= order) return key_of_order(l, r, order, node <<
        1, x, (x + y) / 2);
    else return key_of_order(l, r, order - m, node << 1 | 1,
        (x + y) / 2, y);
}
};

```

---

## 10 Miscellaneous

```

#include "template.hpp"

ll binary_search(ll TOP, ll BOT, function<bool(ll)> check) {
    ll result = BOT - 1;
    for (ll top = TOP, bot = BOT, mid = bot + (top - bot) / 2; bot
        <= top; mid = bot + (top - bot) / 2) {
        if (check(mid) && !check(mid - 1)) { result = mid; break; }
        (check(mid)) ? (top = mid - 1) : (bot = mid + 1);
    }
}

ll gcd(ll a, ll b, ll &x, ll &y) {
    int g = a; x = 1, y = 0;
    if (b != 0) g = gcd(b, a % b, y, x), y -= a / b * x;
    return g;
}

ll mod_inverse(ll a, ll mod) {
    ll x, y; gcd(a, mod, x, y);
    return (x + mod) % mod;
}

```

```

ll mod_power(ll a, ll b, ll MOD) {
    ll cumulative = a, result = 1;
    for (; b > 0; b /= 2) {
        if (b % 2 == 1) result = (result * cumulative) % MOD;
        cumulative = (cumulative * cumulative) % MOD;
    } return result;
}

ll mod_multiply(ll a, ll b, ll MOD) {
    ll cumulative = a, result = 0;
    for (; b > 0; b /= 2) {
        if (b % 2 == 1) result = (result + cumulative) % MOD;
        cumulative = (cumulative + cumulative) % MOD;
    } return result;
}

```

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
typedef tree<int, null_type, less<int>, rb_tree_tag,
    tree_order_statistics_node_update> ordered_set;

```

```

// deterministic for all n <= 2 ^ 64
bool MRPrime(ll N) {
    int primes[12] = {2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37};
    if (N <= 1) return false;
    for (auto p : primes) { if (p == N) return true; if (N % p ==
        0) return false; }
    ll c = N - 1, g = 0; while (!(c & 1)) c >>= 1, ++g;
    for (auto p : primes) {
        ll k = mod_power(p, c, N);
        for (int j = 0; j < g; ++j) { ll kk = mod_multiply(k, k,
            N); if (kk == 1 && k != 1 && k != N - 1) return false;
            k = kk; }
        if (k != 1) return false;
    } return true;
}

```

---

## 11 MobiusSieve

---

```
#include "template.hpp"

class Multiplicative {
// This is the definition for PHI
#define fn_prime_values(prime) (prime - 1)
#define fn_non_coprime(num, prime) (fn[num] * prime)
public:
    ll size; vll fn, primes, lowest_prime_factor;
    Multiplicative(ll size) {
        size = size;
        lowest_prime_factor = vector<ll>(size, 0);
        fn = vector<ll>(size, 0);
        // https://stackoverflow.com/questions/34260399 - linear sieve
        for (ll i = 2; i < size; i++)
            lowest_prime_factor[i] = i;
        // put any specific initialization code here like -
        multiplicative_fn[1] = 1;
        for (ll i = 2; i < size; i++) {
            if (lowest_prime_factor[i] == i) { fn[i] =
                fn_prime_values(i); primes.push_back(i); }
            for (auto p : primes) {
                ll ith_multiple = i * p;
                if (ith_multiple >= size) break;
                lowest_prime_factor[ith_multiple] =
                    min(lowest_prime_factor[i], p);
                if (i % p) { fn[ith_multiple] = fn[i] * fn[p]; }
                else { fn[ith_multiple] = fn_non_coprime(i, p);
                    break; }
            }
        }
    }
};
```

---

## 12 PalindromicTree

---

```
#include "template.hpp"
```

```
struct PalindromicTree {
    const static long long MAXN = 100000;
    struct Node { int start, end; int length; int insert_edge[26];
        int suffix_edge; };
    Node root1, root2; Node tree[MAXN]; int curr_node, ptr, size;
    string s;

    void insert(int idx) {
        int tmp = curr_node;
        while (true) {
            int curLength = tree[tmp].length;
            if (idx - curLength >= 1 and s[idx] == s[idx -
                curLength - 1]) break;
            tmp = tree[tmp].suffix_edge;
        }
        if (tree[tmp].insert_edge[s[idx] - 'a'] != 0) {
            curr_node = tree[tmp].insert_edge[s[idx] - 'a']; return;
        }
        ptr++;
        tree[tmp].insert_edge[s[idx] - 'a'] = ptr;
        tree[ptr].length = tree[tmp].length + 2;
        tree[ptr].end = idx;
        tree[ptr].start = idx - tree[ptr].length + 1;
        tmp = tree[tmp].suffix_edge;
        curr_node = ptr;
        if (tree[curr_node].length == 1) {
            tree[curr_node].suffix_edge = 2; return; }
        while (true) {
            int cur_length = tree[tmp].length;
            if (idx - cur_length >= 1 and s[idx] == s[idx -
                cur_length - 1]) break;
            tmp = tree[tmp].suffix_edge;
        }
        tree[curr_node].suffix_edge = tree[tmp].insert_edge[s[idx]
            - 'a'];
    }

    PalindromicTree(string st) {
        root1.length = -1, root1.suffix_edge = 1, root2.length = 0,
        root2.suffix_edge = 1, tree[1] = root1, tree[2] = root2,
        ptr = 2;
        curr_node = 1, s = st, size = st.size();
    }
};
```



```

    for (int i = 0; i < size; i++) insert(i);
}
vpl get_palindromes() {
    vpl res(ptr - 2);
    for (int i = 3; i <= ptr; i++) res[i - 2] =
        {tree[i].start, tree[i].end};
    return res;
}
};

```

---

## 13 SegmentTree

```
#include "template.hpp"
```

```

template <typename Type>
struct LazySegtree {
    int size;
    vector<Type> tree, lazy;
    Type _default;
    function<Type(Type, Type)> _operation;
    function<Type(Type, Type)> _setter;

    void split(int node) {
        lazy[2 * node] = _setter(lazy[2 * node], lazy[node]);
        tree[2 * node] = _setter(tree[2 * node], lazy[node]);
        lazy[2 * node + 1] = _setter(lazy[2 * node + 1],
            lazy[node]);
        tree[2 * node + 1] = _setter(tree[2 * node + 1],
            lazy[node]);
        lazy[node] = _default;
    }

    void merge(int node) { tree[node] = _operation(tree[2 * node],
        tree[2 * node + 1]); }

    LazySegtree(int n, const function<Type(Type, Type)> &op,
        const function<Type(Type, Type)> &set, const Type
            identity) {
        for (size = 1; size < n; size <= 1);
        _setter = set, _operation = op, _default = identity;
    }
};

```

```

        tree.assign(2 * size, _default);
        lazy.assign(2 * size, _default);
    }

    void modify(int l, int r, Type delta, int node = 1, int x = 0,
        int y = -1) {
        if (y == -1) y = size;
        if (r <= x || l >= y) return;
        if (l <= x && y <= r) {
            lazy[node] = _setter(lazy[node], delta);
            tree[node] = _setter(tree[node], delta);
            return;
        }
        split(node); modify(l, r, delta, 2 * node, x, (x + y) / 2);
        modify(l, r, delta, 2 * node + 1, (x + y) / 2, y);
        merge(node);
    }

    Type query(int l, int r, int node = 1, int x = 0, int y = -1) {
        if (y == -1) y = size;
        if (r <= x || l >= y) return _default;
        if (l <= x && y <= r) return tree[node];
        split(node); Type lres = query(l, r, 2 * node, x, (x + y)
            / 2);
        Type rres = query(l, r, 2 * node + 1, (x + y) / 2, y);
        merge(node);
        return _operation(lres, rres);
    }
};

template <typename Type>
struct ImplicitSegupdate {
    struct Node {
        Type data = 0;
        Node *l_ptr = nullptr, *r_ptr = nullptr;
        Node *l_child() { if (l_ptr == nullptr) l_ptr = new Node,
            r_ptr = new Node; return l_ptr; }
        Node *r_child() { if (r_ptr == nullptr) l_ptr = new Node,
            r_ptr = new Node; return r_ptr; }
    };
    int size; Node *root; function<Type(Type, Type)> _setter;
};

```

```

ImplicitSegupdate(int n, const function<Type(Type, Type)>
    &set) {
    for (size = 1; size < n; size <= 1) ;
    _setter = set; root = new Node;
}
void modify(int l, int r, Type delta, Node *node = nullptr,
    int x = 0,
    int y = -1) {
    if (node == nullptr) node = root, y = size;
    if (r <= x || l >= y) return;
    if (l <= x && y <= r) { node->data = _setter(node->data,
        delta); return; }
    modify(l, r, delta, node->l_child(), x, (x + y) / 2);
    modify(l, r, delta, node->r_child(), (x + y) / 2, y);
}
Type query(int p, Node *node = nullptr, int x = 0, int y = -1)
{
    if (node == nullptr) node = root, y = size;
    if (x == p && y == p + 1) return node->data;
    if (x <= p && p < (x + y) / 2) return _setter(node->data,
        query(p, node->l_child(), x, (x + y) / 2));
    else return _setter(node->data, query(p, node->r_child(),
        (x + y) / 2, y));
}
};

struct PersistentSegtree {
    struct Node {
        int l, r, val;
        Node() { l = r = val = 0; }
    };
    int node_size, query_size; int curr;
    vector<int> root; vector<Node> seg;

    PersistentSegtree(int n, int q) {
        node_size = n, query_size = q;
        seg.resize(2 * (n + q * (log2(n) + 1)));
        root = vector<int>(query_size + 10);
        curr = 1, seg[curr].l = seg[curr].r = seg[curr].val = 0;
    }
    int _new_node(int val, int l, int r) {

```

```

        seg[curr].val = val, seg[curr].l = l, seg[curr].r = r;
        return curr++;
    }
    int insert(int cur, int idx, int val, int lo, int hi) {
        if (idx < lo || idx > hi)
            return cur;
        else if (lo == hi)
            return _new_node(val, 0, 0);
        int mid = (lo + hi) >> 1;
        int pos = _new_node(-1, insert(seg[cur].l, idx, val, lo,
            mid),
            insert(seg[cur].r, idx, val, mid + 1,
                hi));
        seg[pos].val = max(seg[seg[pos].l].val,
            seg[seg[pos].r].val);
        return pos;
    }
};

```

## 14 StonglyConnected

```
#include "template.hpp"
```

```

struct DirectedGraph {
    int size, curr;
    vector<vector<int>> adjacent_f, adjacent_r, comp_nodes;
    vector<int> order, comp;
    vector<bool> visited;

    DirectedGraph(int n) {
        size = n; order.resize(size); adjacent_f.resize(size);
    }
    void add_edge(int v1, int v2) {
        adjacent_f[v1].push_back(v2); adjacent_r[v2].push_back(v1);
    }
    void _scc_dfs1(int u) {
        visited[u] = 1;
        for (auto w : adjacent_f[u]) if (!visited[w]) _scc_dfs1(w);
        order.push_back(u);
    }
};

```

```

}
void _scc_dfs2(int u) {
    visited[u] = 1; comp[u] = curr;
    comp_nodes[curr].push_back(u);
    for (auto w : adjacent_r[u]) if (!visited[w]) _scc_dfs2(w);
}
void stongly_connected_components() {
    fill(visited.begin(), visited.end(), false);
    order.clear();
    for (int i = 0; i < size; i++) if (!visited[i])
        _scc_dfs1(i);
    fill(visited.begin(), visited.end(), false);
    reverse(order.begin(), order.end());
    curr = 0;
    for (auto u : order)
        if (!visited[u])
            comp_nodes[++curr].clear(), _scc_dfs2(u);
}
};

struct Satisfiability : DirectedGraph {
    vector<bool> val;
    Satisfiability(int size) : DirectedGraph(2 * size) {
        val = vector<bool>(size, false);
    }

    bool solvable(int vars) {
        stongly_connected_components();
        for (int i = 0; i < vars; i++)
            if (comp[var(i)] == comp[NOT(var(i))])
                return false;
        return true;
    }
}

vector<bool> solve() {
    fill(val.begin(), val.end(), 0);
    for (int i = 1; i <= curr; i++)
        for (auto it : comp_nodes[i]) {
            int u = it >> 1;
            if (val[u]) continue;
            val[u] = (it & 1 ? +1 : -1);
        }
}

```

```

        return val;
    }
    int var(int x) { return x << 1; }
    int NOT(int x) { return x ^ 1; }
    void add_imp(int v1, int v2) { add_edge(v1, v2); add_edge(1 ^
        v2, 1 ^ v1); }
    void add_equiv(int v1, int v2) { add_imp(v1, v2); add_imp(v2,
        v1); }
    void add_or(int v1, int v2) { add_edge(1 ^ v1, v2); add_edge(1
        ^ v2, v1); }
    void add_xor(int v1, int v2) { add_or(v1, v2); add_or(1 ^ v1,
        1 ^ v2); }
    void add_true(int v1) { add_edge(1 ^ v1, v1); }
    void add_and(int v1, int v2) { add_true(v1); add_true(v2); }
};

```

## 15 StringAlgorithms

```
#include "template.hpp"
```

```

class KMPstring {
    string pattern;
    vll lps;

public:
    explicit KMPstring(const string &pattern) {
        this->pattern = pattern;
        ll m = pattern.size();
        lps = vll(m + 1, 0);
        ll i = 0, j = -1;
        lps[0] = -1;
        while (i < m) {
            while (j >= 0 && pattern[i] != pattern[j])
                j = lps[j];
            i++, j++;
            lps[i] = j;
        }
    }

    vll match(const string &text) {

```

```

    ll n = text.size(), m = pattern.size();
    vll matches, m_length(n);
    ll i = 0, j = 0;
    while (i < n) {
        while (j >= 0 && text[i] != pattern[j])
            j = lps[j];
        i++, j++;
        m_length[i - 1] = j;
        if (j == m) {
            matches.push_back(i - m);
            j = lps[j];
        }
    }
    return move(matches); // or m_length
};

struct SuffixArray {
    string s;
    int n, __log_n;
    vector<int> sa; // Suffix Array
    vector<vector<int>> ra; // Rank Array
    vector<vector<int>> _lcp; // Longest Common Prefix
    vector<int> __msb, __dollar;

    SuffixArray(string st) {
        n = st.size();
        __log_n = log2(n) + 1;
        ra = vector<vector<int>>(__log_n, vector<int>(n));
        sa = vector<int>(n);

        __msb = vector<int>(n);
        int mx = -1;
        for (int i = 0; i < n; i++) {
            if (i >= (1 << (mx + 1)))
                mx++;
            __msb[i] = mx;
        }
        this->s = st;
        build_SA();
    }
};

```

```

void __counting_sort(int l, int k) {
    int maxi = max(300, n);
    vector<int> count(maxi, 0), temp_sa(n, 0);
    for (int i = 0; i < n; i++) {
        int idx = (i + k < n ? ra[l][i + k] : 0);
        count[idx]++;
    }
    for (int i = 0, sum = 0; i < maxi; i++) {
        int t = count[i];
        count[i] = sum;
        sum += t;
    }
    for (int i = 0; i < n; i++) {
        int idx = sa[i] + k < n ? ra[l][sa[i] + k] : 0;
        temp_sa[count[idx]++] = sa[i];
    }
    sa = temp_sa;
}

void build_SA() {
    for (int i = 0; i < n; i++)
        ra[0][i] = s[i];
    for (int i = 0; i < n; i++)
        sa[i] = i;
    for (int i = 0; i < __log_n - 1; i++) {
        int k = (1 << i);
        if (k >= n)
            break;
        __counting_sort(i, k);
        __counting_sort(i, 0);
        int rank = 0;
        ra[i + 1][sa[0]] = rank;
        for (int j = 1; j < n; j++)
            if (ra[i][sa[j]] == ra[i][sa[j - 1]] &&
                ra[i][sa[j] + k] == ra[i][sa[j - 1] + k])
                ra[i + 1][sa[j]] = rank;
            else
                ra[i + 1][sa[j]] = ++rank;
    }
}

```

```

void build_LCP() {
    _lcp = vector<vector<int>>(__log_n, vector<int>(n));
    for (int i = 0; i < n - 1; i++) { // Build the LCP array
        in O(NlogN)
        int x = sa[i], y = sa[i + 1], k, ret = 0;
        for (k = __log_n - 1; k >= 0 && x < n && y < n; k--) {
            if ((1 << k) >= n)
                continue;
            if (ra[k][x] == ra[k][y])
                x += 1 << k, y += 1 << k, ret += 1 << k;
        }
        if (ret >= __dollar[sa[i]] - sa[i])
            ret = __dollar[sa[i]] - sa[i];
        _lcp[0][i] = ret; // LCP[i] shouldnt exceed
        __dollar[sa[i]]
    } // __dollar[i] : index of __dollar to the right of i.
    _lcp[0][n - 1] = 10 * n;
    for (int i = 1; i < __log_n; i++) { // O(1) RMQ structure
        in O(NlogN)
        int add = (1 << (i - 1));
        if (add >= n)
            break; // small optimization
        for (int j = 0; j < n; j++)
            if (j + add < n)
                _lcp[i][j] = min(_lcp[i - 1][j], _lcp[i - 1][j
                    + add]);
            else
                _lcp[i][j] = _lcp[i - 1][j];
    }
}

int lcp(int x, int y) {
    // O(1) LCP. x & y are indexes of the suffix in sa!
    if (x == y)
        return __dollar[sa[x]] - sa[x];
    if (x > y)
        swap(x, y);
    y--;
    int idx = __msb[y - x + 1], sub = (1 << idx);
    return min(_lcp[idx][x], _lcp[idx][y - sub + 1]);
}

```

```

bool equal(int i, int j, int p, int q) {
    if (j - i != q - p)
        return false;
    int idx = __msb[j - i + 1], sub = (1 << idx);
    return ra[idx][i] == ra[idx][p] &&
        ra[idx][j - sub + 1] == ra[idx][q - sub + 1];
} // Note : Do not forget to add a terminating $

// To check substring/LCS, run the string on the automaton. Each
// path in the
// automaton is a substring(if it ends in a terminal node, it is
// a suffix). To
// find occurrences of a string, run it on the automaton, and the
// number of its
// occurrences would be number of ways to reach a terminal node.
// Or, we can keep
// reverse edges of suffix links(all prefixes for that
// substring), and number of
// ways to reach a root, would be the answer(can be used to print
// all answers)
struct AhoCorasick {
    vector<int> sufflink, out;
    vector<map<char, int>> trie; // call findnextstate
    AhoCorasick() {
        out.resize(1);
        trie.resize(1);
    }
    inline void insert(string &s) {
        int curr = 0; // clear to reinit
        for (int i = 0; i < s.size(); i++) {
            if (!trie[curr].count(s[i])) {
                trie[curr][s[i]] = trie.size();
                trie.push_back(map<char, int>());
                out.push_back(0);
            }
            curr = trie[curr][s[i]];
        }
        ++out[curr];
    }
}

```



```

        edges.push_back(edges[q]);
        length.push_back(length[p] + 1);
        link.push_back(link[q]);
        int qq = edges.size() - 1;
        link[q] = qq;
        link[r] = qq;
        while (p >= 0 && edges[p][s[i]] == q)
            edges[p][s[i]] = qq, p = link[p];
    }
}
last = r;
}
vector<int> terminals;
int p = last;
while (p > 0)
    terminals.push_back(p), p = link[p];
};

```

## 16 TreapsIntervals

```
#include "template.hpp"
```

```

struct node{int val,prior,size;node *l,*r;};typedef node*
pnode;int sz(pnode t){return t?t->size:0;}void upd_sz(pnode
t){if(t)t->size = sz(t->l)+1+sz(t->r);}void split(pnode
t,pnode &l,pnode &r,int key){if(!t)l=r=NULL;else
if(t->val<=key)split(t->r,t->r,r,key),l=t;else
split(t->l,l,t->l,key),r=t;upd_sz(t);}void merge(pnode
&t,pnode l,pnode r){if(!l || !r)t=l?l:r;else if(l->prior>
r->prior)merge(l->r,l->r,r),t=l;else
merge(r->l,l,r->l),t=r;upd_sz(t);}void insert(pnode &t,pnode
it){if(!t) t=it;else
if(it->prior>t->prior)split(t,it->l,it->r,it->val),t=it;else
insert(t->val<it->val?t->r:t->l,it);upd_sz(t);}void
erase(pnode &t,int key){if(!t)return;else
if(t->val==key){pnode x=t;merge(t,t->l,t->r);free(x);}else
erase(t->val<key?t->r:t->l,key);upd_sz(t);}void unite (pnode
&t,pnode l, pnode r){if(!l||!r)return void(t=l?l:r);pnode

```

```

lt,rt;if(l->prior<r->prior)swap(l,r);split(r,lt,rt,l->val);unite(l->l,
init(int val){pnode ret =
(pnode)malloc(sizeof(node));ret->val=val;ret->size=1;ret->prior=rand();
ret;}insert(init(x),head);
// Interval Tree
struct node{int prior,size,val,sum,lazy;node *l,*r;};typedef
node* pnode;int sz(pnode t){return t?t->size:0;}void
upd_sz(pnode t){if(t)t->size=sz(t->l)+1+sz(t->r);}void
lazy(pnode t){if(!t ||
!t->lazy)return;t->val+=t->lazy;t->sum+=t->lazy*sz(t);if(t->l)t->l->lazy=0;
reset(pnode t){if(t)t->sum = t->val;already propagated}void
combine(pnode& t,pnode l,pnode r){3
if(!l || !r)return void(t = l?l:r);t->sum = l->sum + r->sum;}void
operation(pnode
t){if(!t)return;reset(t);lazy(t->l);lazy(t->r);combine(t,t->l,t);comb
split(pnode t,pnode &l,pnode &r,int pos,int
add=0){if(!t)return void(l=r=NULL);lazy(t);int
cpos=add+sz(t->l);if(cpos<=pos)split(t->r,t->r,r,pos,cpo+1),l=t;else
split(t->l,l,t->l,pos,add),r=t;upd_sz(t);operation(t);}void
merge(pnode &t,pnode l,pnode r){lazy(l);lazy(r);if(!l || !r) t
= l?l:r;else if(l->prior>r->prior)merge(l->r,l->r,r),t=l;else
merge(r->l,l,r->l),t=r;upd_sz(t);operation(t);}pnode init(int
val){pnode
ret=(pnode)malloc(sizeof(node));ret->prior=rand();ret->size=1;ret->v
ret;}int range_query(pnode t,int l,int r){pnode
L,mid,R;split(t,L,mid,l-1);split(mid,t,R,r-1);/*note:
r-l!*/int ans = t->sum;merge(mid,L,t);merge(t,mid,R);return
ans;}void range_update(pnode t,int l,int r,int val){pnode
L,mid,R;split(t,L,mid,l-1);split(mid,t,R,r-1);/*note:
r-l!*/t->lazy+=val; merge(mid,L,t);merge(t,mid,R);}

```

## 17 TreesCentroids

```
#include "template.hpp"
```

```

class Tree {
public:
    struct Node {
        vector<Node *> adjacent; Node *parent = nullptr;

```

```

    int start_time = 0, end_time = 0, subtree_size = 1;
    int depth = 0, height = 0, index = INT32_MAX;
};
vector<Node> list; Node *root = nullptr;
vector<vector<Node *>> __anc;
Tree(int n = 1e5) {
    list.resize(n); this->root = &list[0];
    for (int i = 0; i < n; i++) list[i].index = i;
}
void add_edge(int x, int y) {
    list[x].adjacent.push_back(&list[y]);
    list[y].adjacent.push_back(&list[x]);
}
Node *lca(Node *a, Node *b) {
    if (b->depth > a->depth) swap(a, b);
    for (int ptr = __anc[0].size() - 1; a->depth > b->depth &&
        ptr >= 0; ptr--)
        if (__anc[a->index][ptr] != nullptr &&
            __anc[a->index][ptr]->depth >= b->depth)
            a = __anc[a->index][ptr];
    if (a == b) return a;
    for (long step = __anc[0].size() - 1; step >= 0; step--)
        if (__anc[a->index][step] != __anc[b->index][step])
            a = __anc[a->index][step], b =
                __anc[b->index][step];
    return a->parent;
}
Node *ancestor(Node *a, int degree) {
    ll target_depth = a->depth - degree;
    for (int ptr = __anc[0].size() - 1; a->depth >
        target_depth && ptr >= 0; ptr--)
        if (__anc[a->index][ptr] != nullptr &&
            __anc[a->index][ptr]->depth >= target_depth)
            a = __anc[a->index][ptr];
    return a;
}
int __build(Node *root = nullptr, int time = 0) {
    if (root == nullptr) root = this->root;
    root->start_time = time;
    for (auto child : root->adjacent) {
        if (child == root->parent) continue;

```

```

        child->parent = root;
        child->depth = root->depth + 1;
        time = __build(child, time + 1);
        root->height = max(root->height, child->height + 1);
        root->subtree_size += child->subtree_size;
    }
    root->end_time = time;
    return time;
}
void __build_lca_matrix() {
    int n = list.size();
    __anc = *new vector<vector<Node *>>(n, vector<Node
        *>(log2(n) + 1, nullptr));
    for (int i = 0; i < list.size(); i++) __anc[i][0] =
        list[i].parent;
    for (int level = 1; level < __anc[0].size(); level++)
        for (int i = 0; i < list.size(); i++) {
            if (__anc[i][level - 1] == nullptr) continue;
            __anc[i][level] = __anc[__anc[i][level -
                1]->index][level - 1];
        }
}
};

struct CentroidTree : Tree {
    vector<bool> __visited; vector<int> __dir_parents,
        __subtree_size; Tree base;
    void __dfs_centroid(int node) {
        __subtree_size[node] = 1;
        for (Node *next : base.list[node].adjacent)
            if (!__visited[next->index] && next->index !=
                __dir_parents[node]) {
                __dir_parents[next->index] = node;
                __dfs_centroid(next->index);
                __subtree_size[node] += __subtree_size[next->index];
            }
    }
    int __get_centroid(int x) {
        __dir_parents[x] = 0; __dfs_centroid(x); int sz =
            __subtree_size[x];
        while (true) {

```



```

    pair<int, int> mx = {0, 0};
    for (Node *next : base.list[x].adjacent)
        if (!__visited[next->index] && next->index !=
            __dir_parents[x])
            mx = max(mx, {__subtree_size[next->index],
                next->index});
    if (mx.first * 2 > sz) x = mx.second; else return x;
}
}
void __build_centroid(int node, Node *parent) {
    node = __get_centroid(node); list[node].parent = parent;
    __visited[node] = true;
    for (Node *next : base.list[node].adjacent)
        if (!__visited[next->index])
            __build_centroid(next->index, &list[node]);
}
CentroidTree(Tree &tree) : Tree((int)tree.list.size()) {
    __visited = vector<bool>(tree.list.size());
    __subtree_size = vector<int>(tree.list.size());
    __dir_parents = vector<int>(tree.list.size());
    base = tree;
    __build_centroid(0, nullptr);
    for (auto el : list) {
        if (el.parent == nullptr) root = &list[el.index];
        else add_edge(el.index, el.parent->index);
    } __build(root);
}
};

ll diameter(Tree tree) {
    ll n = tree.list.size() + 1; vbl visited(n + 1, false); vll
        distances(n + 1, -1);
    queue<pll> q; q.push({tree.root->index, 0});
    ll node_max = tree.root->index, distance_max = 0;
    while (!q.empty()) {
        auto node = q.front(); q.pop();
        if (node.second < distance_max) distance_max =
            node.second, node_max = node.first;
        for (auto neighbor : tree.list[node.first].adjacent)
            if (!visited[neighbor->index]) {
                auto d = node.second + 1;

```

```

                q.push({neighbor->index, d});
                visited[neighbor->index] = 1;
            }
    }
    visited = vbl(n + 1, false);
    q.push({node_max, 0}); distance_max = 0;
    while (!q.empty()) {
        auto node = q.front(); q.pop();
        maximize(distance_max, node.second);
        for (auto neighbor : tree.list[node.first].adjacent)
            if (!visited[neighbor->index]) {
                auto d = node.second + 1;
                q.push({neighbor->index, d});
                visited[neighbor->index] = 1;
            }
    }
}

struct HeavyLightDecomp : Tree {
    int chain_count = 1, narr;
    vector<int> subtree_size, chain, chain_head, chain_next;
    function<ll(int, int, ll)> answer;
    vector<int> pos;

    HeavyLightDecomp(int n, function<ll(int, int, ll)> &ans) :
        Tree(n) {
        subtree_size.resize(n); pos.resize(n); chain.resize(n);
        chain_head.resize(n); chain_next.resize(n); answer = ans;
    }

    void decompose(int node = 0, int parent = -1) {
        pos[node] = ++narr, chain[node] = chain_count; int big = 0;
        for (Node *adj : list[node].adjacent) {
            int u = adj->index;
            if (u == parent) continue;
            else if (!big) big = u;
            else if (subtree_size[u] > subtree_size[big]) big = u;
        }
        if (big) decompose(big, node);
        for (Node *adj : list[node].adjacent) {
            int u = adj->index;

```

```
    if (u == parent || u == big) continue;
    ++chain_count, chain_head[chain_count] = u,
        chain_next[chain_count] = node;
    decompose(u, node);
}
}
// Build Segment Tree using indices of pos array
// Update ans using Range queries on said segment tree
int query_up(int r, int q) {
    int ans = 0, t;
```

```
    while (chain[q] != chain[r]) {
        t = chain[q];
        ans = answer(pos[chain_head[t]], pos[q], ans);
        q = chain_next[t];
    }
    ans = answer(pos[r], pos[q], ans);
    return ans;
}
};
```

---