

1 (a)	<p>Answer the following questions:</p> <ol style="list-style-type: none"> What is Moore's Law, and how does it relate to computer capabilities? What is big data and what are the 4 V's of Big Data? <p>Ans (i): Moore's Law is an observation made by Gordon Moore, co-founder of Intel, in 1965. It states that the number of transistors on a microchip doubles approximately every two years, while the cost of production is halved. This trend has historically led to exponential growth in computing power over time.</p> <p>Relation to Computer Capabilities:</p> <p>Moore's Law directly impacts several aspects of computing:</p> <ol style="list-style-type: none"> Performance Improvements: <ul style="list-style-type: none"> As transistor density increases, processors become faster and more efficient, improving computational capabilities. This allows for more complex and powerful algorithms to be run in shorter times. Cost Reduction: <ul style="list-style-type: none"> The cost per transistor has decreased significantly, making computing power cheaper and more accessible. Energy Efficiency: <ul style="list-style-type: none"> Smaller transistors consume less power, making devices more energy-efficient. Miniaturization: <ul style="list-style-type: none"> The increase in transistor density enables the creation of smaller, more powerful devices, such as smartphones and IoT devices. Parallelism: <ul style="list-style-type: none"> Modern processors include more cores and support for parallel processing, leveraging increased transistor counts. <p>Ans (ii): Big Data refers to extremely large datasets that are too complex, vast, or varied to be efficiently processed, stored, or analyzed using traditional data-processing tools. It encompasses structured, semi-structured, and unstructured data collected from various sources, including social media, sensors, transactions, and logs.</p> <p>The 4 V's of Big Data are Volume, Velocity, Variety and Veracity.</p>	(2)												
(b)	<p>From the following expressions, identify which statements produce a runtime error.</p> <table border="0"> <tr> <td>i. $10/3+7$</td> <td>ii. $10//3+7$</td> <td>iii. $10/(3+7)$</td> </tr> <tr> <td>iv. $10/3-3$</td> <td>v. $10/(3-3)$</td> <td>vi. $10//(3-3)$</td> </tr> </table> <p>Ans:</p> <table border="0"> <tr> <td>i. No runtime error.</td> <td>ii. No runtime error.</td> <td>iii. No runtime error.</td> </tr> <tr> <td>iv. No runtime error.</td> <td>v. Runtime error.</td> <td>vi. Runtime error.</td> </tr> </table>	i. $10/3+7$	ii. $10//3+7$	iii. $10/(3+7)$	iv. $10/3-3$	v. $10/(3-3)$	vi. $10//(3-3)$	i. No runtime error.	ii. No runtime error.	iii. No runtime error.	iv. No runtime error.	v. Runtime error.	vi. Runtime error.	(2)
i. $10/3+7$	ii. $10//3+7$	iii. $10/(3+7)$												
iv. $10/3-3$	v. $10/(3-3)$	vi. $10//(3-3)$												
i. No runtime error.	ii. No runtime error.	iii. No runtime error.												
iv. No runtime error.	v. Runtime error.	vi. Runtime error.												

(c)	<p>Analyze the expression: $5 * (3 + 2) ** 2 - 10 / 2$. Explain how each operator's precedence affects the final outcome.</p> <p>Ans:</p> $5 * (3 + 2) ** 2 - 10 / 2$ $= 5 \times (5) ** 2 - 10 / 2$ $= 5 \times 25 - 10 / 2$ $= 125 - 5.0$ $= 120.0$	(2)
-----	--	-----

2 (a)	<p>Answer the following questions:</p> <ol style="list-style-type: none"> Can you use a conditional expression in Python? Explain with an example. What will happen if the user inputs "abc" when prompted for an integer using <code>int(input('Enter an integer: '))</code>? What type of error will be raised? <p>Ans (i): Yes, Python supports conditional expressions, also known as ternary operators, which allow to write concise, one-line conditional statements.</p> <p>Example:</p> <pre>num = 5 result = "Even" if num % 2 == 0 else "Odd" print(result)</pre> <p>Output: Odd</p> <p>Ans (ii): The <i>input()</i> function reads the user input as a string. The <i>int()</i> function tries to convert the string to an integer. Since "abc" is not a valid integer, the conversion fails and Python will raise a 'ValueError'.</p>	(2)
(b)	<p>Write a Python script that inputs a five-digit integer from the user. Separate the number into its individual digits and print them, separated by a tab. For example, if the user types in the number 42339, the script should print:</p> <p style="text-align: center;">4 2 3 3 9</p> <p>Ans:</p> <pre>num = input('Enter an integer: ') for digit in num: print(digit, end='\t')</pre>	(2)

(c)	<p>Write the output of the following Python script:</p> <pre>count = 1 while count <= 5: print(count, end=' ') count += 1 if count == 5: continue print('ITER', end=' ') print('out from the loop')</pre> <p>Ans: 1 ITER 2 ITER 3 ITER 4 5 ITER out from the loop</p>	(2)
-----	--	-----

3 (a)	<p>How can you calculate the mean, median, and mode of a list of numbers in Python? Write a program that takes a list of integers, computes these statistics, and prints the results.</p> <p>Ans:</p> <pre>import statistics numbers = list(map(int, input("Enter a list of integers separated by spaces: ").split())) mean = statistics.mean(numbers) median = statistics.median(numbers) mode = statistics.mode(numbers) print(f'Mean: {mean}') print(f'Median: {median}') print(f'Mode: {mode}')</pre>	(2)
(b)	<p>Write a Python function that accepts an input parameter for the number of rows to be printed and generates a figure like this:</p> <pre>1 2 1 3 2 1 4 3 2 1 5 4 3 2 1</pre> <p>Ans:</p> <pre>def print_figure(rows): for i in range(1, rows + 1): for j in range(i, 0, -1): print(j, end=" ") print() num_rows = int(input("Enter the number of rows to print: ")) print_figure(num_rows)</pre>	(2)

(c)	<p>Write a Python function that accepts an integer and displays all of its smallest factors in increasing order. For example, if the input integer is 120, the output should be: 2, 2, 2, 3, 5.</p> <p>Ans:</p> <pre>def find_factors(n): divisor = 2 while n > 1: if n % divisor == 0: # If divisor is a factor print(divisor, end=" ") # Print the factor n //= divisor # Reduce n by dividing it by the divisor else: divisor += 1 # Move to the next divisor num = int(input("Enter an integer: ")) if num > 0: print("Smallest factors in increasing order:", end=" ") find_factors(num) else: print("Please enter a positive integer.")</pre>	(2)
-----	---	-----

4 (a)	<p>What is the output of the following code?</p> <pre>def cube(x): """Calculate the cube of x.""" x**3 print('The cube of 2 is', cube(2))</pre> <p>Ans: The cube of 2 is None</p>	(2)
(b)	<p>Write a Python function to print all the perfect numbers between 1 and 100. A number is called perfect if the sum of its proper divisors (excluding the number itself) is equal to the number. For example, the divisors of 6 are 1, 2, and 3, and 1+2+3=6.</p> <p>Ans:</p> <pre>def perfect_numbers(limit): for num in range(2, limit + 1): # Start from 2 as 1 is not a perfect number divisors_sum = 0 for i in range(1, num): if num % i == 0: divisors_sum += i if divisors_sum == num: print(num) perfect_numbers(100)</pre>	(2)

(c)	<p>Using Python, apply the concepts of map, filter, reduce, and lambda expressions to accomplish the following task:</p> <p>Calculate the sum of the cubes of all odd numbers between 1 and 101 (inclusive of both).</p> <p>Guidelines:</p> <ul style="list-style-type: none"> • Use filter to select the odd numbers from the range. • Use map to compute the cube of each odd number. • Use reduce to sum the cubes together. <p>Ans:</p> <pre>from functools import reduce odd_numbers = filter(lambda x: x % 2 != 0, range(1, 102)) cubed_numbers = map(lambda x: x ** 3, odd_numbers) sum_of_cubes = reduce(lambda x, y: x + y, cubed_numbers) print("Sum of cubes of odd numbers between 1 and 101:", sum_of_cubes)</pre>	(2)
-----	--	-----

5 (a)	<p>Mention two differences between lists and tuples.</p> <p>Ans:</p> <table><tr><th>List</th><th>Tuple</th></tr><tr><td>1. Collection of elements separated by commas and enclosed in square brackets [].</td><td>1. Collection of elements separated by commas and enclosed in round brackets ().</td></tr><tr><td>2. Lists are Mutable.</td><td>2. Tuples are Immutable.</td></tr></table>	List	Tuple	1. Collection of elements separated by commas and enclosed in square brackets [].	1. Collection of elements separated by commas and enclosed in round brackets ().	2. Lists are Mutable.	2. Tuples are Immutable.	(2)
List	Tuple							
1. Collection of elements separated by commas and enclosed in square brackets [].	1. Collection of elements separated by commas and enclosed in round brackets ().							
2. Lists are Mutable.	2. Tuples are Immutable.							
(b)	<p>Write a Python program that returns a list of duplicate elements from an input list. For example, if the input list is [1, 2, 3, 6, 5, 2, 3, 6, 7, 8, 6, 4, 5], the output list should be [2, 3, 6, 5].</p> <p>Ans:</p> <pre>l=[1, 2, 3, 6, 5, 2, 3, 6, 7, 8, 6, 4, 5] repeatl=[i for i in l if l.count(i)>1] newl=[] for i in repeatl: if i not in newl: newl.append(i) print(newl)</pre> <p>Output: [2, 3, 6, 5]</p>	(2)						

(c)	<p>What will be the output of the following code? Can you analyze how it works?</p> <pre> import copy list_a = [1, 2, [3, 4]] list_b = list_a.copy() list_b[2][0] = 10 print("List A:", list_a) print("List B:", list_b) list_c = copy.deepcopy(list_a) list_c[2][0] = 20 print("List A", list_a) print("List C", list_c) </pre> <p>Ans: List A: [1, 2, [10, 4]] List B: [1, 2, [10, 4]] List A [1, 2, [10, 4]] List C [1, 2, [20, 4]]</p> <p>list_b is a shallow copy of list_a. So although the non-nested elements of list_a (shallow level elements) are copied properly in list_b, the nested elements are not copied. Thus, any changes in the nested elements are reflected in both list_a and list_b.</p> <p>list_c is a deep copy of the modified list_a. So the nested and non-nested elements of the modified list_a are copied. Thus, changes made to list_c remain confined to list_c only and are not reflected in list_a.</p>	(2)
-----	--	-----