DSA4213 Assignment 1: Does better next-token prediction give better representations?

Language models, embeddings and downstream topic classification on WikiText-2 and AG News

Aniroodh Chaudhary A0284770W AY2026/27 Semester 1

1 Question and setup

Two things are commonly assumed about small language models (LMs): that lower perplexity means a better model, and that better LMs give better text representations. This report tests both on one corpus. The question is: *does better next-token prediction translate into better frozen representations for topic classification, and how much do input-embedding choices matter?* Part I trains four LM families on WikiText-2 under one recipe; Part II keeps the LSTM (the best full-history model of Part I and the cheapest per epoch) and varies only its input table in a 3×2 (source $\times$ trainability) design; Part III feeds the frozen models' states to one linear classifier on AG News. Everything not under study (vocabulary, stream, embedding width, output layer, optimiser, schedule, evaluation, prompts, decoding, classifier) is held fixed.

2 Data and common protocol

Corpus and vocabulary. WikiText-2 [1] (pre-tokenised, with its own `<unk>`) is lowercased once, one `<eos>` is appended per line, and the vocabulary is built from the train split only: 28,913 types. Lowercasing is a fairness decision: GloVe-6B is uncased, so a cased vocabulary would let *The*/*the* share one vector only in Part II's GloVe setting; it shrinks the vocabulary from 33,278 types, so perplexities are not comparable with published numbers. Validation and test contain no out-of-vocabulary tokens beyond the dataset's own `<unk>` (6.2% of test tokens), which every model, including the n-gram, treats as an ordinary vocabulary item.

Streams and perplexity. Each split is one continuous token stream (train 2,075,678 tokens, validation 216,348); no padding exists, so nothing has to be excluded from any loss, and every model is scored on the same 244,102 test targets, perplexity being exp of the mean per-target cross-entropy. Recurrent models are scored with batch 1 and the state carried over the entire stream (full history); the Transformer with a sliding 128-token window moved by 32, scoring the last 32 targets of each window (the first window scores all 128; every later target sees $\geq$96 tokens of context). A second protocol, non-overlapping 128-token blocks with the state reset, is identical for every model and isolates context length. Validation during training uses the same protocols, so curves and final numbers are comparable.

Models and recipe. All neural models share a 300-d input embedding (the largest width GloVe-6B ships, so Part II can reuse it) initialised $\mathcal{U}(-0.1, 0.1)$ and a $300 \times V$ output layer, so they differ only in the sequence core: a 2-layer tanh RNN (0.36 M core parameters), a 2-layer LSTM [2] (1.44 M), a 4-layer pre-LN Transformer [3] with 6 heads and FFN width 1200 (4.37 M) and, as a parameter-count control, the same Transformer with 1 layer (1.12 M). The n-gram baseline is interpolated Kneser–Ney [4, 5] with one discount per order, orders 2–5 fitted and the order chosen on validation. The neural recipe is identical for every run (hyper-parameters in Appendix C): batch 32 $\times$ 128-token BPTT chunks with the state detached between chunks, dropout 0.3 (the Transformer additionally drops attention and FFN activations at 0.3), Adam (10^{-3}, 200-step warm-up), learning rate halved after two consecutive epochs without validation improvement, early stopping after three, at most 12 epochs, global gradient clipping at 1.0 with the pre-clip norm logged at every step. A unit test perturbs future tokens and checks that no model's earlier logits change (causality) and that input and output tables are not tied.

Cost measurement. All runs use one Apple M4 (16 GB) through PyTorch 2.14's MPS backend [6], one process at a time. Timers synchronise the device before and after each measurement; epoch 1 includes shader compilation and is excluded from per-epoch averages. Model size is the parameter count and the saved fp32 checkpoint. The common inference workload is (A) scoring the full test stream with the protocol above and (B) generating 50 tokens for each of 5 prompts at batch 1 with top-k sampling (the Transformer without a KV cache). MPS is not bit-deterministic: the 24-epoch runs repeat the first 12 epochs of the seed-0 runs and differ from them by 0.04 (LSTM) and 0.00 (Transformer) validation PPL at epoch 12, so run-to-run noise is negligible; the seed-1 repeats in Part II measure seed variance instead (about one point), and `-device cpu` reproduces exactly.

Model	Test PPL	Test, ctx≤128	Val, ep. 3	Val, ≤8 min	Val, ep. 12 (best)	Test, 24 ep.
KN 5-gram	214.9	–	–	–	–	–
RNN	173.0	177.2	219.6	210.0	187.3	–
LSTM	134.2	150.4	237.3	214.8	145.4	124.6
Transformer (4L)	140.9	146.4	227.9	227.9	150.1	132.3
Transformer (1L, control)	171.4	174.7	256.9	234.0	183.1	–

Table 1: Part I prediction quality on the common 244,102 test targets. ctx≤128: state reset every 128 tokens for every model (the matched comparison); epoch-3 / ≤8-min columns: matched updates / wall-clock; last column: a separate 24-epoch run.

Model	Params (M)	Core (M)	Size (MB)	Train (min)	Score, blocks (tok/s)	Score, own (tok/s)	Gen. (ms/tok)
KN 5-gram	5.8 entries	–	156	0.1	–	318,385	19.7
RNN	17.7	0.36	71	23.2	46,392	6,779	1.6
LSTM	18.8	1.44	75	22.1	63,206	26,333	1.7
Transformer (4L)	21.8	4.37	87	29.8	50,500	12,694	3.4
Transformer (1L, control)	18.5	1.12	74	22.0	74,059	18,758	2.3

Table 2: Part I cost on one Apple M4 (MPS). Core: excluding the shared embedding and output layers; train: minutes to the best checkpoint; score: throughput on the common workload (128-token blocks, 16 per batch) and under each model's own protocol (batch 1 for recurrent models); generate: batch-1 sampling.

Generation. Five prompts are the first 10 tokens of seeded-random *validation* lines (≥30 tokens, not headings, no `<unk>` in the prompt; never test); every model continues each for 50 tokens with greedy decoding and with top-k=40, T=1 sampling from one shared CPU sampler, so decoding is matched exactly across the n-gram and neural models. Continuations are summarised by distinct-n ratios and the fraction of 4-grams repeating an earlier 4-gram of the same continuation.

3 Part I: four language models on one corpus

Observations. *Prediction quality* (Table 1). With full history the order is LSTM (134.2) < Transformer (140.9) < RNN (173.0) ≈ 1-layer Transformer (171.4) < KN 5-gram (214.9). Under the matched protocol (context reset every 128 tokens for every model; the common evaluation setup, since full-history scoring favours the recurrent models) the order of the two best models *reverses*: the Transformer loses only 5.6 points, the LSTM loses 16.2 and ends up behind it. *Learning behaviour* (Fig. 1). All four neural models were still improving at the 12-epoch cap: no learning-rate halving or early stop fired, and the train/validation gap grows (LSTM: 113.1 with dropout on vs. 145.4 at epoch 12) without the validation loss turning up, i.e. no overfitting at this budget. Per epoch the LSTM and 4-layer Transformer track each other; per wall-clock minute the LSTM leads the Transformer (epochs of 110 vs. 149 s). After three epochs the tanh RNN is the *best* model (219.6 vs. 237.3 and 227.9); it learns fastest and saturates first. *Where the differences sit* (Fig. 2). On the 3.4% of test targets seen at most 10 times in training the n-gram is the best model (12.25 nats vs. 13.16 for the LSTM); every neural model wins on words seen ≥11 times, up to the most frequent bucket (>10k: LSTM 2.26 vs. n-gram 2.65). The Transformer is the best model on `<eos>` (1.09 vs. 1.30) but worse than the LSTM on `<unk>` (3.51 vs. 3.19). *Cost* (Table 2). The 4-layer Transformer needs 29.8 min of training against 22.1 for the LSTM and reaches a worse full-history perplexity with 3× the core parameters. On the common inference workload (scoring the test stream in 128-token blocks, 16 per batch) the models reach 46,392 (RNN), 63,206 (LSTM), 50,500 (4L) and 74,059 (1L) tokens/s; under their own protocols the batch-1 recurrent models fall to 6,779 and 26,333 and the sliding window costs the Transformer 12,694. Sampling costs 1.7 (LSTM) vs. 3.4 ms per token (Transformer, no KV cache). The n-gram fits and validates all four orders in 10 s and scores at 318,385 tokens/s on the CPU, but in this dictionary implementation its 156 MB of tables exceed any checkpoint and sampling its full distribution costs 19.7 ms per token. *Generated text* (Table 3, Appendix A). Under greedy decoding the RNN and 1-layer Transformer loop (74% and 57% of 4-grams repeat an earlier one; n-gram 58%), the LSTM and 4-layer Transformer far less (25%, 31%). Top-k sampling removes repetition for every model (≤2.6%), so sampled continuations differ in local fluency and consistency instead: the LSTM and Transformer hold a topic across the 50 tokens (a "route description" section after the highway prompt, the Ming court after the 1644 prompt), the RNN drifts within a sentence and the n-gram within a few tokens.

Explanations, separated from the observations. *The LSTM's lead is a context-length effect.* Under context reset the Transformer is the better predictor, so the LSTM's full-history lead comes from information carried beyond 128 tokens (WikiText articles are thousands of tokens long); whether a longer-window Transformer would close the gap was not tested, and carrying state indefinitely is itself an architectural property. *Parameter count does not explain the ranking.* The 1-layer Transformer has about the LSTM's core size (1.12M vs. 1.44M) and is 37.2 points worse, while the 4-layer model has 3× the LSTM's core and is still worse with full history; depth matters for the Transformer, but more parameters did not buy a better model at this budget. *Training budget conditions every conclusion.* Nothing converged in 12 epochs and the ranking at epoch 3 (RNN first) differs from that at epoch 12, so we re-ran the LSTM and Transformer for 24 epochs (last column of Table 1, dashed in Fig. 1): the LSTM early-stopped with its best validation at epoch 18 (test PPL 124.6), the Transformer was




Figure 1: Validation perplexity (solid) and train perplexity (dotted) per epoch (left) and validation perplexity against training wall-clock (right); dashed: the separate 24-epoch runs.




Figure 2: Test cross-entropy split by how often the target word occurs in the train split.

still improving at epoch 24 (132.3), and under context reset the Transformer still leads (137.3 vs. 141.0), so both conclusions survive a doubled budget. *The n-gram's edge on rare words* is expected from Kneser–Ney's continuation counts, which model how many contexts a rare type appears in, whereas an embedding row updated at most ten times has barely moved from its initialisation (a hypothesis; Part II tests its input side with pre-trained rows, while the equally under-trained output rows stay untested). *The RNN's slow batch-1 scoring* is a kernel effect, not an architectural one: batched in 128-token blocks it reaches 46,392 tokens/s. *Greedy loops* track model quality (74% and 57% vs. 25% and 31%) under one identical decoder, so they reflect weaker modelling of the recent context rather than the decoding rule.

4 Part II: input-embedding ablation on the LSTM

Design. The LSTM of Part I is retrained with its 300-d input table replaced by (b) skip-gram vectors [7] trained by us on the WikiText-2 train stream only (gensim [8], negative sampling; 1.9 min on the CPU, reported separately from LM training) and (c) public GloVe-6B vectors [9], both kept entirely frozen; (a) is the Part I model itself. Because the required three cells confound *trainability* with *information content*, three cheap extra cells complete a 3×2 factorial: the same two pre-trained tables left trainable, and a frozen random table (no information at all). Skip-gram covers every type that occurs in the stream (`min_count`=1; only `<pad>` is missing). GloVe covers 96.2% of the types and 94.7% of train tokens; the 1,104 missing types include the most frequent tokens of all (`<unk>, <eos>, @-@, @.@, @,@, 't`) and are initialised $\mathcal{N}(0, \sigma_d)$ with σ_d the per-dimension standard deviation of the found rows (a frozen zero row for `<eos>` would cripple the model). The tables differ in scale (mean row norm 6.47 GloVe, 2.37 skip-gram, 1.0 random; nothing is rescaled, a disclosed confound). Freezing is verified by hashing the table before and after training; the required cells are run with seeds 0 and 1.

Observations. *Prediction quality* (Table 4). Both frozen pre-trained tables beat the jointly learned random table: skip-gram 127.9 and GloVe 123.8 against 134.0 test PPL, while the frozen random table collapses to 198.0. Letting the pre-trained tables train improves them further, to 119.0 and 116.5, the two best language models of this report. Seed-0/seed-1 differences in the three repeated cells are 0.5, 1.1 and 0.8 points, so the noise floor is about one point (the three extra cells are single-seed); every contrast below is several times larger except the

Model	Continuation (top-k=40, T=1, 50 tokens; first 20 shown; repetition statistics in Table 7)
Prompt: `the americans knew of the approach of the japanese forces`	
KN 5-gram	`staged a sit in his home . <eos> with the rise of cobra commander in the sequel . <eos> he ...`
RNN	`against the kpa 's king , and a peace @-@ force " it into a high position . <unk> had ...`
LSTM	`during the conflict . <eos> the first time against the american union were created by the royal army , both ...`
Transformer (4L)	`- and some of the song was " impossible " . <unk> said that " this were a " dramatic ...`

Table 3: Matched top-k continuations of one validation prompt (all prompts, all models and greedy decoding in Appendix A).

Embedding source	Trainable	Cov. (%)	Emb. cost	Test PPL	Val ep. 3	Val ep. 6	$\|g\|$ mean	Clipped	Row norm
random	yes	100.0	–	134.0 ± 0.3	237.3	184.9	0.27	0.3%	1.46
random	no	100.0	–	198.0	358.1	274.2	0.32	0.4%	1.00
skip-gram	yes	100.0	1.9 min	119.0	200.8	155.9	0.27	0.3%	2.71
skip-gram	no	100.0	1.9 min	127.9 ± 0.5	228.6	170.4	0.29	0.3%	2.37
GloVe	yes	96.2	public	116.5	190.1	147.7	0.27	0.3%	6.57
GloVe	no	96.2	public	123.8 ± 0.4	205.7	156.0	0.28	0.3%	6.47


Table 4: Part II: the LSTM of Part I with six input-embedding settings (rows 1, 4, 6 required; test PPL ± half-range over seeds 0/1 where run, other columns seed 0). Cov.: types with a pre-trained vector; val ep. 3/6: validation PPL after 3 and 6 epochs; $\|g\|$: mean pre-clip gradient norm; clipped: share of clipped steps; row norm: mean ℓ_2 norm after training.

skip-gram/GloVe difference among trainable tables (2.6 points). *Convergence* (Fig. 3a, columns "val ep. 3/6"). The ordering is visible after three epochs (GloVe-trainable 190.1 vs. random 237.3 vs. random-frozen 358.1), and the frozen skip-gram and GloVe cells pass the random cell's final perplexity at epochs 10 and 8; the random-frozen cell never does. *Stability.* Mean pre-clip gradient norms (0.27–0.32) and clipped-step shares (0.3–0.4%) are indistinguishable across cells; the only differences are isolated spikes (maximum norm 13.1 in one seed of the random cell, 5.8 for the frozen random table, $\leq$2.3 elsewhere). *Generalisation.* Frozen tables fit the training stream less but generalise relatively better: the validation–train perplexity gap at epoch 12 is 13.7 (GloVe frozen) and 14.7 (skip-gram frozen) against 32.2 for the random table and 26.4/29.8 once the pre-trained tables train, consistent with 8.7 M fewer trainable parameters. *Where the gain sits* (Fig. 3b). The per-token benefit of a frozen pre-trained table is largest on rare words: on targets seen at most 10 times, frozen GloVe and skip-gram change the cross-entropy by -0.47 and -0.50 nats relative to the random table; the change shrinks with frequency and vanishes on words seen more than 10k times (0.00 and +0.05). Because rare targets are only 3.4% of the test set, most of the total improvement comes from words seen 11–1k times (74% of frozen GloVe's net gain against 19% from the rarest bucket). Training the tables shifts the pattern: the trainable tables change less on the rarest words (GloVe -0.27) but are the only settings that also improve the most frequent ones (-0.08 and -0.05), and the frozen random table loses on every bucket. *Generated text* (Appendix A). Sampled continuations from the pre-trained cells are locally fluent WikiText (section headings, unit conversions), whereas the frozen random table degenerates into `<unk> @-@ <unk>` chains (top-k distinct-2 0.84 vs. 0.95 for the Part I LSTM). Under greedy decoding repetition is *not* monotone in perplexity: the best cells loop more often (46% of 4-grams for trainable GloVe, 41% for frozen skip-gram) than the Part I LSTM (25%), an observation these experiments do not explain.


Trainability versus extra data. The factorial separates the two factors the brief asks about. *Trainability* (frozen vs. trainable at a fixed source) matters enormously when the table carries no information (64.1 points) and only moderately once it does (skip-gram: 8.8; GloVe: 7.3). *Information in the table* (random vs. skip-gram at fixed trainability) is worth more: 14.9 points among trainable tables and 70.2 among frozen ones. The practical corollary crosses the diagonal: replacing the trainable random table by a frozen skip-gram table trained on the very same 2 M tokens gains 6.1 points for 1.9 min of CPU time (under a tenth of one LM run). *Extra data* (GloVe's 6 B tokens against our 2 M) buys a further 4.1 points frozen and 2.6 trainable, i.e. less than having any sensible pre-trained table at all. Two caveats pull GloVe's figures in opposite directions: its most frequent missing types (`<eos>`, `<unk>`, `@-@`) sit frozen at random vectors, a handicap, while GloVe-6B was trained on Wikipedia 2014 plus Gigaword newswire, which almost certainly contains the WikiText-2 source articles; and the row-norm confound (rows about 6× the random initialisation's norm) could explain part of its edge. Our reading, a hypothesis: with 2 M tokens and 12 epochs the 8.7 M-parameter input table is the slowest-learning part of the model (rare rows receive few updates, cf. the n-gram's rare-word advantage in Part I), so giving every row a usable vector before LM training is worth more than the freedom to adjust it during training.

5 Part III: representations for topic classification

Setup. Each AG News [10] document (title + description, tokenised with the WikiText conventions, lower-cased and mapped to the WikiText vocabulary at 92.5% token coverage, `<eos>`-prefixed, truncated at 96 tokens) becomes one 300-d vector from a frozen model: the mean of the top-layer states over non-pad positions, or the state at the last real token; causal models never let padding reach a real position (unit-tested). One multinomial logistic regression on standardised features is fitted per representation, with C chosen on 2,000 held-out training



(a) Validation curves (thin: seed 1).



(b) Change in test CE vs. random-trainable by target frequency (hatched: frozen); the frozen random table, worse by 0.03–0.64 nats on every bucket, is omitted for scale.

Figure 3: Part II learning behaviour and where each embedding setting helps or hurts.


Representation	Dim	Source LM test PPL	Acc.	F1 (n=20,000)	F1 (n=2,000)	F1 (n=500)
LSTM, last state	300	134.2	62.7	62.3	59.4	54.5
LSTM, mean	300	134.2	68.1	67.9	64.2	60.6
Transformer, last state	300	140.9	73.6	73.6	69.9	66.6
Transformer, mean	300	140.9	77.7	77.6	73.9	69.5
RNN, mean	300	173.0	73.6	73.5	69.6	67.2
Transformer 1L, mean	300	171.4	79.0	78.9	74.8	70.9
LSTM + frozen skip-gram, mean	300	128.4	79.4	79.3	77.1	75.2
LSTM + frozen GloVe, mean	300	123.4	82.4	82.3	79.6	77.8
embedding only: LSTM-learned table	300	–	75.2	75.1	70.0	63.3
embedding only: skip-gram	300	–	83.4	83.4	81.1	80.1
embedding only: GloVe	300	–	87.9	87.9	87.2	85.6
TF-IDF uni+bigrams (reference)	98,555	–	89.9	89.9	84.6	78.3

Table 5: AG News test accuracy and macro-F1 (%) of one multinomial logistic regression per frozen representation, for 20,000 / 2,000 / 500 labelled examples (C chosen on 2,000 validation documents; LM features from seed-0 checkpoints).

documents and the 7,600-document test split never used for selection (the feature scaler and the TF-IDF vocabulary are fitted on all 20,000 unlabelled training documents at every label-set size). Embedding-only baselines (the mean of the raw table rows) and a TF-IDF reference over the same vocabulary ids isolate what the sequence model adds.

Observations. *Pooling.* Mean pooling beats the last state for both the LSTM (67.9 vs. 62.3 macro-F1) and the Transformer (77.6 vs. 73.6). *Models.* With mean pooling the Part I models rank 1-layer Transformer (78.9) > 4-layer Transformer (77.6) > RNN (73.5) > LSTM (67.9): the best language model is the worst feature extractor. *Embedding variants.* The LSTM with a frozen GloVe table gives 82.3 and with frozen skip-gram 79.3, far above the random table, but the raw tables alone do better still (GloVe 87.9, skip-gram 83.4), and even the LSTM's own learned input table (75.1) beats the LSTM's hidden states. *Data size* (Fig. 4b). TF-IDF is the best representation with 20,000 labels (89.9) but falls to 78.3 with 500, where mean GloVe still gives 85.6: dense pre-trained features dominate the low-label regime, sparse lexical features win with plentiful labels, and each LM-based representation sits below the embedding-only baseline built from its own input table at every size. *Errors* (Table 6, for LSTM + frozen GloVe, mean). Business and Sci/Tech are confused most often (526 of 7,600 test documents), then World and Business (285); the most confident errors are partly label noise (sports and stock-market stories filed under *World*) and partly genuine ambiguity (a Google privacy story labelled Business, predicted Sci/Tech). Vocabulary coverage does not explain errors: the `<unk>` rate is 7.5% in correctly and 7.4% in wrongly classified documents.

Does the LM ranking agree with the downstream ranking? Only when the input table changes. Over all 6 LM-based mean-pooled representations ρ(PPL, F1) = −0.60 (p = 0.21; negative means lower perplexity with higher F1, i.e. agreement), but that agreement is carried entirely by the embedding table: across the 4 architectures sharing the random table ρ = +0.40 (p = 0.60; descriptive at this n), the best LM is the worst feature extractor and the 1-layer Transformer (a worse LM) the best, whereas across the 3 LSTM input-table cells ρ = −1.00: both metrics improve together, driven by the table, and the LSTM's states keep only part of what the table provides (82.3 vs. 87.9 for the raw GloVe mean). Our explanation, a hypothesis consistent with all three parts: a next-token objective rewards local syntax and the last few words, so a well-trained recurrent state is specialised away from topic (its last state encodes what comes next, not what the document was about), whereas the Transformer's residual stream carries the input embeddings to the top layer, more faithfully with fewer layers (1 > 4). Two confounds remain: the recurrent models were trained with state carried across the



(a) Source-LM perplexity vs. downstream macro-F1. **(b)** Macro-F1 against labelled-set size.

Figure 4: Does better next-token prediction give better representations? (a) Negative ρ means lower perplexity with higher F1.

true \ pred	World	Sports	Business	Sci/Tech
World	**1570**	102	145	83
Sports	68	**1762**	30	40
Business	140	52	**1430**	278
Sci/Tech	102	51	248	**1499**

True	Pred.	Conf.	Text (truncated)
World	Sports	1.00	Maddux Wins No. 302, Baker Wins No. 1,000 Greg Maddux pitched the Chicago Cubs into the lead in
World	Business	1.00	Oil Prices, Earnings Send Stocks Lower NEW YORK - Investors sent stocks lower Tuesday as oil pr
World	Sci/Tech	1.00	Ancient fungus 'revived' in lab Fungus from a deep-sea sediment core that is hundreds of thousa
Business	World	1.00	World briefs LONDON - A man wielding a machete and a knife attacked two security guards at the
Business	Sci/Tech	1.00	Google puts desktop search privacy up front Google has announced a new desktop search applicati

Table 6: Confusion matrix (left) and the most confident errors (right) of the best LM-based representation (LSTM + frozen GloVe, mean).

stream, but Part III starts every 45-token document from a zero state, a cold start the Transformer never faces; and GloVe-6B includes Gigaword newswire, a domain match for AG News that favours the raw GloVe features. Domain shift (lowercased Wikipedia to news) hurts every LM-based representation alike; fine-tuning was outside the frozen-representation question.

6 Conclusions, limitations and use of AI tools

On this corpus better next-token prediction did *not* give better frozen representations across architectures; across input tables both improved together, so the embedding table mattered more than the sequence model for both tasks. The LSTM is the best full-history predictor only because it carries state beyond 128 tokens; at equal context the 4-layer Transformer is better at 35% more training time and half the scoring throughput. A frozen table trained on the same 2 M tokens in 1.9 min beats jointly learned embeddings; GloVe's extra data adds 4.1 points, training the pre-trained table adds 7.3 more, and the per-token gains are largest on rare words. Downstream, mean-pooled raw GloVe (87.9) beats every LM-based feature and TF-IDF wins with enough labels (89.9). *Lessons learned.* Evaluate under more than one context protocol before crediting an architecture; test the input table alone before crediting the sequence model; never read representation quality off perplexity. *Limitations.* One corpus, small models and a 12-epoch budget at which nothing had converged (bounded by the 24-epoch check); MPS training is not bit-reproducible; GloVe-6B overlaps WikiText's source articles and AG News's newswire domain and its rows are longer than the other tables'; Part III uses frozen models only; AG News carries visible label noise. *Use of AI tools.* Claude Code (Anthropic, Claude Fable 5.1) [11] drafted the experiment design, the code, the scripts that generate every table and figure from the result files, and edits of this text; all experiments were run by the author and the analysis is the author's own (`AI_USAGE.md`).

References

[1] Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. In *International Conference on Learning Representations (ICLR)*, 2017.

[2] Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Computation*, 9(8):1735–1780, 1997.

[3] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

[4] Reinhard Kneser and Hermann Ney. Improved backing-off for m-gram language modeling. In *ICASSP*, 1995.

[5] Stanley F. Chen and Joshua Goodman. An empirical study of smoothing techniques for language modeling. Technical report, Harvard University, TR-10-98, 1998.

[6] Adam Paszke et al. PyTorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[7] Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg Corrado, and Jeffrey Dean. Distributed representations of words and phrases and their compositionality. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2013.

[8] Radim Řehůřek and Petr Sojka. Software framework for topic modelling with large corpora. In *LREC Workshop on New Challenges for NLP Frameworks*, 2010.

[9] Jeffrey Pennington, Richard Socher, and Christopher D. Manning. GloVe: Global vectors for word representation. In *Proceedings of EMNLP*, 2014.

[10] Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text classification. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2015.

[11] Anthropic. Claude code (model claude fable 5.1). `https://claude.com/claude-code`, 2026. Coding assistant used as described in the accompanying AI_USAGE.md.

A All generated continuations

A.1 Part I models

Prompt 1 the americans knew of the approach of the japanese forces

KN 5-gram, greedy in the region . <eos> = = = = <eos> the first recorded in the inventory of <unk> <unk> , a <unk> , a <unk> , a <unk> , a <unk> , a <unk> , a <unk> , a <unk> , a <unk> , a <unk> , a <unk> ,

KN 5-gram, topk staged a sit in his home . <eos> with the rise of cobra commander in the sequel . <eos> he was appointed director @-@ <unk> during the late <unk> . another such cruise ship , loaded with troops , an individual 's perception have suggested that the team . the

RNN, greedy . <eos> = = = = = <eos> = = = = = <eos> = = = = = <eos> = = = = = <eos> = = = = = <eos> = = = = = <eos> = = = = = <eos> = = = = = <eos>

RNN, topk against the kpa 's king , and a peace @-@ force " it into a high position . <unk> had the right end of the 766th (" <eos> <unk> de <unk>) from the huai (emperor <unk>) in the cathedral area with the cathedral . <eos> the

LSTM, greedy . <eos> = = = = = = = = = = = = = = <eos> the first time of the year , the first time , was the first time of the year , and the first time was the first time to be the first time

LSTM, topk during the conflict . <eos> the first time against the american union were created by the royal army , both the republic of their <unk> against the country , and one of the 1st century ce , although the general government was supported by his party . the first two

Transformer (4L), greedy . <eos> = <eos> the song was written by the song by the song , and the song was written

Transformer (4L), topk - and some of the song was " impossible " . <unk> said that " this were a " dramatic <unk> " and " <unk> ' and " <unk> " for the country ; the feast of their <unk> " was a standard word that was a major <unk> of

Transformer (1L, control), greedy . <eos> = = = = = <eos> the 766th regiment was the 766th regiment was the 766th regiment was the 766th regiment , and the 766th regiment was sent to reinforce the 766th regiment . the 766th regiment was sent to the 766th regiment , commanded by the 766th

Transformer (1L, control), topk against the 766th forces . <eos> the 766th headquarters was originally taken over them by the 766th regiment , 2nd division was appointed an <unk> unit of the <unk> , who had no advantage of fighting . these were lost after the 766th unit did not return to the 5th

Prompt 2 the ruins lie among the tropical rainforests of northern guatemala

KN 5-gram, greedy , and the <unk> of the <unk> , and the <unk> of the <unk> , and the <unk> of the <unk> , and the <unk> of the <unk> , and the <unk> of the <unk> , and the <unk> of the <unk> , and the <unk> of the <unk> ,

KN 5-gram, topk , and was replaced by the national library , which was a large @-@ scale <unk> paintings and drawings . a few months later a bomb . <unk> of <unk> , with the <unk> in an attempt to play in the fa cup , but the soviet archives of dumont

RNN, greedy , and <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk> <unk> , <unk>

RNN, topk , and the middle section . <unk> for <unk> and the other group of the <unk> are used as a source of the georgian spacing is in the same . <eos> = = = early sources = = <eos> = = critical reception = = <eos> while critics were given

LSTM, greedy . the first two years later , the first of the first time was the first time in the first season , and the first time of the year , the <unk> of the <unk> , was the first time to be the first time . <eos> = = =

LSTM, topk , and the capital of the north end , which is not as a second <unk> and the east and west west of the southern gulf of the area , and it was the last five years of the united states during the first period , until september 14 ,

Transformer (4L), greedy . the north of the south of the east of the east of the south of the south korean peninsula , the south korean river , and the south korean peninsula were constructed in the north korean peninsula . the 766th was also built in the north korean area .

Transformer (4L), topk , the east 's western coast . the first few species of the west of <unk> were named as the site of the northern hemisphere and the north america , and south of <unk> and a small group of a. hygrometricus ; it was recorded . most recent species had

Transformer (1L, control), greedy , and the island of the island . <eos> = = = = = <eos> the storm was named after the storm , the storm was named after the storm , the storm was named after the storm , the storm was named after the storm , the storm was

Transformer (1L, control), topk , the island 's cathedral . <eos> = = = = <eos> the east of <unk> (<unk>) = = = <eos> = = development = <eos> the new york times the first period = = <eos> the next year) = <eos> = = reception = = =

Prompt 3 in 1644 , hu took it upon himself to create

KN 5-gram, greedy a new york times , the song is a re @-@ interpretation of the hymn " joyful , joyful " , and " <unk> " . <eos> = = = = <eos> the first recorded in the inventory of <unk> <unk> , a <unk> , a <unk> , a <unk>

KN 5-gram, topk a map of the poem 's the country 's " little to no use of this mushroom as if not exactly jammed together . the new yorker , and later , already putting a bit more polished <unk> <unk> , was also the first time in his career . he

RNN, greedy a new <unk> , and the <unk> of the <unk> . <eos> = = = = = <eos> = = = = = <eos> = = = = = <eos> = = = = = <eos> = = = = = <eos> = = = = = <eos> = =

RNN, topk a suitable game . " , the player is the largest and other members of the united states as " its course " , and the belgian company , said in its existence of " one " <eos> <unk> of the city , " and the second of a year

LSTM, greedy a " <unk> " . <eos> = = = = = = = = = = = = = = <eos> = = = = = = = = = = = = = = = <eos> the first time of the film was the first time of

LSTM, topk a key of the school to the house of <unk> that was also used in the area . he also suggested that his life was to seek to a lot of education between the country and their <unk> <unk> , a number of six men . the <unk> @-@ off

Transformer (4L), greedy a <unk> of the jin . the song was the song by the jin , and the jin was the song . the song was the song of the song , and the song was the song by the song . the song was the song by the song song

Transformer (4L), topk a letter of the emperor and the jin would be attacked . the court of modern rule was forced to defend a jin . <eos> the huai river , although the jurchens attempted to secure a treaty , the song had been <unk> to hold the jin , this would

Transformer (1L, control), greedy a new state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of maryland

Transformer (1L, control), topk a budget of 5 @,@ 000 in 2011 . <eos> after the next year , he has been awarded a special candidate for the state of yugoslavia . <eos> there is no doubt that he may have the <unk> , as a <unk> of a year of <unk> in the

Prompt 4 as the highway approaches thompson , us 2 leaves the

KN 5-gram, greedy area . <eos> = = = = <eos> the first recorded in the inventory of <unk> <unk> , a <unk> , a <unk> , a <unk> , a <unk> , a <unk> , a <unk> , a <unk> , a <unk> , a <unk> , a <unk> , a <unk>

KN 5-gram, topk house and <unk> <unk> . the first four starts , and the <unk> <unk> of the hindu in a single . <eos> meanwhile , a 2 @-@ 3 . a total of 15 @,@ 000 @,@ 000 acres (2 @.@ 3 % in the area , and was an

RNN, greedy east of the <unk> <unk> . <eos> = = = <unk> = = = <eos> the kakapo is a <unk> of the <unk> <unk> (<unk>) , and <unk> (<unk>) , <unk> <unk> (<unk>) , <unk> <unk> (<unk>) , <unk> <unk> (<unk>

RNN, topk east state . <eos> = = = = tropical storm developed the season , a tropical wave the system peaked in the azores and a storm . the storm caused wind gusts to a high winds of 65 mph) . <eos> = = = = <eos> a large number

LSTM, greedy <unk> of the <unk> . <eos> = = = = <unk> = = = = <eos> the first part of the first season was the first time of the season , and the first time was the first time to be the first time . <eos> = = = =

LSTM, topk area in the first area of the final half . the first of the south atlantic ocean , an additional , <unk> bridge , is in the end of the northern atlantic 's west . the road ' north of the city is at the top the west and the

Transformer (4L), greedy east of the east coast of the united states . <eos> = = = route description = = <eos> the highway is a highway between the highway of the highway system . the highway is located in the north of the north of the north of the north of the

Transformer (4L), topk east) . <eos> = = = route description = = <eos> the route has been laid in a park , <unk> avenue and the state state route in the village of the east . the highway continues north and south . it is a few <unk> road in the

Transformer (1L, control), greedy highway . <eos> = = = = <eos> the highway is a highway system to the highway system . the highway was designated as the highway system as a highway system of the

highway system . the highway was designated as the highway system . the highway was designated as

Transformer (1L, control), topk system to the first line and , with an early 20th century , and by a village , was completed . <eos> hakim is used in the united states and made from a second @-@ day @-@ old film . <eos> = = = = = <eos> = = =

Prompt 5 churchill , ward (1996) . from a native

KN 5-gram, greedy american tribes , the <unk> , the <unk> <unk> , the <unk> <unk> , the <unk> <unk> , the <unk> <unk> , the <unk> <unk> , the <unk> <unk> , the <unk> <unk> , the <unk> <unk> , the <unk> <unk> , the <unk> <unk> ,

KN 5-gram, topk plant , as they were on the next to the player . " <unk> " and that his personal health , bethesda , maryland , in its original form of the god apollo bunder in the uk still " . in a review for the <unk>) in a large

RNN, greedy american <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk> , <unk>

RNN, topk america , which were not known as , <unk> , tintin , the <unk> of the dominican republic and ireland , frelimo , which was held on the site of the jin dynasty college of war ii (<unk>) . <eos> " this is <unk> by a new york

LSTM, greedy american academy , the <unk> of the <unk> , was the first time of the first time . the first time was the first time of the year , and the first time was the first time to be the first time . <eos> = = = = = =

LSTM, topk newspaper , he had not been built that the other troops in the state is " just so what they had happened of all the life and a] " . he concluded what it was born during the war . <unk> at a further <unk> from the british post

Transformer (4L), greedy american newspaper , the film was published in the united states . <eos> = = = = production = = <eos> the film was released in september 2011 . the film was released in september 2011 . the film was released in september 2011 . the film was released in

Transformer (4L), topk sentence , wheeler 's book was known as the " good and " the first year that year was not the finest of one of the best film of the united kingdom during 1996 . in 2000 of the united states , wheeler continued to <unk> his wife . he

Transformer (1L, control), greedy american academy (<unk>) , <unk> (<unk>) , <unk> (<unk>) , <unk> (<unk>) , <unk> (<unk>) , <unk> (<unk>) , <unk> (<unk>) , <unk> (<unk>) , <unk> (<unk>) , <unk> (<unk>)

Transformer (1L, control), topk korean , which were also described as " <unk> ") , a new school " (1999) . <eos> tintin in april 2010 , 2005 , " <unk> ") : written by james f. kennedy , and wrote that this period in <unk> that year . in

Model	Decoding	distinct-1	distinct-2	distinct-3	repeated 4-grams
KN 5-gram	greedy	0.24	0.36	0.39	0.58
KN 5-gram	topk	0.71	0.98	1.00	0.00
RNN	greedy	0.13	0.20	0.23	0.74
RNN	topk	0.64	0.91	0.97	0.01
LSTM	greedy	0.30	0.50	0.65	0.25
LSTM	topk	0.66	0.95	1.00	0.00
Transformer (4L)	greedy	0.30	0.48	0.61	0.31
Transformer (4L)	topk	0.63	0.94	0.99	0.00
Transformer (1L, control)	greedy	0.20	0.31	0.38	0.57
Transformer (1L, control)	topk	0.63	0.87	0.93	0.03

Table 7: Part I repetition statistics averaged over the five prompts.

A.2 Part II embedding settings (LSTM)

Prompt 1 the americans knew of the approach of the japanese forces

LSTM, random, trainable (Part I LSTM), greedy . <eos> = = = = = = = = = = = = = = <eos> the first time of the year , the first time , was the first time of the year , and the first time was the first time to be the first time

LSTM, random, trainable (Part I LSTM), topk during the conflict . <eos> the first time against the american union were created by the royal army , both the republic of their <unk> against the country , and one of the 1st century ce , although the general government was supported by his party . the first two

LSTM, random, frozen, greedy . the <unk> of the <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk>

<unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk>

LSTM, random, frozen, topk have been observed and the <unk> . <unk> between the song 's actions had been developed by the <unk> with <unk> and the other <unk> - of the <unk> , who had little more for local . however , in december 2010 , ulysses said that the company of the

LSTM, skip-gram, trainable, greedy . <eos> = = = = <unk> = = = = <eos> the first year of the war , the first time of the war , was the first time of the war . <eos> = = = <unk> = = = <eos> the first day of the war ,

LSTM, skip-gram, trainable, topk such as he was a <unk> . the subsequent year of the 19th century . " one of the greatest <unk> " (as the eighth world war <unk> , also was based at the expense of men , in both the portuguese era) , and the <unk> .

LSTM, skip-gram, frozen, greedy . <eos> = = = = <unk> = = = = <eos> the first of the first two @-@ year @-@ old @-@ class @-@ class @-@ class <unk> was the first of the first class of the royal navy , and was the first of the first class of

LSTM, skip-gram, frozen, topk over the atlantic . <eos> the first three battalions of the 9th brigade division were sent from the south korean of south korean forces , taking it as <unk> . this was also supported to conduct the 766th . the 10th division sent forward into the battle of <unk> ,

LSTM, GloVe, trainable, greedy . <eos> = = = = <unk> = = = = <eos> the first of the first season of the first season was the first time in the first season . the first season of the season was the first time in the first season , and the first two

LSTM, GloVe, trainable, topk where it took it to the other . however , the next week they would have moved to the dominican and then were established , making for a <unk> . this was used by the soviets , although the british officer was elected against a number of people . <eos>

LSTM, GloVe, frozen, greedy . <eos> = = = = <unk> = = = = <eos> the first two @-@ year @-@ old <unk> , the <unk> , and the <unk> of the <unk> <unk> <unk> (<unk>) , and the <unk> <unk> (<unk> <unk>) , <unk> <unk> (<unk> <unk>

LSTM, GloVe, frozen, topk against the conflict . <eos> the first two chapters of the united kingdom made his own campaign in the 1920s , but he has a reputation of the <unk> . an attempt to ensure the assassination of independence , and also had taken down his own work and the "

Prompt 2 the ruins lie among the tropical rainforests of northern guatemala

LSTM, random, trainable (Part I LSTM), greedy . the first two years later , the first of the first time was the first time in the first season , and the first time of the year , the <unk> of the <unk> , was the first time to be the first time . <eos> = = =

LSTM, random, trainable (Part I LSTM), topk , and the capital of the north end , which is not as a second <unk> and the east and west west of the southern gulf of the area , and it was the last five years of the united states during the first period , until september 14 ,

LSTM, random, frozen, greedy . the <unk> of the <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk> <unk>

oldest for the largest <unk> which came with a
LSTM, GloVe, frozen, greedy . <eos> = = = = <unk> = = = = <eos> the first @-@ term <unk> of the <unk> <unk> <unk> <unk> (<unk> <unk>) , the <unk> <unk> (<unk> <unk>) , was a <unk> of the <unk> <unk> <unk> <unk> <unk> (<unk> <unk>)
LSTM, GloVe, frozen, topk , and the middle coast of the east , which is not an area of <unk> in the eastern eastern pacific of western africa . they were not known in the eastern south of north africa . the song 's <unk> fleet on the eastern north china area and its

Prompt 3 in 1644 , hu took it upon himself to create
LSTM, random, trainable (Part I LSTM), greedy a " <unk> " . <eos> = = = = = = = = = = = = = = <eos> = = = = = = = = = = = = = = = = = = <eos> the first time of the film was the first time of
LSTM, random, trainable (Part I LSTM), topk a key of the school to the house of <unk> that was also used in the area . he also suggested that his life was to seek to a lot of education between the country and their <unk> <unk> , a number of six men . the <unk> @-@ off
LSTM, random, frozen, greedy the <unk> . <eos> = = = = <unk> = = = = <eos> the first @-@ year @-@ century was the first of the first time in the united states , and the first time of the united states was the first time of the united states . the
LSTM, random, frozen, topk a variety of the people and the jin that the 130th of the state was only a small period of their parents of the song . despite the second phase , they lived a short at their <unk> <unk> , a new <unk> and the <unk> . <eos> = =
LSTM, skip-gram, trainable, greedy a <unk> . <eos> = = = <unk> = = = <eos> the first time of the war was the first time of the war . <eos> = = = <unk> = = = <eos> the first day of the war , the 766th was the first time of the
LSTM, skip-gram, trainable, topk a car . <eos> = = = post @-@ war tour = = = <eos> " he had seen a special experience that was to be interested in the audience . this makes it been an ideal <unk> , and it is <unk> " . <eos> = = music =
LSTM, skip-gram, frozen, greedy the <unk> of the <unk> . <eos> = = = = <unk> = = = = <eos> the first two @-@ year @-@ old @-@ old @-@ old <unk> <unk> was the first of the first <unk> of the <unk> , and the first two @-@ year @-@ old @-@
LSTM, skip-gram, frozen, topk a brief of the government and the former president of their united states . <eos> = = = critical response = = = <eos> the first horizons of the treaty in 1992 began a plan for " <unk> <unk> " and " <unk> " and " to <unk> " .
LSTM, GloVe, trainable, greedy a <unk> of the <unk> of the <unk> . <eos> = = = <unk> = = = <eos> the first two years of the war was the first of the first two years of the war . the first of the first two years of the war was the first
LSTM, GloVe, trainable, topk a criminal in the kingdom of <unk> in may . when the english army was formed in an interview with finkelstein 's post , the first editor of the palestinian state has begun to stay on an <unk> <unk> , as a <unk> and a " <unk> <unk> " .
LSTM, GloVe, frozen, greedy the <unk> of the <unk> . <eos> = = = = <unk> = = = = <eos> = = = = <unk> = = = = <eos> = = = = <unk> = = = = <eos> = = = = <unk> = = = = <eos> = = =
LSTM, GloVe, frozen, topk a peace of the old family , who also were granted to the united states in august 1991 . the majority of the three people was arrested in the dominican and australia between their territory and became <unk> <unk> . the city , with a number of <unk> to the

Prompt 4 as the highway approaches thompson , us 2 leaves the
LSTM, random, trainable (Part I LSTM), greedy <unk> of the <unk> . <eos> = = = = <unk> = = = = <eos> the first part of the first season was the first time of the season , and the first time was the first time to be the first time . <eos> = = = =
LSTM, random, trainable (Part I LSTM), topk area in the first area of the final half . the first of the south atlantic ocean , an additional , <unk> bridge , is in the end of the northern atlantic 's west . the road ' north of the city is at the top the west and the
LSTM, random, frozen, greedy <unk> of the <unk> . <eos> = = = = <unk> = = = = <eos> the first @-@ language war of the song was the first time of the first season , and the first time in the united states . the first year was the first time in
LSTM, random, frozen, topk world as a <unk> . the game 's largest , was the first and most successful television , with a " <unk> race " and the <unk> . <eos> = = = = in the same : = = = = <eos> = = = = <unk> = = =
LSTM, skip-gram, trainable, greedy <unk> <unk> <unk> <unk> (<unk>) . <eos> = = = <unk> = = = <eos> the first time of the united states , the united states , was the first time of the united states . the first time was the first time of the war . <eos>
LSTM, skip-gram, trainable, topk line to the <unk> . the two other groups . the <unk> <unk> <unk>

for the past <unk> of the <unk> <unk> al @-@ <unk> <unk> <unk> the <unk> the the <unk> . <eos> in a week on 7 august , the congo 's <unk> of <unk> , the <unk>

LSTM, skip-gram, frozen, greedy <unk> <unk> , and the <unk> <unk> <unk>

Embedding setting	Decoding	distinct-1	distinct-2	distinct-3	repeated 4-grams
random, trainable (Part I LSTM)	greedy	0.30	0.50	0.65	0.25
random, trainable (Part I LSTM)	topk	0.66	0.95	1.00	0.00
random, frozen	greedy	0.20	0.32	0.40	0.56
random, frozen	topk	0.54	0.84	0.93	0.04
skip-gram, trainable	greedy	0.23	0.39	0.50	0.41
skip-gram, trainable	topk	0.65	0.90	0.97	0.00
skip-gram, frozen	greedy	0.22	0.40	0.52	0.41
skip-gram, frozen	topk	0.63	0.91	0.98	0.00
GloVe, trainable	greedy	0.22	0.36	0.47	0.46
GloVe, trainable	topk	0.66	0.95	0.99	0.00
GloVe, frozen	greedy	0.20	0.36	0.46	0.46
GloVe, frozen	topk	0.66	0.92	0.98	0.00

Table 8: Part II repetition statistics averaged over the five prompts.

B Embedding nearest neighbours

Word	Skip-gram (own, WikiText-2 train)	GloVe-6B
`king`	`veera, leinster, ballala, throne, vassal`	`queen, prince, monarch, kingdom, throne`
`city`	`metropolitan, borough, town, conurbation, burnside`	`cities, town, downtown, mayor, area`
`war`	`outbreak, airbase, italo, civil, hawaiians`	`wars, conflict, battle, civil, occupation`
`album`	`daydream, yankovic, charmbracelet, rca, slayer`	`albums, song, ep, band, songs`
`1990`	`1989, pr, oceania, sap, pursuant`	`1991, 1992, 1987, 1989, 1986`
`north`	`south, west, east, southward, alaska`	`south, east, korea, northeast, west`
`played`	`playing, striker, staged, matches, shortstop`	`playing, plays, play, player, matches`
`@-@`	`93rd, 10m, amassing, defamation, dash`	`channels, regions, beneficial, distress, cable`

Table 9: Five nearest neighbours (cosine) of probe words in the two pre-trained tables.

C Full hyper-parameters and reproduction

Setting	Value
Embedding dim / Transformer d_{model}	300
RNN / LSTM	2 layers, hidden 300, tanh / LSTM cells
Transformer	4 layers (control: 1), 6 heads, FFN 1200, pre-LN, GELU, learned positions, context 128
Dropout	0.3 after embedding, between layers, before output
Batch × BPTT	32 × 128 tokens (continuous stream, state detached between chunks)
Optimiser	Adam, lr 0.001, β=(0.9, 0.98), 200-step linear warm-up
Schedule	halve lr after 2 consecutive epochs without val. improvement; early stop after 3; max 12 epochs
Gradient clipping	global norm 1.0
Output layer	untied (frozen input tables would otherwise freeze the softmax)
Validation / test protocol	recurrent: full history, batch 1; Transformer: sliding window 128 / stride 32
Decoding	greedy and top-k=40, T=1.0, 50 new tokens, seed 1234+prompt index
n-gram	interpolated Kneser–Ney, orders 2–5 fitted, order chosen on validation, $D_n = n_1/(n_1 + 2n_2)$
Skip-gram	gensim, sg=1, window 5, 10 negatives, subsampling 10^{-4}, 10 epochs, min_count 1, 1 worker
GloVe	6B tokens, 300d, uncased; missing rows $\mathcal{N}(0, \sigma_d)$ from the found rows
Part III classifier	scikit-learn multinomial logistic regression (lbfgs), standardised features, $C \in \{0.01, 0.1, 1, 10\}$ on validation
Seeds	0 everywhere; Part II required settings also seed 1

Table 10: Every setting shared by the runs; per-run differences are the model/embedding blocks in `configs/`.

Reproduction: `run_all.sh` in the repository re-creates every number (about 7 h on the M4 with the 24-epoch runs, 5 h without); `README.md` documents data access, preprocessing, dependencies, commands and seeds.