



Python JSON

[< Previous](#)[Next >](#)

JSON is a syntax for storing and exchanging data.

JSON is text, written with JavaScript object notation.

JSON in Python

Python has a built-in package called `json`, which can be used to work with JSON data.

Example

Import the json module:

```
import json
```

Parse JSON - Convert from JSON to Python

If you have a JSON string, you can parse it by using the `json.loads()` method.

The result will be a Python dictionary.

Example

Convert from JSON to Python:

```
import json

# some JSON:
x =  '{ "name":"John", "age":30, "city":"New York"}'

# parse x:
y = json.loads(x)

# the result is a Python dictionary:
print(y["age"])
```

[Try it Yourself »](#)

Convert from Python to JSON

If you have a Python object, you can convert it into a JSON string by using the `json.dumps()` method.

Example

Convert from Python to JSON:

```
import json

# a Python object (dict):
x = {
    "name": "John",
    "age": 30,
    "city": "New York"
}

# convert into JSON:
y = json.dumps(x)

# the result is a JSON string:
print(y)
```

[Try it Yourself »](#)

You can convert Python objects of the following types, into JSON strings:

- dict
- list
- tuple
- string
- int
- float
- True
- False
- None

Example

Convert Python objects into JSON strings, and print the values:

```
import json

print(json.dumps({"name": "John", "age": 30}))
print(json.dumps(["apple", "bananas"]))
print(json.dumps(("apple", "bananas")))
print(json.dumps("hello"))
print(json.dumps(42))
print(json.dumps(31.76))
print(json.dumps(True))
print(json.dumps(False))
print(json.dumps(None))
```

[Try it Yourself »](#)

When you convert from Python to JSON, Python objects are converted into the JSON (JavaScript) equivalent:

Python	JSON
dict	Object
list	Array
tuple	Array
str	String
int	Number
float	Number

True	true
False	false
None	null

Example

Convert a Python object containing all the legal data types:

```
import json

x = {
    "name": "John",
    "age": 30,
    "married": True,
    "divorced": False,
    "children": ("Ann","Billy"),
    "pets": None,
    "cars": [
        {"model": "BMW 230", "mpg": 27.5},
        {"model": "Ford Edge", "mpg": 24.1}
    ]
}

print(json.dumps(x))
```

[Try it Yourself »](#)

Format the Result

The example above prints a JSON string, but it is not very easy to read, with no indentations and line breaks.

The `json.dumps()` method has parameters to make it easier to read the result:

Example

Use the `indent` parameter to define the numbers of indents:

```
json.dumps(x, indent=4)
```

[Try it Yourself »](#)

You can also define the separators, default value is `(", ", ": ")`, which means using a comma and a space to separate each object, and a colon and a space to separate keys from values:

Example

Use the `separators` parameter to change the default separator:

```
json.dumps(x, indent=4, separators=(". ", " = "))
```

[Try it Yourself »](#)

Order the Result

The `json.dumps()` method has parameters to order the keys in the result:


Example

Use the `sort_keys` parameter to specify if the result should be sorted or not:

```
json.dumps(x, indent=4, sort_keys=True)
```

[Try it Yourself »](#)[< Previous](#)[Next >](#)**NEW**


We just launched
W3Schools videos



COLOR PICKER



CODE GAME



[Play Game](#)

[Report Error](#)

[Spaces](#)

[Pro](#)

[Get Certified](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)

[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

Copyright 1999-2022 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

