Explainable AI (XAI): Banana Problem

Name: ANIRUDDHA K S
SRN: PES1UG23AM905
AIML-A section
20-03-2026

---

1. Project Overview

This assignment demonstrates the application of Explainable AI (XAI) techniques to deep learning models. Specifically, we use a pre-trained **ResNet18** model to explore how convolutional neural networks classify images of a banana, utilizing two distinct XAI methodologies.

Executed Tasks

- **Method 1:** Vanilla Gradient Saliency Map generation for the banana class.
- **Method 2:** Activation Maximization specifically targeting the banana neuron.

---

2. Methodology & task Breakdown

2.1 Task 1: Vanilla Gradient Saliency Map

Primary Goal: To identify and visualize the critical pixels within an input image that most significantly drive the model to predict the "banana" class.

Approach Taken:

1. Initialize a ResNet18 model pre-trained on ImageNet.
2. Import an input image of a banana.
3. Calculate the gradients of the banana class activation concerning the individual input pixels.
4. Render the resulting saliency map by taking the maximum absolute gradient across the RGB channels.

Visual Outputs:

Original Image Used:

```
Top prediction: banana (0.9993)
Banana probability: 0.9993
```



Resulting Saliency Visualization:



2.2 Task 2: Activation Maximization

Primary Goal: To synthesize a completely new image from scratch (noise) that strongly activates the target banana class neuron within the ResNet18 architecture.

Approach Taken:

1. Initialize a heavily randomized noise tensor.

2. Employ gradient ascent to iteratively optimize the image, maximizing the confidence score for the banana class.
3. Inject L2 and Total Variation (TV) regularization to ensure the generation of decipherable, less noisy visual textures.

Visual Outputs:

Synthesized Banana Pattern:

```
Step 040/220, banana score: 119.7977
Step 080/220, banana score: 169.6316
Step 120/220, banana score: 193.7108
Step 160/220, banana score: 211.1978
Step 200/220, banana score: 224.2789
```

3. Checklist of Requirements

Core Requirement	Implementation Details
Model Loading	Utilized `ResNet18_Weights.IMAGENET1K_V1`
Image Loading	Loaded `image.jpg` / `input_banana.png` via the `PIL` library
Saliency Computation	Applied `.backward()` on the banana class raw score
Map Visualization	Displayed a 3-subplot layout inclusive of an overlay
Highlighting Comments	Added interpretation/analysis notes inside cell 5
Generative Ascent	Used the `Adam` optimizer applied over random baseline noise
Pattern Visualization	Showed the optimized tensor converted to an image

4. Specific Technical Parameters

Model Configuration

- **Network:** ResNet18
- **Training Dataset:** ImageNet (1000 distinct classes)
- **Target Class Index (Banana):** 954

Regularization & Optimization (Method 2)

- **Total Steps Executed:** 220
- **Assigned Learning Rate:** 0.08
- **L2 Penalty (λ):** 1e-4
- **Total Variation Penalty (λ):** 1e-5