

DEEP SENTIMENT ANALYSIS ON TUMBLR

Anonymous authors

Paper under double-blind review

ABSTRACT

We propose a novel approach to Sentiment Analysis using Deep Neural Networks combining Visual Recognition and Natural Language Processing. Our approach leverages Tumblr posts containing images and text to predict the emotional state of users. Deep convolutional layers extract relevant features from images and high-dimensional word embedding followed by a recurrent layer process the textual information in order to infer the emotion conveyed by a given Tumblr post. We demonstrate that our network architecture, named Deep Sentiment, learns meaningful relations between visual data and language as it vastly outperforms models using a single modality. We then show that Deep Sentiment can also be adapted to generate images and text representative of an emotion.

1 INTRODUCTION

Sentiment analysis has been an active area of research in the past few years, especially on the readily available Twitter data, e.g. Bollen et al. (2011) who investigated the impact of collective mood states on stock market or Flaxman & Kassam (2016) who analysed day-of-week population well-being.

Contrary to Twitter, Tumblr posts are not limited to 140 characters, allowing more expressiveness, and are not focused on the textual content but on the visual content. A Tumblr post will almost always be an image with some text accompanying the latter. Pictures have become prevalent on social media and characterising them could enable the understanding of billions of users.

We propose a novel method to uncover the emotional state of an individual posting on social media. The ground truth emotion will be extracted from the tags, considered as the ‘self-reported’ emotion of the user. Our model incorporates both text and image and we aim to ‘read’ them to be able to understand the emotional content they imply about the user. Concretely, the Deep Sentiment model associates the features learned by the two modalities as follows:

- We fine-tune a pre-trained Deep Convolutional Neural Network, named Inception (Szegedy et al., 2015), to our specific task of emotion inferring.
- We project the text in a rich high-dimensional space with a word representation learned by Word2Vec (Mikolov et al., 2013). The word vectors then go through a Recurrent Neural Network which preserves the word order and captures the semantics of human language.
- A fully-connected layer combines the information in the two modalities and a final softmax output layer gives the probability distribution of the emotional state of the user.

We will also see that Deep Sentiment can be rearranged to generate Tumblr posts expressing one of the learned emotion.

2 TUMBLR DATA

2.1 THE DATASET

Tumblr is a microblogging service where users post multimedia content with the following attributes: an image, text and tags. The tags are really valuable as they indicate the user’s state of mind when writing his post. Ekman popularised the idea that there are six basic emotions [cite Ekman]: happiness, sadness, anger, surprise, fear and disgust. These emotions are said to be *basic*

as they are hardwired regardless of the species: basic emotions are innate, universal, automatic and induce fast reactions that are linked with a high survival rate. [Might need to rewrite when posts with other emotions are added]

To build our dataset, queries were made searching for each of the six emotions appearing in the tags. We considered adjectives as they were more commonly used on Tumblr: #happy, #sad, #angry, #surprised, #scared and #disgusted. The emotion would then become the *label* of the post that has visual and textual contents as features. Figure 1 shows two posts with their associated emotions:



(a) **Happy**: “Just relax with this amazing view #big-sur #california #roadtrip #usa #life #fitness (at McWay Falls)”



(b) **Sad**: “It’s okay to be upset. It’s okay to not always be happy. It’s okay to cry. Never hide your emotions in fear of upsetting others or of being a bother. If you think no one will listen. Then I will.”

Figure 1: Examples of Tumblr posts

2.2 DATA PREPROCESSING

In some posts, the tag containing the emotion of the post also appeared in the text itself, undermining the possibility of learning meaningful relationships between the features and the emotion expressed. We thus removed from the text the tags containing the emotion to be predicted.

Tumblr is used worldwide but we only kept posts written in English. Basically, if a post contained less than a given number of English word, it was deemed as non-English and removed from the dataset. The threshold was set to 5 English words as it appeared to filter out reasonably well non-English posts. [To change: filter posts with less than 90% of English words] The vocabulary of English words was obtained from Word2Vec.

3 VISUAL RECOGNITION

Pictures are valuable to accurately infer the emotion expressed by a user. For instance, happy photos might contain sunny landscapes while sad pictures might contain darker colors. To analyse the images, we’ll use convolutional neural networks, which achieve state-of-the-art performances in many visual recognition tasks.

3.1 TRANSFER LEARNING

Training a convolutional network from scratch can be difficult as a large amount of data is needed and plenty of different architectures and hyperparameters need to be tried before finding a decent model. To circumvent this issue, we can take advantage of the pre-trained Inception network [cite] that learned to recognise images through near 1.2M training examples from the ImageNet dataset, and with a deep architecture (22 layers) that took weeks to train on multiple GPUs.

More specifically, the pre-trained networks learned to recognise features in a picture in order to classify the latter among the 1000 classes in the ImageNet dataset. Those features are combined in the final output layer (of size 1000, each neuron being a class probability). Suppose that instead of

classifying an image into 1000 classes we want to label it according to 6 different emotions (happy, sad, angry, scared, surprised, disgusted). The same features can be combined in a different way to let the network take a decision about what the emotion conveyed by the image is.

The process described above is called *Transfer Learning*: we chop off the last layer of the network and add our own layer given how many classes we have. We then freeze the weights of the other layers and only backpropagate through the newly created layer when training the network on our examples. If we have enough data, we can unfreeze more higher-level layers and backpropagate through them.

Earlier features of ConvNets contain more generic features (such as edges or color blobs) that can be used for any task, while later features become more specific to the details of the classes present in the dataset. For example in ImageNet, there are many dog breeds and the later representational power might be used to distinguish those [cite transfer]. We will be using Google’s Inception network and fine-tune through the last 3 layers.

3.2 RESULTS

The Inception model was fed raw images, that were resized to a fixed size (224, 224, 3), and fine-tuned with the following parameters:

- 9,000 training steps
- Mini-batch of size 32
- Adam optimizer with a learning rate of $1e-6$

After the preprocessing described in Section 2, the dataset contains 295,508 posts that we split as 80% train set and 20% test set. The metric used to evaluate the model is accuracy, which is the fraction of correctly classified images.

The fine-tuned Inception is compared to a baseline: random guessing that includes the prior probabilities of the classes:

Table 1: Prior probabilities of the classes

	happiness	sadness	anger	surprise	fear	disgust
Prior proba.	0.32	0.22	0.19	0.03	0.22	0.02

The results are:

Table 2: Comparison of models using raw images

	Train accuracy	Test accuracy
Random guessing	24%	24%
Inception fine-tuned	48%	42%

4 CITATIONS, FIGURES, TABLES, REFERENCES

These instructions apply to everyone, regardless of the formatter being used.

4.1 CITATIONS WITHIN THE TEXT

Citations within the text should be based on the `natbib` package and include the authors’ last names and year (with the “et al.” construct for more than two authors). When the authors or the publication are included in the sentence, the citation should not be in parenthesis (as in “See Hinton et al. (2006) for more information.”). Otherwise, the citation should be in parenthesis (as in “Deep learning shows promise to make progress towards AI (Bengio & LeCun, 2007).”).

Table 3: Sample table title

PART	DESCRIPTION
Dendrite	Input terminal
Axon	Output terminal
Soma	Cell body (contains cell nucleus)

The corresponding references are to be listed in alphabetical order of authors, in the REFERENCES section. As to the format of the references themselves, any style is acceptable as long as it is used consistently.

4.2 FOOTNOTES

Indicate footnotes with a number¹ in the text. Place the footnotes at the bottom of the page on which they appear. Precede the footnote with a horizontal rule of 2 inches (12 picas).²

4.3 FIGURES

All artwork must be neat, clean, and legible. Lines should be dark enough for purposes of reproduction; art work should not be hand-drawn. The figure number and caption always appear after the figure. Place one line space before the figure caption, and one line space after the figure. The figure caption is lower case (except for first word and proper nouns); figures are numbered consecutively.

Make sure the figure caption does not get separated from the figure. Leave sufficient space to avoid splitting the figure and figure caption.

You may use color figures. However, it is best for the figure captions and the paper body to make sense if the paper is printed either in black/white or in color.




Figure 2: Sample figure caption.

4.4 TABLES

All tables must be centered, neat, clean and legible. Do not use hand-drawn tables. The table number and title always appear before the table. See Table 3.

Place one line space before the table title, one line space after the table title, and one line space after the table. The table title must be lower case (except for first word and proper nouns); tables are numbered consecutively.

¹Sample of the first footnote

²Sample of the second footnote

ACKNOWLEDGMENTS

Use unnumbered third level headings for the acknowledgments. All acknowledgments, including those to funding agencies, go at the end of the paper.

REFERENCES

- Yoshua Bengio and Yann LeCun. Scaling learning algorithms towards AI. In *Large Scale Kernel Machines*. MIT Press, 2007.
- Johan Bollen, Huina Mao, and Xiao-Jun Zeng. Twitter mood predicts the stock market. *Journal of Computational Science*, 2:1–8, 2011.
- Seth Flaxman and Karim Kassam. On #agony and #ecstasy: Potential and pitfalls of linguistic sentiment analysis. In preparation, 2016.
- Geoffrey E. Hinton, Simon Osindero, and Yee Whye Teh. A fast learning algorithm for deep belief nets. *Neural Computation*, 18:1527–1554, 2006.
- Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. In *ICLR*, 2013.
- Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. In *CVPR*, 2015.