WORKING WITH CURSOR,PROCEDURES AND FUNCTION

Program 1

FACTORIAL OF A NUMBER USING FUNCTION

```
CREATE OR REPLACE FUNCTION itfact (a NUMBER) RETURN NUMBER IS fact
   NUMBER := 1; b NUMBER;
BEGIN b
   := a;
   WHILE b > 0 LOOP fact
     := fact * b; b
     := b - 1;
   END LOOP;
   RETURN fact;
END;
/
```

Function created.

```
DECLARE result NUMBER;
BEGIN
   result := itfact(7); -- Call the function with 7 as input
   DBMS_OUTPUT.PUT_LINE('The factorial of 7 is ' || result);
END;
/
```

The factorial of 7 is 5040

Statement processed.

Program 2

Write a PL/SQL program using Procedures IN,INOUT,OUT parameters to retrieve the corresponding book information in library

```sql
-- Create a simple table for the library books
CREATE TABLE library ( book_id
  INT PRIMARY KEY,
  book_name VARCHAR2(100), author_name
  VARCHAR2(100)
);

-- Sample data insertion
INSERT INTO library VALUES (1, 'Introduction to PL/SQL', 'John Doe'); INSERT
INTO library VALUES (2, 'Advanced SQL', 'Jane Smith');

-- Procedure to retrieve book information
CREATE OR REPLACE PROCEDURE get_book_info ( p_book_id
   IN INT, p_book_name IN OUT
   VARCHAR2, p_author_name OUT VARCHAR2
) IS
BEGIN
   -- Retrieve book information based on the book_id
   SELECT book_name, author_name
   INTO p_book_name, p_author_name
   FROM library
   WHERE book_id = p_book_id;

   -- Modify book_name if needed (optional, based on INOUT)
p_book_name := p_book_name || ' - Updated'; END;
/

-- Test the procedure
DECLARE v_book_name
   VARCHAR2(100); v_author_name
   VARCHAR2(100);
BEGIN
   v_book_name := 'Sample Book'; -- Initial value
   get_book_info(1, v_book_name, v_author_name); -- Fetch book info for ID 1
   DBMS_OUTPUT.PUT_LINE('Book Name: ' || v_book_name); -- Output modified book name
   DBMS_OUTPUT.PUT_LINE('Author Name: ' || v_author_name); -- Output author name
END;
```

/

```
Book Name: Introduction to PL/SQL - Updated
Author Name: John Doe

Statement processed.
```