

Q3] Write a menu driven program to perform the following operations on a BST:

- 1-Insert
- 2- In-order traversal
- 3-Delete
- 4-Exit

```
#include <stdio.h>
#include <stdlib.h>
#include <malloc.h>
```

```
struct node
{
    int data;
    struct node *left;
    struct node *right;
} *root = NULL;
```

```
struct node *insert(struct node *, int);
void inorder(struct node *);
struct node *delete (struct node *temp, int val);
```

```
main()
{
    int ch, x, val;
    while (1)
    {
        printf("\nMenu: \n1: insert\n2: in-order traversal\n 3: Delete\n 4: exit\n");
        printf("\n Enter your choice");
        scanf("%d", &ch);
        switch (ch)
        {
            case (1):
                printf("enter the data to insert:");
                scanf("%d", &x);
                root = insert(root, x);
                break;
            case (2):
                inorder(root);
                break;
            case (3):
                printf("Enter element to be searched");
                scanf("%d", &val);
                root = delete (root, val);

            case (4):
                exit(0);
                break;
            default:
                printf("Invalid option");
        }
    }
}
```

```
}
```

```
struct node *insert(struct node *temp, int ele)
{
    if (temp == NULL)
    {
        temp = (struct node *)malloc(sizeof(struct node));
        temp->data = ele;
        temp->left = NULL;
        temp->right = NULL;
    }
    else
    {
        if (ele < temp->data)
            temp->left = insert(temp->left, ele);
        else
        {
            if (ele > temp->data)
                temp->right = insert(temp->right, ele);
        }
    }
    return temp;
}
```

```
void inorder(struct node *p)
{
    if (p != NULL)
    {
        inorder(p->left);
        printf("%d \t", p->data);
        inorder(p->right);
    }
}
```

```
struct node *delete (struct node *temp, int val)
{
    if (temp == NULL)
        return temp;

    if (val < temp->data)
    {
        temp->left = delete (temp->left, val);
    }
    else
    {
        if (val >> temp->data)
        {
            temp->right = delete (temp->right, val);
        }
        else
        {
            if (temp->left == NULL)
```

```
{
    struct node *p = temp->right;
    free(temp);
    return p;
}
else if (temp->right == NULL)
{
    struct node *p = temp->left;
    free(temp);
    return p;
}
}
}
```

ANIRUDH PANDA
SIC - 190610193
ROLL - 16 (D2)