

EXP:06

Error Correction at Data Link Layer

Aim

To write a program to implement error detection and correction using the **Hamming Code** concept.

Algorithm / Procedure

1. **Determine** the number of redundant (parity) bits required for the given data size.
2. **Calculate** the positions of the parity bits (powers of 2).
3. **Implement** the Hamming Code generation algorithm:
 - Place data bits and parity bits in their respective positions.
 - Calculate the value of each parity bit based on the data bits it covers.
4. **Implement** the error detection and correction algorithm:
 - Receive the transmitted codeword.
 - Recalculate the parity bits.
 - Calculate the syndrome (error position) by combining the recalculated parity bits.
 - If the syndrome is non-zero, flip the bit at the error position.
5. **Test** the program with a data stream, introducing a single-bit error to verify the correction feature.

Code:

```
def calc_parity_positions(m):  
    r  
    = 0  
    while (2**r) < (m + r + 1):  
        r  
        += 1  
    return r
```

```
def insert_parity_bits(data, r):  
    j = 0  
    k = 1  
    m = len(data)  
    res = ""  
    for i in range(1, m + r + 1):  
        if i == 2**j:  
            res += '0' # parity bits start as 0 instead of 'P'  
            j  
            += 1  
        else:  
            res += data[-1 * k]  
            k += 1  
    return res[::-1]
```

```
def calc_parity_bits(arr, r):
    n = len(arr)
    arr = list(arr)
    for i in range(r):
        val = 0

        for j in range(1, n + 1):
            if j & (2**i) ==
                (2**i):
                    val ^= int(arr[-1 * j])
        arr[-1 * (2**i)] = str(val)
    return ''.join(arr)
```

```
def detect_error(arr, r):
    n = len(arr)
    res = 0

    for i in range(r):
        val = 0
        for j in range(1, n + 1):
            if j & (2**i) ==
                (2**i):
                    val ^= int(arr[-1 * j])
        res += val * (10**i)
    return int(str(res)[::-1], 2)
```

```
# ----- MAIN PROGRAM -----
```

```
data = input("Enter the data bits (e.g., 1011): ")[::-1]
```

```
# Step 1: Calculate required parity bits r
r = calc_parity_positions(len(data))
```

```
# Step 2: Insert parity bits into data
arr = insert_parity_bits(data, r)
print("\nData with parity placeholders:", arr)
```


```
# Step 3: Calculate parity bits
arr = calc_parity_bits(arr, r)
print("Encoded data (Hamming code):", arr)
```

```
# Step 4: Introduce an error (optional)
error_index = int(input("\nEnter bit position to flip (0 for no error): "))
arr_with_error = list(arr)
if error_index != 0:
    arr_with_error[-error_index] = '1' if arr_with_error[-error_index] == '0' else '0'
    arr_with_error = ''.join(arr_with_error)
print("Received data:", arr_with_error)
```

```
# Step 5: Detect error position
error_pos = detect_error(arr_with_error, r)
if error_pos == 0:
    print("No error detected.")
else:
    print(f"Error detected at bit position: {error_pos}")

# Step 6: Correct the error
arr_corrected = list(arr_with_error)
arr_corrected[-error_pos] = '1' if arr_corrected[-error_pos] == '0' else '0'
print("Corrected data:", ".join(arr_corrected))
```

Output:



```
File Edit Selection View Go Run Terminal Help
...
+ tcp_server.py + chat_server.py + chat_client.py + ping_program.py + wifi.py + hamming_code.py X + tcp_client.py
+ hamming_code.py
26
27 # ----- NOISE INJECTED -----
28 data = input("Enter the data bits (e.g., 1011): ")[:-1]
29
30 # Step 1: Calculate required parity bits
31 p = calc_parity_positions(len(data))
32
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
Microsoft Windows [Version 10.0.26280.7613]
(c) Microsoft Corporation. All rights reserved.
C:\Users\Afrah W\Desktop\cs23532\python>python.exe "c:/Users/Afrah W/Desktop/cn/hamming_code.py"
Enter the data bits (e.g., 1011): 1011
Data with parity placeholders: 1100100
Encoded data (Hamming code): 1100110
Enter bit position to flip (0 for no error): 3
Received data: 1100010
X Error detected at bit position: 3
Corrected data: 1100110
C:\Users\Afrah W\Desktop>
```

Result:

A program to implement the Hamming Code was successfully written. The program demonstrated the ability to detect and correct a single-bit error in the transmitted data stream.