

```
PS C:\Users\ROG FLOW\Documents\learn_git> new-item -Path ./third.txt -
itemtype file
```

Répertoire : C:\Users\ROG FLOW\Documents\learn_git

| Mode | LastWriteTime | Length | Name |
|--------|-------------------|--------|-----------|
| ---- | ----- | ----- | ---- |
| -a---- | 12/5/2024 9:04 PM | 0 | third.txt |

```
PS C:\Users\ROG FLOW\Documents\learn_git> git init
```

Initialized empty Git repository in C:/Users/ROG
FLOW/Documents/learn_git/.git/

```
PS C:\Users\ROG FLOW\Documents\learn_git> git add third.txt
```

```
PS C:\Users\ROG FLOW\Documents\learn_git> git commit "adding third.txt"
```

error: pathspec 'adding third.txt' did not match any file(s) known to git

```
PS C:\Users\ROG FLOW\Documents\learn_git> git commit -m "adding third.txt"
```

[master (root-commit) 440dfd4] adding third.txt

1 file changed, 0 insertions(+), 0 deletions(-)

create mode 100644 third.txt

```
PS C:\Users\ROG FLOW\Documents\learn_git> git log
```

commit 440dfd4103dcf420b37818c256919b0337110484 (HEAD -> master)

Author: ZeuRizzler <st24.djenaoui@gmail.com>

Date: Thu Dec 5 21:05:37 2024 +0100

adding third.txt

```
PS C:\Users\ROG FLOW\Documents\learn_git> new-item -Path ./fourth.txt -
itemtype file
```

Répertoire : C:\Users\ROG FLOW\Documents\learn_git

| Mode | LastWriteTime | Length | Name |
|--------|-------------------|--------|------------|
| ---- | ----- | ----- | ---- |
| -a---- | 12/5/2024 9:07 PM | 0 | fourth.txt |

```
PS C:\Users\ROG FLOW\Documents\learn_git> git add fourth.txt
PS C:\Users\ROG FLOW\Documents\learn_git> git commit -m "adding fourth.txt"
[master 5e6ac70] adding fourth.txt
    1 file changed, 0 insertions(+), 0 deletions(-)
    create mode 100644 fourth.txt
PS C:\Users\ROG FLOW\Documents\learn_git> git rm third.txt
rm 'third.txt'
PS C:\Users\ROG FLOW\Documents\learn_git> git commit -m "removing
third.txt"
[master 553bf71] removing third.txt
    1 file changed, 0 insertions(+), 0 deletions(-)
    delete mode 100644 third.txt
PS C:\Users\ROG FLOW\Documents\learn_git> git log
commit 553bf71d676254b68e64d7a18b9377b6984237a7 (HEAD -> master)
Author: ZeuRizzler <st24.djenaoui@gmail.com>
Date: Thu Dec 5 21:12:15 2024 +0100

    removing third.txt

commit 5e6ac7033dd7f43c5bd03b41e810c4de3e50ad95
Author: ZeuRizzler <st24.djenaoui@gmail.com>
Date: Thu Dec 5 21:10:28 2024 +0100

    adding fourth.txt

commit 440dfd4103dcf420b37818c256919b0337110484
Author: ZeuRizzler <st24.djenaoui@gmail.com>
Date: Thu Dec 5 21:05:37 2024 +0100

    adding third.txt
```

```
PS C:\Users\ROG FLOW\Documents\learn_git> git config --global
```

```
usage: git config [<options>]
```

Config file location

| | |
|-------------------|------------------------------------|
| --global | use global config file |
| --system | use system config file |
| --local | use repository config file |
| --worktree | use per-worktree config file |
| -f, --file <file> | use given config file |
| --blob <blob-id> | read config from given blob object |

Action

| | |
|----------------------------------|---|
| --get | get value: name [value-pattern] |
| --get-all | get all values: key [value-pattern] |
| --get-regexp | get values for regexp: name-regex [value-pattern] |
| --get-urlmatch | get value specific for the URL: section[.var] URL |
| --replace-all [value-pattern] | replace all matching variables: name value |
| --add | add a new variable: name value |
| --unset | remove a variable: name [value-pattern] |
| --unset-all | remove all matches: name [value-pattern] |
| --rename-section | rename section: old-name new-name |
| --remove-section | remove a section: name |
| -l, --list | list all |
| --fixed-value 'value-pattern' | use string equality when comparing values to |
| -e, --edit | open an editor |
| --get-color | find the color configured: slot [default] |
| --get-colorbool | find the color setting: slot [stdout-is-tty] |

Type

| | |
|-------------------|----------------------------|
| -t, --type <type> | value is given this type |
| --bool | value is "true" or "false" |

| | |
|----------------------------|--|
| <code>--int</code> | value is decimal number |
| <code>--bool-or-int</code> | value is <code>--bool</code> or <code>--int</code> |
| <code>--bool-or-str</code> | value is <code>--bool</code> or string |
| <code>--path</code> | value is a path (file or directory name) |
| <code>--expiry-date</code> | value is an expiry date |

Other

| | |
|---|--|
| <code>-z, --null</code> | terminate values with NUL byte |
| <code>--name-only</code> | show variable names only |
| <code>--includes</code> | respect include directives on lookup |
| <code>--show-origin</code> blob, command line) | show origin of config (file, standard input, |
| <code>--show-scope</code> system, command) | show scope of config (worktree, local, global, |
| <code>--default <value></code> | with <code>--get</code> , use default value when missing entry |

PS C:\Users\ROG FLOW\Documents\learn_git>