Practical No : 2

1) **Create an application to demonstrate Node.js Events.**

```
var events = require('events');
var em = new events.EventEmitter();
em.on('FirstEvent', function (data)
{
    console.log('First subscriber: ' + data);
    });
    em.emit('FirstEvent', 'This is my first Node.js event emitter example.');
```

output:

```
PS D:\WT> node event2.js
First subscriber: This is my first Node.js event emitter example.
```

q

Custom event:

```
const events = require("events");
const eventEmitter = new events.EventEmitter(); eventEmitter.on("connection",
handleConnectionEvent); eventEmitter.emit("connection"); eventEmitter.emit("connection");
eventEmitter.emit("connection"); eventEmitter.emit("connection");
function handleConnectionEvent() { console.log("Conneciton Made!");
}
console.log("End of Program");
```

Output:

```
PS D:\WT> node customevent.js
Conneciton Made!
Conneciton Made!
Conneciton Made!
Conneciton Made!
End of Program
```

Implement all Methods of EventEmitter class.

I. **using addlistner method**

```
var events=require('events');
var eventEmitter=new events.EventEmitter();
var connectHandler = function connected()
{
    console.log('connection successful.');
    eventEmitter.emit('data_recieved');
}
eventEmitter.addListener('connection',connectHandler);
eventEmitter.addListener('data_recieved',function()
    {
        console.log('data received successfully.');
    });
```

```
eventEmitter.emit('connection');
console.log("program Ended");
```

Output:

```
PROBLEMS  OUTPUT  DEBUG CONSOLE  TERMINAL
C:\Program Files\nodejs\node.exe .\usingaddlistner.js
connection successful.
data received successfully.
program Ended
```

II. **Remove Listner**

```
const events = require("events");
const eventEmitter =new events.EventEmitter();
function listner1()
{
   console.log("Event received by Listner 1");
}
function listner2()
{
   console.log("Event received by Listner 2");
}
eventEmitter.addListener("write",listner1);
eventEmitter.on("write",listner2);

eventEmitter.emit("write");
console.log(eventEmitter.listenerCount("write"));

eventEmitter.removeListener("write",listner1);
console.log("Listner 1 is removed");
eventEmitter.emit("Write");

console.log(eventEmitter.listenerCount("write"));
console.log("Program ended");
```

Output:

```
PROBLEMS  OUTPUT  DEBUG CONSOLE  TERMINAL
C:\Program Files\nodejs\node.exe .\removelistner.js
Event received by Listner 1
Event received by Listner 2
2
Listner 1 is removed
1
Program ended
```

Implement Event Emitter Patterns

a)using return value of function

```
var emitter=require('events').EventEmitter;
function LoopProcessor(num)
{
   var e=new emitter();
   setTimeout(function()
   {
      for(var i=1;i<=num;i++)
      {
         e.emit('BeforeProcess',i);
         console.log('Processing number:'+i);
         e.emit('AfterProcess',i);
      }
   },2000)
   return e;
}
   var lp=LoopProcessor(3);
   lp.on('BeforeProcess',function(data)
   {
      console.log('About to start the process for '+data);
   });
   lp.on('AfterProcess',function(data)
   {
      console.log('completed processing '+data);
   });
```

Output:



b)Extend Event emitter class(using Util module)

Extend Event Emitter Class

```
var emitter=require('events').EventEmitter;
var util=require('util');
function LoopProcessor(num)
{
   var me=this;
   setTimeout(function()
   {
      for(var i=1;i<=num;i++)
      {
         me.emit('BeforeProcess',i);
         console.log("Processing Number: "+i);
         me.emit('AfterProcess',i);
      }
   },2000)
   return this;
}
util.inherits(LoopProcessor,emitter)
var lp=new LoopProcessor(3);
lp.on('BeforeProcess',function(data)
{
   console.log('About to start the process for'+data);
});
lp.on('AfterProcess',function(data)
{
```

```
  console.log('Completed processing',data);
});
```

Output: