

PHPTravels Automation Framework

```
<project xmlns="http://maven.apache.org/POM/4.0.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
http://maven.apache.org/xsd/maven-4.0.0.xsd">
```

```
<modelVersion>4.0.0</modelVersion>
```

```
<groupId>PHPTravelsFramework</groupId>
```

```
<artifactId>PHPTravelsFramework</artifactId>
```

```
<version>0.0.1-SNAPSHOT</version>
```

```
<dependencies>
```

```
<dependency>
```

```
<groupId>org.seleniumhq.selenium</groupId>
```

```
<artifactId>selenium-java</artifactId>
```

```
<version>4.21.0</version>
```

```
</dependency>
```

```
<dependency>
```

```
<groupId>org.testng</groupId>
```

```
<artifactId>testng</artifactId>
```

```
<version>7.10.2</version>
```

```
</dependency>
```

```
<dependency>
```

```
<groupId>io.cucumber</groupId>
```

```
<artifactId>cucumber-java</artifactId>
```

```
<version>7.18.0</version>
```

```
</dependency>
```

```
<dependency>
```

```
<groupId>io.cucumber</groupId>
```

```
<artifactId>cucumber-testng</artifactId>
```

```
<version>7.18.0</version>
```

```
</dependency>
```

```
<dependency>
```

```
<groupId>io.github.bonigarcia</groupId>
```

```
<artifactId>webdrivermanager</artifactId>
```

```
<version>5.8.0</version>
```

```
</dependency>
```

```

    <dependency>
      <groupId>org.apache.poi</groupId>
      <artifactId>poi-ooxml</artifactId>
      <version>5.2.5</version>
    </dependency>

    <dependency>
      <groupId>com.aventstack</groupId>
      <artifactId>extentreports</artifactId>
      <version>5.1.1</version>
    </dependency>

  </dependencies>

</project>

```

DriverFactory.java

```

package base;

import org.openqa.selenium.WebDriver;

public class DriverFactory {

    private static ThreadLocal<WebDriver> tlDriver = new
    ThreadLocal<>();

    public static void setDriver(WebDriver driver) {

        tlDriver.set(driver);
    }

    public static WebDriver getDriver() {

        return tlDriver.get();
    }

    public static void unload() {

        tlDriver.remove();
    }
}

```

BaseClass.java

```

package base;

```

```

import org.openqa.selenium.WebDriver; import
org.openqa.selenium.chrome.ChromeDriver;
import org.openqa.selenium.edge.EdgeDriver;
import org.openqa.selenium.firefox.FirefoxDriver;

import io.github.bonigarcia.wdm.WebDriverManager;
import utilities.ConfigReader;

public class BaseClass {

    public void initialization() {

        String browser = ConfigReader.getProperty("browser");

        WebDriver driver = null;

        if(browser.equalsIgnoreCase("chrome")) {

            WebDriverManager.chromedriver().setup();
            driver = new ChromeDriver();
        }

        else if(browser.equalsIgnoreCase("firefox")) {

            WebDriverManager.firefoxdriver().setup();
            driver = new FirefoxDriver();
        }

        else if(browser.equalsIgnoreCase("edge")) {

            WebDriverManager.edgedriver().setup();
            driver = new EdgeDriver();
        }

        DriverFactory.setDriver(driver);

        DriverFactory.getDriver().manage().window().maximize();

        DriverFactory.getDriver().get("https://phptravels.net/login");
    }
}

```

ConfigReader.java

```

package utilities;

```

```

import java.io.FileInputStream;
import java.util.Properties;

public class ConfigReader {

    static Properties prop;

    public static String getProperty(String key) {
        try
        {

            prop = new Properties();

            FileInputStream fis = new FileInputStream(
                "src/test/resources/config/config.properties");

            prop.load(fis);

        }

        catch(Exception e) {

            System.out.println(e);

        }

        return prop.getProperty(key);
    }
}

```

ExcelUtility.java

```

package utilities;

import java.io.FileInputStream;

import org.apache.poi.xssf.usermodel.XSSFSheet;
import org.apache.poi.xssf.usermodel.XSSFWorkbook;

public class ExcelUtility {

    public static String getData(String sheetName,
int row, int cell) {
        String value = "";
        try
        {

```

```

        FileInputStream fis = new FileInputStream(
            "src/test/resources/testdata/TestData.xlsx");

        XSSFWorkbook workbook = new XSSFWorkbook(fis);

        XSSFSheet sheet = workbook.getSheet(sheetName);

        value = sheet.getRow(row)
            .getCell(cell)
            .toString();

        workbook.close();
    }

    catch(Exception e) {

        System.out.println(e);
    }

    return value;
}
}

```

WaitUtility.java

```

package utilities;

import java.time.Duration;

import org.openqa.selenium.Alert; import
org.openqa.selenium.By; import
org.openqa.selenium.WebDriver; import
org.openqa.selenium.WebElement; import
org.openqa.selenium.support.ui.ExpectedConditions;
import org.openqa.selenium.support.ui.WebDriverWait;

public class WaitUtility {

    public static void waitForClickable(WebDriver driver,
        WebElement element) {

        WebDriverWait wait =
        new WebDriverWait(driver,
            Duration.ofSeconds(10));
        wait.until(ExpectedConditions
            .elementToBeClickable(element));
    }
}

```

```

    }

    public static void waitForVisible(WebDriver driver,
    WebElement element) {

        WebDriverWait wait =
    new WebDriverWait(driver,
        Duration.ofSeconds(10));

        wait.until(ExpectedConditions
            .visibilityOf(element));
    }

    public static void waitForPresence(WebDriver driver,
    By locator) {

        WebDriverWait wait =
    new WebDriverWait(driver,
        Duration.ofSeconds(10));

        wait.until(ExpectedConditions
            .presenceOfElementLocated(locator));
    }

    public static Alert waitForAlert(WebDriver driver) {

        WebDriverWait wait =
    new WebDriverWait(driver,
        Duration.ofSeconds(10));

        return wait.until(
            ExpectedConditions.alertIsPresent());
    }

    public static void waitForFrame(WebDriver driver,
    String frameName) {

        WebDriverWait wait =
    new WebDriverWait(driver,
        Duration.ofSeconds(10));

        wait.until(ExpectedConditions
            .frameToBeAvailableAndSwitchToIt(frameName));
    }
}
ScreenshotUtility.java

```

```
package utilities;

import java.io.File; import
java.text.SimpleDateFormat;
import java.util.Date;

import org.apache.commons.io.FileUtils; import
org.openqa.selenium.OutputType;
import org.openqa.selenium.TakesScreenshot;

import base.DriverFactory;

public class ScreenshotUtility {

    public static String captureScreenshot(String testName) {

        String timestamp =
            new SimpleDateFormat("yyyyMMddHHmmss")
                .format(new Date());

        String path =
            "Screenshots/" + testName + timestamp + ".png";
        try
        {

            File src =
                ((TakesScreenshot)
                    DriverFactory.getDriver())
                    .getScreenshotAs(OutputType.FILE);

            FileUtils.copyFile(src,
                new File(path));
        }

        catch(Exception e) {

            System.out.println(e);
        }

        return path;
    }
}
```

RetryAnalyzer.java

```
package utilities;

import org.testng.IRetryAnalyzer;
import org.testng.ITestResult;

public class RetryAnalyzer implements IRetryAnalyzer {

    int count = 0;

    int maxTry = 2;

    public boolean retry(ITestResult result) {

        if(count < maxTry) {

            count++;
            return true;
        }

        return false;
    }
}
```

ExtentManager.java

```
package utilities;

import com.aventstack.extentreports.ExtentReports; import
com.aventstack.extentreports.reporter.ExtentSparkReporter;

public class ExtentManager {

    public static ExtentReports extent;

    public static ExtentReports getReport() {

        if(extent == null) {

            ExtentSparkReporter spark =
new ExtentSparkReporter(
                "reports/ExtentReport.html");

            extent = new ExtentReports();

            extent.attachReporter(spark);
```



```
    }  
  
    return extent;  
}  
}
```

TestListener.java

```
package listeners;  
  
import org.testng.ITestContext;  
import org.testng.ITestListener;  
import org.testng.ITestResult;  
  
public class TestListener implements ITestListener {  
  
    public void onTestStart(ITestResult result) {  
  
        System.out.println("Test Started");  
    }  
  
    public void onTestSuccess(ITestResult result) {  
  
        System.out.println("Test Passed");  
    }  
  
    public void onTestFailure(ITestResult result) {  
  
        System.out.println("Test Failed");  
    }  
  
    public void onTestSkipped(ITestResult result) {  
  
        System.out.println("Test Skipped");  
    }  
  
    public void onStart(ITestContext context) {  
  
        System.out.println("Execution Started");  
    }  
  
    public void onFinish(ITestContext context) {  
  
        System.out.println("Execution Finished");  
    }  
}
```

LoginPage.java

```
package pages;

import org.openqa.selenium.By;
import org.openqa.selenium.WebDriver;

public class LoginPage {

    WebDriver driver;

    By email = By.name("email");

    By password = By.name("password");

    By loginBtn = By.xpath(
        "//button[contains(text(),'Login')]");

    public LoginPage(WebDriver driver) {

        this.driver = driver;
    }

    public void enterEmail(String user) {

        driver.findElement(email)
            .sendKeys(user);
    }

    public void enterPassword(String pass) {

        driver.findElement(password)
            .sendKeys(pass);
    }

    public void clickLogin() {

        driver.findElement(loginBtn)
            .click();
    }
}
```

RegistrationPage.java

```
package pages;

import org.openqa.selenium.By;
import org.openqa.selenium.WebDriver;

public class RegistrationPage {

    WebDriver driver;

    By firstName = By.name("first_name");

    By lastName = By.name("last_name");

    By email = By.name("email");

    By phone = By.name("phone");

    By password = By.name("password");

    public RegistrationPage(WebDriver driver) {

        this.driver = driver;
    }

    public void enterFirstName(String fname) {

        driver.findElement(firstName)
            .sendKeys(fname);
    }

    public void enterLastName(String lname) {

        driver.findElement(lastName)
            .sendKeys(lname);
    }

    public void enterEmail(String mail) {

        driver.findElement(email)
            .sendKeys(mail);
    }

    public void enterPhone(String number) {
```

```

        driver.findElement(phone)
        .sendKeys(number);
    }

    public void enterPassword(String pass) {

        driver.findElement(password)
        .sendKeys(pass);
    }
}

```

HotelSearchPage.java

```

package pages;

import org.openqa.selenium.By;
import org.openqa.selenium.WebDriver;

public class HotelSearchPage {

    WebDriver driver;

    By city = By.id("select2-hotels_city-container");

    By checkin = By.id("checkin");

    By checkout = By.id("checkout");

    By travellers = By.id("travellersInput");

    By searchBtn = By.id("submit");

    public HotelSearchPage(WebDriver driver) {

        this.driver = driver;
    }

    public void selectCity() {

        driver.findElement(city).click();
    }

    public void clickSearch() {

```

```
        driver.findElement(searchBtn).click();
    }
}
```

BookingPage.java

```
package pages;

import org.openqa.selenium.By;
import org.openqa.selenium.WebDriver;

public class BookingPage {

    WebDriver driver;

    By bookNow = By.xpath(
        "//button[contains(text(),'Book Now')]");

    By confirmBtn = By.xpath(
        "//button[contains(text(),'Confirm Booking')]");

    public BookingPage(WebDriver driver) {

        this.driver = driver;
    }

    public void clickBookNow() {

        driver.findElement(bookNow).click();
    }

    public void confirmBooking() {

        driver.findElement(confirmBtn).click();
    }
}
```

Hooks.java

```
package hooks;

import base.BaseClass; import
base.DriverFactory; import
io.cucumber.java.After; import
```

```

io.cucumber.java.Before; import
io.cucumber.java.Scenario;
import utilities.ScreenshotUtility;

public class Hooks extends BaseClass {
    @Before    public
    void setup() {

        initialization();
    }

    @After
    public void tearDown(Scenario scenario) {

        if(scenario.isFailed()) {

            ScreenshotUtility.captureScreenshot(
                scenario.getName());
        }

        DriverFactory.getDriver().quit();

        DriverFactory.unload();
    }
}

```

LoginSteps.java

```

package stepdefinitions;

import base.DriverFactory; import
io.cucumber.java.en.And; import
io.cucumber.java.en.Given;
import io.cucumber.java.en.Then;
import
io.cucumber.java.en.When;
import pages.LoginPage;

public class LoginSteps {

    LoginPage login;

    @Given("user launches browser")

```

```

public void user_launches_browser() {

    login = new LoginPage(
DriverFactory.getDriver());
    }
    @When("user enters {string} and {string}")
public void user_enters_and(String username,
    String password) {

        login.enterEmail(username);

        login.enterPassword(password);
    }

    @And("clicks on login button")
public void clicks_on_login_button() {

        login.clickLogin();
    }

    @Then("validate login result")
public void validate_login_result() {

        System.out.println("Login Validated");
    }
}

```

RegistrationSteps.java

```

package stepdefinitions;

import io.cucumber.java.en.Then;

public class RegistrationSteps {

    @Then("validate successful registration")
public void validate_successful_registration() {

        System.out.println(
            "Registration Successful");
    }
}

```

```
}  
}
```

HotelSearchSteps.java

```
package stepdefinitions;  
  
import io.cucumber.java.en.Then;  
  
public class HotelSearchSteps {  
  
    @Then("validate search results")  
    public void validate_search_results() {  
  
        System.out.println(  
            "Hotel Results Displayed");  
    }  
}
```

BookingSteps.java

```
package stepdefinitions;  
  
import io.cucumber.java.en.Then;  
  
public class BookingSteps {  
  
    @Then("validate booking confirmation")  
    public void validate_booking_confirmation() {  
  
        System.out.println(  
            "Booking Confirmed");  
    }  
}
```

TestRunner.java

```
package runners;  
  
import io.cucumber.testng.AbstractTestNGCucumberTests;  
import io.cucumber.testng.CucumberOptions;
```



```

@CucumberOptions(

features = "src/test/resources/features",

glue = { "stepdefinitions",
"hooks" },

plugin = {
"pretty",
"html:target/cucumber-report.html"
},

monochrome = true,

tags = "@Smoke"

)

public class TestRunner
extends AbstractTestNGCucumberTests {

}

```

login.feature

Feature: PHPTravels Login Module

@Smoke @Regression

Scenario Outline: Validate Login Functionality

Given user launches browser

When user enters "<username>" and "<password>"

And clicks on login button

Then validate login result

Examples:

username	password
user@phptravels.com	demouser
invalid@gmail.com	invalid
demouser	
user@phptravels.com	

registration.feature

Feature: Registration Module

Scenario: Validate User Registration

Given user launches browser
Then validate successful registration

hotelsearch.feature

Feature: Hotel Search Module

Scenario: Validate Hotel Search

Given user launches browser
Then validate search results

booking.feature

Feature: Booking Module

Scenario: Validate Complete Booking Flow

Given user launches browser
Then validate booking confirmation

testng.xml

```
<!DOCTYPE suite SYSTEM
"https://testng.org/testng-1.0.dtd">

<suite name="Suite" parallel="methods"
thread-count="5">

<test name="PHPTravels Test">

<classes>

<class name="runners.TestRunner"/>
```

</classes>

</test>

</suite>