# Assignment 3

**Name:** Anish Pote
**PRN:** 123B1B079

Code:
Dynamic E-Commerce Web Application

**1. HTML Structure**

```
<header>
  <div class="nav">
    <h1>NeoCart</h1>

    <div class="nav-right">
      <input type="text" id="search" placeholder="Search..." onkeyup="searchProducts()">

      <div class="cart-icon" onclick="scrollToCart()">
          <span id="cart-count">0</span>
      </div>
    </div>
  </div>
</header>

<section class="hero">
  <div class="hero-content">
    <h2>Upgrade Your Style</h2>
    <p>Explore modern fashion & tech essentials</p>
    <button onclick="scrollToProducts()">Shop Now</button>
  </div>
</section>

<section id="products">
  <h2>Our Products</h2>
  <div class="product-grid" id="product-grid"></div>
</section>

<section id="cart">
  <h2>Your Cart</h2>
  <div id="cart-items"></div>
  <p>Total: ₹<span id="total">0</span></p>
</section>
```

**2. CSS Styling**

```
.hero{
height:90vh;
display:flex;
justify-content:center;
align-items:center;
text-align:center;
color:white;
background:
linear-gradient(rgba(0,0,0,0.7), rgba(0,0,0,0.9)),
url("https://images.unsplash.com/photo-1490481651871-ab68de25d43d?w=1600") center/cover no-repeat;
}

.product-grid{
display:grid;
grid-template-columns:repeat(auto-fit,minmax(250px,1fr));
gap:20px;
margin-top:30px;
}

.card{
background:#111;
padding:15px;
border-radius:10px;
transition:0.3s;
}

.card:hover{
transform:translateY(-8px);
box-shadow:0 0 15px #00ffcc;
}
```

**3. JavaScript Functionality**

```
function addToCart(id){
let item = cart.find(p=>p.id===id);

if(item){
item.qty++;
}else{
let product = products.find(p=>p.id===id);
cart.push({...product, qty:1});
}
```

```
updateCart();
}

function updateCart(){
let total = 0;
let html = "";

cart.forEach(item=>{
total += item.price * item.qty;

html += `
<p>${item.name} - ₹${item.price} x ${item.qty}</p>
`;
});

document.getElementById("cart-items").innerHTML = html;
document.getElementById("total").innerText = total;
}

function searchProducts(){
let value = document.getElementById("search").value.toLowerCase();

let filtered = products.filter(p =>
p.name.toLowerCase().includes(value)
);

displayProducts(filtered);
}
```