

```
In [1]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.linear_model import LogisticRegression
```

```
In [2]: df=pd.read_csv(r"C:\Users\user\Downloads\health care diabetes.csv")
df
```

```
Out[2]:
```

	Pregnancies	Glucose	BloodPressure	SkinThickness	Insulin	BMI	DiabetesPedigreeFunction	Age
0	6	148	72	35	0	33.6	0.627	50
1	1	85	66	29	0	26.6	0.351	31
2	8	183	64	0	0	23.3	0.672	32
3	1	89	66	23	94	28.1	0.167	21
4	0	137	40	35	168	43.1	2.288	33
...
763	10	101	76	48	180	32.9	0.171	63
764	2	122	70	27	0	36.8	0.340	27
765	5	121	72	23	112	26.2	0.245	30
766	1	126	60	0	0	30.1	0.349	47
767	1	93	70	31	0	30.4	0.315	23

768 rows × 9 columns



```
In [3]: feature_matrix=df.iloc[:,0:34]
target_vector=df.iloc[:,-1]
```

```
In [4]: feature_matrix.shape
```

```
Out[4]: (768, 9)
```

```
In [5]: target_vector.shape
```

```
Out[5]: (768,)
```

```
In [6]: from sklearn.preprocessing import StandardScaler
```

```
In [7]: fs=StandardScaler().fit_transform(feature_matrix)
```

```
In [8]: logr=LogisticRegression()
```

```
In [9]: logr.fit(fs,target_vector)
```

```
Out[9]: LogisticRegression()
```

```
In [10]: observation=[[1,2,3,4,5,6,7,8,9]]
```

```
In [11]: prediction=logr.predict(observation)
```

```
In [12]: print(prediction)
```

```
[1]
```

```
In [13]: logr.classes_
```

```
Out[13]: array([0, 1], dtype=int64)
```

```
In [14]: logr.predict_proba(observation)[0][0]
```

```
Out[14]: 0.0
```

```
In [15]: logr.predict_proba(observation)[0][1]
```

```
Out[15]: 1.0
```

Logistic Regression 2

```
In [16]: import re
from sklearn.datasets import load_digits
from sklearn.model_selection import train_test_split
```

```
In [17]: digits=load_digits()
digits
```

```
Out[17]: {'data': array([[ 0.,  0.,  5., ...,  0.,  0.,  0.],
                        [ 0.,  0.,  0., ..., 10.,  0.,  0.],
                        [ 0.,  0.,  0., ..., 16.,  9.,  0.],
                        ...,
                        [ 0.,  0.,  1., ...,  6.,  0.,  0.],
                        [ 0.,  0.,  2., ..., 12.,  0.,  0.],
                        [ 0.,  0., 10., ..., 12.,  1.,  0.])),
          'target': array([0, 1, 2, ..., 8, 9, 8]),
          'frame': None,
          'feature_names': ['pixel_0_0',
                           'pixel_0_1',
```

```
'pixel_0_2',
'pixel_0_3',
'pixel_0_4',
'pixel_0_5',
'pixel_0_6',
'pixel_0_7',
'pixel_1_0',
'pixel_1_1',
'pixel_1_2',
'pixel_1_3',
'pixel_1_4',
'pixel_1_5',
'pixel_1_6',
'pixel_1_7',
'pixel_2_0',
'pixel_2_1',
'pixel_2_2',
'pixel_2_3',
'pixel_2_4',
'pixel_2_5',
'pixel_2_6',
'pixel_2_7',
'pixel_3_0',
'pixel_3_1',
'pixel_3_2',
'pixel_3_3',
'pixel_3_4',
'pixel_3_5',
'pixel_3_6',
'pixel_3_7',
'pixel_4_0',
'pixel_4_1',
'pixel_4_2',
'pixel_4_3',
'pixel_4_4',
'pixel_4_5',
'pixel_4_6',
'pixel_4_7',
'pixel_5_0',
'pixel_5_1',
'pixel_5_2',
'pixel_5_3',
'pixel_5_4',
'pixel_5_5',
'pixel_5_6',
'pixel_5_7',
'pixel_6_0',
'pixel_6_1',
'pixel_6_2',
'pixel_6_3',
'pixel_6_4',
'pixel_6_5',
'pixel_6_6',
'pixel_6_7',
'pixel_7_0',
'pixel_7_1',
'pixel_7_2',
'pixel_7_3',
'pixel_7_4',
'pixel_7_5',
'pixel_7_6',
'pixel_7_7'],
'target_names': array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9]),
'images': array([[[ 0.,  0.,  5., ...,  1.,  0.,  0.],
 [ 0.,  0., 13., ..., 15.,  5.,  0.]
```

```

[ 0., 3., 15., ..., 11., 8., 0.],
...,
[ 0., 4., 11., ..., 12., 7., 0.],
[ 0., 2., 14., ..., 12., 0., 0.],
[ 0., 0., 6., ..., 0., 0., 0.]],

[[ 0., 0., 0., ..., 5., 0., 0.],
 [ 0., 0., 0., ..., 9., 0., 0.],
 [ 0., 0., 3., ..., 6., 0., 0.],
 ...,
 [ 0., 0., 1., ..., 6., 0., 0.],
 [ 0., 0., 1., ..., 6., 0., 0.],
 [ 0., 0., 0., ..., 10., 0., 0.]],

[[ 0., 0., 0., ..., 12., 0., 0.],
 [ 0., 0., 3., ..., 14., 0., 0.],
 [ 0., 0., 8., ..., 16., 0., 0.],
 ...,
 [ 0., 9., 16., ..., 0., 0., 0.],
 [ 0., 3., 13., ..., 11., 5., 0.],
 [ 0., 0., 0., ..., 16., 9., 0.]],

...,

[[ 0., 0., 1., ..., 1., 0., 0.],
 [ 0., 0., 13., ..., 2., 1., 0.],
 [ 0., 0., 16., ..., 16., 5., 0.],
 ...,
 [ 0., 0., 16., ..., 15., 0., 0.],
 [ 0., 0., 15., ..., 16., 0., 0.],
 [ 0., 0., 2., ..., 6., 0., 0.]],


[[ 0., 0., 2., ..., 0., 0., 0.],
 [ 0., 0., 14., ..., 15., 1., 0.],
 [ 0., 4., 16., ..., 16., 7., 0.],
 ...,
 [ 0., 0., 0., ..., 16., 2., 0.],
 [ 0., 0., 4., ..., 16., 2., 0.],
 [ 0., 0., 5., ..., 12., 0., 0.]],

[[ 0., 0., 10., ..., 1., 0., 0.],
 [ 0., 2., 16., ..., 1., 0., 0.],
 [ 0., 0., 15., ..., 15., 0., 0.],
 ...,
 [ 0., 4., 16., ..., 16., 6., 0.],
 [ 0., 8., 16., ..., 16., 8., 0.],
 [ 0., 1., 8., ..., 12., 1., 0.]]]),
'DESCR': '.. _digits_dataset:\n\nOptical recognition of handwritten digits dataset\n---
-----\n\n**Data Set Characteristics:**\n\n
:Number of Instances: 1797\n      :Number of Attributes: 64\n      :Attribute Information: 8
x8 image of integer pixels in the range 0..16.\n      :Missing Attribute Values: None\n
:Creator: E. Alpaydin (alpaydin '@' boun.edu.tr)\n      :Date: July; 1998\n\nThis is a cop
y of the test set of the UCI ML hand-written digits datasets\nhttps://archive.ics.uci.ed
u/ml/datasets/Optical+Recognition+of+Handwritten+Digits\n\nThe data set contains images
of hand-written digits: 10 classes where\neach class refers to a digit.\n\nPreprocessing
programs made available by NIST were used to extract\nnormalized bitmaps of handwritten
digits from a preprinted form. From a\ntotal of 43 people, 30 contributed to the trainin
g set and different 13\nto the test set. 32x32 bitmaps are divided into nonoverlapping b
locks of\n4x4 and the number of on pixels are counted in each block. This generates\nan
input matrix of 8x8 where each element is an integer in the range\n0..16. This reduces d
imensionality and gives invariance to small\ndistortions.\n\nFor info on NIST preprocess
ing routines, see M. D. Garriss, J. L. Blue, G.\nT. Candela, D. L. Dimmick, J. Geist, P.
J. Grother, S. A. Janet, and C.\nL. Wilson, NIST Form-Based Handprint Recognition Syste
m, NISTIR 5469,\n1994.\n\n.. topic:: References\n\n - C. Kaynak (1995) Methods of Combi
ning Multiple Classifiers and Their\n      Applications to Handwritten Digit Recognition,

```

MSc Thesis, Institute of Graduate Studies in Science and Engineering, Bogazici University.
 - E. Alpaydin, C. Kaynak (1998) Cascading Classifiers, Kybernetika.
 - Ken Tang and Ponnuthurai N. Suganthan and Xi Yao and A. Kai Qin. Linear dimensionality reduction using relevance weighted LDA. School of Electrical and Electronic Engineering Nanyang Technological University. 2005.
 - Claudio Gentile. A New Approximate Maximal Margin Classification Algorithm. NIPS. 2000.

```
In [18]: plt.figure(figsize=(20,4))
for index,(image,label)in enumerate(zip(digits.data[0:5],digits.target[0:5])):
    plt.subplot(1,5,index+1)
    plt.imshow(np.reshape(image,(8,8)),cmap=plt.cm.gray)
    plt.title("Number:%i\n"%label,fontsize=25)
```



```
In [19]: x_train,x_test,y_train,y_test=train_test_split(digits.data,digits.target,test_size=0.30)
```

```
In [20]: logr=LogisticRegression(max_iter=10000)
```

```
In [21]: logr.fit(x_train,y_train)
```

```
Out[21]: LogisticRegression(max_iter=10000)
```

```
In [22]: print(logr.predict(x_test))
```

```
[3 7 4 6 9 7 2 2 0 2 3 6 4 6 4 5 0 1 0 0 0 7 6 1 5 0 2 1 0 1 7 2 9 5 6 4 8
 1 5 3 1 0 5 6 9 4 8 4 1 3 0 0 3 2 4 0 0 2 7 4 9 6 4 1 5 2 8 8 8 3 2 9 5 2
 4 7 5 0 1 6 6 7 9 1 0 4 0 5 9 3 7 7 6 9 8 5 3 4 3 3 7 5 0 5 6 4 8 0 1 8 7
 4 2 2 7 2 9 0 1 0 8 1 0 6 6 0 0 4 4 7 7 0 5 9 5 3 8 7 9 6 7 6 0 0 3 6 4 5
 3 2 3 7 6 7 6 6 7 2 9 4 6 7 2 1 7 5 7 1 6 2 2 3 5 5 9 1 0 1 2 2 1 5 3 3
 8 7 4 6 4 9 0 6 0 3 0 4 6 0 9 1 9 0 8 3 8 9 6 3 2 2 2 9 0 7 0 8 8 0 5 8 1
 7 0 6 1 6 4 8 9 6 9 2 0 3 7 4 1 7 9 4 3 9 6 3 9 1 1 6 4 7 8 8 0 0 3 0 2 3
 7 1 4 9 6 0 8 5 2 5 3 9 7 2 3 8 4 1 1 6 7 3 5 5 0 1 0 4 1 1 7 4 1 7 6 2 2
 9 3 5 6 0 3 5 7 9 3 7 0 2 3 5 6 8 8 8 3 5 5 3 5 0 6 2 1 2 0 2 5 4 1 2 6 2
 0 7 5 1 9 3 2 3 0 9 4 4 9 8 2 4 3 2 0 7 8 5 8 2 3 4 3 6 2 1 8 0 5 0 8 8 1
 1 7 3 1 0 4 4 0 9 0 4 0 9 6 3 2 4 3 7 6 5 7 0 4 6 8 2 3 7 5 5 2 8 0 8 8 4
 1 9 4 8 0 5 2 0 1 6 9 7 2 1 9 6 1 3 2 5 9 6 3 5 0 3 9 7 8 6 1 8 8 8 1 8 4
 7 9 7 4 6 4 5 1 1 2 3 1 7 1 8 4 5 1 8 4 8 1 8 6 9 3 5 4 0 0 5 5 5 3 9 5 9
 5 8 2 6 1 7 4 4 3 3 5 0 1 6 3 4 3 6 3 6 9 0 2 2 5 8 9 7 6 8 0 2 1 7 0 0 0
 1 7 5 0 6 6 3 4 2 2 6 4 7 5 1 8 5 9 2 4 2 9]
```

```
In [23]: print(logr.score(x_test,y_test))
```

```
0.9666666666666667
```

In []: