

Packet Tracer - Use Diagnostic Commands

Objectives

Part 1: Gather End User Device Settings

Part 2: Gather Information about Network Devices

Part 3: Diagnose Connectivity Issues

Background / Scenario

In this Packet Tracer (PT) activity, you will use various commands to gather device information and troubleshoot device configuration and connectivity issues. Device information includes IP address, default gateway, and DNS server settings. These settings are critical to enable a device to communicate on networks and connect to the internet.

Instructions

Part 1: Gather End User Device Settings

In this part, you will document the IP address settings for end devices.

Step 1: Document the IP address settings for HQ-Laptop-1.

- The activity opens in the **HQ** cluster. The **Wiring Closet** is the tall, black chassis in the bottom left corner of the first floor. Locate all the devices on the first floor: PCs **1-1**, **1-2**, **1-3**, and **1-4**; printer **FL-1P**; and **HQ-Laptop-1**.
- Click **HQ-Laptop-1** > **Desktop** tab > **Command Prompt**.
- Enter the **ipconfig** command.

Which IPv4 address is displayed for the **Wireless0** Connection?

Answer

169.254.238.170

If the IPv4 address is in the 169.254.0.0/16 range, what method is being used to assign IPv4 addresses? Why is the laptop assigned an IPv4 address in the 169.254.0.0/16 range?

Answer

It indicates that the device was unable to obtain addressing from a DHCP server. Therefore, the device assigned itself an address 169.254.0.0/16 pool used for automatic private IP addressing (APIPA).

If the IPv4 address is in the 169.254.0.0/16, wait a few seconds and repeat the **ipconfig** command.

When the IPv4 address is no longer from 169.254.0.0/16 range, what is the IP addressing information displayed? Record your answers in the table below.

Wireless0	IP Addressing Information
Link-local IPv6 Address	FE80::20A:F3FF:FEE4:EEAA
IPv6 Address	::
IPv4 Address	192.168.50.2

Wireless0	IP Addressing Information
Subnet Mask	255.255.255.0
Default Gateway	192.168.50.1
DNS Servers	N/A

Do you see a DNS server address? Explain.

Answer

No, The ipconfig command does not report the DNS server address.

- d. Enter the **ipconfig /all** command.

Do you see the DNS server address? What is it?

Answer

Yes, 10.2.0.125

Step 2: Document the IP address settings for Net-Admin.

- Click **Wiring Closet > Net-Admin > Desktop** tab > **Command Prompt**.
- Enter the **ipconfig /all** command.

What is the IP addressing information displayed under the FastEthernet0 interface? Record your answers in the table below.

FastEthernet0	IP Addressing Information
Physical Address	0001.C910.22D6
Link-local IPv6 Address	FE80::201:C9FF:FE10:22D6
IPv6 Address	::
IPv4 Address	192.168.99.9
Subnet Mask	255.255.255.0
Default Gateway	192.168.99.1
DNS Servers	0.0.0.0

Part 2: Gather Information about Network Devices

In this part, you will document information about the link to ISP. You will then document the IP addressing information for all the end devices in HQ and discover that devices belong to different virtual local area networks (VLANs).

Step 1: Gather network connection information about the link between HQ and ISP.

The **HQ-Edge** router is the router between the HQ network and the ISP. We need to identify the upstream device information located in the ISP.

- In the **Wiring Closet** left rack, click **HQ-Edge > CLI** tab.
- Press **Enter** to get the **HQ-Edge>** prompt, and then enter the **enable** command.
- Enter the **show ip route | begin Gateway** command.

What is the address for the gateway of last resort (or default gateway)?

Answer

0.0.0.0

Why is the next hop address not displayed?

Answer

It is not explicitly configured.

- d. Enter the **show running-config | begin ip route** command.

How is the default route configured? Does it use the next hop address?

Answer

It is configured with the exit interface instead of next hop address.

- e. Enter the **show cdp neighbors detail** command.

What is the IPv4 address of the next hop (ISP) address?

Answer

10.0.0.49

Which port on the ISP router is connected to **HQ-Edge**?

Answer

GigabitEthernet 1/0

What IOS version is used on the ISP router?

Answer

IOS (tm) PT1000 Software (PT1000-I-M), Version 12.2(28), RELEASE SOFTWARE (fc5)

- f. Enter the **ping 10.0.0.49** command.

- g. Enter the **show arp** command.

What is the MAC address of the interface on the **ISP** router that is connected to **HQ-Edge**?

Answer

0060.2FE1.903B

- h. Close **HQ-Edge** and exit the **Wiring Closet**.

Step 2: Gather network connection information about the devices in HQ.

- a. From **1-1**, **1-2**, **1-3**, **1-4**, **FL-1P**, and **HQ-Laptop-1**, use the **ipconfig** command to find their IPv4 addresses and Default Gateways.

Device	IPv4 Address	Default Gateway
1-1	192.168.10.2	192.168.10.1
1-2	192.168.10.3	192.168.10.1
1-3	192.168.20.2	192.168.20.1
1-4	192.168.20.3	192.168.20.1
FL-1P	192.168.50.4	192.168.50.1
HQ-Laptop-1	192.168.50.3	192.168.50.1

- b. From PC **1-1**, open **Command Prompt**, and then enter the **arp -a** command.

What information is displayed?

Answer

No ARP Entries Found.

- c. Use the **ping** command to ping **1-2**, **1-3**, **1-4**, **FL-1P**, and **HQ-Laptop-1**.
- d. Enter the **arp -a** command.

What information is displayed?

Answer

Internet Address	Physical Address	Type
192.168.10.1	000a.41ea.6b47	dynamic
192.168.10.3	0002.4a8a.d20e	dynamic

Why do the entries in the ARP table not contain information about devices in the 192.168.20.0 and 192.168.50.0 networks while the ping is successful?

Answer

192.168.10.0/24, 192.168.20.0/24, and 192.168.50.0/24 are on different VLANs.

What information is displayed?

Answer

Tracing route to 10.2.0.125 over a maximum of 30 hops:

1	0 ms	2 ms	0 ms	192.168.10.1
2	12 ms	0 ms	0 ms	10.0.0.49
3	1 ms	0 ms	0 ms	10.2.0.125

How many routers, or hops, are between PC 1-1 and the DNS server?

Answer

2

Part 3: Diagnose Connectivity Issues

In this part, you will use a variety of diagnostic commands and techniques. You will use the **nslookup** command to query a DNS server and troubleshoot a DNS database. You will then diagnose why a ping fails but web access is successful. Finally, you will use the **netstat** command to discover which ports are listening on the target device.

Step 1: Test a URL to investigate a connectivity issue.

- a. On PC 1-1, close the **Command Prompt**, and then click **Web Browser**.
- b. Enter the URL **test.ptsecurity.com**.

Does the web page display? If not, what is the message?

Answer

No, The message is "Host Name Unresolved".

- c. Enter the IP address **192.168.75.2**.

Does the web page display?

Answer

Yes

Why does the web page display by using the IP address but not the domain name?

Answer

The PC cannot resolve the domain name to the IP address.

Step 2: Use the nslookup command to verify DNS service.

- Close **Web Browser**, and then click **Command Prompt**.
- Enter the **ping test.ptsecurity.com** command.

What message is displayed?

Answer

Ping request could not find host test.ptsecurity.com. Please check the name and try again.

What does the message indicate?

Answer

The DNS entry is not in the database of the DNS server.

- Enter the **nslookup test.ptsecurity.com** command.

What message is displayed?

Answer

```
Server: [10.2.0.125]
Address: 10.2.0.125
*** UnKnown can't find test.ptsecurity.com: Non-existent domain.
```

Which server is the default DNS server?

Answer

10.2.0.125

- The **nslookup** command supports the use of alternate DNS server. Enter the **nslookup /?** command to learn options available for the command.
- Enter the **nslookup test.ptsecurity.com 192.168.99.3** command and press **Enter**.

Note: Packet Tracer may take several seconds to converge.

What message is displayed?

Type your answers here.

Answer

```
C:\> nslookup test.ptsecurity.com 192.168.99.3 Server: [192.168.99.3]
Address: 192.168.99.3
Non-authoritative answer:
Name: test.ptsecurity.com Address: 192.168.75.2
```

In Step 2c, why is the domain name unable to be resolved?

Answer

The PC is trying to resolve it through the default DNS server. In this case, the default DNS server does not contain the information in its database.

Step 3: Use output from the ping command to diagnose connectivity issues.

- Enter the **ping mail.cybercloud.com** command.

What message is displayed?

Answer

```
C:\> ping mail.cybercloud.com
Pinging 172.19.0.4 with 32 bytes of data:
Request timed out.
```

Request timed out.
Request timed out.
Request timed out
Ping statistics for 172.19.0.4:
Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

What information is indicated by the message?

Answer

The DNS name resolution is successful. However, the ping failed. Possible reasons are that the host is inactive or the ICMP echo/echo-reply is disabled on the host.

- b. Enter the **ping www.ptsecurity.com** command.

What message is displayed?

Type your answers here.

Answer

Pinging 10.0.0.3 with 32 bytes of data:
Request timed out.
Request timed out.
Reply from 10.0.0.3: Destination host unreachable.
Reply from 10.0.0.3: Destination host unreachable.
Ping statistics for 10.0.0.3:
Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

What information is indicated by the message?

Answer

There is a firewall in the path that blocks the ping to the destination.

- c. Close the **Command Prompt**, open **Web Browser**, and then navigate to **www.ptsecurity.com**.

Does the web page display?

Answer

Yes

What conclusion can be drawn?

Answer

The web host is running; however, the ping to the web server is blocked.

Step 4: Use the netstat command to find active and listening ports.

- Close **Web Browser**, and reopen **Command Prompt**.
- In **HQ**, click the **Wiring Closet**
- From the right rack, click the **FTP** server > **Desktop** tab > **Command Prompt**.
- Arrange the PC 1-1 and FTP server **Command Prompt** windows side by side.
- From the PC 1-1 window, enter the **netstat** command.

What message is displayed? Does it show any data?

Answer

C:\>netstat

Active Connections

Proto Local Address Foreign Address State

C:\>

No data is shown.

- f. From the **FTP** server, enter the **netstat** command.

What message is displayed? Does it show any data?

Answer

C:\>netstat

Active Connections

Proto	Local Address	Foreign Address	State
TCP	0.0.0.0:25	0.0.0.0:0	CLOSED
TCP	0.0.0.0:110	0.0.0.0:0	CLOSED
TCP	0.0.0.0:8443	0.0.0.0:0	CLOSED

C:\>

It shows no active connection to other devices and no listening ports.

- g. On **FTP** server, enter the **ipconfig** command to determine its IP address.
h. From **PC 1-1**, start an FTP session with the FTP server.
i. On the **FTP** server, enter the **netstat** command.

What message is displayed? Is there any new information?

Answer

Yes, a new entry shows TCP 192.168.75.2:21 192.168.10.3:1025 ESTABLISHED.

Which port is the listening port and what is the status of the connection?

Answer

The listening port is TCP 21 and the TCP connection is established.

- j. From **PC 1-1**, enter **bob** as the username.
k. From the **FTP** server, enter the **netstat** command.

Does the displayed information change?

Answer

No.

- l. From **PC 1-1**, enter **cisco123** as the password.
m. From **PC 1-1**, enter the **dir** command.
n. From the **FTP** server, enter the **netstat** command.

Does the displayed information change?

Answer

Yes. A new entry shows TCP 192.168.75.2:1028 192.168.10.3:1028 CLOSED.

What is indicated by this new entry?

Answer

A new TCP connection is opened to transfer the file names in the FTP directory and the connection is closed after the operation completes.

- o. From **PC 1-1**, enter the **put Sample2.txt** command and press **Enter**. This will upload the Sample2.txt file to the **FTP** server.

- p. From the **FTP** server, enter the **netstat** command.

Does the displayed information change?

Answer

Yes.

TCP 192.168.75.2:1030 192.168.10.3:1029 CLOSING.

- q. Wait for a few seconds and then enter the **netstat** command again.

Does the displayed information change?

Answer

Yes. The "CLOSING" line is gone.

- r. From **PC 1-1**, enter the **quit** command.

- s. From the **FTP** server, enter the **netstat** command.

Does the displayed information change?

Answer

Yes. Now the TCP connection between 192.168.75.2:21 and 192.168.10.2:1027 is CLOSED.

- t. From **PC 1-1**, close **Command Prompt**, and then open **Web Browser**.

- u. Navigate to **192.168.75.2**.

- v. From the **FTP** server, enter the **netstat** command.

Does the displayed information change?

Answer

Yes. A new entry shows TCP 192.168.75.2:80 192.168.10.2:1030 CLOSED.

What does this new entry indicate?

Answer

A web page request is made by the host 192.168.10.2. The web page is transmitted (displayed on the web browser of PC 1-1) and the TCP connection is closed.