

# Softmax and categorical cross entropy loss

Pawel Wocjan

March 18, 2019

## Abstract

We define softmax and categorical cross entropy for multiclass classification

## 1 Classification

Problem type	Last-layer activation	Loss function
Binary classification	sigmoid	binary_crossentropy
Multiclass, single-label classification	softmax	categorical_crossentropy
Multiclass, multi-label classification	sigmoid	binary_crossentropy

## 2 Softmax activation function

Let  $z_1, \dots, z_m$  be the weighted inputs of the  $m$  neurons of the last layer. Each of the neurons corresponds to one of the  $m$  classes of the multiclass classification problem at hand. We consider the single-label situation. We convert the weighted input vector  $\mathbf{z} = (z_1, \dots, z_m)^T \in \mathbb{R}^m$  into a probability vector  $\mathbf{a} = (a_1, \dots, a_m)^T \in \mathbb{R}^n$  by applying the so-called softmax activation function.

For  $k \in [m]$ , the activation  $a_k$  of the  $k$ th neuron is defined as follows:

$$a_k = \frac{e^{z_k}}{\sum_{j=1}^n e^{z_j}}. \quad (1)$$

It is straightforward to verify that this yields a probability distribution. The values  $a_k$  are all positive because the range of the exponential function is  $(0, \infty)$ . They sum up to 1 because of the normalization in the denominator.

Using the product and chain rule, we can show that

$$\frac{\partial a_k}{\partial z_j} = a_k \cdot (\delta_{jk} - a_j), \quad (2)$$

where  $\delta_{jk}$  is the so called Kronecker delta, which is equal to 1 if  $j = k$  and 0 if  $j \neq k$ .

### 3 Cross entropy

Let  $\mathbf{p} = (p_1, \dots, p_m)$  and  $\mathbf{q} = (q_1, \dots, q_m)$  be two probability distributions. In information theory, the cross entropy is defined by

$$H(\mathbf{p}, \mathbf{q}) = - \sum_{k=1}^m p_k \log q_k. \quad (3)$$

See [https://en.wikipedia.org/wiki/Cross\\_entropy](https://en.wikipedia.org/wiki/Cross_entropy) for a quick overview.

### 4 Categorical cross entropy loss function

Let  $y \in [m]$  be a label. Using the so-called one-hot or categorical encoding, we construct a corresponding vector  $\mathbf{y} = (y_1, \dots, y_m)^T \in \mathbb{R}^m$  such that  $m - 1$  of its entries are equal to 0 and exactly one entry is equal to 1. The position of the entry 1 is given by the label  $y$ . For instance, for  $m = 3$  classes, label 1 corresponds to  $(1, 0, 0)$ , the label 2 to  $(0, 1, 0)$ , and the label 3 to  $(0, 0, 1)$ .

Assume that the feature vector  $\mathbf{x}$  produces the activation vector  $\mathbf{a} = (a_1, \dots, a_m)$  in the last layer. Assume that the correct label is  $y$ . Then the categorical cross entropy loss  $\mathcal{L}$  is defined by

$$\mathcal{L} = - \sum_{k=1}^m y_k \log a_k, \quad (4)$$

where  $\mathbf{y} = (y_1, \dots, y_m)$  is the categorical encoding of  $y$ . Observe that  $\mathcal{L} = H(\mathbf{y}, \mathbf{a})$ .

The partial derivatives of  $\mathcal{L}$  with respect to  $a_k$  is

$$\frac{\partial \mathcal{L}}{\partial a_k} = - \frac{y_k}{a_k}. \quad (5)$$

The partial derivatives of  $\mathcal{L}$  with respect to  $z_j$  is

$$\frac{\partial \mathcal{L}}{\partial z_j} = \sum_{k=1}^m \frac{\partial \mathcal{L}}{\partial a_k} \cdot \frac{\partial a_k}{\partial z_j} \quad (6)$$

$$= \sum_{k=1}^m - \frac{y_k}{a_k} \cdot a_k \cdot (\delta_{kj} - a_j) \quad (7)$$

$$= \sum_{k=1}^m y_k \cdot (a_j - \delta_{kj}) \quad (8)$$

$$= \left( \sum_{k=1}^m y_k \right) \cdot a_j - \sum_{k=1}^m y_k \cdot \delta_{kj} \quad (9)$$

$$= a_j - y_j \quad (10)$$

since  $\sum_{k=1}^m y_k = 1$ . Recall that the  $y_k$  are the entries of the one-hot-encoding. In matrix notation, this is given by

$$\nabla_z \mathcal{L} = \mathbf{a} - \mathbf{y} \quad (11)$$

## 5 Simple neural network with softmax activation and categorical cross entropy

Let us consider a network that takes feature vectors of the form  $\mathbf{x} = (x_1, \dots, x_n)^T \in \mathbb{R}^n$  as input and has  $m$  output neurons with softmax activation. Then for  $j \in [m]$ , the weighted input of the  $j$ th neuron is given by

$$z_j = \sum_{i=1}^n w_{ji} x_i + b_j. \quad (12)$$

The weights and the bias of  $j$ th neuron are  $(w_{j1}, \dots, w_{jn})$  and  $b_j$ , respectively. The weighted inputs  $z_j$  are transformed into probabilities by the softmax activation as discussed above.

The loss function changes as follows with respect to the weights and biases:

$$\frac{\partial \mathcal{L}}{\partial w_{ji}} = \frac{\partial \mathcal{L}}{\partial z_j} \cdot x_i \quad (13)$$

$$\frac{\partial \mathcal{L}}{\partial b_j} = \frac{\partial \mathcal{L}}{\partial z_j} \quad (14)$$