



Data Structures and Algorithms Laboratory	
Laboratory 3: Linked Lists	School of Information Technology
Name: Sai Hae Naing Lay	ID: 6531501208 Section: 4
Date: 10 Feb 2023	Due date: on the LMS

Objective

- To create, access and modify linked lists
- To implement singly linked lists

Exercise 1: (In-class) From the given class diagram, create a singly linked list and complete the program to get the results as shown. Assume that elements in all nodes are integer.



Expected result

```

1->2->3->null
2->3->null
2->null
  
```

Complete the codes below.

```

package lab3;
class SLL {
    // ----- Node -----
    private class Node {
        private int element;
        private Node next;

        // constructor
        public Node(int data) {
            element = data;
            next = null;
        }

        // link a new node to this node
  
```

```

        public void link(Node newNode) {
            next = newNode;
        }

        // return next node
        public Node getNextNode() {
            return next;
        }

        // return element of this node
        public int getElement() {
            return element;
        }
    }
    // ----- End Node -----

    // SLL properties and methods
    private Node head = null;
    private Node tail = null;
    private int size = 0; // SLL's size

    public void addLast(int data) {
        // create new node
        Node newNode = new Node(data);
        if (size == 0) {
            head = newNode;
        } else {
            tail.link(newNode);
        }
        tail = newNode;
        size++;
    }

    public void addFirst(int data) {
        Node newNode = new Node(data);
        if(size == 0){
            tail = newNode;
        }else{
            newNode.link(head);
        }
        head = newNode;
        size++;
    }

    public void removeFirst() {
        if(size == 1){
            head = null;
            tail = null;
        }
    }

```

```

        size--;
    }
    else{
        head = head.getNextNode();
        size--;
    }
}

public void removeLast() {

    if(size == 1){
        head = null;
        tail = null;
        size--;
    }
    else{
        Node p = head;
        while(p.getNextNode() != tail){
            p = p.getNextNode();
        }
        tail = p;
        tail.link(null);
        size--;
    }

}

public void print() {
    if (size == 0) {
        System.out.println("Empty linked list");
    } else {
        for (Node p = head; p != null; p = p.getNextNode()) {
            System.out.print(p.getElement() + "->");
        }
        System.out.println("null");
    }
}

}

//===== Main Class =====
public class MainSLL {
    public static void main(String[] args) {
        SLL sll = new SLL();
        sll.addFirst(2);
        sll.addLast(3);
        sll.addFirst(1);
        sll.print();
        sll.removeFirst();
        sll.print();
        sll.removeLast();
    }
}

```

```
    s11.print();  
}  
}
```

Exercise 2: (In-class) From the previous exercise, create four new methods as follows:

1. *int getSize()* → return size of SLL
2. *boolean isEmpty()* → return true if SLL is empty
3. *element get(index)* → return element at specified position
4. *void clear()* → remove all elements

For example, if we have a SLL.



Expected result

```
=== Empty SLL ===
```

```
Size = 0
```

```
Empty = true
```

```
=== After adding elements ===
```

```
Size = 3
```

```
Empty = false
```

```
Element 0 = 11
```

```
Element 1 = 22
```

```
Element 2 = 11
```

```
=== After clearing elements ===
```

```
Size = 0
```

```
Empty = true
```

```
package lab3;
class SLL {
    // ----- Node -----
    private class Node {
        private int element;
        private Node next;

        // constructor
        public Node(int data) {
            element = data;
            next = null;
        }

        // link a new node to this node
        public void link(Node newNode) {
            next = newNode;
        }

        // return next node
    }
}
```

```

        public Node getNextNode() {
            return next;
        }

        // return element of this node
        public int getElement() {
            return element;
        }
    }

    // ----- End Node -----

    // SLL properties and methods
    private Node head = null;
    private Node tail = null;
    private int size = 0; // SLL's size

    public int size() {
        return size;
    }
    public boolean isEmpty() {
        boolean isEmpty=false;
        if(size==0) {
            isEmpty= true;
        }
        return isEmpty;
    }
    public int get(int index) {
        Node p = head;
        for(int i=0;i<index;i++) {
            p = p.getNextNode();
        }
        return p.getElement();
    }

    public void clear() {
        size=0;
        head=null;
        tail=null;
    }

    public void addLast(int data) {
        // create new node
        Node newNode = new Node(data);
        if (size == 0) {
            head = newNode;
        } else {
            tail.link(newNode);
        }
    }

```

```

        tail = newNode;
        size++;
    }

    public void addFirst(int data) {

        Node newNode = new Node(data);
        if(size == 0){
            tail = newNode;
        }else{
            newNode.link(head);
        }
        head = newNode;
        size++;
    }

    public void removeFirst() {

        if(size == 1){
            head = null;
            tail = null;
            size--;
        }
        else{
            head = head.getNextNode();
            size--;
        }
    }

    public void removeLast() {

        if(size == 1){
            head = null;
            tail = null;
            size--;
        }
        else{
            Node p = head;
            while(p.getNextNode() != tail){
                p = p.getNextNode();
            }
            tail = p;
            tail.link(null);
            size--;
        }
    }

    public void print() {
        if (size == 0) {

```

```

        System.out.println("Empty linked list");
    } else {
        for (Node p = head; p != null; p = p.getNextNode()) {
            System.out.print(p.getElement() + "->");
        }
        System.out.println("null");
    }
}

}

}

public class MainSLL{
public static void main(String[] args){
    SLL sll = new SLL();
    System.out.println("=== Empty SLL ===");
    System.out.println("Size = " + sll.size());
    System.out.println("Empty = " + sll.isEmpty());
    System.out.println();

    //add elements
    sll.addLast(11);
    sll.addLast(22);
    sll.addLast(11);
    System.out.println("=== After adding elements ===");
    System.out.println("Size = " + sll.size());
    System.out.println("Empty = " + sll.isEmpty());
    System.out.println("Element 0 = " + sll.get(0));
    System.out.println("Element 1 = " + sll.get(1));
    System.out.println("Element 2 = " + sll.get(2));
    System.out.println();


    //clear
    sll.clear();
    System.out.println("=== After clearing elements ===");
    System.out.println("Size = " + sll.size());
    System.out.println("Empty = " + sll.isEmpty());
    }
}

```


Exercise 3(Homework):From the previous exercise, create three new methods as follows:

1. **findElement(element)** to find whether a number is in a SLL and return **true** or **false** when found and not found respectively
2. **countElement(element)** to count nodes whose elements are equal to a number
3. **sumElement()** to find summation of all numeric elements of nodes

For example, if we have a SLL.



- findElement(11) will return true but findElement(33) will return false
- countElement(11) will return 2, countElement(22) will return 1 and countElement(33) will return 0
- sumElement() will return 44

Expected result

11->22->11->null

Find element 11: true
Find element 22: true
Find element 33: false
Count element 11: 2
Count element 22: 1
Count element 33: 0
Sum of all elements: 44

```
package lab3;
class SLL {
    // ----- Node -----
    private class Node {
        private int element;
        private Node next;

        // constructor
        public Node(int data) {
            element = data;
            next = null;
        }

        // link a new node to this node
        public void link(Node newNode) {
            next = newNode;
        }
    }
}
```

```

        // return next node
        public Node getNextNode() {
            return next;
        }

        // return element of this node
        public int getElement() {
            return element;
        }
    }

    // ----- End Node -----

    // SLL properties and methods
    private Node head = null;
    private Node tail = null;
    private int size = 0; // SLL's size

    public int size() {
        return size;
    }
    public boolean isEmpty() {
        boolean isEmpty=false;
        if(size==0) {
            isEmpty= true;
        }
        return isEmpty;
    }
    public boolean findElement(int fe) {
        boolean findElement=true;
        Node p =head;
        while(p.getNextNode() != tail){
            p = p.getNextNode();
            if (p.getElement() == fe) {
                findElement=true;
            }
            else {
                findElement=false;
            }
        }
        if (head.getElement() == fe || tail.getElement() == fe) {
            findElement=true;
        }
        return findElement;
    }
    public int countElement (int ce) {
        int countElement=0;
        Node p =head;
        while(p.getNextNode() != null){

```

```

        if (p.getElement() == ce) {
            countElement++;
        }
        p = p.getNextNode();
    }
    if ( tail.getElement() == ce) {
        countElement++;
    }
    return countElement;
}

public int sumElement () {
    int sumElement=0;
    Node p =head;
    while(p.getNextNode() != null){
        sumElement+=p.getElement();
        p = p.getNextNode();
    }
    sumElement+=tail.getElement();
    return sumElement;
}

public int get(int index) {
    Node p = head;
    for(int i=0;i<index;i++) {
        p = p.getNextNode();
    }
    return p.getElement();
}

}

public void clear() {
    size=0;
    head=null;
    tail=null;
}

public void addLast(int data) {
    // create new node
    Node newNode = new Node(data);
    if (size == 0) {
        head = newNode;
    } else {
        tail.link(newNode);
    }
    tail = newNode;
    size++;
}

public void addFirst(int data) {

```

```

        Node newNode = new Node(data);
        if(size == 0){
            tail = newNode;
        }else{
            newNode.link(head);
        }
        head = newNode;
        size++;
    }

    public void removeFirst() {

        if(size == 1){
            head = null;
            tail = null;
            size--;
        }
        else{
            head = head.getNextNode();
            size--;
        }
    }

    public void removeLast() {

        if(size == 1){
            head = null;
            tail = null;
            size--;
        }
        else{
            Node p = head;
            while(p.getNextNode() != tail){
                p = p.getNextNode();
            }
            tail = p;
            tail.link(null);
            size--;
        }
    }

    public void print() {
        if (size == 0) {
            System.out.println("Empty linked list");
        } else {
            for (Node p = head; p != null; p = p.getNextNode()) {
                System.out.print(p.getElement() + "->");
            }
        }
    }

```

```

        System.out.println("null");
    }
}

public class MainSLL{
    public static void main(String[] args){
        SLL sll = new SLL();
        sll.addFirst(11);
        sll.addLast(22);
        sll.addLast(11);
        sll.print();

        System.out.println();
        System.out.println("Find element 11: "+sll.findElement(11));
        System.out.println("Find element 22: "+sll.findElement(22));
        System.out.println("Find element 33: "+sll.findElement(33));
        System.out.println("Count element 11: "+sll.countElement(11));
        System.out.println("Count element 22: "+sll.countElement(22));
        System.out.println("Count element 33: "+sll.countElement(33));
        System.out.println("Sum of all elements: "+sll.sumElement());
    }
}

```

Example (Optional): Implementation of SLL using ArrayList

JAVA provides a class ArrayList which is one type of SLL with several built-in methods. Try to observe the following codes.

Be careful that the data to store in ArrayList must be objects not the primitive variables.

```
import java.util.ArrayList;

public class MainArrayList {

    public static void main(String[] args) {
        //create an Integer ArrayList with default size of 10
        ArrayList<Integer> sll = new ArrayList<Integer>();

        //add first
        sll.add(0, new Integer(2));    //[2]
        //add last
        sll.add(new Integer(3));    //[2,3]
        //add first
        sll.add(0, new Integer(1));    //[1,2,3]
        //print
        System.out.println(sll);

        //remove first
        sll.remove(0);    //[2,3]
        //remove last
        sll.remove(sll.size() - 1);    //[2]
        //print
        System.out.println(sll);

        //find element
        System.out.println(sll.contains(new Integer(2)));    //true
        System.out.println(sll.contains(new Integer(1)));    //false
    }
}
```

To see more details and functionality of ArrayList, please visit <https://docs.oracle.com/javase/8/docs/api/java/util/ArrayList.html>

Exercise 4 (Optional): Use the ArrayList and its functions above to get the following result.

Assume that we want to create a back-end of a shopping system for the administrator. This system allows to add, delete and show products. Suppose that we use two SLL to store product name and product price.

Expected result

```
==== Shopping Backend ====
1. Show product
2. Add product
3. Delete product
4. Exit
Choose 1-4...1
    --- Product ---
    No product

==== Shopping Backend ====
1. Show product
2. Add product
3. Delete product
4. Exit
Choose 1-4...2
    Enter product name: Shirt
    Enter product price: 199

==== Shopping Backend ====
1. Show product
2. Add product
3. Delete product
4. Exit
Choose 1-4...2
    Enter product name: Shoes
    Enter product price: 299

==== Shopping Backend ====
1. Show product
2. Add product
3. Delete product
4. Exit
Choose 1-4...1
    --- Product ---
    1. Shirt 199 baht
    2. Shoes 299 baht
```

```

=== Shopping Backend ===
1. Show product
2. Add product
3. Delete product
4. Exit
Choose 1-4...3
    1. Shirt 199 baht
    2. Shoes 299 baht
    Enter the number of product to delete...1

=== Shopping Backend ===
1. Show product
2. Add product
3. Delete product
4. Exit
Choose 1-4...1
    --- Product ---
    1. Shoes 299 baht

=== Shopping Backend ===
1. Show product
2. Add product
3. Delete product
4. Exit
Choose 1-4...4
    Good bye

```

Paste your code here.

```

package asdf;

import java.util.ArrayList;

import java.util.Scanner;

public class Optional {

    public static void main(String[] args) {

        // TODO Auto-generated method stub

        int choice;

        int delete;

        int i = 0;

        String productname = "";

```



```

int productprice;

ArrayList<String> name = new ArrayList<String>();

ArrayList<Integer> price = new ArrayList<Integer>();

Scanner input = new Scanner(System.in);

while(true) {

System.out.println("=== Shopping Backend === \n1.Show Product\n2.Add
Product\n3.Delete Product\n4.Exit");

System.out.print("Choose 1-4...");

choice = input.nextInt();

if(choice == 1) {

System.out.println("---Product---");

if(name.isEmpty()) {

System.out.println("No Product");

}

else {

for(int j=0; j<name.size();j++) {

System.out.println((j+1)+ ". " + name.get(j)+ " "+ price.get(j)+"
baht");

}

}

}

else if(choice == 2) {

System.out.print("Enter product name: ");

productname = input.next();

name.add(productname);

System.out.print("Enter the product price: ");

```

```

productprice = input.nextInt();

price.add(productprice);

i++;

}

else if(choice == 3) {

for(int j=0; j<name.size();j++) {

System.out.println((j+1)+ ". " + name.get(j)+ " "+ price.get(j)+"
baht");

}

System.out.print("Enter the number of product to delete...");

delete = input.nextInt();

if (delete <= name.size()) {

name.remove(delete - 1);

price.remove(delete -1);

i--;

}

}

else if (choice == 4){

System.out.println("Good Bye");

break;

}

}

}

}

```

