

Day 5 – CSS Position Property

1. Introduction to CSS Position

The CSS position property is used to control the placement of HTML elements on a web page. It determines how an element is positioned and how it interacts with other elements. The main position values are static, relative, absolute, fixed, and sticky.

2. Static Position (position: static)

The static position is the default position of every HTML element. Elements are displayed in the normal document flow, and the top, right, bottom, and left properties do not affect them.

Example:

```
.box{  
    position: static;  
}
```

3. Relative Position (position: relative)

The relative position moves an element from its original position without affecting the layout of other elements. The top, bottom, left, and right properties can be used to adjust its position.

Example:

```
.box{  
    position: relative;  
    top: 20px;  
    left: 30px;  
}
```

4. Absolute Position (position: absolute)

The absolute position places an element relative to its nearest positioned parent element. If no positioned parent exists, the element is positioned relative to the webpage.

Example:

```
.box{  
    position: absolute;
```

```
top: 50px;  
left: 100px;  
}
```

5. Fixed Position (position: fixed)

The fixed position keeps an element fixed at a specific location on the screen. It remains visible even when the user scrolls the page.

Example:

```
.box {  
    position: fixed;  
    bottom: 20px;  
    right: 20px;  
}
```

6. Sticky Position (position: sticky)

The sticky position behaves like a relative element until the user scrolls to a specified position. After that, it becomes fixed and stays visible until its parent container ends.

Example:

```
.header {  
    position: sticky;  
    top: 0;  
}
```

7. Practical Task – CSS Position

In today's practical session, I created different boxes and applied all five CSS position properties. I observed how each position value affects the placement of elements and how properties like top, left, right, and bottom change their location on the webpage.

Example:



Conclusion

Today, I learned about the CSS position property and its different values: static, relative, absolute, fixed, and sticky. I practiced positioning elements in different ways and understood how each position behaves on a webpage. This knowledge will help me create better layouts, navigation bars, sticky headers, floating buttons, and responsive web page designs.