

PRODUCT CODE 8031

Royale Bling

Asian Paints Royale Bling emits a brilliant sparkle, gives an elegant sheen, and a world-class finish to the wall with unmatched stain resistance.

PRODUCT BENEFITS

Excellent Sheen

Lumino-Tech gives your walls the brightest colours, total opacity, and a smooth finish. It ensures that the splendour of your interiors remains intact.

10 Years Performance Assurance

It preserves the wall film integrity and shade fidelity. Royale Bling maintains the beauty of your walls by ensuring there is no lack of uniformity. The combination guarantees good leveling and intercoat adhesion leading to smooth finish and improved durability.

Anti-Microbial

Royale Bling protects your walls against harmful Micro-organisms like fungus that can cause considerable damage.

Unmatched Stain Resistance

The balance between wax and fluorinated additives fortifies walls against stains. Royale Bling's washability feature is designed to protect your walls from the harshest stains, making sure they stay beautiful for a long time. Royale Bling offers Advanced Surface Protector that increases durability and reinforces the strength of the paint films.

Green Assure

Green Assure is our promise that the product conforms with international environmental and safety standards. It is low VOC and does not contain hazardous raw material.

Nail Scratch Proof

Royale Bling has excellent resistance to scratch protecting your walls for years to come.



WATER BASED



asianpaints



**No Added Mercury,
Arsenic & Chromium**

Lead content does not exceed 90 parts per million.

PRODUCT FEATURES

WASHABILITY



✓ **BEST IN CLASS***

HIGH

MEDIUM

LOW

AVAILABLE PACKS




Shelf life: 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

COLOURS AVAILABLE

**1480
SHADES***

*Currently available in more than 1480 shades as per the Asian Paints Colour Spectra.



FINISH

MATT SOFT SHEEN HI SHEEN **SUPER SHEEN**

✓ **SMOOTH**

Refer to gloss levels in technical details

COVERAGE

On normal masonry surface after brushing / roller




2 COATS
120sq.ft/ltr**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.

HOW TO APPLY

PRE PAINTING STEPS



PLASTER New masonry surfaces must be allowed to cure completely. It is recommended to allow 3 months as the curing time for new masonry surfaces.



CLEANING Surface should be free from any loose paint, dust or grease. Growths of fungus, algae or moss should be removed by wire brushing and water. In case of areas having excessive dampness, correct it to limit further dampness. Bio block can be used for removing fungus, algae or moss.



FILLING FOR CRACKS For filling cracks upto 3mm use Asian Paints Crack Seal product.



FILLING FOR HOLES & DENTS

In case of dents and holes, use TruCare acrylic wall putty. For larger dents/holes it is recommended to use white cement and fine sand in the ratio 1:3.

For interior surfaces or substrates that are subjected to continuous seepage or dampness, kindly use suitable product which blocks the dampness before the top coat application.

HOW TO CHOOSE COLOURS

Browse through Asian Paints colour tools to help you find the right colour combination.

COLOUR SPECTRA FAN DECK*



*These shades are for reference only. Please refer to the Colour Spectra or Colour Palette for correct shade reference.

PAINT APPLICATION PROCESS

APPLICATION	CODE	THINNER	DILUTION %	RECOATING PERIOD
SANDING				
SAND THE SURFACE WITH EMERY PAPER 180 AND WIPE CLEAN				
ASIAN PAINTS DECOPRIME WALL PRIMER ROLLER	8360	WATER	ROLLER 1:1	4-6 HRS
ASIAN PAINTS WALL PUTTY PUTTY KNIFE	8753	WATER	AS REQUIRED	-
SANDING				
SAND THE SURFACE WITH EMERY PAPER 180 AND WIPE CLEAN				
ASIAN PAINTS DECOPRIME WALL PRIMER ROLLER	8360	WATER	ROLLER 1:1	4-6 HRS
SANDING				
SAND THE SURFACE WITH EMERY PAPER 320 AND WIPE CLEAN				
ASIAN PAINTS ROYALE BLING 1 ST COAT ROLLER, SPRAY	8031	WATER	ROLLER 15-20 SPRAY 15-20	4-6 HRS
STEP 8 ASIAN PAINTS ROYALE BLING 2 ND COAT ROLLER, SPRAY	8031	WATER	ROLLER 15-20 SPRAY 15-20	4-6 HRS

*Dilution measured with glass on volume basis. Recoat period is quoted for 25deg cel. And 50% relative humidity, these may vary under different conditions.

ADDITIONAL INFORMATION

PRECAUTIONS

- > Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- > Do not apply when humidity exceeds 85% or when raining outside.
- > Do not over-thin or over-extend the brush.
- > Tint using Asian Paints machine colorants only.
- > Stir well and strain before use.
- > Tinted paints need thorough shaking immediately after tinter addition as well as before use.

POST PAINTING CARE

The Golden rule for removing any wall stains is that one should remove it immediately.

Remove all dirt using a clean cloth or duster. Always remove dirt from top to bottom, this helps in avoiding loose dirt to smudge the walls.

For regular household stains like use 5% mild soap/detergent solution only. Use a sponge to remove the stains.

TECHNICAL DETAILS

- Drying time:** Surface dry time 90 min
- Gloss levels:** 55 at 60 deg GH
- Flash point IS101/1987 Part 1, Sec 6: NA**
- Stability of thinned paint:** To be used within 24 hours

SAFETY FEATURES

- > Kindly refer to the MSDS for Asian Paints Royale Bling which gives detailed information on safety measures while handling the paint, which is available on request.
- > Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- > Keep out of reach of children and away from eatables.
- > May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- > Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- > In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- > Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- > Do not pour leftover paint down the drain or in water courses.
- > In the event of spills, contain spillage using sand or earth.
- > No added Lead, Mercury or Chromium compounds.
- > Customers should consult a local recycling agency for proper disposal of paints/drum
- > Ensure that the surface is dry. Surface Moisture (On moisture meter) is under 16%. In case it is higher, find out the source of water and address it before painting. Allow undercoats to dry sufficiently before applying paint.
- > Ensure the paint is cured for 2 week under normal atmospheric conditions. (300C; 50-60% RH) prior cleaning stains.
- > Application of Acrylic Wall Putty and adherence to the painting system will be to best results.
- > Avoid use of Alkyd Based Primer with Cement Based Putty or filling compounds.



For enquiries, feedback and complaints, please call toll-free number 16600124680/9802033515 or write to us at weassure@asianpaints.com.np