

Implementation of Network Commands

Command 1: hostname

```
C:\Users\Exam25>hostname
MCN-0030
```

The `hostname` command displays the name of my computer on the network. This name is used to identify the system uniquely in a local or network environment.

Command 1: systeminfo

```
C:\Users\Exam25>systeminfo

Host Name:                  MCN-0030
OS Name:                    Microsoft Windows 11 Pro
OS Version:                 10.0.22H2.0 N/A Build 22H2
OS Manufacturer:           Microsoft Corporation
OS Configuration:          Member Workstation
OS Build Type:               Multiprocessor Free
Registered Owner:           user
Registered Organization:     N/A
Product ID:                  00330-33854-38626-AA0EM
Original Install Date:       04-01-2025, 02:26:25
System Boot Time:            04-12-2025, 09:20:38
System Manufacturer:        Dell Inc.
System Model:                 OptiPlex AIO 7420 35W
System Type:                 x64-based PC
Processor(s):                1 Processor(s) Installed.
                              [01]: Intel(R) family 6 Model 191 Stepping 2 GenuineIntel ~1700 Mhz
BIOS Version:                Dell Inc. 1.28.4, 05-06-2025
Windows Directory:           C:\WINDOWS
System Directory:             C:\WINDOWS\system32
Boot Device:                  \Device\HarddiskVolume1
System Locale:                 en-us;English (United States)
Input Locale:                 08004089
Time Zone:                    (UTC+05:30) Chennai, Kolkata, Mumbai, New Delhi
Total Physical Memory:        16,071 MB
Available Physical Memory:    7,588 MB
Virtual Memory: Max Size:     17,095 MB
Virtual Memory: Available:    7,141 MB
Virtual Memory: In Use:       9,954 MB
Page File Location(s):        C:\pagefile.sys
Domain:                       \MC-ADC
Logon Server:                  \\MC-ADC
Hotfix(s):                    4 Hotfix(s) Installed.
                              [01]: KB5046131
                              [02]: KB5074109
                              [03]: KB5076035
                              [04]: KB5071102
Network Card(s):              2 NIC(s) Installed.
                              [01]: Intel(R) Ethernet Connection (17) I219-LM
                                  Connection Name: Ethernet
                                  Status:          hardware not present
                              [02]: Intel(R) Wi-Fi 6 AX201 160MHz
                                  Connection Name: Wi-Fi
                                  DHCP Enabled:     Yes
                                  DHCP Server:      172.20.10.1
                                  IP address(es)
                                  [01]: 172.20.10.2
                                  [02]: fe80::c79b:1c5f:2993:66b6
                                  [03]: 2409:4808:12ea:e52d:4c78:98ab:8cbf:ec08
                                  [04]: 2409:4808:12ea:e52d:7c15:a035:c44d:d62d
Virtualization-based security: Status: not enabled
App Control for Business policy: Enforced
App Control for Business user mode policy: Off
Security Features Enabled:
Hyper-V Requirements:         VM Monitor Mode Extensions: Yes
                              Virtualization Enabled In Firmware: Yes
                              Second Level Address Translation: Yes
                              Data Execution Prevention Available: Yes
```

The `systeminfo` command provides detailed information about my computer system. It shows the operating system version, hardware details, memory information, and system configuration. This command is useful for checking system specifications and troubleshooting.

Command 3: netstat

```
C:\Users\Linab>netstat -an

Active Connections

Proto Local Address           Foreign Address         State
TCP    0.0.0.0:135              0.0.0.0:0               LISTENING
TCP    0.0.0.0:445              0.0.0.0:0               LISTENING
TCP    0.0.0.0:2387             0.0.0.0:0               LISTENING
TCP    0.0.0.0:5848             0.0.0.0:0               LISTENING
TCP    0.0.0.0:7688             0.0.0.0:0               LISTENING
TCP    0.0.0.0:49664            0.0.0.0:0               LISTENING
TCP    0.0.0.0:49665            0.0.0.0:0               LISTENING
TCP    0.0.0.0:49666            0.0.0.0:0               LISTENING
TCP    0.0.0.0:49667            0.0.0.0:0               LISTENING
TCP    0.0.0.0:49668            0.0.0.0:0               LISTENING
TCP    0.0.0.0:49669            0.0.0.0:0               LISTENING
TCP    0.0.0.0:49671            0.0.0.0:0               LISTENING
TCP    10.10.13.120:7688        10.10.6.177:49701       TIME_WAIT
TCP    10.10.13.120:7688        10.10.6.177:49701       TIME_WAIT
TCP    10.10.13.120:7688        10.10.6.177:52723       TIME_WAIT
TCP    [fe80::c78b:2c5f:2993:6d66%4]:64624 [fe80::3c1e:b5ff:fe61:7d66%4]:53 TIME_WAIT
TCP    [fe80::c78b:2c5f:2993:6d66%4]:64625 [fe80::3c1e:b5ff:fe61:7d66%4]:53 TIME_WAIT
TCP    [fe80::c78b:2c5f:2993:6d66%4]:64966 [fe80::3c1e:b5ff:fe61:7d66%4]:53 TIME_WAIT
UDP    0.0.0.0:123              **
UDP    0.0.0.0:1686             **
UDP    0.0.0.0:5353             **
UDP    0.0.0.0:5353             **
UDP    0.0.0.0:5353             **
UDP    0.0.0.0:5353             **
UDP    0.0.0.0:5353             **
UDP    0.0.0.0:5353             **
UDP    0.0.0.0:5353             **
UDP    0.0.0.0:51165           **
UDP    0.0.0.0:53357           **
UDP    0.0.0.0:55803           0.0.0.0:443             **
UDP    0.0.0.0:56639           **
UDP    0.0.0.0:52406           0.0.0.0:443             **
UDP    0.0.0.0:64077           95.242.117.196:443      **
UDP    127.0.0.1:1988           **
UDP    127.0.0.1:49664         127.0.0.1:49664         **
UDP    127.0.0.1:49669         **
UDP    127.0.0.1:51794         127.0.0.1:51794         **
UDP    127.0.0.1:56753         127.0.0.1:56753         **
UDP    127.0.0.1:57332         127.0.0.1:57332         **
UDP    127.0.0.1:57797         127.0.0.1:57797         **
UDP    172.20.10.2:137         **
UDP    172.20.10.2:138         **
UDP    172.20.10.2:1988        **
UDP    172.20.10.2:2177        **
UDP    172.20.10.2:49668       **
UDP    [:]:123                  **
UDP    [:]:5353                 **
UDP    [:]:5353                 **
UDP    [:]:5353                 **
UDP    [:]:5353                 **
UDP    [:]:5353                 **
UDP    [:]:51165                **
UDP    [:]:53357                **
UDP    [:]:55803                [2004:6880:4802:81b:2004]:443
UDP    [:]:56639                **
UDP    [:]:64096                [2004:6880:4802:829:2004]:443
UDP    [:]:64077                [2004:4700:9642:7c8c:2004:484:5ff2:75c4]:443
UDP    [:]:1988                 **
UDP    [:]:49667                **
UDP    [2009:40d0:12ea:e52d:4c78:98ab:8cbf:ec08]:2177 **
UDP    [2009:40d0:12ea:e52d:7c15:ed35:c4dd:d62d]:2177 **
UDP    [fe80::c78b:2c5f:2993:6d66%4]:1988 **
UDP    [fe80::c78b:2c5f:2993:6d66%4]:2177 **
UDP    [fe80::c78b:2c5f:2993:6d66%4]:49666 **
```

The `netstat` command displays active network connections on my computer.

It shows which ports are open and which connections are currently established.

This command helps in monitoring network activity and detecting unauthorized connections.