



ROSEMOUNT™ 3051HT HYGIENIC PRESSURE TRANSMITTER

Industry-leading batch repeatability.

Reduce Costs & Cycle Times

Life sciences and food and beverage industries are facing continuous pressure to reduce costs and cycle time in order to increase batch quality and yields – all while complying with demanding industry regulations.

The Rosemount™ 3051HT Hygienic Pressure Transmitter places Emerson's proven sensor technologies in a sanitary package to provide industry-leading batch repeatability which meets 3-A, EHEDG, and ASME BPE industry standards.



Rosemount 3051HT Hygienic Pressure Transmitter

How it Works

Increase batch consistency and achieve repeatable measurements without extensive calibrations using the Rosemount 3051HT Pressure Transmitter. Polished stainless steel housing ensures easy cleaning and multiple process connection and surface finish options are available to uniquely suit a wide variety of hygienic applications. A robust design also offers:

- Sensor technology provides excellent batch repeatability up to $\pm 0.02\%$ upper range limit for 60 batches
- Withstands washdown conditions (IP66/68 rated) for long-term performance and durability
- Best-in-class stability decreases operating costs and extends maintenance intervals

Key Features

Improved Display

High contrast graphical back-lit display communicates information with improved clarity

Optimized User Interface

New interfaces and menu for optimized maintenance and simplified commissioning

Bluetooth® Connectivity

Bluetooth connectivity streamlines tasks while keeping personnel safe



ROSEMOUNT 3051HT HYGIENIC PRESSURE TRANSMITTER

Advanced Capabilities

Best-in-Class Performance

- 0.065% span reference accuracy
- 100:1 rangedown
- CIP/SIP up to 302 °F (150 °C)
- 5-year stability

Local Operator Interface (LOI) & Bluetooth® Connectivity

Simplify commissioning and routine maintenance operations with the Local Operator Interface's built-in configuration buttons and straightforward menus. Bluetooth® connectivity also adds the option of performing maintenance up to 50 feet away from the device.

Loop Integrity Diagnostic

Proactively detect electrical loop integrity issues resulting from factors such as corrosion, moisture, or power supply failures before they cause unplanned downtime with the Loop Integrity Diagnostic.

Plugged Impulse Line Diagnostic

Ensure that your output responds to process changes before it impacts the quality of the process for increased safety and reduced downtime.



For more information, visit
[Emerson.com/Rosemount3051HT](https://www.emerson.com/Rosemount3051HT)

The Emerson logo is a trademark and service mark of Emerson Electric Co.
Rosemount is a registered trademark of one of the Emerson family of companies.
All other marks are the property of their respective owners. ©2025 Emerson Electric Co. All rights reserved.

00807-0100-4091 Rev BB

ROSEMOUNT™


EMERSON™