

Politecnico di Torino

Politecnico di Torino

Master of science program in CYBERSECURITY

A.a. 2025/2026

Graduation Session July 2026

An Experimental Framework for Evaluating Secure Deletion Techniques in Modern Digital Environments

Relatori:

Andrea Atzeni

Giuseppe Emiliano Vaciago

Candidati:

Imesha Ann Anjalie Ponnamperumage

Abstract

Within the branch of Anti-Forensics, secure deletion has emerged as a critical component in cybersecurity, regulatory compliance and digital Forensics. While standard deletion operations remove file-system references without erasing the underlying data, secure deletion techniques aim to ensure that data is made irrecoverable. This Thesis presents an experimental framework for evaluating the effectiveness, performance, and observability of secure deletion techniques in modern solid-state drives. The framework addresses the lack of standardized and reproducible evaluation methods by considering measurable factors such as post-deletion data recoverability, deletion latency, timing variability and verification limitations. The experimental study will evaluate data recoverability after TRIM, conventional overwriting, and drive-level sanitization at different time intervals. The experiments will also examine how filesystem journaling, overwrite operations under Flash Translation Layer remapping, workload intensity, drive fill level, and vendor-specific controller behaviour influence deletion outcomes. The results will be analysed to identify the reliability, limitations, and security implications of current deletion mechanisms, and to determine how effectively they support verifiable and standards-aligned data sanitization. In addition to the technical evaluation, this thesis will also explore the regulatory and legal implications of secure deletion practices, particularly in the context of data protection laws and individual privacy rights. By establishing a reproducible evaluation methodology, this work contributes a foundation for systematically assessing secure deletion techniques and bridging the gap between technical capabilities and regulatory compliance requirements.

The importance of secure deletion is highlighed in cases where sensitive information, such as personal data, financial records, or confidential business information, expected by users to be permanently removed, can be recovered by malicious actors or forensic investigators. This disconnected between user expectation and technical reality has led to a cascade of high-profile data breaches across public and private sectors. Further the widespread transition from HDDs to SSDs has resulted in a paradigm shift in data storage and management, introducing new challenges for secure deletion through out-of-place updates, wear levelling, garbage collection, and Flash Translation Layer abstraction. These mechanisms can preserve residual copies of deleted data even after deletion or overwriting operations have been performed.

Keywords : *secure data deletion; NAND flash memory; solid-state drives; Flash Translation Layer; data remanence; data sanitization; cryptographic erasure; block erasure; deletion verification; regulatory compliance.*

Acknowledgements

Table of Contents

List of Tables VI

List of Figures VII

1 Introduction 1
- 1.1 NAND flash storage architecture . . . 3
  - 1.1.1 Cell Structure and Memory Organization . . . 3
  - 1.1.2 Basic Operations and Timing . . . 4
  - 1.1.3 Write-Once Property and Out-of-Place Updates . . . 4
  - 1.1.4 Flash Translation Layer . . . 4
  - 1.1.5 Scrubbing: Overwriting at the Page Level . . . 5
  - 1.1.6 Partial Overwriting and Down-Bit Programming . . . 6
  - 1.1.7 The Communication Path . . . 7
- 1.2 Implications for Secure Deletion . . . 8
  - 1.2.1 Verification of Secure Deletion . . . 12
- 1.3 Native Drive-Level Sanitization . . . 13
  - 1.3.1 Key Native Commands by Interface . . . 14
  - 1.3.2 What is MEK Rotation . . . 17

2 Comparative Analysis of Existing Literature 19
- 2.1 A Taxonomy of Anti-Forensic Techniques . . . 19
- 2.2 A Comparative Analysis of Secure Deletion Techniques . . . 20
  - 2.2.1 A Layer-Based Taxonomy of Secure Deletion . . . 20
  - 2.2.2 Comparative Evaluation of Secure Deletion Techniques . . . 26
  - 2.2.3 Comparison Matrix . . . 29
- 2.3 Synthesized Observations from the Literature . . . 44
- 2.4 Empirical Evaluation Approaches in the Literature . . . 47
- 2.5 Legal and Ethical Dimensions . . . 47
  - 2.5.1 GDPR and the Right to Erasure . . . 47
  - 2.5.2 Technical Challenges to the Right to Be Forgotten . . . 48
  - 2.5.3 Digital Evidence and Cross-Border Procedure . . . 49

2.5.4 Comparative Regulatory Landscape 49
2.6 Summary and Identified Research Gaps 51

3 Experimental Framework and Methodology 52
3.1 Research Objectives 52
3.1.1 Research Questions 53
3.2 Experimental Environment 54
3.3 Analysis Methodology 54
3.4 Experiments and Results 54
3.5 Evaluation Metrics 54
3.6 Statistical Analysis Methods 54

4 Experimental Results and Analysis 55

5 Interpretation of Findings and Implications 56

6 Conclusions and Future Work 57

A Appendix A 58

Bibliography 59

List of Tables

1.1 Comparison of NIST SP 800-88 Sanitization Levels 14
1.2 The Key Hierarchy Within an NVMe SED 16

2.1 Summary of Anti-Forensic Techniques 20
2.2 Secure Deletion Approaches by System Layer 25
2.3 Comprehensive Comparison of Secure Deletion Approaches for Flash Storage 30

List of Figures

Chapter 1

Introduction

The task of deleting data and ensuring that they remain irrecoverable is known as Secure Data deletion. It has currently become one of the most pressing concerns in the cybersecurity, regulatory compliance, and digital forensics domains. While there exists physical means of making data irrecoverable in the physical world where confidential documents are shredded, and storage media containing classified material are physically destroyed, in the digital domain this is significantly complex. The standard delete operation on modern systems only implements file unlinking, which only changes the file system metadata while full contents will still remain intact in the system but users assume that all the content has been permanently erased. [1]

The criticality of this problem has been addressed by two intersecting forces. First, regulatory frameworks including GDPR right to erasure, NIST SP 800-88 Rev. 1, and IEEE 2883-2022 have mandated demonstrative and verifiable data removal evidences at defined sanitization levels; Clear, Purge and Destroy, with specific assurance against data recovery. Next, the mainstream transition from the usage of Hard Disk Drives (HDDs) to Solid-State Drives (SSDs) has led to a fundamental alteration of the storage landscape resulting in decades of secure deletion practices being inadequate.[2] The problem of secure deletion not only occurs in the technical domain but also spans into the legal and ethical domains. On the legal front, regulations such as the GDPR, the California Consumer Privacy Act (CCPA), and emerging AI governance frameworks impose obligations for data erasure that existing technical mechanisms struggle to satisfy.

Taking into account the criticality of the problem, a Study conducted by two MIT graduate students in 2003 by purchasing 158 used hard drives from eBay found that 117 (74%) drives contained recoverable data, 28 (17%) had fully installed operating systems with user data requiring no special effort to recover, only 12 drives (8%) had been properly sanitized. Recovered data included medical records, love letters, corporate financial records, and over 5,000 credit card numbers [3]. A

near-identical experiment was conducted by Blancco Technology Group in 2018 with 159 used drives across the U.S., U.K., Germany, and Finland. Every seller insisted the drives had been "wiped." Researchers recovered passport scans, spreadsheets full of customer data, and intimate photographs. [4].

As per the 2024 Verizon Data Breach Investigations Report, 68% of data breaches involve non-malicious human error—including failure to properly delete sensitive information from decommissioned devices [5]. Separately, Blancco Technology Group's annual data sanitization report found that 42% of used drives sold on secondary markets contain recoverable personally identifiable information (PII), with 15% containing corporate financial data [6]. The public sector contributes some of the earlist cases, In 2002, the Pennsylvania Department of Labor and Industry sold computers to local resellers without sanitizing the drives. The machines contained "thousands of files of information about state employees" that had never been removed [3]. More recently, in 2026, Cornwall Council in the UK suffered a redaction failure when it sent PDF documents that appeared redacted but revealed the full personal details of 10 complainants—names, home addresses, emails, and phone numbers—when opened. The failure mechanism was using visual overlays, a redaction approach that does not securely delete the underlying data instead of applying permanent redaction with sanitization [7].

Within the financial Sector, Between 2015 and 2022, Morgan Stanley Smith Barney (MSSB) committed a series of secure deletion failures that became one of the most expensive examples of improper data disposal on record. In 2015, MSSB decommissioned thousands of hard drives and servers by hiring a company which had no prior experience or expertise in proper data destruction. These hard drives and server were later resold on an internet auction site while containing the PII of 15 million customers. [8]. In a separate incident, 42 servers went missing during a hardware refresh program. All potentially contained unencrypted customer data. The servers had encryption capability, but the firm never activated the encryption software. Recovered drives contained at least 140,000 pieces of customer PII on 13 out of 14 hard drives examined forensically. The SEC stated the "vast majority" of devices were never recovered [9]. The company ended up paying over $155 million in fines and settlements related to these incidents [10].

The common thread across every case is the same: standard deletion does not remove data. Operating systems typically only remove file system pointers, leaving the underlying data intact on the storage medium. On SSDs, the problem compounds because the Flash Translation Layer performs out-of-place updates, wear leveling, and garbage collection that can silently preserve copies even after overwrite attempts. Whether the mechanism is a visual redaction overlay, a missing encryption activation, an unverified third-party promise, or a simple failure to wipe before resale, the result is identical: data thought to be gone remains recoverable.

The literature review below surveys state-of-the-art techniques in secure deletion,

identifies methodological gaps, and motivates the need for a systematic framework that can reliably assess deletion effectiveness across diverse modern storage environments. The remainder of this thesis is organized as follows. The next section reviews the background of NAND flash storage architecture and the secure deletion problem in detail. Chapter 2 presents a systematic review of existing secure deletion techniques and their empirical evaluations along with a review on the Legal and Ethical Aspects. Chapter 3 describes the proposed experimental framework, including its metric system, test methodology, and verification protocols. Chapter 4 presents the results of applying the framework across a diverse set of storage devices and deletion techniques. Chapter 5 discusses the implications of the findings and Chapter 6 concludes with directions for future work.

1.1 NAND flash storage architecture

NAND flash memory which was introduced by Toshiba in 1988, is a type of non-volatile semiconductor memory that has become the dominant storage technology for solid-state drives (SSDs), USB flash drives, and mobile devices [2]. Unlike NOR flash, which supports random access and high read performance at smaller capacities, NAND flash offers significantly higher storage density and faster write/erase operations at a lower cost, making it ideal for bulk data storage [11]

1.1.1 Cell Structure and Memory Organization

At the physical level, each NAND flash memory cell is a floating-gate transistor. Data is stored by injecting electrical charge into the floating gate, which is electrically isolated and can retain charge without power. A charged floating gate (programmed state) represents a logical "0," while an uncharged gate (erased state) represents a logical "1" [11]. The amount of charge determines the cell's threshold voltage (Vt), which is read and interpreted as one or more bits depending on the cell type:Single-level cell (SLC) flash stores one bit per cell, whereas multi-level cell (MLC) stores two bits, triple-level cell (TLC) stores three bits, and quad-level cell (QLC) stores four bits. Each increase in bit density reduces cost per gigabyte at the expense of reduced endurance and lower performance [2].

Memory cells are arranged hierarchically. Cells connected to the same word line form a page, which is the smallest unit for read and program (write) operations. Pages are grouped into blocks, the smallest unit for erase operations. Blocks are organized into planes, multiple planes reside on a single die, and multiple dies are packaged into a NAND chip. Typical page sizes range from 2 KB to 16 KB, and blocks typically contain 64 to 256 pages[2]. Each page also includes a spare or out-of-band (OOB) area used to store error-correcting codes (ECC) and metadata [12]. During a normal program operation, charge is injected into the floating gate

using Fowler-Nordheim tunneling, shifting the Vt to a target distribution window. A read operation applies a reference voltage and senses whether current flows, revealing the cell's programmed state. The erase operation removes charge by applying a high voltage across the transistor, returning the cell to its erased (lowest Vt) state.

1.1.2 Basic Operations and Timing

The three fundamental operations on NAND flash are read, program, and erase. Read and program operate at page granularity, while erase operates at block granularity. Their latencies differ by orders of magnitude: a page read takes approximately 20 to 60 μs, a page program takes 200 to 500 μs, and a block erase takes 1.5 to 5 ms [2, 12]. An erase-before-write architecture means that updating even a single byte requires eventually erasing an entire block, which the Flash Translation Layer (FTL) works around using out-of-place updates. The FTL abstracts these physical details behind a standard block-device interface, mapping logical block addresses (LBAs) to physical NAND pages [13]. This abstraction allows traditional file systems (ext4, NTFS, HFS+) to remain compatible, but it also hides the true physical state of the data from the host [2].

1.1.3 Write-Once Property and Out-of-Place Updates

NAND flash has a fundamental constraint: a page cannot be overwritten in place. To write new data to a page, the entire encompassing block must first be erased, which resets all cells in that block to the "1" (erased) state [2] Because erasing a block is an expensive operation that destroys all data within it, SSDs do not perform in-place updates. Instead, they use out-of-place updates: modified data is written to an available free page elsewhere, and the old page is marked as invalid [14]. Pages containing current data are termed valid pages, while those holding superseded data are invalid pages. This write-once property is the root cause of many of the secure deletion challenges discussed in this review.

1.1.4 Flash Translation Layer

To maintain compatibility with traditional block-based file systems (e.g., ext4, NTFS), SSDs incorporate a Flash Translation Layer (FTL) that runs on the device controller [2]. The FTL maps logical block addresses (LBAs) issued by the operating system to physical flash addresses. This abstraction hides the complexity of NAND flash from the host and enables the SSD to manage internal operations transparently [12].

The FTL implements several critical management functions:

Wear leveling distributes program/erase (P/E) cycles evenly across all blocks to extend device lifespan. Each NAND flash block has a finite endurance typically 100,000 cycles for SLC and 10,000 to 100,000 for MLC/TLC after which the block becomes unreliable. Dynamic wear leveling distributes writes among free blocks, while static wear leveling periodically relocates infrequently accessed (cold) data to prevent some blocks from remaining idle while others wear out [11].

Garbage collection reclaims space occupied by invalid pages. When the number of free pages falls below a threshold, the FTL selects a victim block with a high proportion of invalid pages, copies any remaining valid pages to a free block, and then erases the victim block [2, 12]. This process introduces write amplification, where a single host write triggers multiple internal writes due to data migration.

Bad block management tracks blocks that have become defective through wear or manufacturing defects. These blocks are recorded in a bad block table and excluded from further use, with any valid data relocated to healthy blocks [12, 11].

Over-provisioning reserves a portion of the total flash capacity as spare area to improve performance and endurance. This over-provisioned space is used for wear leveling, garbage collection, and bad block management. [2, 15]

Error correction is essential because NAND flash cells are susceptible to read disturb, program disturb, charge leakage, and retention errors. The FTL computes ECC data stored in each page's OOB area to detect and correct bit errors[14].

An SSD packages multiple NAND chips with a controller that manages the FTL, host interface, and error correction. The storage architecture spans several layers: the host interface (e.g., SATA or NVMe) communicates with the FTL, which translates LBAs to physical addresses and coordinates access across multiple channels, packages, and dies in parallel to maximize throughput. To overcome the density scaling limits of planar (2D) NAND, manufacturers have adopted 3D NAND technology, which stacks memory cells vertically in layers [2]. 3D NAND achieves higher storage density without shrinking individual cell geometries, which improves endurance and reduces interference between adjacent cells. However, the vertical architecture introduces more complex disturb characteristics and new challenges for secure deletion, as erasing data in one layer can disturb adjacent layers [15].

1.1.5 Scrubbing: Overwriting at the Page Level

Since page-level erase is physically impossible, scrubbing was proposed by Wei et al. in 2011 as a way to destroy data on individual programmed pages without block erasure. Scrubbing works by re-programming all remaining 1 bits on a page to 0, effectively overwriting the entire page with zeros. This is possible because NAND flash does allow programming individual bits from 1 to 0; the reverse transition (0 to 1) is what requires a block erase. The mechanism uses incremental step pulse

programming (ISPP), which iteratively applies programming pulses and verifies the cell Vt until it reaches the target state [2, 16].

Scrubbing comes with a serious reliability cost called cell disturbance. The act of reprogramming one cell unintentionally shifts the Vt of neighboring cells due to parasitic coupling through the word lines and bit lines. In 2D NAND, programming a page disturbs the two immediately adjacent pages. In 3D NAND, where flash cells are stacked vertically, as many as four adjacent pages can be disturbed, and the problem grows more severe with each additional layer. The increased bit error rate (BER) from scrubbing disturbance may trigger error correction failures, requiring the data on affected adjacent pages to be migrated before scrubbing can safely proceed.

The concept of a scrub budget was introduced to limit how many times a given block can be scrubbed before exhibiting significant data error risk. Once the budget is exceeded, secure deletion for that block must fall back to a full block erase or garbage collection. Determining the correct budget requires experimental BER analysis and is pattern-dependent and wear-cycle-dependent, making it difficult to set a universal safe threshold[17, 14].

A full scrubbed page is uniformly zeros, which itself signals to a forensic examiner that a deletion occurred at that location. Partial scrubbing addresses this by modifying only a subset of bits in the page or block, avoiding the tell-tale all-zero pattern. This is a form of anti-forensic deletion that blends sanitized data with the appearance of normal programmed content.

More critically, Hasan and Ray demonstrated in 2020 that scrubbing is partially reversible[18]. By performing analog reads that measure the precise threshold voltage distribution (rather than a single binary interpretation), an attacker can distinguish between a cell that was programmed to a 1 and then scrubbed to 0, and a cell that was originally programmed to 0. The residual Vt difference, though small, is detectable with precision sense amplifiers. Analog sanitization was proposed as a remediation: instead of a single binary scrubbing pass, the page is reprogrammed to a Vt distribution that is statistically indistinguishable from a native 0-programmed page[19].

1.1.6 Partial Overwriting and Down-Bit Programming

Multiple finer-grained overwriting schemes operate at sub-page granularity by exploiting the fact that MLC and TLC cells have multiple threshold voltage states. Partial overwriting programs random data into only some of the Vt states of a multi-bit cell, destroying the original data without fully programming the cell to the highest state. Down-bit programming takes this further by programming a page originally stored in a 3-bit-per-cell (TLC) mode into a 1-bit-per-cell (SLC) mode, effectively compacting and destroying the original data in a single operation.

The deletion pulse application scheme applies a series of erase-like pulses to a programmed page, shifting its Vt distribution without performing a full block erase. These schemes cause lower program disturbance than conventional scrubbing because they do not push cells to the highest Vt state, but they also provide less security assurance since some Vt residue may remain [20, 19].

1.1.7 The Communication Path

The operating system does not have direct knowledge of the physical flash layout. After a file is deleted, the file system deallocates the logical blocks by removing their entries from the file system index (inode table, MFT, etc.), but the actual data remains intact on the NAND cells. The host cannot simply overwrite the physical location because the FTL may have remapped those logical addresses to any physical page on the drive. There are three main channels through which the OS conveys block-deallocation information to the storage device

TRIM : The TRIM command is an ATA command that allows the file system to inform the SSD controller about which LBAs no longer store valid data. When a file is deleted, the OS issues a TRIM command for the LBAs covered by that file, and the controller adds those blocks to an internal queue of blocks to be blanked. The TRIM command was not designed for secure deletion but rather as an efficiency optimization for flash: without it, the FTL cannot distinguish logically discarded blocks from valid data and must assume that the only deletable block on the physical medium is the one being overwritten, eventually causing a thrashing effect. TRIM operates through the ATA DATA SET MANAGEMENT command and is supported by most modern operating systems (Windows 7+, Linux 2.6.28+, macOS) and file systems (NTFS, ext4, HFS+). Importantly, the TRIM command provides no false negatives: it indicates every time a block is discarded. However, it is an asynchronous notification: the controller is free to schedule the actual physical erasure at its own discretion, and the OS receives no confirmation of when or whether the erasure happened. TRIM is a suitable command for deleting specific files, but the FTL only uses the information to mark address mappings as invalid [1, 21].

TrueErase : Diesburg et al. proposed TrueErase as a refinement that provides similar information to TRIM but only for blocks belonging to files specifically marked as sensitive. TrueErase adds a new communication channel between the file system and the device driver that forwards deallocation information selectively. Device drivers are modified to implement immediate secure deletion when provided with this notification, avoiding the performance cost of blanket TRIM for all deleted blocks [1].

Out-of-place updates as implicit notification : When the host writes new data to an LBA that already has a physical mapping, the FTL performs an

out-of-place update: it allocates a new physical page, writes the new data there, and marks the old physical page as invalid. This gives the FTL indirect evidence that the old data at that LBA is no longer needed. However, this mechanism only works for blocks that are explicitly overwritten, not for blocks that are simply deallocated by file deletion or truncation [17].

The FTL performs the address mapping function that translates the logical addresses used by the host into the physical addresses on the NAND flash memory. When the host issues a deletion or overwrite request, the FTL invalidates the address mapping information linking the logical address to the previous physical address. For deletion, the FTL receives the file's LBA range through the TRIM command and marks the corresponding address mappings as invalid [17].

Crucially, the invalidation step is purely a metadata operation. The FTL terminates the host's request immediately after updating the mapping table, and the actual data on the NAND cells is left entirely untouched. The flash controller does not erase, overwrite, or otherwise modify the physical pages at this point. The data persists in an undamaged state on the NAND cells, fully recoverable through low-level access techniques. The only change is that the FTL will never again return that physical page in response to a read of that LBA. This design is intentional: erasing a block is time-consuming (on the order of milliseconds per block), and performing it eagerly on every deallocation would destroy performance[12].

1.2 Implications for Secure Deletion

The architectural features described above create fundamental obstacles to secure deletion. Out-of-place updates cause multiple copies of data to persist across the device as stale pages are left behind. Garbage collection and wear leveling can relocate data transparently, making it impossible for host-level software to predict where data physically resides. Over-provisioned areas are inaccessible to the operating system, yet may retain residual copies of deleted data. These characteristics mean that a conventional delete command at the file-system level does not remove the underlying data from the physical medium, and techniques that are effective on HDDs such as overwriting are ineffective on NAND flash [2].

Garbage Collection and the Zombie Time

Garbage collection is the FTL process that physically reclaims NAND blocks containing invalid pages. Its canonical procedure has three steps: selecting a victim block with the largest number of invalid pages, copying any remaining valid pages from the victim block to a free block, and then erasing the victim block [12]. The erase operation makes the block available for future writes. Free blocks are managed from a pool, and modern SSDs are typically over-provisioned with 25% or more

spare NAND capacity to absorb write pressure and give garbage collection time to keep up [13].

The zombie time is defined as the interval between the point when the FTL invalidates the address mapping of a file's pages and the point when garbage collection physically erases those pages from the NAND cells [17]. During this window, the data remains fully intact and recoverable, even though the file system and the host consider it deleted. The zombie time has no fixed duration: it depends on the storage usage pattern, the prevalence of free blocks in the over-provisioning pool, the FTL's victim selection policy, and whether TRIM commands were issued for the deallocated blocks.

The fundamental cause of the zombie time is that the FTL is designed to minimize garbage collection frequency, since garbage collection degrades I/O response by introducing read-copy-erase cycles that add latency. The FTL only triggers garbage collection under two conditions. In the foreground (normal garbage collection), garbage collection is triggered when the free-block pool drops below a threshold, meaning the device has no clean blocks available to service incoming writes. n the background, some FTL implementations opportunistically erase stale blocks during idle time. The foreground garbage collection event is driven entirely by write pressure: if the host is mostly reading and the free-block pool is adequate, garbage collection may not occur for long periods. There is a compounding factor: even when normal garbage collection is triggered, the zombie time for a specific file depends on whether the blocks containing its pages are selected as victim blocks. The FTL selects the victim with the highest count of invalid pages [17], so a block containing only a few invalid pages is unlikely to be chosen until many pages in that block have accumulated. If a block contains mostly valid pages plus one or two invalidated pages from a deleted file, that block will sit untouched indefinitely while the deleted data remains recoverable.

The Zombie-Kill (ZK) TRIM scheme, proposed by Kwak et al., introduces a compulsory garbage collection mechanism that directly limits the zombie time, it operates in three modes that trade deletion speed against I/O performance [17]. *Normal mode* defers all physical erasure to the FTL's standard garbage collection policy (normal garbage collection). The TRIM handling process is the same as standard file deletion: the address mapping is invalidated, and the target pages are erased only when the free-block pool runs low and the blocks happen to be selected as victims. This mode has the longest zombie time, and in workloads with sufficient free blocks, the zombie time becomes effectively unbounded: deleted data may persist indefinitely because garbage collection is never triggered. *Immediate mode* erases the data using the compulsory garbage collection upon receiving the TRIM command. As soon as the TRIM command arrives, the FTL invalidates the address mappings and then immediately performs compulsory garbage collection on the blocks containing the target pages. This mode limits the zombie time to

the execution time of the compulsory garbage collection itself, which is determined by the number of blocks containing target pages and the number of valid pages that must be copied out of each victim block. In the experiments by Kwak et al., immediate mode achieved the smallest zombie time in all cases, but the I/O response time was 68 times larger on average than normal mode because the compulsory garbage collection introduces processing delays even when free blocks are abundant. *Suspension mode* balances the trade-off. After receiving the TRIM command, the FTL saves the invalidation time of each deleted file's pages to a TRIM command table. The FTL then monitors the suspension time of each file by comparing the current time against the invalidation time. Until the suspension time exceeds a configurable maximum, target pages can only be erased by the normal garbage collection policy. If target pages remain unerased after the maximum suspension time, the blocks containing them are erased by the compulsory garbage collection. This mode limits the zombie time to the sum of the maximum suspension time and the compulsory garbage collection execution time, while producing a smaller I/O penalty than immediate mode. Fewer compulsory garbage collection events occur because target pages accumulate during the suspension window, and blocks with a higher proportion of invalid pages are selected, making each garbage collection event more efficient [17].

The zombie time is workload-dependent with significant forensic implications. In write-heavy workloads, the free-block pool drains quickly and normal garbage collection is triggered frequently, reducing the zombie time. In read-heavy workloads, the free-block pool remains ample, and normal garbage collection may never activate the blocks containing deleted pages. Under these conditions, the zombie time can be effectively infinite: the deleted data persists until the device is eventually subjected to a write- intensive workload that forces garbage collection. Compounding this, the distribution of invalid pages across blocks affects whether a given deleted file's pages are reclaimed. The FTL selects the victim with the largest number of invalid pages, so blocks where the deleted file's pages are scattered across many blocks (each containing few invalid pages) experience longer zombie times than blocks with concentrated invalid pages.

TRIM Implementation Variance Across Drives

: Black-box testing has revealed significant variation in how different SSDs implement TRIM and garbage collection. On the Corsair F60, TRIM triggered within 1-10 seconds of a deletion. On other drives, TRIM behavior depended on the percentage of allocated space. Some drives did not erase all TRIM-marked blocks but rather a subset based on internal drive policies, meaning that even after TRIM and GC, some deleted blocks remained unerased. Importantly, garbage collection can operate independently of the host: it can be triggered whenever the disk is

powered on, even if no write commands are issued, rendering write blockers and other forensic precautions useless. This means the forensic examiner cannot assume that data persists in a known state across reboots. Most modern operating systems and their default file systems have built-in support for the ATA TRIM command, but the implementation of TRIM varies from controllers in SSDs to kernels in operating systems. [22, 21]

FTL Internals and its Forensic Impact

Wear leveling distributes program-erase (P/E) cycles evenly across all blocks to prevent premature wear-out of frequently written blocks. Dynamic wear leveling operates on newly allocated blocks, while static wear leveling also moves cold (infrequently rewritten) data to ensure even wear on otherwise idle blocks. Every data migration performed by wear leveling creates opportunities for data duplication: a page may be copied to a new physical location while the old location is not immediately erased, leaving recoverable copies that neither the file system nor the OS is aware of. The write amplification factor (WAF) measures the ratio of physical writes to logical writes. A WAF of 3 means that every logical write from the host causes 3 physical writes due to garbage collection and wear leveling overhead. Each extra write represents a potential duplicate of the original data, and each duplicate must be separately sanitized for secure deletion to be effective. [12, 13]

The copy-back program operation is an internal NAND flash operation that moves data from one page to another without transferring data to the controller. It is used by FTLs during garbage collection and wear leveling to reduce latency. Ahn and Lee revealed that the copy-back program operation leaves unmanaged original data in the source page, which becomes a major forensic target. The source page may contain the original data even after the copy-back completes, and because the copy-back is a low-level operation invisible to the host, no higher-layer deletion mechanism can target it. Secure copy-back programming adds an enhanced secure program operation after the conventional copy-back. This can take two forms: programming random data into the source page (destroying the stored data) or applying a series of deletion pulses to the source page to shift its Vt distribution. To minimize disturbance to adjacent victim cells, the controller can first read victim cell group information from the adjacent word line and selectively inhibit programming on cells that would cause errors. [15]

FTL operations systematically create multiple copies of data that persist after the primary copy is deleted. Garbage collection copies valid pages from victim blocks to free blocks before erasing, leaving the original data in unerased cells that may remain in the free block pool. Wear leveling similarly migrates data, and the old physical location is not always erased immediately. Bad block management copies data away from failing blocks, creating yet another duplicate. The RedFlash

scheme addresses this by maintaining a duplicate chain in the out-of-band (OOB) area of each flash page. The OOB area is typically reserved for ECC parity and bad block markers, the RedFlash was repurposed to store metadata linking each page to all other pages that contain copies of the same logical data. When a deletion command is issued, the OOB chain enables backtracking so that every duplicate is located and erased, not just the primary copy [12].

Encryption-based deletion alone does not eliminate structural artifacts. Chen and Chen showed that the physical location of data on flash storage can itself leak information even when the data content is encrypted or destroyed. For example, knowing that certain blocks are allocated to specific applications or user profiles reveals usage patterns. When a block is sanitized while surrounding blocks remain intact, the spatial pattern of erasures implicitly confirms which data the user considered sensitive. Sanitizing data content without addressing structural context leaves a recoverable forensic profile [2].

1.2.1 Verification of Secure Deletion

A persistent gap in secure deletion is the inability to independently confirm that data has been physically destroyed. Ahn and Lee proposed an in-band verification technique based on cell count information. After a secure deletion operation, the NAND cells in the sanitized area exhibit a characteristic Vt distribution that differs from normal programmed data. Under normal program conditions, the number of cells in each Vt state is approximately uniformly distributed. After a scrubbing or block erase, the distribution shifts to a non-uniform pattern. A simple read operation can count cells per distribution and compare against a reference threshold, determining pass or fail without comparing personal data directly. This verification can be performed in real time immediately after secure deletion and requires no structural changes to existing NAND flash memory. For higher assurance, the verification scheme can use XOR operations between the data sensed from the sanitized area and the original personal data, with pass/fail determination accounting for the ECC correction capability. If the residual data is within the correctable bit error range, deletion is considered successful. [15]

Modern SSDs can vary the size of the over-provisioning (OP) area in real time to optimize performance, with OP areas reaching up to 50% of total NAND capacity. Changing the OP area size generates an invalid data region: when OP shrinks, blocks that were previously reserved become accessible as user space, and the data they contain has never been sanitized. A forensic attacker can exploit this by manipulating the OP area allocation to expose blocks that still hold residual data. Even if the user data is encrypted, an attacker with sufficient resources could read the encrypted data from the invalidated area and attempt decryption offline. This makes deletion verification for dynamically allocated OP areas an essential but

largely unaddressed requirement. Some proposed solutions include pseudo-erase operations that combine partial programming with lightweight verification, trading full sanitization for real-time performance [15].

Achieving secure deletion in modern systems is fundamentally challenging because storage architectures are organized into multiple layers application, file system, block device, and physical medium each of which can retain residual copies of data [12]. Performing deletion at the application layer, for example, only removes the logical reference; the underlying data remains in the file system and may persist on the physical media indefinitely [14].

1.3 Native Drive-Level Sanitization

Native drive-level sanitization refers to built-in hardware/firmware commands defined by storage interface standards (ATA, NVMe, SCSI) that instruct a drive's controller to erase all user data on the physical medium. Unlike software-based overwriting tools that operate through the file system, these commands execute inside the drive's controller and can potentially reach areas the OS cannot access — including over-provisioned zones and retired blocks [17].

The three major standrds; NIST SP 800-88 Rev. 1 (2014), IEEE 2883-2022, and NATO AEDP-3 use a three tier classification of sanitization methods: Clear, Purge, and Destruct. [2].

Table 1.1: Comparison of NIST SP 800-88 Sanitization Levels

Level	Description	Effectiveness	Reusability
Clear	Logical sanitization that removes user-accessible data only. Example: ATA Secure Erase, NVMe Format without CRYPTO flag.	Low — residual data may remain in hidden areas	Storage can be reused
Purge	Advanced sanitization making recovery infeasible even under lab conditions. Example: ATA Enhanced Secure Erase, NVMe Secure Erase (CRYPTO flag enabled), Cryptographic Erase.	High	Storage can be reused
Destruct	Physical destruction of the media.	Complete	Device cannot be reused

1.3.1 Key Native Commands by Interface

ATA/ATAPI

- `SECURITY ERASE PREPARE` : prerequisite that unlocks the drive for erasure.
- `SECURITY ERASE UNIT` : overwrites every NAND cell with zeros or ones. Operates at the factory-reset level and covers reserved areas (over-provision and retired blocks) that the host cannot normally address.
- `ENHANCED SECURITY ERASE` : vendor-defined extension that may erase more thoroughly (e.g., SanDisk calls this "sanitize").
- `SANITIZE DEVICE` : a newer, more flexible command supporting three modes: crypto scramble, overwrite, and block erase.

- `DATA SET MANAGEMENT` : not a sanitization command, but marks logical blocks as free so the controller's garbage collection can reclaim them over time.

NVMe

- `Format NVM` : reformats the namespace. Without the CRYPTO flag it is a Clear-level operation; with the CRYPTO flag enabled it reaches Purge level.

- `Sanitize` : supports Block Erase, Overwrite, and Crypto Erase modes. The `nvme sanitize-log` command reports progress and completion status.

SCSI

- `SANITIZE` : functionally similar to the ATA SANITIZE DEVICE command, supporting block erase, overwrite, and cryptographic erase options.

As stated above there are two principle purge mechanisms: block erase and cryptographic erase.

Block Erase : The controller issues the NAND flash erase command for every block on the device, forcing each block to its unprogrammed (erased) state. This is inherently slow — a 900 GB NVMe drive can take significant time — and the time estimates reported by tools are often inaccurate. Critically, block erase behavior is governed by usage-aware controller logic that may compromise the guarantee of full sanitization; studies found that the controller sometimes returns all-zero data during verification without having physically erased every cell, suggesting internal masking rather than true physical deletion. [2]

Cryptographic Erase : On self-encrypting drives (those supporting TCG Opal SSC or similar), all user data is encrypted by a media encryption key stored in the controller. Cryptographic erase works by scrambling or deleting that key, making the ciphertext on the medium permanently undecryptable. This is nearly instantaneous and does not wear the NAND cells. The flip side: security rests entirely on the vendor's key management. If the key is not fully destroyed, if a copy persists in a controller cache, or if there is a backdoor, the protection fails. [2]

As stated above,NVMe's Sanitize command supports Cryptographic Erase as one of its three modes. Cryptographic erasure renders data irrecoverable by destroying the media encryption key (MEK) rather than overwriting physical cells and n a self-encrypting drive, all user data is encrypted by a MEK that never leaves the controller's secure boundary. An NVMe self-encrypting drive complying with TCG Opal 2.0 maintains multiple keys at different privilege levels and the MEK is the root of every data confidentiality guarantee. All user data written to the NAND medium is ciphertext under this single key, encrypted and decrypted transparently by the hardware encryption engine in the drive controller [2].

Table 1.2: The Key Hierarchy Within an NVMe SED

Key	**Role**	**Storage Location**
Authentication Key (AK)	Proves the user/host is authorized to issue commands	Derived from user password, never stored in plaintext
Band Master Key (BMTK)	Protects individual locking ranges (bands) on the drive	Encrypted under the AK, stored on the NAND medium
Media Encryption Key (MEK)	The actual AES cipher key that encrypts/decrypts all user data on the NAND flash	Inside the controller's dedicated key memory — never leaves the controller die

1.3.2 What is MEK Rotation

MEK rotation is the act of replacing the current Media Encryption Key with a new one and securely discarding the old key. Within the TCG Opal framework, this is accomplished through the RevertSP and Revert methods, which are the Opal equivalents of the NVMe Sanitize (Crypto Scramble) command [2].

The procedure, as implemented by Opal-compliant drives, works as follows:

1. The host issues a RevertSP (or Revert) command to the drive's TCG Storage Interface.

2. The controller generates a new random AES-128 or AES-256 key.

3. The controller overwrites its internal MEK register with the new key — this is a purely volatile operation within the controller logic.

4. The old MEK is destroyed as the register is overwritten. Since the MEK never leaves the controller in plaintext, and the controller has no mechanism to export it, the old key becomes unrecoverable.

5. All ciphertext on the NAND medium is now permanently undecryptable. The data has not been physically erased — every bit pattern remains exactly where it was — but it can never be recovered because the cryptographic secret that produced the plaintext is gone.

6. Optionally, per the NATO AEDP-3 standard, a block erase can follow the cryptographic erase to physically scrub the NAND cells, adding defense in depth [2].

A full block erase on a large NVMe drive (e.g. 1 TB) can take tens of minutes because it must cycle through every NAND block's erase operation sequentially, with verification [2] while MEK rotation completes in approximately 0.22 seconds regardless of drive capacity or how much data is stored

But still, these approaches has their practical limitations. Firstly, vendors can be inconsistent in supporting and implementing these commands, with some drives ignoring them or providing false assuarances of completion [26]. Further, Native commands are all-or-nothing where they sanitize the entire device which makes them suitable for decommissioning but useless in routine per-file deletions. And the controller's internal logic is not transparent, making it difficult to verify that the intended sanitization has actually occurred, all-zero reads may reflect the controller lying rather than physical erasure [2]. Finally, wear-leveling mechanisms spreads data across cells, garbage collection creates copies in unexpected locations, and over-provisioning hides blocks from the host, all of which mean that even a correctly executed sanitize command may leave data remnants in retired or remapped blocks

[2]. A verifiable alternative method SAFE (Scramble and Finally Erase) was proposed to overcome these limitations. SAFE encrypts all data with a key held only in the controller's volatile memory, then on receiving a sanitize command: (1) erases the controller key memory, (2) erases every NAND block, (3) writes a known verification pattern, (4) erases again, and (5) reinitializes with a new key. This provides controller-level verifiability but, like the other native commands, offers no selective deletion capability [1].

SAFE (Scramble and Finally Erase) essentially performs an MEK rotation combined with a follow-up block erase and verification pattern — a verified MEK rotation plus physical scrub [14]. The Eraser and Holepunch schemes operate at a higher layer, using host-level master key rotation with tree-based or PPRF-based file key derivation to achieve the equivalent of selective "mini-MEK rotations" at file granularity, solving the all-or-nothing limitation of native NVMe MEK rotation [2, 25].

Chapter 2

Comparative Analysis of Existing Literature

The growing dependence on digital systems for both personal and professional activities has resulted in an unprecedented accumulation of sensitive information. As organizations and individuals increasingly store confidential data on a wide range of digital media—ranging from traditional hard drives to solid-state drives and cloud environments—the need for reliable and verifiable data deletion mechanisms has become critical. Failure to ensure proper data sanitization can expose users to privacy breaches, corporate espionage, and regulatory non-compliance. From a cybersecurity perspective, secure deletion plays a dual role. On one hand, it is an essential component of data protection and privacy preservation, ensuring that information is irretrievably removed when no longer needed. On the other hand, it can also be employed as part of anti-forensic strategies, deliberately obstructing digital investigations by erasing potential evidence. Understanding this duality is fundamental to appreciating the technical and ethical challenges that surround secure deletion.

2.1 A Taxonomy of Anti-Forensic Techniques

The field of digital forensics is founded on the assumption that traces of user activity persist within digital systems and can be extracted for analysis and attribution. Anti-Forensics challenges this assumption by allowing the deliberate use of various techniques, procedures, tools and stratergies to obstruct the collection of digital evidences from a computer system. The main objective of these methodologies are to hinder Data Collection and impede Forensic investigations. These techniques aim to obscure, alter, or destroy digital evidence in ways that reduce the likelihood of recovery or interpretation. Anti-Forensics Techniques can be categorized into

four distinct categories based on their approach: **data hiding, artefact deletion, obfuscation of traces, and attacks on forensic tools and methods.** [23]

Table 2.1: Summary of Anti-Forensic Techniques

Category	What it does	Examples
Data Hiding	Conceals data so it's difficult to find, while keeping it accessible to the adversary	Encryption, steganography, filesystem manipulation, Host Protected Area modification
Artifact Deletion	Permanently destroys or overwrites data to eliminate recoverable traces	Secure file deletion, disk wiping utilities, degaussing, physical destruction
Obfuscation of traces	Confuses or misdirects the forensic process	Log cleaners, timestamp alteration, spoofing, backbone hopping
Attacks Against Tools/Methods	Directly targets forensic software or procedures	Compression bombs, hash collision attacks, anti-reverse engineering

Secure deletion falls under the **artifact deletion** category, as it focuses on the permanent destruction of data to prevent recovery.

2.2 A Comparative Analysis of Secure Deletion Techniques

2.2.1 A Layer-Based Taxonomy of Secure Deletion

Secure deletion techniques can be organized into a layered taxonomy based on the layer of the storage stack at which they operate. Each layer offers a different interface to the physical medium, and the choice of layer involves a fundamental trade-off: lower layers give stronger irrecoverability guarantees, while higher layers make it easier to identify which data objects to delete [1]. Below is the taxonomy, ordered from the lowest (physical) to the highest (application) layer, followed by cross-layer approaches that bridge multiple layers.

Physical Layer

The interface at this layer is the set of physical actions one can perform on the medium. Secure deletion here entails physical destruction: shredding, incineration, or use of an NSA/CSS-approved degausser. Magnetic media are securely deleted by degaussing; flash memory, optical discs, and punched cards are not — they require incineration or mechanical destruction. This layer achieves the strongest guarantee of irrecoverability but operates at full-device granularity only; no individual data object can be singled out.

Controller Layer

Controllers translate between the analog physical medium and the binary format used by higher layers. They expose standardized hardware interfaces such as SCSI or ATA, which offer reading and writing of fixed-size logical blocks [1]. Secure deletion at this layer takes these forms:

- **Full-device sanitization.** Both SCSI and ATA offer secure-erase or security-initialize commands that exhaustively overwrite every block. NIST recommends these as the non-destructive way to sanitize magnetic hard drives.
- **Block overwriting.** A single block can be overwritten to displace its old content, but without knowledge of which blocks constitute a particular data object, the controller cannot target individual files — it must sanitize every block to guarantee deletion of any one object.
- **Analog remnants** Gutmann demonstrated that on magnetic media, the precise analog voltage of an overwritten bit can reveal its prior value, motivating multi-pass overwriting schemes.
- **Flash controller caveats** Implementation of secure erase on SSDs is not always correct — some devices report success while the data remains accessible. Swanson et al. propose encrypting all data with a controller-stored key, then erasing that key before performing a three-pass sanitization.

Block Device / Device-Driver Layer

Device drivers are software abstractions that consolidate hardware access behind a common interface. Two distinct interfaces are relevant:

- **Block device driver** : Permits reading and writing of logically addressed blocks; used for magnetic hard drives and SSDs fronted by an FTL.

- **Memory Technology Device (MTD)** : Accesses raw flash memory directly. MTD permits reading and writing, but blocks must be erased before being written, and erasure occurs at a much coarser granularity than reads and writes. Unsorted Block Images (UBI) builds on MTD to simplify raw-flash access.

At this layer, the device driver cannot distinguish between valid data and deleted data without guidance from higher layers — a limitation that motivates the cross-layer approaches described in latter section.

File System Layer: In-Place Updates

For physical media whose device driver supports in-place updates (primarily magnetic hard drives), secure deletion can be integrated directly into the file system:

- **ext2 secure-deletion patch** : Adds a sensitive attribute for files. When a sensitive file is deleted, the freed blocks are passed to a kernel daemon that overwrites them asynchronously, sorted by disk seek position for efficiency.
- **ext3 secure deletion** : Two variants: a basic mode that overwrites file data once, and a comprehensive mode that overwrites both data and metadata using a configurable scheme such as Gutmann's 35-pass pattern. Both can be restricted to files with a sensitive extended attribute.
- **Secure deletion via renaming** : Intercepts unlink and truncate events, moving affected files into a special secure-deletion directory where a background process (e.g., shred) sanitizes them.
- **Purgefs** : A file-system extension for any block-based file system that overwrites blocks when they are returned to the free list, supporting per-file sensitivity flags.
- **Versioning file systems** : Uses all-or-nothing cryptographic transforms: each data block is expanded into an encrypted block plus a key-sized tag. Deleting a file version requires overwriting only the version's tags, leaving the shared encrypted data block intact but undecipherable.

File System Layer: No In-Place Updates

For flash memory and other media that do not permit in-place updates, overwriting is not a viable strategy. These approaches instead work within the constraint that data can only be destroyed by erasing an entire erase unit:

- **Compaction (immediate)** : Copy all valid data out of the erase unit containing the deleted data, then erase the unit. This is costly: one erasure per deletion, plus the read-copy overhead.

- **Batched compaction** : Accumulate deletions and compact all affected erase units intermittently, amortizing the erasure cost. Log-structured file systems already perform a similar technique (garbage collection), but prioritize space reclamation over deletion latency.

- **Per-file encryption** : Encrypts each file with a unique key stored in the file header. By colocating all header versions on the same erase unit, deleting a file requires compacting only one erase unit — the one holding the key — under computational assumptions.

- **DNEFS** : Encrypts every data block with a unique key and colocates keys in a dedicated key-storage area. Secure deletion is performed intermittently by replacing the key-storage area with a new version, omitting keys for deleted blocks. This achieves many-block deletion with few erasures.

- **Scrubbing** : Reprograms all 1 bits on a programmed page to 0 without erasing the block. Scrubbing destroys data without requiring compaction, but carries a reliability cost: cell disturbance shifts the threshold voltage of adjacent cells, increasing bit error rates. In 3-D NAND, as many as four adjacent pages can be disturbed[16].

- **Partial scrubbing and down-bit programming** Partial scrubbing modifies a subset of bits to avoid the tell-tale all-zero pattern. Down-bit programming rewrites a TLC page in SLC mode, compacting the data into a single-bit representation and destroying the original multi-bit content[20].

Application Layer

User-level approaches interact only through a POSIX-compliant file-system interface. They are easy to deploy but have the least control over the physical medium:

- **Secure Erase utility (UCSD)** : A user-level application that invokes the hardware controller's secure-erase command, propagating a lower-layer capability to the user interface. Erases the entire device.

- **File-overwriting tools (srm, wipe, shred)**: Open the file from user space, overwrite its contents multiple times with insensitive data (zeros, random patterns), then unlink. These tools fail silently on file systems that do not perform in-place updates, such as journaling or log-structured file systems.

- **Free-space filling tools** Fill all unused blocks of the file system, thereby overwriting any deleted data that still resides in free blocks. Cost is proportional to free space; on flash media, the high wear from filling can be mitigated by perpetually maintaining free space within a target range.
- **Database secure deletion** MySQL and SQLite offer compile-time or run-time options to overwrite deleted records with zeros. However, this relies on the underlying file system to ensure that overwritten data is actually replaced at the physical level — an assumption that does not always hold.
- **Revocable backup system** Encrypts each backup with a unique key, then re-encrypts keys under a temporal master key hierarchy. Backups are deleted by not re-encrypting the corresponding key in the next time interval — the first cryptographic secure-deletion scheme.

Cross-Layer Approaches

These approaches, as described in Chapter 1, bridge the file system and device-driver layers by passing information about deleted blocks downward, enabling efficient sanitization at layers that otherwise lack the semantics to identify deleted data:

- **TRIM (ATA DATA SET MANAGEMENT)** : The file system notifies the SSD controller about logical blocks that no longer store valid data. Originally designed as a performance optimization (to prevent flash thrashing), TRIM gives the controller knowledge of which blocks are discardable. However, TRIM is asynchronous — the OS receives no confirmation of physical erasure — and it provides no mechanism to restrict notification to sensitive blocks only.
- **TrueErase**: Adds a dedicated communication channel between the file system and the device driver. Unlike TRIM, TrueErase only notifies the driver about blocks belonging to files explicitly marked as sensitive, and it triggers immediate sanitization rather than deferring to the controller's scheduler.
- **ZK TRIM (Zombie-Kill)**: Extends TRIM with three modes — normal (defer to garbage collection), immediate (trigger compulsory GC on the TRIM'd blocks), and suspension (delay compulsory GC by a configurable threshold, then enforce it). Immediate mode limits the zombie time but incurs up to 68x higher I/O response latency.

Table 2.2: Secure Deletion Approaches by System Layer

Layer	**Approaches**	**Strengths**	**Limitations**
Physical	Shredding, incineration, degaussing	Unconditional irrecoverability	Full-device only; destroys medium
Controller	ATA/SCSI Secure Erase, block overwriting, multi-pass (Gutmann)	Well-defined hardware interface; works on any block device	No file-level granularity; FTL remapping may foil overwrites
Driver / Block Device	Block device driver, MTD, UBI	Software abstraction; MTD exposes raw flash	No visibility into which blocks hold deleted data
FS (In-Place)	ext2/3 secure deletion, Purgefs, versioning FS crypto (Peterson)	File-aware; balances granularity and control	Requires in-place-update device driver; journaling may preserve data
FS (No In-Place)	Compaction, batched compaction, DNEFS, scrubbing, per-file encryption (Lee)	Works under erase-before-write constraint; encryption amortizes erasures	High cost for compaction; scrubbing causes cell disturbance
User / Application	Secure Erase utility, srm/wipe/shred, free-space filling, DB secure deletion	Easy to deploy; no kernel modification	Silently fails on log-structured / journaling FS; least physical control
Cross-Layer	TRIM, TrueErase, ZK TRIM (Zombie-Kill)	Bridges FS semantics with driver-level sanitization; per-file sensitivity possible	TRIM is asynchronous & unverifiable; ZK TRIM imposes I/O latency

2.2.2 Comparative Evaluation of Secure Deletion Techniques

To compare methods across different layers, a consistent set of evaluation dimensions is required. The following dimensions are derived from the literature and from the technical constraints established in Chapter 1. Each dimension captures a distinct trade-off that system designers and compliance officers must consider.

Layer of Implementation

The layer at which a secure deletion technique operates fundamentally shapes its capabilities, each abstraction layer between the user and the physical medium complicates secure deletion in a different way: the controller may remap LBAs to hide bad blocks, the FTL performs out-of-place updates that preserve old versions, the file system may journal writes that retain stale copies, and the OS cache may hold sensitive data in memory long after the file is unlinked. The choice of layer embodies a fundamental trade-off — lower layers provide the strongest irrecoverability guarantee because no abstraction stands between the deletion action and the storage cells, but they operate at full-device granularity only and cannot identify individual files. Higher layers can pinpoint exactly which data object to remove, but they have the least control over whether the deletion actually reaches the physical medium, making them vulnerable to FTL remapping, journaling, and copy-on-write semantics that silently preserve old data. Understanding the layer at which a given approach operates is therefore the first and most critical step in evaluating whether it can meet a given security requirement.

Deletion Latency

The deletion latency refers to the time from deletion command issuance to data being unrecoverable. Approaches divide broadly into immediate and delayed categories: an immediate approach offers a negligibly small latency, while a delayed approach defers physical erasure to a later garbage collection or compaction cycle. On flash-based storage, this distinction is most visible in the zombie time — the interval between when the FTL marks address mappings as invalid and when garbage collection physically erases the NAND cells. During the zombie time, the data remains fully intact and recoverable through low-level access, even though the file system and the OS consider it deleted.4 The duration of the zombie time is highly workload-dependent: under read-heavy workloads, the free-block pool remains ample and garbage collection may never activate the blocks containing deleted pages, making the zombie time effectively unbounded. Latency is therefore not a fixed property of a deletion mechanism but emerges from the interaction between the mechanism and the device's internal state and workload pattern.

Write Amplification Factor

Write Amplification Factor (WAF) represents the additional writes caused by deletion operations that also reduces the SSD lifespan. NAND flash has a limited program-erase (P/E) cycle budget per block — typically 1,000-10,000 cycles for TLC — and every deletion operation that triggers an erase consumes part of that budget. Three FTL-internal processes compound this: garbage collection copies valid pages from a victim block to a free block before erasing, wear leveling migrates cold data to balance P/E cycles across blocks, and bad-block management relocates data away from failing regions — each migration creates an extra physical write that must be separately sanitized for deletion to be complete. The write amplification factor (WAF) captures this overhead as the ratio of physical writes to logical writes; a WAF of 3 means every logical write causes 3 physical writes on the NAND medium. Aggressive secure deletion policies such as immediate-mode ZK TRIM can increase I/O response latency by 68x on average by forcing compulsory garbage collection on every deletion, though suspension-mode ZK TRIM reduces this penalty by batching deletions within a configurable time window. For scrubbing-based approaches, the disturbance to adjacent cells from each reprogramming pass increases the bit error rate, potentially triggering further read-copy-erase cycles that amplify wear still more.

Crash Consistency

Whether deletion guarantees survive power loss or system crash. In cryptographic secure-deletion schemes, the key state (master key, key-encryption-key hierarchy, or PPRF state) and the on-disk data it protects must remain in sync at all times: if a crash occurs after a key is rotated but before the on-disk key table is updated, the file system is left with encrypted data whose decryption key is permanently lost or, worse, with stale keys that still grant access to supposedly deleted files. ERASER, the prior state-of-the-art, suffers from precisely this problem — after a crash during master-key rotation, laboratory experiments show that up to 64 files may become irrevocably lost or recoverable due to desynchronization between the TPM-hosted key store and the on-disk file-key table. Holepunch resolves this by embedding a journaling scheme in the key-management path: before any puncture or rotation operation, the intended change is written to a dedicated journal region on disk, and if a crash interrupts the operation, the journal is replayed on recovery to bring the key state back to a consistent point. For physical-erasure approaches, crash consistency is less fragile — an interrupted erase leaves the NAND cells in a partially erased state that is at least as secure as before the command — but the metadata describing which blocks were meant to be erased may be lost on power cycle, meaning the system cannot confirm post-crash whether the deletion was completed.

Granularity of Deletion

The size of the smallest data unit that a secure deletion approach can independently target. The SoK taxonomy divides granularity into three categories: per-physical-medium (sanitizes the entire device — useful only for decommissioning, not routine operation), per-file (targets individual files as the deletion unit), and per-data-block (sanitizes at the smallest unit the physical medium offers, such as a sector or NAND page).1 Per-file granularity is the most intuitive for users, but it can be deceptive: long-lived files such as databases or virtual machine images store many distinct data objects within a single file, so deleting the file means deleting everything inside it — an extraordinary measure that is impractical as a routine defense against a disclosure-timing adversary. Conversely, per-data-block granularity provides fine-grained control but introduces its own complications: scrubbing disturbs adjacent cells, the sanitized all-zero pattern is itself detectable by forensic analysis, and approaches that work at the block or erase-unit level must migrate valid colocated data before erasing, incurring write amplification proportional to the valid-data density of the victim block. A related dimension is scope — whether an approach is untargeted (sanitizes all deleted data, guaranteeing no false negatives) or targeted (only sanitizes files explicitly marked as sensitive). Targeted approaches are more efficient but introduce usability risk: users must correctly classify every sensitive file, and a single false negative can leak confidential data. The choice of granularity therefore has cascading effects on performance, wear, forensic detectability, and user error tolerance.

Verifiability Level

Ability to independently confirm that deletion actually occurred. Most deployed schemes provide no verification at all — the host simply trusts the controller's completion signal (e.g., the return value of an ATA Secure Erase command), even though studies have found controllers that report success while leaving the data fully intact. Cryptographic erase is inherently unverifiable at the physical level: discarding a key makes data computationally inaccessible but does not alter the stored ciphertext, so a laboratory adversary with physical access can still recover the encrypted bits and may decrypt them in the future if the encryption is broken or the key is later reconstructed. Ahn and Lee proposed an in-band verification technique for NAND flash that exploits the threshold-voltage distribution of sanitized cells: under normal program conditions, the number of cells in each Vt state is approximately uniform, but after a successful block erase or scrubbing, the distribution shifts to a characteristic non-uniform pattern. A simple read operation can count cells per Vt distribution and compare the result against a manufacturer-set threshold, determining pass or fail without exposing the original personal data. This check requires no changes to existing NAND flash hardware and can be

performed immediately after any deletion operation.17 A higher-assurance variant uses an XOR between known data and the sensed residual from the sanitized area, passing only if the residual falls within the ECC-correctable range — confirming physical destruction to within a small, quantifiable error margin.

Regulatory Alignment

Whether the method meets NIST Purge level or GDPR Article 17 requirements. NIST SP 800-88 Rev. 1 and the newer IEEE 2883-2022 define three sanitization tiers: Clear, Purge and Destroy. Overwriting-based methods on flash are currently categorized as Clear rather than Purge because they are not standardized or vendor-validated for that purpose, while erasure-based methods and cryptographic erase qualify as Purge when implemented correctly.20 GDPR Article 17 does not prescribe specific technical mechanisms but requires that data be rendered irrecoverable across all storage locations, including backups and caches. In practice, this means deletion mechanisms must survive device decommissioning, outsourced cloud storage, and unexpected data duplication by the storage stack — a bar that standard file deletion or TRIM alone cannot meet because neither physically destroys the data nor confirms its destruction. The practical implication is that regulatory compliance demands multi-layer strategies: cryptographic erase for at-rest data, verifiable physical erasure for decommissioned devices, and auditable deletion logs to demonstrate compliance to regulators.

2.2.3 Comparison Matrix

Table 2.3: Comprehensive Comparison of Secure Deletion Approaches for Flash Storage

Approach	**Layer**	**Granularity**	**Deletion Latency**	**WAF**	**Crash Consistency**	**Verifiability**	**Regulatory Alignment**
Overwrite (user-level, shred/dd)	User / OS	File	Seconds to minutes (depends on file size)	High: Full file rewrite + FTL out-of-place update creates additional physical writes	None: No guarantees; power loss during overwrite leaves partial data	Host cannot confirm physical overwrite occurred; FTL may have mapped writes elsewhere	Does not meet NIST Clear, Purge, or Destroy for SSDs

Continued on next page

Table 2.3: Comprehensive Comparison of Secure Deletion Approaches (continued)

Approach	**Layer**	**Granularity**	**Deletion Latency**	**WAF**	**Crash Consistency**	**Verifiability**	**Regulatory Alignment**
Scrubbing (page overwrite)	Device / FTL	Page	390 μs per page	High:Cell disturbance forces valid page migration from adjacent pages; each scrub consumes part of scrub budget; increased BER triggers ECC correction overhead	None: Power loss during scrubbing leaves page in indeterminate Vt state; adjacent cells may be corrupted	Partial: Vt distribution analysis can distinguish scrubbed cells from native zeros ; requires special equipment	No: Not approved by NIST SP 800-88 or IEEE 2883-2022

Continued on next page

Table 2.3: Comprehensive Comparison of Secure Deletion Approaches (continued)

Approach	**Layer**	**Granularity**	**Deletion Latency**	**WAF**	**Crash Consistency**	**Verifiability**	**Regulatory Alignment**
Analog sanitization	Device / FTL	Page	390 μs to 1 ms per page	Low: Reprograms to Vt distribution indistinguishable from native zero; less cell disturbance than scrubbing	None: Power loss during multi-step Vt programming leaves intermediate state	High: Vt distribution statistically indistinguishable from native 0-programmed page; forensic recovery infeasible	No: Not standard-approved; research only
Down-bit programming	Device / FTL	Page (MLC/TLC)	<500 μs per page (single operation)	Very low: TLC→SLC conversion requires one program operation; no erase needed	None: Power loss during mode conversion leaves page in undefined state	Low: Residual Vt distribution may still reveal original data pattern; forensic detection possible	No: Not standard-approved; research only

Continued on next page

Table 2.3: Comprehensive Comparison of Secure Deletion Approaches (continued)

Approach	**Layer**	**Granularity**	**Deletion Latency**	**WAF**	**Crash Consistency**	**Verifiability**	**Regulatory Alignment**
TRIM (standard)	OS → FTL	LBA range (block)	Unbounded (seconds to indefinite – zombie time)	None : TRIM itself adds no writes; GC adds WAF 1.1–3× depending on workload	None: TRIM commands are asynchronous; power loss erases pending TRIM queue; data remains on NAND	None: Host receives no confirmation; controller may ignore TRIM entirely; no way to verify physical erasure	No: Clear level only (NIST SP 800-88); does not guarantee physical removal
ZK-TRIM Immediate	FTL	Block	Bounded by GC execution time (I/O penalty: 68× normal operation)	High: Compulsory garbage collection on every TRIM; forces valid page migration even when free blocks available	None: Power loss during compulsory GC leaves victim block in partially erased state	None: Same as standard TRIM – no confirmation of physical erasure	No: Research only; not deployed in commercial drives

Continued on next page

Table 2.3: Comprehensive Comparison of Secure Deletion Approaches (continued)

Approach	**Layer**	**Granularity**	**Deletion Latency**	**WAF**	**Crash Consistency**	**Verifiability**	**Regulatory Alignment**
ZK-TRIM Suspension	FTL	Block	Bounded	Medium: 60× I/O penalty compared to normal operation; fewer GC events than Immediate mode	None: Power loss during suspension window or GC leaves data recoverable	None: Same as standard TRIM – no confirmation	No: Research only; not deployed
Secure Erase (ATA/ eMMC)	Controller	Block / Device	2.5–8 seconds (device-level)	Medium: Full block erase of every block; no valid page migration needed; one erase cycle per block	None: Power loss during erase leaves some blocks erased, others untouched – inconsistent state	Low: Vendor-dependent; some drives return all-zero reads without physical erase (controller masking) ; no independent verification	Partial: Clear level only (NIST SP 800-88); not Purge

Continued on next page

Table 2.3: Comprehensive Comparison of Secure Deletion Approaches (continued)

Approach	Layer	Granularity	Deletion Latency	WAF	Crash Consistency	Verifiability	Regulatory Alignment
NVMe Sanitize Block Erase	Controller	Device	5–8 seconds (small drive) to tens of minutes (1 TB+)	Medium: One erase cycle per block; no valid page migration needed	None: Power loss during erase leaves device in inconsistent state; NVMe spec defines no recovery semantics	Low: Controller may report success without physical erase (masking); returns all-zero reads as abstraction layer lie	Yes: Purge level (NIST SP 800-88, IEEE 2883-2022)

Continued on next page

Table 2.3: Comprehensive Comparison of Secure Deletion Approaches (continued)

Approach	**Layer**	**Granularity**	**Deletion Latency**	**WAF**	**Crash Consistency**	**Verifiability**	**Regulatory Alignment**
NVMe Sanitize Crypto Erase (key discard)	Controller	Device	0.22 seconds (capacity-independent)	None: No NAND write operations; only key register overwritten	Vulnerable: Power loss during key register write leaves old key partially overwritten; undefined behavior; no recovery spec	None: Host receives completion status but cannot confirm key was destroyed; controller may preserve key in debug area or retired key table	Yes: Purge level (NIST SP 800-88, IEEE 2883-2022)

Continued on next page

Table 2.3: Comprehensive Comparison of Secure Deletion Approaches (continued)

Approach	**Layer**	**Granularity**	**Deletion Latency**	**WAF**	**Crash Consistency**	**Verifiability**	**Regulatory Alignment**
NVMe Sanitize Crypto Erase (full re-encryption)	Controller	Device	Minutes to hours (capacity-dependent)	High: Rewrites every user block (decrypt with old MEK, encrypt with new MEK, write back)	Vulnerable: Power loss during re-encryption leaves some blocks with old key, some with new key – data may be partially unrecoverable or corrupt	Low: Host sees completion but cannot verify each block was re-encrypted; controller may skip blocks	Yes: Purge level (vendor-dependent implementation)

Continued on next page

Table 2.3: Comprehensive Comparison of Secure Deletion Approaches (continued)

Approach	**Layer**	**Granularity**	**Deletion Latency**	**WAF**	**Crash Consistency**	**Verifiability**	**Regulatory Alignment**
Cryptographic Erasure (per-block key)	OS / FS	Block / File	Milliseconds (key deletion only)	None: Key deletion only; no NAND writes	None: Power loss during key table update leaves key references inconsistent	None: No mechanism to confirm key was destroyed; key may remain in memory or swap	Yes: Purge level if key destruction is verifiable (assumption only)

Continued on next page

Table 2.3: Comprehensive Comparison of Secure Deletion Approaches (continued)

Approach	**Layer**	**Granularity**	**Deletion Latency**	**WAF**	**Crash Consistency**	**Verifiability**	**Regulatory Alignment**
Eraser (tree-based CE)	Block device / Kernel	File	<1 second (branch revocation)	None: Key operations only; no additional NAND writes beyond metadata	Weak: TPM desync on crash; post-crash experiments show up to 64 files lost when master key rotation desynchronizes from on-disk file key table	None: TPM black box; host cannot confirm master key was revoked; no audit trail	Partial: Meets Purge cryptographically but crash vulnerability creates compliance risk under GDPR Article 17

Continued on next page

Table 2.3: Comprehensive Comparison of Secure Deletion Approaches (continued)

Approach	**Layer**	**Granularity**	**Deletion Latency**	**WAF**	**Crash Consistency**	**Verifiability**	**Regulatory Alignment**
Holepunch (PPRF-based CE)	Block device / Kernel	File	0.22 seconds (puncture operation)	None: No per-file key storage; puncture modifies only master PPRF key; no additional writes beyond journal	Strong: Journaled puncture scheme; crash-consistent – on recovery, journal replays pending punctures; no file loss or undeleted files	None: Same as Eraser – host cannot verify puncture occurred; TPM black box	Yes: Purge level + crash safe; strongest regulatory alignment among file-level CE

Continued on next page

Table 2.3: Comprehensive Comparison of Secure Deletion Approaches (continued)

Approach	**Layer**	**Granularity**	**Deletion Latency**	**WAF**	**Crash Consistency**	**Verifiability**	**Regulatory Alignment**
TrueErase (cross-layer)	FS + Driver	File	Fast (immediate at driver notification)	Low: Selective notification; only sensitive files trigger immediate actions; no blanket TRIM	None: Power loss during driver notification leaves file in indeterminate state	None: No verification mechanism proposed	Partial: No standard approval; cross-layer approach not recognized by NIST
SAFE (controller-level)	Controller	Device	Slow (multi-step: key erase + block erase + pattern write + re-erase)	High: Triple erase	Limited: Power loss during multi-step sequence leaves device inconsistent; verification pattern may be partially written	Medium: Verification pattern written and checked; controller can attest completion; host can read pattern to confirm	Yes: Purge level + verifiable; but device-only

Continued on next page

Table 2.3: Comprehensive Comparison of Secure Deletion Approaches (continued)

Approach	**Layer**	**Granularity**	**Deletion Latency**	**WAF**	**Crash Consistency**	**Verifiability**	**Regulatory Alignment**
RedFlash (OOB duplicate chain)	FTL / Controller	Page / Block	Medium (chain traversal + erase; no specific benchmark)	Medium: Additional OOB writes to maintain duplicate chain; each write adds metadata	None: Power loss during chain update leaves duplicates untracked; OOB metadata may be corrupted	None: No verification mechanism; depends on correct chain traversal	No: Research only; not deployed
Secure Copy-Back	FTL / Controller	Page	Low (single program operation)	Low: No extra erase; programs source page with random data or deletion pulses	None: Power loss during source page programming leaves partial destruction	None: No verification that source page was actually sanitized	No: Research only; not deployed

Continued on next page

Table 2.3: Comprehensive Comparison of Secure Deletion Approaches (continued)

Approach	**Layer**	**Granularity**	**Deletion Latency**	**WAF**	**Crash Consistency**	**Verifiability**	**Regulatory Alignment**
SAS Deletion (scrub-aware)	FTL / Controller	Page / Block	Optimized: 82% reduction in scrubbing latency (70 µs per page)	Controlled: Scrub budget limits total scrubs per block; valid page migration when budget exceeded	None: Same as scrubbing – power loss leaves indeterminate state	Medium: Cell-count verification possible; Vt distribution analysis	No: Research only; not standard-approved
Physical destruction	Physical	Device	Permanent (seconds to minutes, irreversible)	N/A: Device destroyed; no further writes possible	N/A: Device non-operational after destruction	High: Physical inspection can confirm destruction (e.g., crushed, shredded, incinerated)	Yes: Destroy level (NIST SP 800-88, IEEE 2883-2022)

2.3 Synthesized Observations from the Literature

The secure deletion literature spans a wide range of approaches and evaluation methods, reading across the literature reveals patterns and several persistent challenges in secure deletion techniques, particularly in modern storage environments.

Layer Seperation Problem :

Secure deletion in a modern storage system is fundamentally complicated by the layered architecture through which data passes. Each layer - application, file system, block device, controller (FTL), and physical medium – provides its own interface to the layer above and introduces its own abstraction over the layer below. At the physical layer one can ensure true irrecoverability, but at the user layer one can easily identify which data object to delete. The two capabilities never coincide at the same layer. The FTL abstracts NAND flash behind a standard block-device interface so that traditional file systems remain compatible, but this same abstraction hides the physical state of data from the host. When raw flash is accessed directly, a different controller interface is exposed; when accessed through an FTL, overwriting a logical block does not replace its physical content – it creates two versions, one of which persists.

Secure deletion implemented at any single layer is systematically incomplete. Performing secure deletion in one layer cannot eliminate data because leakage may persist in the other layers. There is no one ideal layer for secure deletion because the criteria are in tension. Low-layer approaches (controller-level block erasure) require fewer assumptions about the interface's behavior and provide physical irrecoverability, but cannot select individual data objects for deletion. High-layer approaches (file-system-level or cryptographic erasure) let users clearly mark which data to delete, but must trust that the layers beneath faithfully execute the instruction. This is not an implementation bug; it is a structural property of layered storage architectures, and no single-layer solution can close it.

Verifiability Crisis :

After performing a secure deletion operation, there is currently no reliable, independent, and non-destructive way to confirm that the data has been physically destroyed. This is the verifiability crisis, and it cuts across every approach category. Cryptographic erasure is inherently opaque. When a key is deleted from a TPM or key store, the storage device may return zeroed data at the abstraction layer, but this does not confirm that the underlying physical cells have been sanitized or even that the key has actually been removed. TPMs are themselves black boxes with limited externally accessible mechanisms to confirm key deletion independently. Because the binding between key revocation and physical inaccessibility is mediated entirely by the encryption scheme, verification collapses to trusting that the key was truly erased, no copies of the key exist elsewhere, and no side-channel or future cryptanalytic advance can recover the plaintext. None of these are independently

verifiable after the fact.

Physical erasure has the opposite profile. A block-erase command physically removes charge from NAND cells. In principle this is verifiable through electrical inspection of Vt distributions, but practical verification at scale remains expensive, destructive, and vendor-dependent. Scrubbing provides page-level erasure but introduces disturbance effects that complicate assessment of whether complete data removal was achieved. The irony is that the approaches with the strongest physical guarantees have the weakest practical verification paths.

Standards such as NIST SP 800-88 Rev. 1 and IEEE 2883-2022 define sanitization levels - Clear, Purge, and Destroy - that require "demonstrable and verifiable data removal evidence" at each level. Yet no deployed technique today can independently demonstrate that a Purge-level operation on an SSD has succeeded without destructive physical inspection. The crisis is not merely technical: regulatory mandates for demonstrable deletion exist, but the technical means to satisfy them do not, creating a gap between legal obligation and practical verification.

Performance-latency Trade-offs :

Secure deletion oscillates between two poles: immediate guarantees with severe performance cost, or deferred guarantees with unbounded latency. This tension is structurally embedded in how flash storage manages physical erasure. After the FTL invalidates a file's address mapping, the physical data on the NAND cells remains intact until garbage collection erases the containing block. The zombie time is the core latency parameter of any erasure-based scheme. Its duration is not fixed: it depends on write pressure, over-provisioning ratios, FTL victim selection policy, and whether TRIM was issued.

The trade-off extends beyond GC to the approach category itself. Delayed approaches reduce wear and I/O overhead but introduce a fixed worst-case upper bound on deletion latency that may be minutes, hours, or longer. Purging and ballooning techniques address this by deliberately filling the device with junk data to force GC, but the erasing time scales with device capacity and write speed. Performance overhead is not limited to erasure-based methods, even scrubbing incurs a performance decrease due to overhead. Every performance-enhancing mechanism inside SSDs is counterproductive to secure deletion guarantees.The pattern is clear: at one end, cryptographic erasure achieves sub-second deletion latency regardless of device usage but provides no physical guarantee. At the other end, immediate-mode compulsory GC provides bounded physical erasure but at a 68x I/O penalty. There is currently no technique that achieves both bounded physical erasure and negligible performance cost on commodity hardware.

Shifting Trust, Not Eliminating It :

Cryptographic erasure is often presented as a clean solution, delete the key, and the encrypted data becomes irrecoverable. The literature reveals that this framing obscures multiple layers of trust that cryptographic erasure merely relocates rather

than removes. Every secure deletion approach relies on a trust model, an assumption about which components behave correctly and can be observed. Cryptographic erasure replaces trust in the physical storage medium with trust in a cryptographic key store. This is a favorable trade for most deployment contexts, but it is a shift of trust, not its removal. The approach that is strong on security guarantees is simultaneously weak on verifiability. It assumes that encrypted data, once the key is destroyed, is computationally irrecoverable. This is a forward-looking assumption that depends on the encryption algorithm remaining secure against future cryptanalytic advances. For long-term confidentiality requirements, this is a significant assumption that physical erasure does not require. FTL operations create duplicate copies of data at the physical level, the same problem applies at the key management level: if duplicate copies of encryption keys exist in journal files, crash recovery logs, or backup metadata, cryptographic erasure fails silently because the attacker can recover the key from a copy the OS does not know exists. Verifying that all key copies have been eliminated requires the same kind of system-wide visibility that physical erasure struggles with.

Absence of Crash Consistency in Regulatory Frameworks : The patterns across above discussed systems reveals a structural principle: the crash consistency of a secure deletion system is determined by whether key metadata and data metadata share the same durability domain. When key state is maintained in a separate trusted component (TPM) while data metadata is on disk, the interface between them becomes the consistency bottleneck. Any system that crosses durability domains must explicitly address this interface or accept the crash consistency gap. The GDPR right to erasure (Article 17), the CCPA's right to deletion, and standards including NIST SP 800-88 Rev. 1 and IEEE 2883-2022 mandate timely, demonstrable data removal at defined sanitization levels. None of these frameworks describe any requirement for crash-consistent deletion. They specify what must be deleted and at what assurance level, but they are silent on what happens when the deletion process itself is interrupted by a power failure or system fault. A system could be fully compliant with every regulatory sanitization mandate and still leave data in an inconsistent, partially recoverable state after a crash during deletion.

Large cloud providers describe deletion as an iterative process requiring up to 180 days due to data replication and backup cycles, far exceeding the timelines implied by GDPR Article 17. At that scale, crash events during the deletion window are a statistical certainty rather than a corner case. Regulatory standards that specify a deletion outcome but not the reliability of the deletion process create a dangerous gap: a provider can certify compliance based on policy while the technical mechanism silently fails under crash conditions. Shastri et al.'s identification of six GDPR anti-patterns in cloud-scale systems – storing data without clear deletion timelines, reusing data indiscriminately, and risk-agnostic data processing – reinforces that achieving regulatory compliance requires systemic

architectural changes, not point solutions. Crash consistency is a prime example of a systemic architectural requirement that regulation has not yet addressed.

2.4 Empirical Evaluation Approaches in the Literature

Experimental evaluations in the literature vary widely in methodology. Reardon et al. conducted controlled tests examining block-unaligned truncations and sparse files across multiple file systems to evaluate practical secure deletion approaches [1]. Aronsson and Lund performed timing measurements of block erase and cryptographic erase on commercial SSDs (SN7100 and SN850X), revealing vendor-specific inconsistencies and the need for device-independent verification methods [2]. Wang et al. compared encryption-based, overwriting-based, and erasure-based methods across storage technologies, categorizing trade-offs in security guarantees, performance overhead, and practical feasibility [26]. The scrubbing-aware design by Wang et al. (2018) used a flash-memory simulator to evaluate deletion efficiency, achieving 82% average response time reduction through optimized allocation of sensitive data [16].

The key methodological gap across these studies is the absence of a standardized, reproducible evaluation framework. Experiments are conducted on specific hardware with vendor-specific firmware behavior, making cross-study comparisons unreliable. There is no agreed set of metrics for measuring deletion effectiveness, performance impact, or verifiability.

2.5 Legal and Ethical Dimensions

2.5.1 GDPR and the Right to Erasure

The General Data Protection Regulation (GDPR), effective May 2018, introduces the right to erasure (Article 17) as a foundational data protection obligation that directly intersects with secure deletion. Politou et al. (2018) provide a comprehensive analysis of these provisions, noting that the right encompasses both the erasure of personal data and the broader right to be forgotten, requiring deletion from all possible sources in which the data resides, including third-party controllers to whom the data has been disseminated [27]. The GDPR introduces the withdrawal of consent as a trigger for erasure, a condition not present in prior data protection frameworks, and obligates controllers to take reasonable steps, including technical measures, to inform other controllers processing the data of the erasure request. Politou et al. argue that enforcement is feasible provided that

implementation guidelines and low-level business specifications are put in place in a clear, cross-platform manner [27].

Shastri et al. (2019) identify six GDPR anti-patterns arising from the design and operation of modern cloud-scale systems: storing data without a clear timeline for deletion, reusing data indiscriminately, creating walled gardens and black markets, risk-agnostic data processing, hiding data breaches, and making unexplainable decisions [28]. They highlight that Articles 5 and 13 of the GDPR require controllers to specify retention periods at the point of collection and to ensure personal data is deleted when no longer necessary for the purpose for which it was collected. In practice, large cloud providers describe deletion as an iterative process that can take up to 180 days due to data replication and backup cycles far exceeding the timeline implied by the regulation.

The GDPR does not, however, define what constitutes full deletion or erasure at a technical level, leaving a significant gap between legal requirements and technical implementation [29]. The regulation requires that controllers take reasonable steps to inform other controllers of erasure requests [30], creating an obligation without specifying the means by which compliance is to be achieved. Legal analysis of the landmark Google Spain case further illustrates the territorial and procedural complexity of deletion obligations, where search engine operators were held responsible as data controllers for processing personal data linked through search results [29].

2.5.2 Technical Challenges to the Right to Be Forgotten

The tension between the right to be forgotten and technical system design is a recurring theme in the literature. Visconti (2024) examines the Right to Be Forgotten (RtBF) through a cryptographic lens, identifying challenges such as the avalanche effect, where removing a single piece of personal data creates inconsistencies in correlated data stored on a digital platform [31]. Traditional cryptographic tools are insufficient to enforce GDPR compliance, and the gap between the language of the regulation and the technical specifications required by developers is wide enough to introduce significant uncertainty. Visconti shows that zero-knowledge (ZK) proofs can bridge this gap by allowing digital platforms to prove compliance with deletion requests without revealing the underlying personal data, and proposes an assessment scheme applicable to use cases including machine unlearning and redactable blockchains [31].

At the standards level, Aronsson and Lund (2023) review NIST SP 800-88, IEEE 2883-2022, and NATO AEDP-3, all of which structure deletion methods by security level. These standards categorize sanitization into Clear and Purge levels, where Purge renders data infeasible to recover through block erase or cryptographic erase, and Destruct covers physical destruction [2]. Overwriting methods such as

scrubbing are not regulation-approved, which limits their practical applicability despite promising performance and security characteristics.

2.5.3 Digital Evidence and Cross-Border Procedure

The handling of digital evidence across borders intersects directly with secure deletion obligations. Casino et al. (2022), in their systematization of digital forensics research, identify that one of the most reported challenges across the field is the lack of jurisdictional and legal requirements for different investigation scenarios, particularly regarding ethics and data management of confidential and personal data [32]. Distributed systems such as cloud and blockchain mean that software and data may reside in different countries, requiring specific cross-border collaborations. A proper understanding between all actors involved, including stakeholders, law enforcement agencies, and court members, is mandatory to ensure successful prosecution, with the chain of custody remaining a persistent challenge [32].

Ontanu (2023) examines the normative framework for electronic evidence in EU civil procedure, finding that while regulations such as the GDPR, eIDAS, and the revised Taking of Evidence Regulation address some aspects, there is little guidance on metadata, technical standards, or requirements for electronic evidence [33]. The evaluation of electronic evidence is left to domestic legislation under principles of procedural autonomy, leaving significant uncertainty about how deletion obligations apply to evidentiary materials across member states. Allah Rakha (2024) addresses jurisdiction and governance in the global digital economy, arguing that ambiguous jurisdiction enables large platforms to circumvent laws while prescriptive control risks stifling innovation, and calls for cooperative solutions aligned to collective rights and welfare [34].

2.5.4 Comparative Regulatory Landscape

Birrell et al. (2024) provide the broadest cross-jurisdictional analysis, examining 25 Internet privacy and data protection regulations from around the world and developing a taxonomy of rights and obligations. Their work systematizes 270 technical research papers, finding that the overwhelming majority study either the GDPR or the CCPA, laws protecting approximately 6.3% of the world's population, while other aspects such as the right to non-discrimination remain largely unexplored [35]. They identify significant technical challenges to implementing the right to delete, including the difficulty of deleting all replicas of data across distributed data centers, backups, and offline copies, with some systems taking months to complete deletion. The right to erasure under GDPR is the most widely known of the self-management rights, yet users are often not aware of or do not use deletion

controls due to difficulties locating them or encountering dark patterns [35].

Beyond the GDPR, the California Consumer Privacy Act (CCPA) similarly confers a right to deletion, and sectoral laws such as Sarbanes-Oxley mandate retention periods after which secure deletion becomes necessary to limit liability [29]. The technical literature contextualizes these frameworks directly: the Holepunch system explicitly frames secure deletion via cryptographic erasure as a promising mechanism for enforcing GDPR-style regulations, provided that challenges involving key management, performance, and crash consistency can be solved [25].

Bridging Technical and Legal Perspectives

The literature reveals both alignment and tension between the technical capabilities of secure deletion and the legal requirements imposed by data protection regulations.

On the alignment side, cryptographic erasure offers a technically mature approach that maps well to regulatory requirements. The ability to render data irrecoverable through key deletion, independent of the underlying storage medium, provides a mechanism that can satisfy right-to-erasure obligations across diverse technical environments [1]. The key management architectures developed in systems such as Eraser, DNEFS, and Holepunch demonstrate that file-granularity deletion is achievable with acceptable performance overhead [25].

On the tension side, regulatory mandates require timely and demonstrable deletion, but technical constraints often prevent this. Large cloud providers describe deletion as an iterative process that can take up to 180 days due to data replication and backup cycles [35], far exceeding the timelines implied by Article 17 of the GDPR. The six GDPR anti-patterns identified by Shastri et al. (2019) in cloud-scale systems — storing data without clear deletion timelines, reusing data indiscriminately, and risk-agnostic data processing, among others — suggest that achieving regulatory compliance requires systemic architectural changes rather than point solutions [28].

The gap between legal language and technical specification remains a central challenge. Visconti (2024) demonstrates that the gap between the language of the GDPR and the technical specifications required by developers is wide enough to introduce significant uncertainty, and proposes zero-knowledge proofs as a bridge [31]. Cross-border procedure adds further complexity, as Casino et al. (2022) note that distributed systems mean software and data may reside in different countries, requiring specific cross-border collaborations that existing deletion frameworks do not adequately address [32]. Standardized evaluation frameworks such as NIST SP 800-88 Rev. 1 and IEEE 2883-2022 provide operational definitions for sanitization levels but remain limited by their focus on traditional storage media [2], leaving emerging contexts such as containers, cloud storage, and AI systems without clear compliance guidance.

2.6 Summary and Identified Research Gaps

Secure deletion in modern digital environments is a multi-layered problem spanning storage architecture, cryptographic key management, regulatory compliance, and empirical verification. The literature has produced a rich taxonomy of techniques overwriting, encryption-based, erasure-based, and integrated approaches each with distinct trade-offs. However, the absence of a standardized experimental framework for evaluating these techniques across diverse storage platforms limits both academic progress and practical deployment. An experimental framework that defines consistent metrics, covers a representative range of modern storage devices, incorporates verification protocols, and aligns with regulatory standards would address a critical gap in the current state of the art.

Gaps and Directions for an Experimental Framework

The literature consistently identifies several gaps that motivate an experimental framework for evaluating secure deletion techniques.

Broader device coverage. Existing studies test only a handful of SSD models and manufacturers. Given the significant variability in FTL implementation across vendors, broader testing is essential for generalizable conclusions [2]

Standardized metrics. The absence of standardized evaluation criteria for deletion effectiveness, performance overhead, and verifiability prevents meaningful comparisons between techniques. A framework should define measurable outcomes including residual data recoverability, deletion latency, write amplification, and device wear.

Verification protocols. Cryptographic erasure requires protocols that can independently verify key deletion rather than relying on opaque TPM or SSD controller attestations. Research into verifiable deletion, including cell-count-based verification techniques, points toward practical verification mechanisms [15].

Alignment with regulatory standards. Future frameworks should align experimental evaluation with regulatory requirements NIST SP 800-88 Purge level, IEEE 2883-2022 to ensure that laboratory testing directly demonstrates compliance readiness [2].

Chapter 3

Experimental Framework and Methodology

This chapter details the proposed experimental framework for evaluating secure deletion techniques in modern digital environments. The methodology is designed to bridge the gap between theoretical system-layer taxonomies and empirical forensic verification, specifically addressing the architectural complexities of NAND flash storage. The primary aim of this research is to develop and validate an experimental framework for evaluating secure deletion techniques. Due to the abstraction layers introduced by file systems, flash translation layers (FTLs), and storage controllers, direct verification of deletion operations is often impossible from the host perspective. Therefore, this work focuses on measurable and observable indicators of deletion effectiveness, performance, and recoverability.

3.1 Research Objectives

The aim of this thesis is to develop an experimental framework to evaluate the effectiveness, performance, and practical limitations of secure deletion techniques in modern storage environments. Although many secure deletion mechanisms have been proposed in the literature, their behavior in real-world systems is difficult to verify because of the abstraction layers introduced by file systems, flash translation layers (FTLs), and storage controllers. This work therefore focuses on outcomes that are observable and measurable from the host perspective.

The objectives of this study are:

1. To evaluate the effectiveness of different secure deletion techniques in preventing post-deletion data recovery.

2. To investigate how long deleted data persists after TRIM and sanitization operations, and to assess the practical implications of data remanence.

3. To compare the latency characteristics and variability of secure deletion mechanisms, including TRIM, block erase, and cryptographic erase operations.

4. To examine how filesystem and storage-layer behavior, such as journaling and FTL remapping, influences the effectiveness of secure deletion.

5. To analyse differences in secure deletion behavior across consumer and enterprise storage devices.

6. To identify the practical limitations of host-side verification and establish a methodology for evaluating secure deletion techniques under realistic operating conditions.

3.1.1 Research Questions

To achieve these objectives, the following research questions are investigated:

RQ1: To what extent do different secure deletion techniques prevent the recovery of previously stored data from a host-side forensic perspective?

RQ2: How does the recoverability of deleted data change over time following TRIM and sanitization operations?

RQ3: What are the latency characteristics and performance variability of TRIM, block erase, and cryptographic erase operations across different storage devices?

RQ4: How do filesystem mechanisms and flash translation layer behavior affect the effectiveness of secure deletion techniques?

RQ5: How does secure deletion behavior vary across different SSD implementations and vendors?

RQ6: What are the practical limitations of verifying secure deletion from the host side, and how can these limitations be incorporated into an experimental evaluation framework?

3.2 Experimental Environment

3.3 Analysis Methodology

3.4 Experiments and Results

3.5 Evaluation Metrics

3.6 Statistical Analysis Methods

Chapter 4

Experimental Results and Analysis

Chapter 5

Interpretation of Findings and Implications

Chapter 6

Conclusions and Future Work

Appendix A

Appendix A

Bibliography

[1] Joel Reardon, David Basin, and Srdjan Čapkun. «SoK: Secure Data Deletion». In: *Proceedings of the 2013 IEEE Symposium on Security and Privacy (SP'13)*. San Francisco, CA, USA: IEEE, 2013, pp. 301–315. DOI: 10.1109/SP.2013.28 (cit. on pp. 1, 7, 18, 20, 21, 47, 50).

[2] Fabian Aronsson and Oskar Lund. «Secure Data Deletion: Ensuring Confidentiality in Digital Systems ; A Survey of Methods for Data Erasure». LIU-IDA/LITH-EX-A–2025/074–SE. Master's thesis. Linköping, Sweden: Linköping University, 2025. URL: http://www.ep.liu.se/ (cit. on pp. 1, 3–6, 8, 12, 13, 15, 17, 18, 47, 48, 50, 51).

[3] Paul Roberts. «MIT: Discarded hard drives yield private info». In: *Computerworld* (Jan. 2003). From IDG News Service. URL: https://www.computerworld.com/article/1334164/mit-discarded-hard-drives-yield-private-info.html (cit. on pp. 1, 2).

[4] NetGuardia. *Your "deleted" data isn't deleted. It's just inconvenient to find.* NetGuardia. May 2026. URL: https://netguardia.com/privacy/data-protection/your-deleted-data-isnt-deleted-its-just-inconvenient-to-find/ (cit. on p. 2).

[5] Verizon Business. *2024 Data Breach Investigations Report*. Annual Report. Verizon, 2024. URL: https://www.verizon.com/business/resources/reports/2024-dbir-data-breach-investigations-report.pdf (cit. on p. 2).

[6] Blancco Technology Group. *2026 State of Data Sanitization Report: Enterprise Security Anxiety*. Industry report. Blancco, May 2026. URL: https://blancco.com/resources/rs-data-sanitization-report/ (cit. on p. 2).

[7] Compliance Hub. «When Redactions Un-Redact Themselves: The Cornwall Council GDPR Breach Explained». In: *Compliance Hub Wiki* (Mar. 2026). URL: https://compliancehub.wiki/uk-council-gdpr-redaction-fail-2026/ (cit. on p. 2).

[8] Dan Goodin. «$35M fine for Morgan Stanley after unencrypted, unwiped hard drives are auctioned». In: *Ars Technica* (Sept. 2022). URL: https://arstechnica.com/information-technology/2022/09/morgan-stanley-pays-35m-penalty-for-extensive-failure-to-safeguard-customer-data/ (cit. on p. 2).

[9] U.S. Securities and Exchange Commission. *Morgan Stanley Smith Barney to Pay $35 Million for Extensive Failures to Safeguard Personal Information of Millions of Customers*. SEC Press Release No. 2022-168. Sept. 2022. URL: https://www.sec.gov/newsroom/press-releases/2022-168 (cit. on p. 2).

[10] Cybersecurity Dive. «Morgan Stanley fined $35M by SEC over improper data disposal». In: *Cybersecurity Dive* (Sept. 2022). URL: https://www.cybersecuritydive.com/news/morgan-stanley-fine-sec-customer-data-disposal/632254/ (cit. on p. 2).

[11] Omar A. Homaidi. «Data Remanence: Secure Deletion of Data in SSDs». Bachelor's thesis. Blekinge Institute of Technology, 2009. URL: https://urn.kb.se/resolve?urn=urn:nbn:se:bth-5165 (cit. on pp. 3, 5).

[12] Niusen Chen and Bo Chen. «Duplicates also Matter! Towards Secure Deletion on Flash-based Storage Media by Removing Duplicates». In: *Proceedings of the 2022 ACM on Asia Conference on Computer and Communications Security*. ASIA CCS '22. Nagasaki, Japan: Association for Computing Machinery, 2022, pp. 54–66. ISBN: 9781450391405. DOI: 10.1145/3488932.3523255. URL: https://doi.org/10.1145/3488932.3523255 (cit. on pp. 3–5, 8, 11–13).

[13] Kaan Onarlioglu, William Robertson, and Engin Kirda. «Eraser: Your Data Won't Be Back». In: 2018. DOI: 10.1109/EuroSP.2018.00019 (cit. on pp. 4, 9, 11).

[14] Qi Zhang, Siqi Jia, Bo Chang, Yan Chen, and Zheli Liu. «Ensuring data confidentiality via plausibly deniable encryption and secure deletion - a survey». In: *Cybersecurity* 1.1 (2018), p. 1. DOI: 10.1186/s42400-018-0005-8. URL: https://doi.org/10.1186/s42400-018-0005-8 (cit. on pp. 4–6, 13, 18).

[15] Na Young Ahn and Dong Hoon Lee. «Forensics and Anti-Forensics of a NAND Flash Memory: From a Copy-Back Program Perspective». In: *IEEE Access* 9 (2021), pp. 14130–14137. DOI: 10.1109/ACCESS.2021.3052353 (cit. on pp. 5, 11–13, 51).

[16] Wei-Chen Wang, Chien-Chung Ho, Yuan-Hao Chang, Tei-Wei Kuo, and Ping-Hsien Lin. «Scrubbing-Aware Secure Deletion for 3-D NAND Flash». In: *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems* 37.11 (2018), pp. 2790–2801. DOI: 10.1109/TCAD.2018.2857260 (cit. on pp. 6, 23, 47).

[17] Jaewook Kwak, Hyung Chan Kim, Il Hwan Park, and Yong Ho Song. «Anti-forensic deletion scheme for flash storage systems». In: *2016 IEEE International Conference on Network Infrastructure and Digital Content (IC-NIDC)*. IEEE, 2016, pp. 317–321. DOI: 10.1109/ICNIDC.2016.7974588. URL: https://doi.org/10.1109/ICNIDC.2016.7974588 (cit. on pp. 6, 8–10, 13).

[18] Aya Fukami, Francesco Regazzoni, and Zeno Geradts. «Data Sanitization on eMMCs». In: *Proceedings of the 28th Asia and South Pacific Design Automation Conference*. ASPDAC '23. Tokyo, Japan: Association for Computing Machinery, 2023, pp. 455–460. ISBN: 9781450397834. DOI: 10.1145/3566097.3568349. URL: https://doi.org/10.1145/3566097.3568349 (cit. on p. 6).

[19] Na Young Ahn and Dong Hoon Lee. «Security of IoT Device: Perspective Forensic/Anti-Forensic Issues on Invalid Area of NAND Flash Memory». In: *IEEE Access* 10 (2022), pp. 74207–74219. DOI: 10.1109/ACCESS.2022.3190957 (cit. on pp. 6, 7).

[20] Na-Young Ahn and Dong Hoon Lee. «Schemes for Privacy Data Destruction in a NAND Flash Memory». In: *IEEE Access* 7 (2019), pp. 181305–181313. DOI: 10.1109/ACCESS.2019.2958628 (cit. on pp. 7, 23).

[21] Alastair Nisbet and Rijo Jacob. «TRIM, Wear Levelling and Garbage Collection on Solid State Drives: A Prediction Model for Forensic Investigators». In: *2019 18th IEEE International Conference On Trust, Security And Privacy In Computing And Communications/13th IEEE International Conference On Big Data Science And Engineering (TrustCom/BigDataSE)*. 2019, pp. 419–426. DOI: 10.1109/TrustCom/BigDataSE.2019.00063 (cit. on pp. 7, 11).

[22] Gabriele Bonetti, Marco Viglione, Alessandro Frossi, Federico Maggi, and Stefano Zanero. «Black-box forensic and antiforensic characteristics of solid-state drives». In: *Journal of Computer Virology and Hacking Techniques* 10.4 (Aug. 2014), pp. 255–271. DOI: 10.1007/s11416-014-0221-z. URL: https://link.springer.com/article/10.1007/s11416-014-0221-z (cit. on p. 11).

[23] Rafael González Arias, Javier Bermejo Higuera, J. Javier Rainer Granados, Juan Ramón Bermejo Higuera, and Juan Antonio Sicilia Montalvo. «Systematic Review: Anti-Forensic Computer Techniques». In: *Applied Sciences* 14.12 (2024). ISSN: 2076-3417. DOI: 10.3390/app14125302. URL: https://www.mdpi.com/2076-3417/14/12/5302 (cit. on p. 20).

[24] Zachary N. J. Peterson, Randal Burns, Joe Herring, Adam Stubblefield, and Aviel D. Rubin. «Secure Deletion for a Versioning File System». In: *Proceedings of the 4th USENIX Conference on File and Storage Technologies (FAST '05)*. San Francisco, CA, 2005.

[25] Zachary Ratliff, Wittmann Goh, Abe Wieland, James Mickens, and Ryan Williams. *Holepunch: Fast, Secure File Deletion with Crash Consistency*. Cryptology ePrint Archive, Paper 2023/1927. 2023. URL: https://eprint.iacr.org/2023/1927 (cit. on pp. 18, 50).

[26] Wei-Chen Wang, Chien-Chung Ho, Yu-Ming Chang, and Yuan-Hao Chang. «Challenges and Designs for Secure Deletion in Storage Systems». In: *2020 Indo - Taiwan 2nd International Conference on Computing, Analytics and Networks (Indo-Taiwan ICAN)*. 2020, pp. 181–189. DOI: 10.1109/Indo-TaiwanICAN48429.2020.9181335 (cit. on pp. 17, 47).

[27] Eugenia Politou, Efthimios Alepis, and Constantinos Patsakis. «Forgetting personal data and revoking consent under the GDPR: Challenges and proposed solutions». In: *Journal of Cybersecurity* 4.1 (2018). DOI: 10.1093/cybsec/tyy001 (cit. on pp. 47, 48).

[28] Supreeth Shastri, Melissa Wasserman, and Vijay Chidambaram. «GDPR Anti-Patterns: How Design and Operation of Modern Cloud-Scale Systems Conflict with GDPR». In: *ACM SIGOPS Operating Systems Review* 54.2 (2020), pp. 1–7. DOI: 10.1145/3445039.3445040 (cit. on pp. 48, 50).

[29] Tiffany C. Li. «Algorithmic Destruction». In: *SMU Law Review* 75 (3 2022), p. 479. URL: https://scholar.smu.edu/smulr/vol75/iss3/7 (cit. on pp. 48, 50).

[30] I. van Ooijen and Helena U. Vrabec. «Does the GDPR Enhance Consumers' Control over Personal Data? An Analysis from a Behavioural Perspective». In: *Journal of Consumer Policy* 42 (2019), pp. 91–107. DOI: 10.1007/s10603-018-9399-7. URL: https://doi.org/10.1007/s10603-018-9399-7 (cit. on p. 48).

[31] Ivan Visconti. «The Right to Be Zero-Knowledge Forgotten». In: *Proceedings of the 19th International Conference on Availability, Reliability and Security*. ARES 24. Vienna, Austria: Association for Computing Machinery, 2024. ISBN: 9798400717185. DOI: 10.1145/3664476.3669973. URL: https://doi.org/10.1145/3664476.3669973 (cit. on pp. 48, 50).

[32] Fran Casino, Thomas K. Dasaklis, Georgios P. Spathoulas, Marios Anagnostopoulos, Amrita Ghosal, István Böröcz, Agusti Solanas, Mauro Conti, and Constantinos Patsakis. «Research Trends, Challenges, and Emerging Topics in Digital Forensics: A Review of Reviews». In: *IEEE Access* 10 (2022), pp. 25464–25493. DOI: 10.1109/ACCESS.2022.3154059 (cit. on pp. 49, 50).

[33] Elena Alina Ontanu. «The Digitalisation of European Union Procedures: A New Impetus Following a Time of Prolonged Crisis». In: *Law, Technology and Humans* 5.1 (2023), pp. 93–110. DOI: 10.5204/lthj.2706. URL: https://doi.org/10.5204/lthj.2706 (cit. on p. 49).

[34] N. AllahRakha. «Rethinking Digital Borders to Address Jurisdiction and Governance in the Global Digital Economy». In: *International Journal of Law and Policy* 2.1 (2024). DOI: 10.59022/ijlp.124. URL: https://doi.org/10.59022/ijlp.124 (cit. on p. 49).

[35] Eleanor Birrell, Jay Rodolitz, Angel Ding, Jenna Lee, Emily McReynolds, Jevan Hutson, and Ada Lerner. «SoK: Technical Implementation and Human Impact of Internet Privacy Regulations». In: *Proceedings of the 2024 IEEE Symposium on Security and Privacy (SP)*. IEEE Computer Society, 2024. DOI: 10.1109/SP54263.2024.00182. URL: https://doi.ieeecomputersociety.org/10.1109/SP54263.2024.00182 (cit. on pp. 49, 50).