

100 JavaScript Coding Challenges for Intern Developers

1. Print "Hello World" using console.log().

```
<!DOCTYPE html>
<html lang="en">
<head>
  <title>Hello World</title>
</head>
<body>

  <script>

    document.write("Hello World");

  </script>

</body>
</html>
```

2. Create variables using var, let, and const.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <title>Variables</title>
</head>
<body>

  <script>

    var city = "Mumbai";
    let age = 21;
```

```
const country = "India";
```

```
document.write(city + "<br>");
```

```
document.write(age + "<br>");
```

```
document.write(country);
```

```
</script>
```

```
</body>
```

```
</html>
```

3. Add two numbers and display output.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Addition</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    let num1 = 10;
```

```
    let num2 = 20;
```

```
    let sum = num1 + num2;
```

```
    document.write("Addition is : " + sum);
```

```
  </script>
```

```
</body>
```

```
</html>
```

4. Swap two numbers without third variable.

```
<!DOCTYPE html>

<html lang="en">

<head>

  <title>Swap Numbers</title>

</head>

<body>


  <script>


    let a = 5;

    let b = 10;


    document.write("Before Swap <br>");

    document.write("a = " + a + "<br>");

    document.write("b = " + b + "<br><br>");


    a = a + b;

    b = a - b;

    a = a - b;


    document.write("After Swap <br>");

    document.write("a = " + a + "<br>");

    document.write("b = " + b);


  </script>


</body>

</html>
```

5. Find square and cube of a number.

```
<!DOCTYPE html>
```

```
<html lang="en">
<head>
  <title>Square and Cube</title>
</head>
<body>

  <script>

    let number = 4;

    let square = number * number;
    let cube = number * number * number;

    document.write("Square = " + square + "<br>");
    document.write("Cube = " + cube);

  </script>

</body>
</html>
```

6. Convert Celsius to Fahrenheit.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <title>Temperature Converter</title>
</head>
<body>

  <script>

    let celsius = 30;
```

```
let fahrenheit = (celsius * 9/5) + 32;
```

```
document.write("Fahrenheit = " + fahrenheit);
```

```
</script>
```

```
</body>
```

```
</html>
```

7. Find area of rectangle and circle.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Calculator</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    let num1 = 20;
```

```
    let num2 = 5;
```

```
    document.write("Addition = " + (num1 + num2) + "<br>");
```

```
    document.write("Subtraction = " + (num1 - num2) + "<br>");
```

```
    document.write("Multiplication = " + (num1 * num2) + "<br>");
```

```
    document.write("Division = " + (num1 / num2));
```

```
  </script>
```

```
</body>
```

```
</html>
```

8. Create simple calculator using operators.

```
<!DOCTYPE html>

<html lang="en">

<head>

  <title>Calculator</title>

</head>

<body>


  <script>


    let num1 = 20;

    let num2 = 5;


    document.write("Addition = " + (num1 + num2) + "<br>");

    document.write("Subtraction = " + (num1 - num2) + "<br>");

    document.write("Multiplication = " + (num1 * num2) + "<br>");

    document.write("Division = " + (num1 / num2));


  </script>


</body>

</html>
```

9. Take user input using prompt().

```
<!DOCTYPE html>

<html lang="en">

<head>

  <title>User Input</title>

</head>

<body>


  <script>
```

```
let name = prompt("Enter Your Name");
```

```
document.write("Welcome " + name);
```

```
</script>
```

```
</body>
```

```
</html>
```

10. Display output using alert() and document.write().

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Output Methods</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    alert("Welcome to JavaScript");
```

```
    document.write("Hello User");
```

```
  </script>
```

```
</body>
```

```
</html>
```

11. Check number is positive or negative.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
<title>Positive or Negative</title>
</head>
<body>

<script>

    let number = -5;

    if(number >= 0)
    {
        document.write("Positive Number");
    }
    else
    {
        document.write("Negative Number");
    }

</script>

</body>
</html>
```

12. Check even or odd number.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <title>Largest Number</title>
</head>
<body>

<script>
```



```
let a = 20;
```

```
let b = 50;
```

```
let c = 35;
```

```
if(a > b && a > c)
```

```
{
```

```
    document.write("A is Largest");
```

```
}
```

```
else if(b > a && b > c)
```

```
{
```

```
    document.write("B is Largest");
```

```
}
```

```
else
```

```
{
```

```
    document.write("C is Largest");
```

```
}
```

```
</script>
```

```
</body>
```

```
</html>
```

13. Find largest among 3 numbers.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <title>Largest Number</title>
```

```
</head>
```

```
<body>
```

```
<script>
```

```
let a = 20;

let b = 50;

let c = 35;


if(a > b && a > c)
{
    document.write("A is Largest");
}

else if(b > a && b > c)
{
    document.write("B is Largest");
}

else
{
    document.write("C is Largest");
}
```

```
</script>
```

```
</body>
```

```
</html>
```

14. Check leap year.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <meta charset="UTF-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
    <title>Leap Year</title>
```

```
</head>
```

```
<body>
```

```
<script>

    let year = 2026;

    if(year %4==0){
        document.write(year +"Year is Leap")
    }else{
        document.write(year +"year is not Leap")
    }
</script>
</body>
</html>
```

15. Create grading system using if-else.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Mark System</title>
</head>
<body>
    <script>
        let mark =90;

        if(mark >= 90){
            document.write("Grade A+");
        }
        else if(mark >=70){
            document.write("Grade B+")
        }
        else if(mark >=50){
```

```
        document.write("Grade c+")
    }
    else if(mark >= 40){
        document.write("Grade D+")
    }else{
        document.write("Fail")
    }
</script>
</body>
</html>
```

16. Create login validation system.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Login Validation</title>
</head>
<body>
    <script>
        let username = "komalk";
        let password =8720;

        if(username == "komalk" && password == 8720){
            document.write("Login Successfull")
        }else{
            document.write("Invalid Username And Password")
        }
    </script>
</body>
```

```
</html>
```

17. Check voter eligibility.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <meta charset="UTF-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
  <title>Voter Eligibility</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    let age =10;
```

```
    if(age >= 18){
```

```
      document.write("Voter Eligibal")
```

```
    }else{
```

```
      document.write("Voter Not Eligible")
```

```
    }
```

```
  </script>
```

```
</body>
```

```
</html>
```

18. Create traffic signal system.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <meta charset="UTF-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
  <title>Document</title>
```

```
</head>
<body>
  <script>
    let signal = "green";

    if(signal == "red"){
      document.write("Stop")
    }else if(signal == "Yellow"){
      document.write("Ready")
    }else if(signal == "green"){
      document.write("Go")
    }else{
      document.write("Invalid Signal")
    }
  </script>
</body>
</html>
```

19. Create ATM withdrawal validation.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
</head>
<body>
  <script>
    let balance = 100000;
    let withdrawl = 4000;

    if(withdrawl <= balance){
```

```
        document.write("withdrawl Successful")
    }else{
        document.write("Balance Not Available")
    }
</script>
</body>
</html>
```

20. Create nested condition-based dashboard.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <script>
        let user = "admin";
        let password = 1234

        if(user == "admin"){
            if(password == 1234){
                document.write("Welcome to Dashboard")
            }else{
                document.write("invalid Password")
            }
        }else{
            document.write("invalid user")
        }
    </script>
```

```
</body>
```

```
</html>
```

21. Print numbers from 1 to 100.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <meta charset="UTF-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
  <title>Document</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    for(var i=1 ; i<=100 ; i++){
```

```
      document.write(i+ "<br>")
```

```
    }
```

```
  </script>
```

```
</body>
```

```
</html>
```

22. Print even numbers using loop.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <meta charset="UTF-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
  <title>Document</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    for(var i=1; i<=100 ;i++){
```



```
        if(i %2 == 0){
            document.write(i+ "<br>")
        }
    }
</script>
</body>
</html>
```

23. Print odd numbers using loop.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <script>
        for(var i=1;i<=50 ;i++){
            if(i % 2 != 0){
                document.write(i+ "<br>")
            }
        }
    </script>
</body>
</html>
```

24. Find factorial of number.

```
<!DOCTYPE html>
<html lang="en">
<head>
```

```

<meta charset="UTF-8">

<meta name="viewport" content="width=device-width, initial-scale=1.0">

<title>Document</title>

</head>

<body>

<script>

    let number = 5 ;

    let factorial = 1;

    for(var i =1 ; i<number ; i++){

        factorial = factorial * i

    }

    document.write("Factorial="+ factorial)

</script>

</body>

</html>

```

25. Print multiplication table.

```

<!DOCTYPE html>

<html lang="en">

<head>

    <meta charset="UTF-8">

    <meta name="viewport" content="width=device-width, initial-scale=1.0">

    <title>Document</title>

</head>

<body>

<script>

    let number =7;

    for(var i =1 ; i<10 ; i++){

        document.write(number + " x " + i + " = " + (number * i) + "<br>");

    }

</script>

```

```
</body>
```

```
</html>
```

26. Find sum of numbers.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <meta charset="UTF-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
    <title>Document</title>
```

```
</head>
```

```
<body>
```

```
    <script>
```

```
        let sum = 0 ;
```

```
        for(var i=1 ; i<=10 ;i++){
```

```
            sum = sum+1;
```

```
        }
```

```
        document.write("Total sum =" +sum)
```

```
    </script>
```

```
</body>
```

```
</html>
```

27. Reverse a number.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <title>Reverse Number</title>
```

```
</head>
```

```
<body>
```

```
    <script>
```

```
let number = 1234;

let reverse = 0;

while(number > 0)
{
    let digit = number % 10;

    reverse = reverse * 10 + digit;

    number = parseInt(number / 10);
}

document.write("Reverse Number = " + reverse);

</script>

</body>

</html>
```

28. Check palindrome number.

```
<!DOCTYPE html>

<html lang="en">

<head>

    <title>Palindrome Number</title>

</head>

<body>

    <script>

        let number = 121;
```

```
let original = number;

let reverse = 0;

while(number > 0)
{
    let digit = number % 10;

    reverse = reverse * 10 + digit;

    number = parseInt(number / 10);
}

if(original == reverse)
{
    document.write("Palindrome Number");
}
else
{
    document.write("Not Palindrome");
}
```

</script>

</body>

</html>

29. Print star pattern.

<!DOCTYPE html>

<html lang="en">

<head>

<meta charset="UTF-8">

<meta name="viewport" content="width=device-width, initial-scale=1.0">

```
<title>Document</title>
</head>
<body>
  <script>
    for(var i=1 ;i<5 ; i++){
      for(var j=1;j<=i ;j++){
        document.write("*")
      }
      document.write("<br>")
    }
  </script>
</body>
</html>
```

30. Create pyramid pattern.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
</head>
<body>

  <script>

    for(var i = 1; i <= 5; i++){

      for(var j = 1; j <= 5 - i; j++){

        document.write("&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;");
```

```
}
```

```
for(var k = 1; k <= i; k++){
```

```
    document.write("*");
```

```
}
```

```
document.write("<br>");
```

```
}
```

```
</script>
```

```
</body>
```

```
</html>
```

31. Create simple function.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <meta charset="UTF-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
    <title>Document</title>
```

```
</head>
```

```
<body>
```

```
    <script>
```

```
        function welcome(){
```

```
            document.write("welcome To javascript")
```

```
        }
```

```
        welcome()
```

```
    </script>
```

```
</body>
```

```
</html>
```

32. Create function with parameters.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <meta charset="UTF-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
  <title>Document</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    function Addition(a,b){
```

```
      document.write("Addition="+a+b))
```

```
    }
```

```
    Addition(30,50);
```

```
  </script>
```

```
</body>
```

```
</html>
```

33. Create function with return value.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <meta charset="UTF-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
  <title>Document</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```



```

    function square(number){
        return number*number;
    }

    var result = square(5);

    document.write("Squre = "+result);

</script>
</body>
</html>

```

34. Create calculator using functions.

```

<!DOCTYPE html>

<html lang="en">

<head>

    <meta charset="UTF-8">

    <meta name="viewport" content="width=device-width, initial-scale=1.0">

    <title>Document</title>

</head>

<body>

    <script>

        function ganerateOTP(){

            let otp = Math.floor(1000 +Math.random()*9000);

            return otp;

        }

        document.write("Your OTP is="+ganerateOTP())

    </script>

</body>
</html>

```

35. Create OTP generator function

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
</head>
<body>
  <script>
    function generateOTP(){
      let otp = Math.floor(1000 + Math.random()*9000);
      return otp;
    }

    document.write("Your OTP is="+generateOTP())

  </script>
</body>
</html>
```

36. Create age calculator function.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
</head>
<body>
  <script>
    function calculateAge(birthYear){
```

```
    var currentYear = 2026;

    return currentYear - birthYear;
}

let age = calculateAge(2005);

document.write("Your Age :"+age)

</script>
</body>
</html>
```

37. Create percentage calculator.

```
<!DOCTYPE html>

<html lang="en">

<head>

    <meta charset="UTF-8">

    <meta name="viewport" content="width=device-width, initial-scale=1.0">

    <title>Document</title>

</head>

<body>

    <script>

        function percentage(totalMarks,ObtainMarks){

            return(ObtainMarks/totalMarks)*100;

        }

        let result = percentage(400,420);

        document.write("Percentage"+result+"%");

    </script>

</body>

</html>
```

38. Create reusable validation function.

```
<!DOCTYPE html>
```

```
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
</head>
<body>
  <Script>
    function validate(username){
      if(username == ""){
        return "Username is required"
      }else{
        return "Valid Username"
      }
    }
    let result = validate("komal");
    document.write(result);
  </Script>
</body>
</html>
```

39. Create EMI calculator function.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
</head>
<body>
  <script>
```

```
function calculateEMI(loanAmount,months){  
    return loanAmount/months;  
}  
var emi =calculateEMI(2000,12);  
document.write("monthly Emi"+emi)  
</script>  
</body>  
</html>
```

40. Create real-time invoice function.

```
<!DOCTYPE html>  
<html lang="en">  
<head>  
    <title>Invoice Function</title>  
</head>  
<body>  
  
    <script>  
  
        function invoice(productName, quantity, price)  
        {  
            let total = quantity * price;  
  
            document.write("Product Name : " + productName + "<br>");  
            document.write("Quantity : " + quantity + "<br>");  
            document.write("Price : " + price + "<br>");  
            document.write("Total Bill : " + total);  
        }  
  
        invoice("Laptop", 2, 45000);
```

```
</script>
```

```
</body>
```

```
</html>
```

41. Find string length.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <meta charset="UTF-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
  <title>Document</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    let text = "javascript";
```

```
    document.write("String Length="+text.length)
```

```
  </script>
```

```
</body>
```

```
</html>
```

42. Convert string to uppercase.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <meta charset="UTF-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
  <title>Document</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    let text = "javascript"
```

```
        let result = text.toUpperCase();

        document.write(result);

    </script>
</body>
</html>
```

43. Convert string to lowercase.

```
<!DOCTYPE html>

<html lang="en">

<head>

    <meta charset="UTF-8">

    <meta name="viewport" content="width=device-width, initial-scale=1.0">

    <title>Document</title>

</head>

<body>

    <script>

        let text = "javascript"

        let result = text.toLowerCase();

        document.write(result);

    </script>

</body>
</html>
```

44. Reverse a string.

```
<!DOCTYPE html>

<html lang="en">

<head>

    <meta charset="UTF-8">

    <meta name="viewport" content="width=device-width, initial-scale=1.0">

    <title>Document</title>

</head>
```

```
<body>

  <script>

    var text = "javascript";

    var reverse = text.split("").reverse().join("");

    document.write("Reverse String="+reverse)

  </script>

</body>

</html>
```

45. Check palindrome string.

```
<!DOCTYPE html>

<html lang="en">

<head>

  <title>Palindrome String</title>

</head>

<body>


  <script>


    let text = "madam";


    let reverse = text.split("").reverse().join("");


    if(text == reverse)
    {
      document.write("Palindrome String");
    }
    else
    {
      document.write("Not Palindrome");
    }

  </script>

</body>

</html>
```



```
</script>
```

```
</body>
```

```
</html>
```

46. Count vowels in string.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Count Vowels</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    let text = "JavaScript";
```

```
    let count = 0;
```

```
    for(let i = 0; i < text.length; i++)
```

```
    {
```

```
      let ch = text[i].toLowerCase();
```

```
      if(ch == "a" || ch == "e" || ch == "i" || ch == "o" || ch == "u")
```

```
      {
```

```
        count++;
```

```
      }
```

```
    }
```

```
    document.write("Total Vowels = " + count);
```

```
</script>
```

```
</body>
```

```
</html>
```

47. Replace word in string.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <meta charset="UTF-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
  <title>Document</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    var text = "I Love Javascript";
```

```
    var result = text.replace("javascript", "java");
```

```
    document.write(result);
```

```
  </script>
```

```
</body>
```

```
</html>
```

48. Remove spaces from string.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <meta charset="UTF-8">
```

```
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
  <title>Document</title>
```

```
</head>
```

```
<body>
```

```
<script>

    var text = "javascript language";

    var result = text.replaceAll("", "");

    document.write(result)

</script>
</body>
</html>
```

49. Create username generator.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <script>
        let name = "komal";
        let birthYear = 2005;
        let username = name+birthYear;
        document.write("Username =" +username)
    </script>
</body>
</html>
```

50. Create password strength checker.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Document</title>
</head>
<body>
  <script>
    var password = "komal123";
    if(password.length>=8){
      document.write("Strong Password")
    }else{
      document.write("Weak Password")
    }
  </script>
</body>
</html>
```

51. Create array of students.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
</head>
<body>
  <script>
    var students=["komal","shivani","rutuja","snehal"];
    document.write(students)
  </script>
</body>
</html>
```

52. Add elements in array.

```
<!DOCTYPE html>

<html lang="en">

<head>

  <meta charset="UTF-8">

  <meta name="viewport" content="width=device-width, initial-scale=1.0">

  <title>Document</title>

</head>

<body>

  <script>

    var fruits = ["mango", "apple"];

    fruits.push("banana");

    document.write(fruits)

  </script>

</body>

</html>
```

53. Remove elements from array.

```
<!DOCTYPE html>

<html lang="en">

<head>

  <meta charset="UTF-8">

  <meta name="viewport" content="width=device-width, initial-scale=1.0">

  <title>Document</title>

</head>

<body>

  <script>

    var colors = ["red", "pink", "yellow", "black", "white"];

    colors.pop();

    document.write(colors)

  </script>
```

```
</body>
```

```
</html>
```

54. Find largest number in array.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Largest Number</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    let numbers = [10, 50, 25, 90, 45];
```

```
    let largest = numbers[0];
```

```
    for(let i = 0; i < numbers.length; i++)
```

```
    {
```

```
      if(numbers[i] > largest)
```

```
      {
```

```
        largest = numbers[i];
```

```
      }
```

```
    }
```

```
    document.write("Largest Number = " + largest);
```

```
  </script>
```

```
</body>
```

```
</html>
```

55. Find smallest number in array.

```
<!DOCTYPE html>

<html lang="en">

<head>

  <title>Smallest Number</title>

</head>

<body>


  <script>


    let numbers = [10, 50, 25, 90, 5];


    let smallest = numbers[0];


    for(let i = 0; i < numbers.length; i++)
    {
      if(numbers[i] < smallest)
      {
        smallest = numbers[i];
      }
    }


    document.write("Smallest Number = " + smallest);


  </script>


</body>

</html>
```

56. Sort array ascending order.

```
<!DOCTYPE html>

<html lang="en">
```

```
<head>
  <title>Sort Array</title>
</head>
<body>

  <script>

    let numbers = [40, 10, 90, 20, 5];

    numbers.sort(function(a, b)
    {
      return a - b;
    });

    document.write(numbers);

  </script>

</body>
</html>
```

57. Reverse array elements.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
</head>
<body>
  <script>

    var numbers =[12,56,30,58,90,20];
```



```
        numbers.reverse();

        document.write(numbers)

    </script>
</body>
</html>
```

58. Search element in array.

```
<!DOCTYPE html>

<html lang="en">

<head>

    <meta charset="UTF-8">

    <meta name="viewport" content="width=device-width, initial-scale=1.0">

    <title>Document</title>

</head>

<body>

    <script>

        var fruits =["apple","banan","orange","mango"];

        var result = fruits.includes("mango");

        document.write(result)

    </script>

</body>
</html>
```

59. Merge two arrays.

```
<!DOCTYPE html>

<html lang="en">

<head>

    <title>Merge Arrays</title>

</head>

<body>
```

```
<script>

    let array1 = [10, 20, 30];
    let array2 = [40, 50, 60];

    let mergeArray = array1.concat(array2);

    document.write(mergeArray);

</script>

</body>
</html>
```

60. Create shopping cart system.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <title>Merge Arrays</title>
</head>
<body>

    <script>

        let array1 = [10, 20, 30];
        let array2 = [40, 50, 60];

        let mergeArray = array1.concat(array2);

        document.write(mergeArray);
```

```
</script>
```

```
</body>
```

```
</html>
```

61. Create student object.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Student Object</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    let student =
```

```
    {
```

```
      name : "Komal",
```

```
      age : 21,
```

```
      course : "BCA"
```

```
    };
```

```
    document.write("Name : " + student.name + "<br>");
```

```
    document.write("Age : " + student.age + "<br>");
```

```
    document.write("Course : " + student.course);
```

```
  </script>
```

```
</body>
```

```
</html>
```

62. Create employee object.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <title>Employee Object</title>
</head>
<body>

  <script>

    let employee =
    {
      empId : 101,
      empName : "Rahul",
      salary : 35000
    };

    document.write("Employee ID : " + employee.empId + "<br>");
    document.write("Employee Name : " + employee.empName + "<br>");
    document.write("Salary : " + employee.salary);

  </script>

</body>
</html>
```

63. Access object properties.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <title>Access Properties</title>
</head>
<body>
```

```
<script>
```

```
let mobile =
```

```
{
```

```
  brand : "Samsung",
```

```
  price : 25000
```

```
};
```

```
document.write(mobile.brand + "<br>");
```

```
document.write(mobile.price);
```

```
</script>
```

```
</body>
```

```
</html>
```

64. Add new property in object.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Add Property</title>
```

```
</head>
```

```
<body>
```

```
<script>
```

```
let car =
```

```
{
```

```
  brand : "BMW",
```

```
  color : "Black"
```

```
};
```

```
car.price = 5000000;
```

```
document.write("Brand : " + car.brand + "<br>");
```

```
document.write("Color : " + car.color + "<br>");
```

```
document.write("Price : " + car.price);
```

```
</script>
```

```
</body>
```

```
</html>
```

65. Delete object property.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <title>Delete Property</title>
```

```
</head>
```

```
<body>
```

```
<script>
```

```
    let user =
```

```
    {
```

```
        name : "Komal",
```

```
        age : 21,
```

```
        city : "Mumbai"
```

```
    };
```

```
    delete user.city;
```

```
    document.write("Name : " + user.name + "<br>");
```

```
document.write("Age : " + user.age);
```

```
</script>
```

```
</body>
```

```
</html>
```

66. Loop through object values.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Loop Object</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    let student =
```

```
    {
```

```
      name : "Amit",
```

```
      age : 20,
```

```
      course : "BSc"
```

```
    };
```

```
    for(let key in student)
```

```
    {
```

```
      document.write(key + " : " + student[key] + "<br>");
```

```
    }
```

```
  </script>
```

```
</body>
```

```
</html>
```

67. Create product management object.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Product Management</title>
```

```
</head>
```

```
<body>
```

```
  <script>
```

```
    let product =
```

```
    {
```

```
      productName : "Laptop",
```

```
      price : 45000,
```

```
      quantity : 2,
```

```
      totalPrice : function()
```

```
      {
```

```
        return this.price * this.quantity;
```

```
      }
```

```
    };
```

```
    document.write("Product : " + product.productName + "<br>");
```

```
    document.write("Total Price : " + product.totalPrice());
```

```
  </script>
```

```
</body>
```

```
</html>
```

68. Create banking account object.


```
<!DOCTYPE html>

<html lang="en">

<head>

  <title>Bank Account</title>

</head>

<body>


  <script>


    let bankAccount =

    {

      accountHolder : "Komal",

      balance : 10000,


      deposit : function(amount)

      {

        this.balance += amount;

      }

    };


    bankAccount.deposit(5000);


    document.write("Account Holder : " + bankAccount.accountHolder + "<br>");

    document.write("Balance : " + bankAccount.balance);


  </script>


</body>

</html>
```

69. Create real-time invoice object.

```
<!DOCTYPE html>
```

```
<html lang="en">

<head>

  <title>Invoice Object</title>

</head>

<body>


  <script>


    let invoice =

    {

      product : "Mobile",

      quantity : 3,

      price : 15000,


      total : function()

      {

        return this.quantity * this.price;

      }

    };


    document.write("Product : " + invoice.product + "<br>");

    document.write("Total Bill : " + invoice.total());


  </script>


</body>

</html>
```

70. Create admin dashboard data object.

```
<!DOCTYPE html>

<html lang="en">

<head>
```

```

    <title>Admin Dashboard</title>
</head>
<body>

    <script>

        let dashboard =
        {
            totalUsers : 500,
            totalProducts : 120,
            totalOrders : 75
        };

        document.write("Total Users : " + dashboard.totalUsers + "<br>");
        document.write("Total Products : " + dashboard.totalProducts + "<br>");
        document.write("Total Orders : " + dashboard.totalOrders);

    </script>

</body>
</html>

```

71. Change text using JavaScript.

```

<!DOCTYPE html>
<html lang="en">
<head>
    <title>Change Text</title>
</head>
<body>

    <h1 id="heading">Hello User</h1>

```

```
<button onclick="changeText()">Change Text</button>
```

```
<script>
```

```
function changeText()
{
    document.getElementById("heading").innerHTML = "Welcome to JavaScript";
}
```

```
</script>
```

```
</body>
```

```
</html>
```

72. Change CSS using JS.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <title>Change CSS</title>
```

```
</head>
```

```
<body>
```

```
<h1 id="title">JavaScript Styling</h1>
```

```
<button onclick="changeStyle()">Change Style</button>
```

```
<script>
```

```
function changeStyle()
{
    document.getElementById("title").style.color = "red";
    document.getElementById("title").style.fontSize = "40px";
}
```

```
}
```

```
</script>
```

```
</body>
```

```
</html>
```

73. Hide and show element.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Hide Show</title>
```

```
</head>
```

```
<body>
```

```
  <h2 id="text">Welcome User</h2>
```

```
  <button onclick="hideText()">Hide</button>
```

```
  <button onclick="showText()">Show</button>
```

```
<script>
```

```
  function hideText()
```

```
  {
```

```
    document.getElementById("text").style.display = "none";
```

```
  }
```

```
  function showText()
```

```
  {
```

```
    document.getElementById("text").style.display = "block";
```

```
  }
```

```
</script>
```

```
</body>
```

```
</html>
```

74. Create dark mode toggle.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Dark Mode</title>
```

```
</head>
```

```
<body id="body">
```

```
  <button onclick="darkMode()">Dark Mode</button>
```

```
  <script>
```

```
    function darkMode()
```

```
    {
```

```
      document.getElementById("body").style.backgroundColor = "black";
```

```
      document.getElementById("body").style.color = "white";
```

```
    }
```

```
  </script>
```

```
</body>
```

```
</html>
```

75. Create image slider.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Image Slider</title>
```

```
</head>
<body>

  

  <br><br>

  <button onclick="changeImage()">Next Image</button>

  <script>

    function changeImage()
    {
      document.getElementById("slider").src = "pro6.jpg";
    }

  </script>

</body>
</html>
```

76. Create responsive navbar toggle.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <title>Navbar Toggle</title>

  <style>

    #menu
    {
```

```
display: none;  
}
```

```
</style>
```

```
</head>
```

```
<body>
```

```
<button onclick="showMenu()">Menu</button>
```

```
<div id="menu">
```

```
<h3>Home</h3>
```

```
<h3>About</h3>
```

```
<h3>Contact</h3>
```

```
</div>
```

```
<script>
```

```
function showMenu()
```

```
{
```

```
    let menu = document.getElementById("menu");
```

```
    if(menu.style.display == "none")
```

```
    {
```

```
        menu.style.display = "block";
```

```
    }
```

```
    else
```

```
    {
```

```
        menu.style.display = "none";
```

```
    }
```

```
}
```



```
</script>
```

```
</body>
```

```
</html>
```

77. Create popup modal.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Popup Modal</title>
```

```
  <style>
```

```
    #popup
```

```
    {
```

```
      width: 300px;
```

```
      padding: 20px;
```

```
      background: lightgray;
```

```
      display: none;
```

```
    }
```

```
</style>
```

```
</head>
```

```
<body>
```

```
  <button onclick="openPopup()">Open Popup</button>
```

```
  <div id="popup">
```

```
    <h2>Welcome User</h2>
```

```
    <button onclick="closePopup()">Close</button>
```

```
</div>
```

```
<script>
```

```
function openPopup()
```

```
{
```

```
    document.getElementById("popup").style.display = "block";
```

```
}
```

```
function closePopup()
```

```
{
```

```
    document.getElementById("popup").style.display = "none";
```

```
}
```

```
</script>
```

```
</body>
```

```
</html>
```

78. Create live character counter.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <title>Character Counter</title>
```

```
</head>
```

```
<body>
```

```
    <textarea id="message" onkeyup="countCharacter()"></textarea>
```

```
    <h3 id="result">0</h3>
```

```
<script>
```

```
function countCharacter()
{
    let text = document.getElementById("message").value;

    document.getElementById("result").innerHTML = text.length;
}
```

```
</script>
```

```
</body>
```

```
</html>
```

79. Create password show/hide feature.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <title>Password Toggle</title>
```

```
</head>
```

```
<body>
```

```
    <input type="password" id="password">
```

```
    <button onclick="showPassword()">Show Password</button>
```

```
<script>
```

```
function showPassword()
```

```
{
```

```
    let password = document.getElementById("password");
```

```
    if(password.type == "password")
```

```
{  
    password.type = "text";  
}  
else  
{  
    password.type = "password";  
}  
}
```

```
</script>
```

```
</body>
```

```
</html>
```

80. Create real-time form validation.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <title>Form Validation</title>
```

```
</head>
```

```
<body>
```

```
<input type="text" id="username" placeholder="Enter Username">
```

```
<button onclick="validateForm()">Submit</button>
```

```
<h3 id="message"></h3>
```

```
<script>
```

```
function validateForm()
```

```
{
```

```
let username = document.getElementById("username").value;

if(username == "")
{
    document.getElementById("message").innerHTML = "Username is Required";
}
else
{
    document.getElementById("message").innerHTML = "Form Submitted";
}
}

</script>
```

</body>

</html>

82. Handle keyboard event.

<!DOCTYPE html>

<html lang="en">

<head>

 <title>Button Click Event</title>

</head>

<body>

 <button onclick="showMessage()">Click Me</button>

 <script>

 function showMessage()

 {

 document.write("Button Clicked Successfully");

```
}
```

```
</script>
```

```
</body>
```

```
</html>
```

83. Handle mouseover event.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Keyboard Event</title>
```

```
</head>
```

```
<body>
```

```
  <input type="text" onkeydown="showKey()">
```

```
  <script>
```

```
    function showKey()
```

```
    {
```

```
      document.write("Key Pressed");
```

```
    }
```

```
</script>
```

```
</body>
```

```
</html>
```

84. Create dropdown change event.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
<title>Dropdown Event</title>
</head>
<body>

  <select onchange="showValue()" id="course">

    <option>HTML</option>
    <option>CSS</option>
    <option>JavaScript</option>

  </select>

  <h2 id="result"></h2>

  <script>

    function showValue()
    {
      let value = document.getElementById("course").value;

      document.getElementById("result").innerHTML = value;
    }

  </script>

</body>
</html>
```

85. Create image hover effect.

```
<!DOCTYPE html>
<html lang="en">
<head>
```

```
<title>Image Hover Effect</title>
</head>
<body>



<script>

function changeImage(img)
{
    img.src = "pro2.jpg";
}

function originalImage(img)
{
    img.src = "pro6.jpg";
}

</script>

</body>
</html>
```

86. Create typing event validation.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <title>Typing Validation</title>
```



```
</head>
```

```
<body>
```

```
<input type="text"  
      id="username"  
      onkeyup="validateInput()">
```

```
<h3 id="message"></h3>
```

```
<script>
```

```
function validateInput()  
{  
  let username =  
    document.getElementById("username").value;  
  
  if(username.length < 5)  
  {  
    document.getElementById("message").innerHTML =  
      "Minimum 5 Characters Required";  
  }  
  else  
  {  
    document.getElementById("message").innerHTML =  
      "Valid Username";  
  }  
}
```

```
</script>
```

```
</body>
```

```
</html>
```

87. Create live search filter.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Live Search</title>
```

```
</head>
```

```
<body>
```

```
  <input type="text"
```

```
    id="search"
```

```
    onkeyup="searchItem()"
```

```
    placeholder="Search">
```

```
  <ul id="list">
```

```
    <li>Apple</li>
```

```
    <li>Banana</li>
```

```
    <li>Mango</li>
```

```
    <li>Orange</li>
```

```
</ul>
```

```
<script>
```

```
  function searchItem()
```

```
  {
```

```
    let input =
```

```
    document.getElementById("search").value.toLowerCase();
```

```
    let items =
```

```
document.querySelectorAll("#list li");
```

```
for(let i = 0; i < items.length; i++)
```

```
{
```

```
    let text =
```

```
    items[i].innerHTML.toLowerCase();
```

```
    if(text.includes(input))
```

```
    {
```

```
        items[i].style.display = "block";
```

```
    }
```

```
    else
```

```
    {
```

```
        items[i].style.display = "none";
```

```
    }
```

```
}
```

```
}
```

```
</script>
```

```
</body>
```

```
</html>
```

88. Create drag and drop structure.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <title>Drag and Drop</title>
```

```
</head>
```

```
<body>
```

```
    <div id="box"
```

```
draggable="true"
ondragstart="drag(event)"
style="width:100px;
      height:100px;
      background:red;">
</div>
```

```
<div ondrop="drop(event)"
      ondragover="allowDrop(event)"
      style="width:300px;
            height:300px;
            border:2px solid black;
            margin-top:20px;">
</div>
```

```
<script>
```

```
function allowDrop(event)
{
    event.preventDefault();
}
```

```
function drag(event)
{
    event.dataTransfer.setData("text", event.target.id);
}
```

```
function drop(event)
{
    event.preventDefault();
```

```
    let data =  
    event.dataTransfer.getData("text");  
  
    event.target.appendChild(  
    document.getElementById(data));  
  }  
  
</script>  
  
</body>  
</html>
```

89. Create interactive cards.

```
<!DOCTYPE html>  
<html lang="en">  
<head>  
  <title>Interactive Card</title>  
  
  <style>  
  
    .card  
    {  
      width: 250px;  
      padding: 20px;  
      border: 2px solid black;  
    }  
  
</style>  
  
</head>  
<body>
```

```
<div class="card" onclick="changeCard()"
  id="card">
```

```
<h2>Product Card</h2>
```

```
<p>Click to Change Color</p>
```

```
</div>
```

```
<script>
```

```
function changeCard()
{
  document.getElementById("card")
    .style.backgroundColor = "lightblue";
}
```

```
</script>
```

```
</body>
```

```
</html>
```

90. Create dynamic notification system.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
<title>Notification System</title>
```

```
</head>
```

```
<body>
```

```
<button onclick="showNotification()">
```

```
  Show Notification
```

```
</button>
```

```
<h2 id="notification"></h2>
```

```
<script>
```

```
function showNotification()  
{  
    document.getElementById("notification")  
        .innerHTML = "New Notification Received";  
}
```

```
</script>
```

```
</body>
```

```
</html>
```

91. Create digital clock.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <title>Digital Clock</title>
```

```
</head>
```

```
<body>
```

```
<h1 id="clock"></h1>
```

```
<script>
```

```
function showTime()  
{  
    let date = new Date();
```

```
let time =  
  
date.getHours() + ":" +  
date.getMinutes() + ":" +  
date.getSeconds();  
  
document.getElementById("clock")  
.innerHTML = time;  
}
```

```
setInterval(showTime, 1000);
```

```
</script>
```

```
</body>
```

```
</html>
```

92. Create stopwatch.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Stopwatch</title>
```

```
</head>
```

```
<body>
```

```
  <h1 id="time">0</h1>
```

```
  <button onclick="startWatch()">Start</button>
```

```
  <script>
```

```
    let count = 0;
```



```
function startWatch()
{
    setInterval(function()
    {
        count++;

        document.getElementById("time")
        .innerHTML = count;

    }, 1000);
}
```

</script>

</body>

</html>

93. Create to-do list application.

<!DOCTYPE html>

<html lang="en">

<head>

<title>To Do List</title>

</head>

<body>

<input type="text" id="task">

<button onclick="addTask()">Add</button>

<ul id="list">

```
<script>

function addTask()
{
    let task =
    document.getElementById("task").value;

    let li = document.createElement("li");

    li.innerHTML = task;

    document.getElementById("list")
    .appendChild(li);
}

</script>
```

```
</body>
```

```
</html>
```

94. Create calculator application.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <title>Calculator App</title>
```

```
</head>
```

```
<body>
```

```
    <input type="number" id="num1">
```

```
    <input type="number" id="num2">
```

```
<button onclick="calculate()">Add</button>
```

```
<h2 id="result"></h2>
```

```
<script>
```

```
function calculate()
{
    let num1 =
        Number(document.getElementById("num1").value);

    let num2 =
        Number(document.getElementById("num2").value);

    let sum = num1 + num2;

    document.getElementById("result")
        .innerHTML = "Result = " + sum;
}
```

```
</script>
```

```
</body>
```

```
</html>
```

95. Create quiz application.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <title>Quiz App</title>
```

```
</head>
```

```
<body>
```

```
<h2>What is the Capital of India?</h2>
```

```
<button onclick="checkAnswer('Mumbai')">
```

```
    Mumbai
```

```
</button>
```

```
<button onclick="checkAnswer('Delhi')">
```

```
    Delhi
```

```
</button>
```

```
<h3 id="result"></h3>
```

```
<script>
```

```
    function checkAnswer(answer)
```

```
    {
```

```
        if(answer == "Delhi")
```

```
        {
```

```
            document.getElementById("result")
```

```
            .innerHTML = "Correct Answer";
```

```
        }
```

```
        else
```

```
        {
```

```
            document.getElementById("result")
```

```
            .innerHTML = "Wrong Answer";
```

```
        }
```

```
    }
```

```
</script>
```

```
</body>
```

```
</html>
```

96. Create student result management system.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
  <title>Student Result</title>
```

```
</head>
```

```
<body>
```

```
  <input type="number" id="marks">
```

```
  <button onclick="checkResult()">
```

```
    Check Result
```

```
  </button>
```

```
  <h2 id="result"></h2>
```

```
  <script>
```

```
    function checkResult()
```

```
    {
```

```
      let marks =
```

```
      document.getElementById("marks").value;
```

```
      if(marks >= 40)
```

```
      {
```

```
        document.getElementById("result")
```

```
        .innerHTML = "Pass";
```

```
      }
```

```
      else
```

```
{
    document.getElementById("result")
        .innerHTML = "Fail";
}
```

```
</script>
```

```
</body>
```

```
</html>
```

97. Create shopping cart system.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <title>Shopping Cart</title>
```

```
</head>
```

```
<body>
```

```
    <button onclick="addCart('Laptop')">
```

```
        Add Laptop
```

```
</button>
```

```
    <button onclick="addCart('Mobile')">
```

```
        Add Mobile
```

```
</button>
```

```
<ul id="cart"></ul>
```

```
<script>
```

```
    function addCart(product)
```

```
{  
  let li = document.createElement("li");  
  
  li.innerHTML = product;  
  
  document.getElementById("cart")  
    .appendChild(li);  
}
```

</script>

</body>

</html>

98. Create expense tracker.

<!DOCTYPE html>

<html lang="en">

<head>

<title>Expense Tracker</title>

</head>

<body>

<input type="number" id="expense">

<button onclick="addExpense()">

Add Expense

</button>

<h2 id="total">0</h2>

<script>

```
let total = 0;

function addExpense()
{
    let amount =
    Number(document.getElementById("expense").value);

    total = total + amount;

    document.getElementById("total")
    .innerHTML = "Total Expense = " + total;
}
```

```
</script>
```

```
</body>
```

```
</html>
```

99. Create weather application UI logic.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <title>Weather App</title>
```

```
</head>
```

```
<body>
```

```
    <input type="text" id="city"
        placeholder="Enter City">
```

```
    <button onclick="showWeather()">
```

```
        Check Weather
```

```
</button>
```



```
<h2 id="weather"></h2>
```

```
<script>
```

```
function showWeather()
{
    let city =
    document.getElementById("city").value;

    document.getElementById("weather")
    .innerHTML =
    "Weather of " + city + " is Sunny";
}
```

```
</script>
```

```
</body>
```

```
</html>
```

100. Create mini admin dashboard using JavaScript.

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
<title>Admin Dashboard</title>
```

```
<style>
```

```
.box
{
    width: 200px;
    padding: 20px;
```

```
    margin: 10px;
    background: lightblue;
    display: inline-block;
    text-align: center;
}
```

```
</style>
```

```
</head>
```

```
<body>
```

```
<div class="box">
```

```
  <h2 id="users">500</h2>
```

```
  <p>Total Users</p>
```

```
</div>
```

```
<div class="box">
```

```
  <h2 id="orders">120</h2>
```

```
  <p>Total Orders</p>
```

```
</div>
```

```
<div class="box">
```

```
  <h2 id="products">75</h2>
```

```
  <p>Total Products</p>
```

```
</div>
```

```
</body>
```

```
</html>
```