

CS121 Problem Set 3

Instructions: This problem set is due before 7:30pm on April 12, 2018. Submit a hardcopy of your solutions to the TA, or email your solutions to shw@cs121.org.

- 1) Consider the problem of performing a circular q -shift in a p -node hypercube, for $0 < q < p$, using *E-cube routing*. Recall that E-cube routing from a node x to y consists of writing x and y in binary, and routing along the dimensions in which x and y differ, in order of increasing dimension.

Show that if links are bidirectional, then for any q , all p data paths in a circular q -shift are congestion-free when E-cube routing is used. For example, Figure Q1 shows a congestion-free routing of a 3-shift in an 8 node hypercube. Conclude that any q -shift can be performed in $t_s + t_w m$ time when all messages have size m .

Hint: Use induction, and show that if $q > p/2$, then a q -shift is isomorphic to a $(p - q)$ -shift.




Figure Q1

- 2) Consider the following sequential *rank sort* algorithm for n values assuming no duplicate values:

```
for (i = 0; i < n; i++) {  
    x = 0;  
    for (j = 0; j < n; j++)  
        if (a[i] > a[j]) x++;  
    b[x] = a[i];  
}
```

- (a) Rewrite this as a parallel algorithm using OpenMP assuming that $p < n$ threads are used. Indicate clearly the use of private and shared variables and the schedule type.
- (b) Modify the OpenMP code in part (a) to handle duplicates in the list of values, i.e. to sort into non-decreasing order. For example, the list of values [3, 5, 7, 5, 7, 9, 2, 3, 6, 7, 8, 1] should give the sorted list [1, 2, 3, 3, 5, 5, 6, 7, 7, 7, 8, 9].

- 3) The following sequential code calculates a triangular matrix using a function **calc(i, j)**, which has no data dependences and requires a constant (but large) amount of computation.

```
for (i = 0; i < n; i++)
    for (j = 0; j <= i; j++)
        a[i,j] = calc(i,j);
```

By inserting OpenMP directives into the sequential code, show how the following schemes for assigning work to threads may be implemented on a shared memory parallel architecture, commenting on the efficiency of each scheme:

- A static block assignment of contiguous rows to threads.
 - A static cyclic assignment of single rows to threads.
 - A dynamic assignment of single rows to threads.
- 4) The *Back Substitution* algorithm solves a set of linear equations in upper (or lower) triangular form, as shown in Figure Q4a. A sequential algorithm to solve such a set of linear equations is given in Figure Q4b. Design a parallel algorithm for a shared memory architecture and express it using OpenMP assuming that $p < n$ threads are used. What schedule type would you use?

$$\begin{array}{rcl}
 a_{n-1,0}x_0 + a_{n-1,1}x_1 + a_{n-1,2}x_2 & \dots & + a_{n-1,n-1}x_{n-1} & = b_{n-1} \\
 & & \cdot & \\
 & & \cdot & \\
 a_{2,0}x_0 + a_{2,1}x_1 + a_{2,2}x_2 & & & = b_2 \\
 a_{1,0}x_0 + a_{1,1}x_1 & & & = b_1 \\
 a_{0,0}x_0 & & & = b_0
 \end{array}$$

Figure Q4a

```
/* Back Substitution */
for (i = 0; i < n; i++) {
    x[i] = b[i]/a[i][i];
    for (j = i+1; j < n; j++) {
        b[j] = b[j] - a[j][i]*x[i];
        a[j,i] = 0;
    }
}
```

Figure Q4b