

HTML Ruby Tag

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Ruby Tag</title>
</head>
<body>
<ruby>
html html<rp>(</rp><rt>This is it</rt><rp>)</rp>
</ruby>
</body>
</html>
```

HTML <strike> Tag

```
<!DOCTYPE html>
<html>
<head>
<title>HTML strike Tag</title>
</head>
<body>
The HTML strike tag renders a <strike>strike</strike> through the middle of the
text .
</body>
</html>
```

HTML Phrase Elements

<abbr>Indicates an abbreviated form like pvt. inc. etc.
<acronym>Indicates an acronym (e.g., WAC, radar, etc.).
Indicates emphasis.
Indicates stronger emphasis.
<cite>Contains a citation or a reference to other sources.
<dfn>Indicates that this is the defining instance of the enclosed term.
<code>Designates a fragment of computer code.
<samp>Designates sample output from programs, scripts, etc.
<kbd>Indicates text to be entered by the user.
<var>Indicates an instance of a variable or program argument.

HTML <select> Tag

```
<html>
<head>
<title>HTML select Tag</title>
</head>
```

```

<body>
<form action="/cgi-bin/dropdown.cgi" method="post">
<select name="dropdown">
<option value="Data Structures" selected>Data Structures</option>
<option value="Data Mining">Data Mining</option>
</select>
<input type="submit" value="Submit" />
</form>
</body>
</html>

```

Attributes:

disable, name, required, size.

HTML textarea Tag

Example

```

<!DOCTYPE html>
<html>
<head>
<title>HTML textarea Tag</title>
</head>
<body>
<form action="/cgi-bin/hello_get.cgi" method="get">
Fill the Detail: <br />
<textarea rows="5" cols="50" name="description">
Enter your name
</textarea>
<input type="submit" value="submit" />
</form>
</body>
</html>

```

Attributes : disable, cols, name, maxlength, placeholder, readonly, required, rows .

HTML <video> Tag

```

<!DOCTYPE html>
<html>
<head>
<title>HTML video Tag</title>
</head>
<body>
<p>Run your first program using an Online Compiler (compileonline.com)</p><br />
<video width="500" height="300" controls>
<source src="/html/compileonline.mp4" type="video/mp4">
This browser doesn't support video tag.
</video>

```

```
</body>
</html>
```

Attributes : Autoplay, height, width, loop, muted, src .

HTML <wbr> Tag

The HTML <wbr> tag defines a potential line break point if needed. This stands for Word Break Opportunity.

```
<!DOCTYPE html>
<html>
<head>
<title>HTML wbr Tag</title>
</head>
<body>
<wbr />
```

the browser to extend the document window beyond the size of the viewing pane and the poor user must scroll right

```
<wbr />
</body>
</html>
```

Progress Tag

```
<!DOCTYPE html>
<html>
<body>
```

```
<h1>The progress element</h1>
```

```
<label for="file">Downloading progress:</label>
<progress id="file" value="32" max="100"> 32% </progress>
```

```
</body>
</html>
```