Auditing Membership Leakage in Small SMILES Language Models: LiRA, Randomized-SMILES Training and DP-SGD (Preliminary Study)

Ankit Dhattarwal

Abstract—Autoregressive language models trained on molecular string representations (SMILES) are increasingly explored for computer-aided molecular generation. However, training sets in biopharmaceutical contexts often contain proprietary chemical structures, confidential screening hits, and patented scaffolds. In this study, we empirically evaluate Membership Inference Attacks (MIA) against small causal SMILES language models (2 layers, $d = 128$, ~ 0.4M parameters) on a subset of the MOSES molecular benchmark. We evaluate standard sequence loss thresholding (LOSS) alongside calibrated Likelihood-Ratio Attacks (LiRA) across training epochs (5, 20, 60), dataset sizes ($N \in \{1\text{k}, 2.5\text{k}, 5\text{k}, 10\text{k}\}$), a transfer learning scenario (pretrain then fine-tune), and two defensive strategies: randomized-SMILES data augmentation and Differentially Private SGD (DP-SGD).
In our baseline setting evaluated with canonical SMILES queries and sequence negative log-likelihood sum (nll_sum), models exhibit substantial membership leakage by epoch 60: online LiRA reaches a ROC-AUC of 0.898 ± 0.003 and a True Positive Rate (TPR) of $27.82 \pm 1.47\%$ at a 1% False Positive Rate (FPR) ($8.15 \pm 1.58\%$ at 0.1% FPR), compared to 0.689 ± 0.005 AUC and $2.96 \pm 0.24\%$ TPR@1% FPR for standard LOSS. In smaller training cohorts ($N = 1,000$), attack sensitivity increases (LOSS AUC reaches 0.998 ± 0.001, TPR@1% $= 93.99 \pm 4.35\%$; offline LiRA AUC reaches 0.957 ± 0.006, TPR@1% $= 20.75 \pm 6.51\%$; online LiRA AUC reaches 0.975 ± 0.004, TPR@1% $= 45.49 \pm 33.14\%$, with high LiRA estimation variance). Private fine-tuning after public pretraining also exhibits leakage (offline LiRA AUC 0.801 ± 0.003, TPR@1% $= 4.36 \pm 0.51\%$).
Crucially, we find that membership leakage in canonical models is string-form dependent: querying the epoch-60 canonical baseline with up to 10 distinct SMILES strings per molecule (the canonical form plus randomized forms, with mean NLL) reduces online LiRA AUC to 0.528 ± 0.006 (offline LiRA AUC 0.560 ± 0.007, LOSS AUC 0.511 ± 0.004), indicating that under mean aggregation, alternative string forms remove most of the signal (individual non-canonical forms were not scored separately). Training with randomized-SMILES augmentation similarly suppresses canonical attack AUC to 0.528 ± 0.004. In our preliminary DP-SGD arm ($\epsilon \in \{8.0, 3.0\}$, $\delta = 10^{-5}$), attack AUC drops to $0.500 - 0.528$, but models suffer severe utility collapse: chemical validity evaluations for DP-SGD were not recorded in the released summary; preliminary runs suffered severe utility degradation and generated strings failed standard valence checks (AUC ~ 0.5 for a model that does not generate valid molecules is not evidence of a useful defense). Finally, an empirical audit of 15,000 generated samples across baseline models observed 12 exact member replications versus 7 holdout replications; a one-sided binomial test ($p = 0.1796 > 0.05$) and Fisher exact test ($p = 0.359 > 0.05$) indicate that this difference is not statistically significant at the current sample size. We conclude with a discussion of open limitations and recommendations for privacy evaluation in chemical language models.

Index Terms—Membership Inference Attacks, Molecular Generative Models, SMILES, Differential Privacy, Likelihood-Ratio Attack, Privacy Auditing.

1 Introduction

Autoregressive generative sequence models parameterize discrete token distributions to explore chemical space. By modeling the Simplified Molecular Input Line Entry System (SMILES) [1], causal transformers can generate candidate structures and propose chemical variations for lead optimization.

In commercial drug discovery, generative models are often fine-tuned or trained directly on proprietary compound collections, including patented chemical series, internal bioassay screening hits, and confidential leads. If an adversary can infer whether a specific target compound was included in the training cohort—a vulnerability formalized as a Membership Inference Attack (MIA) [2]—they may extract competitive intelligence regarding active medicinal chemistry programs or unreleased intellectual property.

While membership inference has been widely investigated in computer vision and natural language processing, auditing molecular generative sequence models presents distinctive factors:

1) Molecules admit multiple non-unique equivalent SMILES representations (non-canonical string enumeration).
2) Chemical libraries often contain recurring core frameworks (Bemis-Murcko scaffolds [3]) that induce structural correlation across compounds.
3) Language models may memorize specific surface syntax without learning generalized semantic invariants.

In this work, we present an empirical audit of membership leakage in small SMILES autoregressive models. Using

A. Dhattarwal is an independent researcher in Machine Learning and Computational Chemistry. Project code and experiment artifacts are available at: https://github.com/Ankit-Dhattarwal/chem-generative-privacy-audit

a shadow-model ensemble framework based on Carlini et al.'s Likelihood-Ratio Attack (LiRA) [4], we systematically evaluate exposure across training duration, dataset scaling, transfer learning, and defensive interventions.

2 Threat Model and Formulation

2.1 Sequence Modeling and Scoring Metric

Let a molecular SMILES string be represented as a token sequence $x = (x_1, \ldots, x_T) \in \mathcal{V}^T$, where $\mathcal{V}$ is a discrete vocabulary of chemical tokens. An autoregressive transformer parameterizes the likelihood:

$$P_\theta(x) = \prod_{t=1}^{T} P_\theta(x_t \mid x_{<t}) \tag{1}$$

The sequence negative log-likelihood (NLL) sum is defined as:

$$\mathrm{NLL}_{\mathrm{sum}}(\theta; x) = -\sum_{t=1}^{T} \log P_\theta(x_t \mid x_{<t}) \tag{2}$$

Throughout this paper, we consistently report and evaluate metrics using sequence NLL sum (*nll_sum*). We adopt *nll_sum* because gradient-based privacy formulations (such as DP-SGD) operate on total loss per sample, and sequence-length normalization (*nll_mean*) introduces length-dependent shrinkage that alters likelihood calibration across molecules of differing lengths. Where indicated, we also report randomized-SMILES variant scoring (*nll_variants_mean*), which averages NLL across $K = 10$ randomized string representations of each molecule.

2.2 Attack Formulations: LOSS vs. LiRA

Given a query molecule x, the adversary computes a test statistic $S(x)$ to predict whether $x \in \mathcal{D}_{\mathrm{train}}$:

1) Loss Thresholding (LOSS):

$$S_{\mathrm{LOSS}}(x) = -\mathrm{NLL}_{\mathrm{sum}}(\mathcal{M}_{\mathrm{target}}; x) \tag{3}$$

LOSS assumes that training examples achieve lower sequence cross-entropy loss than non-training examples. However, intrinsic molecular complexity varies substantially: complex macrocycles or long branched chains exhibit higher baseline loss than simple aromatics regardless of membership.

2) Calibrated Likelihood-Ratio Attack (LiRA): To adjust for molecular complexity, LiRA [4] trains an ensemble of K shadow models $\{\mathcal{M}_k\}_{k=1}^{K}$ on random subsets of the data pool. For each query x, the models are partitioned into in-models $\mathcal{S}_{\mathrm{in}}(x) = \{k : x \in \mathcal{D}_k\}$ and out-models $\mathcal{S}_{\mathrm{out}}(x) = \{k : x \notin \mathcal{D}_k\}$.

   - Offline LiRA (Out-only): Estimates the out-distribution parameters $\mu_{\mathrm{out}}(x)$ and $\sigma_{\mathrm{out}}(x)$ over out-models:

$$\Lambda_{\mathrm{offline}}(x) = -\frac{\mathrm{NLL}_{\mathrm{sum}}(\mathcal{M}_{\mathrm{target}}; x) - \mu_{\mathrm{out}}(x)}{\sigma_{\mathrm{out}}(x) + 10^{-6}} \tag{4}$$

   - Online LiRA (In vs. Out): Estimates both in-distribution $(\mu_{\mathrm{in}}, \sigma_{\mathrm{in}})$ and out-distribution $(\mu_{\mathrm{out}}, \sigma_{\mathrm{out}})$ parameters, computing the log-likelihood ratio under parametric Gaussian assumptions:

$$\Lambda_{\mathrm{online}}(x) = -\frac{1}{2}\left(\frac{\mathrm{obs} - \mu_{\mathrm{in}}}{\sigma_{\mathrm{in}}}\right)^2 + \log\left(\frac{\sigma_{\mathrm{out}}}{\sigma_{\mathrm{in}}}\right) + \frac{1}{2}\left(\frac{\mathrm{obs} - \mu_{\mathrm{out}}}{\sigma_{\mathrm{out}}}\right)^2 \tag{5}$$

2.3 Threat Model Assumptions

We evaluate our models under an explicit, optimistic threat model:

1) Distribution Match: Shadow models are sampled from the exact same marginal distribution as the target model (MOSES benchmark pool).
2) Likelihood Access: The adversary has query access enabling exact calculation of token-level sequence log-likelihoods (*nll_sum*).
3) Canonical-String Queries: The adversary queries the target and shadow models using standard canonical SMILES representations.

These represent strong assumptions favoring the attacker. In restricted black-box deployments (e.g., API rate limits, generation-only access, or query filtering), adversary effectiveness may be substantially lower.

3 Experimental Setup and Architecture

3.1 Model Architecture

All evaluations utilize a small causal GPT architecture: 2 transformer layers, hidden embedding dimension $d_{\mathrm{model}} = 128$, 4 attention heads, context window of 128 tokens, parameter count of $\sim 410,000$, and a vocabulary of 27 tokens. Models are trained using Adam ($\mathrm{lr} = 5 \times 10^{-4}$), batch size 32, with a fixed sequence length of 128 tokens.

3.2 Dataset and Shadow Model Partitioning

Data are sourced from the MOSES benchmark [5]. The evaluation pool size is POOL_N = 20,000 molecules. For each shadow model k, exactly $N = 10,000$ molecules are sampled uniformly at random without replacement using seed k (_membership(pool, k) in colab_pipeline.py). Evaluation is conducted across all 20,000 candidate compounds (10,000 members, 10,000 non-members). In the baseline and randomized-augmentation (E5a) experiments, 32 shadow models are trained ($k \in \{0, \ldots, 31\}$). In data scaling (E3), DP-SGD, and pretrain-finetune experiments, 8 shadow models are trained per condition.

3.3 Opacus DP-SGD Implementation

Differentially private training is implemented using Opacus (version 1.6.0) [6]. The noise scale σ is computed dynamically using opacus.accountants.utils.get_noise_multiplier(target_epsilon=eps, target_delta=1e-5, sample_rate=32/N, epochs=60). Gradient clipping is set to max_grad_norm = 1.0, targeting $\epsilon \in \{8.0, 3.0\}$ with $\delta = 10^{-5}$. The causal attention layer avoids fused operations incompatible with Opacus per-sample gradient hooks. If training resumes from a checkpoint, privacy

accounting restarts from zero unless serialized accountant state is restored. In results_summary/manifest.json, a stale launch record with an ImportError for DPCausalGPT from an earlier initialization attempt is noted; subsequent runs completed.

4 Empirical Results and Findings

4.1 Baseline Leakage vs. Training Duration

Table 1 and Fig. 1 present membership inference performance across 5, 20, and 60 training epochs on canonical SMILES representations evaluated using *nll_sum*.




Fig. 1. Baseline Attack Vulnerability vs. Training Epochs. (a) ROC-AUC progression. (b) True Positive Rate at 1% False Positive Rate.

At epoch 5, membership leakage is modest (strongest attack: offline LiRA AUC 0.630 ± 0.008). By epoch 60, extensive exposure occurs: online LiRA reaches ROC-AUC 0.898 ± 0.003, with TPR@1% FPR reaching $27.82 \pm 1.47\%$. At a stricter threshold of 0.1% FPR, online LiRA still identifies $8.15 \pm 1.58\%$ of member molecules. Standard loss thresholding substantially underestimates vulnerability (AUC 0.689 vs. 0.898 for online LiRA at epoch 60).

Statistical Uncertainty: The reported $\pm$ values reflect the standard deviation across 32 leave-one-out shadow target models. To assess uncertainty over the 20,000 evaluation molecules, we computed 95% bootstrap confidence intervals for epoch-60 online LiRA across three independent target models:

- Target 0: AUC 0.9004, 95% CI $[0.8962, 0.9045]$; TPR@1% 0.2684, 95% CI $[0.2492, 0.3000]$.
- Target 1: AUC 0.8916, 95% CI $[0.8870, 0.8961]$; TPR@1% 0.2510, 95% CI $[0.2178, 0.2756]$.
- Target 2: AUC 0.8972, 95% CI $[0.8930, 0.9012]$; TPR@1% 0.2838, 95% CI $[0.2613, 0.3136]$.

4.2 String-Form Sensitivity: Randomized-SMILES Scoring

A key finding in our audit is that memorization in small canonical-trained models is strongly syntax-specific. In colab_pipeline.py, each molecule was scored at epoch 60 using up to 10 distinct SMILES strings per molecule (the canonical form plus randomized forms generated via RDKit Chem.MolToSmiles(mol, doRandom=True, canonical=False)), with the average NLL recorded as *nll_variants_mean*. Under mean aggregation, individual non-canonical forms were not scored separately; in our setting, mean-aggregated scoring over alternative string forms removes most of the signal.

As reported in Table 1 (bottom section), scoring canonical models with randomized variants drops LOSS AUC from 0.689 to 0.511 ± 0.004, offline LiRA AUC from 0.880 to 0.560 ± 0.007, and online LiRA AUC from 0.898 to 0.528 ± 0.006. This indicates that the target model primarily memorized the canonical string sequence rather than the invariant molecular graph. An adversary restricted to non-canonical queries loses almost all advantage.

4.3 Private Dataset Scaling

We examine vulnerability across dataset sizes $N \in \{1\text{k}, 2.5\text{k}, 5\text{k}, 10\text{k}\}$ trained for 60 epochs, with 8 shadow models per size ($2N$ candidate universe). Results are presented in Table 2 and Fig. 2, separating LOSS and LiRA attacks.




Fig. 2. Dataset Size Scaling (E3). (a) Loss thresholding attack (LOSS). (b) Calibrated Likelihood-Ratio Attacks (LiRA).

Smaller training cohorts experience pronounced overfitting at 60 epochs. At $N = 1,000$, standard LOSS reaches AUC 0.998 ± 0.001 with TPR@1% $= 93.99 \pm 4.35\%$, while offline LiRA reaches AUC 0.957 ± 0.006 (TPR@1% $= 20.75 \pm 6.51\%$) and online LiRA reaches AUC 0.975 ± 0.004 (TPR@1% $= 45.49 \pm 33.14\%$). With only 8 shadow models, LiRA density estimation at small N suffers from high variance (e.g., online LiRA TPR@1% standard deviation is $\pm 33.14\%$). We report these empirical numbers directly and do not claim a formal parametric scaling law.

4.4 Transfer Learning: Pretraining to Fine-Tuning

We evaluated a transfer learning setting where a model was pretrained on 10,000 public molecules for 60 epochs, then fine-tuned on 10,000 private molecules for 20 epochs across 8 shadow targets (Table 3).

Offline LiRA achieves an AUC of 0.801 ± 0.003 and TPR@1% of $4.36 \pm 0.51\%$. While lower than baseline epoch 60 (0.880 / 27.15%), this confirms that fine-tuning on private data remains susceptible to membership inference.

4.5 Defense Benchmark at Epoch 60

Table 4 and Fig. 3 benchmark two defensive approaches at epoch 60: (1) Randomized-SMILES training (E5a), where models are trained with random-SMILES data augmentation applied per batch; and (2) DP-SGD targeting $\epsilon \in \{8.0, 3.0\}$ with $\delta = 10^{-5}$.

Randomized-SMILES training strongly suppresses canonical attack performance: offline LiRA drops from 0.880 to 0.528 ± 0.004, and TPR@1% drops from 27.15% to 1.38%. When attacked via randomized variants scoring, offline LiRA AUC remains low at 0.552 ± 0.005.

In preliminary runs, DP-SGD reduces attack AUC near random guess ($0.500 - 0.528$). However, these models suffered

TABLE 1
Baseline membership inference vulnerability across training epochs on canonical SMILES. Evaluated over 32 shadow models on 20,000 candidate targets (10,000 members, 10,000 non-members). Values report mean ± standard deviation across 32 leave-one-out target evaluations (not a confidence interval). All metrics use negative log-likelihood sum (nll_sum), with randomized-SMILES variants scoring ($K = 10$ variants) reported at epoch 60.

Epochs	Scoring Representation	Attack Method	ROC-AUC	TPR @ 1% FPR (%)	TPR @ 0.1% FPR
5	Canonical (nll_sum)	Loss Thresholding (LOSS)	0.535 ± 0.004	1.23 ± 0.18	0.14 ± 0.07
5	Canonical (nll_sum)	Offline LiRA (Out-only)	0.630 ± 0.008	3.15 ± 0.36	0.42 ± 0.15
5	Canonical (nll_sum)	Online LiRA (In vs. Out)	0.595 ± 0.006	2.12 ± 0.35	0.19 ± 0.09
5	Canonical (nll_sum)	Strongest: offline_LiRA	0.630 ± 0.008	3.15 ± 0.36	0.42 ± 0.15
20	Canonical (nll_sum)	Loss Thresholding (LOSS)	0.591 ± 0.004	1.66 ± 0.21	0.21 ± 0.08
20	Canonical (nll_sum)	Offline LiRA (Out-only)	0.763 ± 0.007	9.58 ± 0.84	1.86 ± 0.47
20	Canonical (nll_sum)	Online LiRA (In vs. Out)	0.760 ± 0.006	8.66 ± 0.62	1.34 ± 0.33
20	Canonical (nll_sum)	Strongest: offline_LiRA	0.763 ± 0.007	9.58 ± 0.84	1.86 ± 0.47
60	Canonical (nll_sum)	Loss Thresholding (LOSS)	0.689 ± 0.005	2.96 ± 0.24	0.41 ± 0.15
60	Canonical (nll_sum)	Offline LiRA (Out-only)	0.880 ± 0.004	27.15 ± 1.63	8.22 ± 1.32
60	Canonical (nll_sum)	Online LiRA (In vs. Out)	0.898 ± 0.003	27.82 ± 1.47	8.15 ± 1.58
60	Canonical (nll_sum)	Strongest: online_LiRA	0.898 ± 0.003	27.82 ± 1.47	8.15 ± 1.58
60 (variants)	Randomized-SMILES ($K = 10$)	Loss Thresholding (LOSS)	0.511 ± 0.004	1.09 ± 0.12	0.12 ± 0.05
60 (variants)	Randomized-SMILES ($K = 10$)	Offline LiRA (Out-only)	0.560 ± 0.007	2.01 ± 0.29	0.30 ± 0.10
60 (variants)	Randomized-SMILES ($K = 10$)	Online LiRA (In vs. Out)	0.528 ± 0.006	1.45 ± 0.47	0.18 ± 0.12
60 (variants)	Randomized-SMILES ($K = 10$)	Strongest: offline_LiRA	0.560 ± 0.007	2.01 ± 0.29	0.30 ± 0.10

TABLE 2
Membership leakage scaling as private dataset size varies ($N \in \{1k, 2.5k, 5k, 10k\}$). Each size uses 8 shadow models ($2N$ candidate universe). LiRA estimates exhibit high variance at small N due to limited shadow samples per molecule. Evaluated using nll_sum. We present empirical measurements without assuming a parametric power law.

	Loss Thresholding (LOSS)		Offline LiRA		Online LiRA	
Size (N)	ROC-AUC	TPR@1% (%)	ROC-AUC	TPR@1% (%)	ROC-AUC	TPR@1% (%)
1,000	0.998 ± 0.001	93.99 ± 4.35	0.957 ± 0.006	20.75 ± 6.51	0.975 ± 0.004	45.49 ± 33.14
2,500	0.941 ± 0.006	27.68 ± 3.97	0.936 ± 0.003	12.85 ± 2.97	0.939 ± 0.003	6.53 ± 1.60
5,000	0.820 ± 0.010	7.99 ± 1.55	0.898 ± 0.008	8.19 ± 1.05	0.882 ± 0.006	3.23 ± 0.60
10,000	0.689 ± 0.003	2.84 ± 0.09	0.827 ± 0.006	4.81 ± 0.63	0.785 ± 0.003	2.07 ± 0.28

TABLE 3
Membership leakage in transfer learning (public pretraining on 10,000 molecules, fine-tuning on 10,000 private molecules). Metrics report mean ± std across 8 independent target models. Note: there is no from-scratch control trained at the exact same size/epochs in this experiment.

Attack Method	ROC-AUC	TPR @ 1% FPR ('
Loss Thresholding (LOSS)	0.640 ± 0.003	2.31 ± 0.26
Offline LiRA	0.801 ± 0.003	4.36 ± 0.51
Online LiRA	0.751 ± 0.004	2.00 ± 0.22




Fig. 3. Defense Benchmark Comparison at Epoch 60 showing the strongest attack per defense. *Note: DP-SGD runs suffered severe utility collapse; AUC ∼ 0.5 is not evidence of a useful defense.

severe utility collapse: chemical validity evaluations for DP-SGD were not recorded in the released summary; preliminary runs suffered severe utility degradation and generated strings failed standard valence checks. We emphasize that an AUC of ∼ 0.5 for a model that fails to generate chemically valid molecules is not evidence of a useful defense, and no privacy-utility conclusion can be drawn without preserving generation validity.

4.6 Generative Memorization Audit

To audit whether models generate verbatim copies of training leads, we sampled 5,000 molecules per model for three baseline models (Models 0, 15, 31; total 15,000 samples) on Apple Silicon (MPS). Generated molecules were evaluated for chemical validity, uniqueness, and exact string matches against 10,000 training members versus 10,000 holdout molecules (Table 5 and Fig. 4).

Across 15,000 samples, models produced 12 exact member copies and 7 holdout copies. Individual binomial test p-values are 0.750, 0.500, and 0.194. The pooled one-sided binomial test yields $p = 0.1796$ ($p > 0.05$), and a Fisher exact test yields $p = 0.359$. Under the evaluated sample budget (5,000 per model), the difference between member copies and holdout

TABLE 4
Comparison of privacy defenses at epoch 60 under standard and calibrated attacks. All values use nll_sum (except randomized variants scoring which evaluates mean NLL across $K = 10$ variants). The strongest attack per row (by highest AUC) is bolded. *Note on DP rows: preliminary run with utility collapse; no privacy-utility conclusion. AUC 0.5 for a model that does not generate valid molecules is not evidence of a useful defense.

		Loss Thresholding		Offline LiRA	
Defense Configuration	Shadows	AUC	TPR@1%	AUC	TPR@1%
Baseline (Unmitigated)	32 shadows	0.689 ± 0.005	2.96 ± 0.24	0.880 ± 0.004	$27.15 \pm 1.$
Randomized-SMILES Training (Canonical Scoring)	32 shadows	0.506 ± 0.004	1.08 ± 0.16	0.528 ± 0.004	$1.38 \pm 0.$
Randomized-SMILES Training (Variants Scoring, $K = 10$)	32 shadows	0.506 ± 0.004	1.10 ± 0.16	0.552 ± 0.005	$1.56 \pm 0.$
DP-SGD ($\epsilon = 8.0, \delta = 10^{-5}$)*	8 shadows; prelim.	0.505 ± 0.004	1.13 ± 0.15	0.528 ± 0.003	$1.20 \pm 0.$
DP-SGD ($\epsilon = 3.0, \delta = 10^{-5}$)*	8 shadows; prelim.	0.503 ± 0.004	1.10 ± 0.06	0.520 ± 0.003	$1.12 \pm 0.$

TABLE 5
Generative memorization audit (Experiment E6; 5,000 samples per model evaluated against 10,000 training members and 10,000 non-members). Replication counts denote verbatim matches: Count = Fraction $\times$ 5,000. One-sided binomial tests ($p = 0.5$) evaluate whether member replications exceed non-member replications. All p-values exceed 0.05, confirming that the observed replication differences are not statistically significant at the current sample size.

Model ID	Validity (%)	Uniqueness (%)	Novelty (%)	Member Copies	Out Copies	Binomial p-value	Statistically Significa
Model 0	60.24%	99.97%	99.97%	1	1	0.7500	No ($p > 0.05$)
Model 15	62.26%	99.87%	99.90%	3	2	0.5000	No ($p > 0.05$)
Model 31	59.10%	99.90%	99.73%	8	4	0.1938	No ($p > 0.05$)
Pooled (15k)	60.53%	99.91%	99.87%	12	7	0.1796	No ($p > 0.05$)




Fig. 4. Generative Memorization and Chemical Quality Audit (E6) across 15,000 samples.

copies is not statistically significant. Generative memorization cannot be claimed as statistically confirmed without higher-power sampling ($\geq$ 100k samples).

5 Related Work

Our work interfaces with privacy auditing, generative chemistry, and membership inference:

- Membership Inference Attacks: Carlini et al. [4] established Likelihood-Ratio Attacks (LiRA) to overcome sequence hardness confounding. Shokri et al. [2] originally formulated shadow-model attacks. Recent theoretical analysis by Zhang et al. [7] emphasized that empirical membership inference attacks face significant evidentiary caveats and cannot formally prove that a specific sample was present in a training set without known reference baselines.
- Privacy in Cheminformatics & Molecular Models: Krüger et al. [8] investigated membership leakage in molecular property predictors (molprivacy), demonstrating that publishing neural network weights poses data confidentiality risks. Aubinais et al. [9] studied membership inference risks in quantized models, incorporating chemical language model experiments. Ross et al. [10] developed GP-MoLFormer and noted training data memorization across 1.1 billion SMILES strings.
- Privacy Auditing in Biological Sequence Models: Nemecek et al. [11] analyzed memorization and privacy risk in genomic language models, illustrating domain-specific sequence leakage dynamics.
- SMILES Randomization & Data Augmentation: Arús-Pous et al. [12] and Bjerrum [13] demonstrated that randomized SMILES enumeration expands the effective representation space and regularizes generative models against overfitting.
- Differential Privacy in Deep Learning: Abadi et al. [14] and the Opacus library [6] formalized differential privacy via DP-SGD and Rényi Differential Privacy (RDP) accounting.

Our contribution provides a focused empirical audit of small causal SMILES language models across training epochs, dataset sizes, randomized representation scoring, and DP-SGD training. We do not claim to present the first or definitive study, but rather a transparent, reproducible benchmark of these dynamics in small chemical generative LMs.

6 Limitations

This preliminary study has several explicit limitations:

1) Model Capacity and Architecture: Models evaluate a 2-layer, $d = 128$, $\sim$ 0.4M parameter GPT with modest chemical validity ($\sim$ 60%). These findings may not generalize directly to larger generative models.

2) Dataset Scope: Experiments are restricted to a single filtered subset of the MOSES benchmark. Diverse proprietary libraries with differing scaffold distributions may exhibit different leakage profiles.
3) Shadow Ensemble Scale Asymmetry: While baseline and E5a arms used 32 shadow models, compute limits restricted E3, DP-SGD, and pretrain-FT to 8 shadow models, leading to higher estimation variance.
4) Reported Uncertainty: Metrics report standard deviation across leave-one-out shadow target models, rather than per-molecule bootstrap confidence intervals. Our computed 95% bootstrap CIs across molecules for epoch 60 online LiRA on three targets span roughly ± 0.005 in AUC and ± 0.03 in TPR@1%.
5) Generative Sample Size and Hardware: Experiment E6 sampled 5,000 molecules per model (15,000 total) and ran on Apple Silicon (MPS), whereas shadow training was conducted on CUDA Tesla T4. Statistical tests confirm that verbatim replication differences are not statistically significant ($p > 0.05$).
6) DP-SGD Utility Collapse: The DP-SGD arm represents a preliminary run with utility collapse: chemical validity evaluations were not recorded in the released summary, preliminary runs suffered severe utility degradation and generated strings failed standard valence checks, and privacy accounting logs and accountant state deserialization were not independently verified. Achieving an AUC of ~ 0.5 in a model lacking chemical generation utility does not demonstrate a practical defense.
7) Lack of From-Scratch Control: The pretrain $\rightarrow$ finetune experiment lacks an exact from-scratch baseline trained for 20 epochs on 10,000 molecules, preventing full disentanglement of pretraining effects from training duration.

7 Conclusion

This preliminary study audited membership leakage in small SMILES language models. We observed that under canonical queries and likelihood access, models overfit over 60 epochs, enabling calibrated LiRA attacks to reach an AUC of 0.898. However, memorization is strongly coupled to canonical string representations: evaluating models with randomized SMILES variants or training with randomized augmentation suppresses attack AUC to near baseline levels ($0.51 - 0.55$). While DP-SGD mathematically bounds gradient leakage, current preliminary implementations suffer from severe utility collapse in small chemical sequence models; AUC ~ 0.5 in an invalid generator is not evidence of a useful defense. Future work must investigate scaling laws on larger architectures, higher-power generative sampling, and privacy-preserving training that maintains chemical validity.

References

[1] D. Weininger, "Smiles, a chemical language and information system. 1. introduction to methodology and encoding rules," Journal of Chemical Information and Computer Sciences, vol. 28, no. 1, pp. 31–36, 1988.
[2] R. Shokri, M. Stronati, C. Song, and V. Shmatikov, "Membership inference attacks against machine learning models," IEEE Symposium on Security and Privacy (S&P), pp. 3–18, 2017.
[3] G. W. Bemis and M. A. Murcko, "The properties of known drugs. 1. molecular frameworks," Journal of Medicinal Chemistry, vol. 39, no. 15, pp. 2887–2893, 1996.
[4] N. Carlini, S. Chien, M. Nasr, S. Song, A. Terzis, and F. Tramer, "Membership inference attacks from first principles," IEEE Symposium on Security and Privacy (S&P), pp. 1897–1914, 2022.
[5] D. Polykovskiy, A. Zhebrak, B. Sanchez-Lengeling, S. Golovanov, O. Tatanov, S. Belyaev, R. Krotov, Y. Shabalin, D. Yanakar, A. Aspuru-Guzik et al., "Molecular sets (moses): A benchmarking platform for molecular generation models," Frontiers in Pharmacology, vol. 11, p. 565644, 2020.
[6] A. Yousefpour, I. Shintre, A. Serrano, P. Overman, S. Zhao, H. Yang, H. Zou, N. Zhang, C. Biron, S. Gopi et al., "Opacus: User-friendly differential privacy library in pytorch," arXiv preprint arXiv:2109.12298, 2021.
[7] J. Zhang, D. Das, G. Kamath, and F. Tramèr, "Membership inference attacks cannot prove that a model was trained on your data," arXiv preprint arXiv:2409.19798, 2024.
[8] F. P. Krüger, J. Östman, L. Mervin, I. V. Tetko, and O. Engkvist, "Publishing neural networks in drug discovery might compromise training data privacy," Journal of Cheminformatics, vol. 17, no. 1, p. 38, 2025.
[9] E. Aubinais, P. Formont, P. Piantanida, and E. Gassiat, "Membership inference risks in quantized models: A theoretical and empirical study," in International Conference on Artificial Intelligence and Statistics (AISTATS), 2026.
[10] J. Ross, B. Belgodere, S. C. Hoffman, V. Chenthamarakshan, J. Navratil, Y. Mroueh, and P. Das, "Gp-molformer: a foundation model for molecular generation," Digital Discovery, vol. 4, no. 10, pp. 2684–2696, 2025.
[11] A. Nemecek, W. Li, X. Jiang, J. Vaidya, and E. Ayday, "Quantifying memorization and privacy risks in genomic language models," arXiv preprint arXiv:2603.08913, 2026.
[12] J. Arús-Pous, S. V. Johansson, O. Prykhodko, E. J. Bjerrum, C. Tyrchan, J.-L. Reymond, H. Chen, and O. Engkvist, "Randomized SMILES strings improve the quality of molecular generative models," Journal of Cheminformatics, vol. 11, no. 1, p. 71, 2019.
[13] E. J. Bjerrum, "Smiles enumeration as data augmentation for neural network modeling of molecules," arXiv preprint arXiv:1703.07076, 2017.
[14] M. Abadi, A. Chu, I. Goodfellow, H. B. McMahan, I. Mironov, K. Talwar, and L. Zhang, "Deep learning with differential privacy," in Proceedings of the 2016 ACM SIGSAC conference on computer and communications security, 2016, pp. 308–318.