

Question: 1:

Write Java code to define List . Insert 5 floating point numbers in List, and using an iterator, find the sum of the numbers in List.

```
package collectionAssignment;

import java.util.ArrayList;
import java.util.Iterator;
import java.util.Scanner;

public class Ques1 {
    public static void main(String[] args) {
        ArrayList<Float> floatList = new ArrayList<>();
        Scanner in = new Scanner(System.in);
        for (int i = 0; i < 5; i++) {
            floatList.add(in.nextFloat());
        }

        Iterator<Float> it = floatList.iterator();
        float sum = 0;
        while(it.hasNext()){
            sum += it.next();
        }

        System.out.println("Sum : "+sum);
    }
}
```

```
/home/ankit/.sdkman/candidates/java/8.0.242-zulu/bin/java ...
```

```
5
```

```
4
```

```
6
```

```
7
```

```
8
```

```
Sum : 30.0
```

```
Process finished with exit code 0
```

Question: 2:

Write a method that takes a string and returns the number of unique characters in the string.

```

package collectionAssignment;

import java.util.HashMap;
import java.util.Scanner;

public class Ques2 {
    public static void main(String[] args) {
        Scanner in = new Scanner(System.in);
        String str = in.nextLine();
        System.out.println(uniqueChar(str.toCharArray()));
    }

    static int uniqueChar(char[] arr){
        int uniqueCount = 0;
        HashMap<Character,Integer> hash = new HashMap<>();
        for (char c : arr) {
            if(hash.containsKey(c)){
                hash.put(c,hash.get(c)+1);
            } else{
                hash.put(c,1);
            }
        }

        for (Character k : hash.keySet()) {
            uniqueCount += hash.get(k)==1 ? 1 : 0;
        }

        return uniqueCount;
    }
}

```

```

/home/ankit/.sdkman/candidates/java/8.0.242-zulu/bin/java ...
abbccdef
4

Process finished with exit code 0
|

```

Question: 3:

Write a method that takes a string and print the number of occurrence of each character characters in the string.

```

package collectionAssignment;

import java.util.HashMap;
import java.util.Map;
import java.util.Scanner;

public class Ques3 {
    public static void main(String[] args) {
        Scanner in = new Scanner(System.in);
        String str = in.nextLine();
        Map<Character,Integer> totalOccurrences = occurrences(str.toCharArray());
        for (Character k : totalOccurrences.keySet()) {
            System.out.println(k+" : " + totalOccurrences.get(k));
        }
    }

    static HashMap occurrences(char[] arr){
        HashMap<Character,Integer> hash = new HashMap<>();
        for (char c : arr) {
            if(hash.containsKey(c)){
                hash.put(c,hash.get(c)+1);
            } else{
                hash.put(c,1);
            }
        }
        return hash;
    }
}

```

```

/home/ankit/.sdkman/candidates/java/8.0.242-zulu/bin/java ...

```

```

abbcdfeaafe

```

```

a : 3

```

```

b : 2

```

```

c : 1

```

```

d : 1

```

```

e : 2

```

```

f : 2

```

```

Process finished with exit code 0

```

Question: 4:

Write a program to sort HashMap by value.

```

/home/ankit/.sdkman/candidates/java/8.0.242-zulu/bin/java ...

```

```

-----
Original Values
-----

```

```

{Key274=274, Key351=351, Key588=588, Key977=977, Key170=170, Key139=139, Key723=723, Key382=382, Key20=20, Key44=44}
-----

```

```

Sorted Values
-----

```

```

{Key139=139, Key170=170, Key20=20, Key274=274, Key351=351, Key382=382, Key44=44, Key588=588, Key723=723, Key977=977}
-----

```

```

Process finished with exit code 0

```

Question: 5:

Write a program to sort Employee objects based on highest salary using Comparator. Employee class{ Double Age; Double Salary; String Name

```
package collectionAssignment;

import java.util.*;

class Employee {
    Double age;
    Double salary;
    String name;

    public Employee(Double age, Double salary, String name) {
        this.age = age;
        this.salary = salary;
        this.name = name;
    }

    @Override
    public String toString() {
        return "Employee{" + "age=" + age + ", salary=" + salary + ", name='" + name + '\'' + '}';
    }
}
```

```
public class Ques5 {
    public static void main(String[] args) {
        List<Employee> empList = new ArrayList<>(initialCapacity: 10);
        Random rand = new Random();
        for (int i = 0; i < 10; i++) {
            empList.add(new Employee(
                age: (double) rand.nextInt( bound: 30)+20,
                salary: (double) rand.nextInt( bound: 20000)+10000,
                name: "Name" + (i + 1))
            );
        }

        for (Employee employee : empList) {
            System.out.println(employee);
        }

        Collections.sort(empList, new Comparator<Employee>() {
            @Override
            public int compare(Employee o1, Employee o2) {
                int ret = 0;
                ret = o1.salary > o2.salary ? 1 : -1;
                return ret;
            }
        });
    }
}
```

```

        System.out.println("-----");
        System.out.println("Sorted");
        System.out.println("-----");
        for (Employee employee : empList) {
            System.out.println(employee);
        }
    }
}

```

```
/home/ankit/.sdkman/candidates/java/8.0.242-zulu/bin/java ...
```

```
Employee{age=31.0, salary=19166.0, name='Name1'}
Employee{age=33.0, salary=22177.0, name='Name2'}
Employee{age=38.0, salary=22144.0, name='Name3'}
Employee{age=38.0, salary=25145.0, name='Name4'}
Employee{age=48.0, salary=15410.0, name='Name5'}
Employee{age=46.0, salary=17382.0, name='Name6'}
Employee{age=36.0, salary=29441.0, name='Name7'}
Employee{age=22.0, salary=12299.0, name='Name8'}
Employee{age=39.0, salary=26924.0, name='Name9'}
Employee{age=47.0, salary=26589.0, name='Name10'}
```

Sorted

```
Employee{age=22.0, salary=12299.0, name='Name8'}
Employee{age=48.0, salary=15410.0, name='Name5'}
Employee{age=46.0, salary=17382.0, name='Name6'}
Employee{age=31.0, salary=19166.0, name='Name1'}
Employee{age=38.0, salary=22144.0, name='Name3'}
Employee{age=33.0, salary=22177.0, name='Name2'}
Employee{age=38.0, salary=25145.0, name='Name4'}
Employee{age=47.0, salary=26589.0, name='Name10'}
Employee{age=39.0, salary=26924.0, name='Name9'}
Employee{age=36.0, salary=29441.0, name='Name7'}
```

Process finished with exit code 0

Question: 6:

Write a program to sort the Student objects based on Score , if the score are same then sort on First Name . Class Student{ String Name; Double Score; Double Age

```

package collectionAssignment;
import java.util.*;

class Student {
    String name;
    Double score;
    Double age;

    public Student(Double age, Double score, String name) {
        this.name = name;
        this.score = score;
        this.age = age;
    }

    @Override
    public String toString() {
        return "Student{" + "name='" + name + '\'' + ", score=" + score + ", age=" + age + '}';
    }
}

public class Ques6 {
    public static void main(String[] args) {
        List<Student> studList = new ArrayList<>( initialCapacity: 10);
        Random rand = new Random();
        for (int i = 0; i < 10; i++) {
            studList.add(new Student(
                age: (double) rand.nextInt( bound: 30) + 20,
                score: (double) rand.nextInt( bound: 20)+20,
                name: "Name" + (i + 1))
            );
        }
    }
}

```

```

        for (Student student : studList) {
            System.out.println(student);
        }

        Collections.sort(studList, new Comparator<Student>() {
            @Override
            public int compare(Student o1, Student o2) {
                int ret = 0;
                if(o1.score==o2.score){
                    ret = o1.name.compareTo(o2.name);
                }
                ret = o1.score > o2.score ? 1 : -1;
                return ret;
            }
        });

        System.out.println("-----");
        System.out.println("Sorted");
        System.out.println("-----");

        for (Student student : studList) {
            System.out.println(student);
        }
    }
}

```

```
/home/ankit/.sdkman/candidates/java/8.0.242-zulu/bin/java ...
```

```
Student{name='Name1', score=31.0, age=32.0}  
Student{name='Name2', score=35.0, age=38.0}  
Student{name='Name3', score=38.0, age=45.0}  
Student{name='Name4', score=33.0, age=25.0}  
Student{name='Name5', score=36.0, age=46.0}  
Student{name='Name6', score=24.0, age=34.0}  
Student{name='Name7', score=32.0, age=48.0}  
Student{name='Name8', score=22.0, age=46.0}  
Student{name='Name9', score=34.0, age=46.0}  
Student{name='Name10', score=32.0, age=25.0}
```

```
-----  
Sorted
```

```
-----  
Student{name='Name8', score=22.0, age=46.0}  
Student{name='Name6', score=24.0, age=34.0}  
Student{name='Name1', score=31.0, age=32.0}  
Student{name='Name10', score=32.0, age=25.0}  
Student{name='Name7', score=32.0, age=48.0}  
Student{name='Name4', score=33.0, age=25.0}  
Student{name='Name9', score=34.0, age=46.0}  
Student{name='Name2', score=35.0, age=38.0}  
Student{name='Name5', score=36.0, age=46.0}  
Student{name='Name3', score=38.0, age=45.0}
```

```
Process finished with exit code 0
```

```
|
```

Question: 7:

Print the elements of an array in the decreasing frequency if 2 numbers have same frequency then print the one which came first.

Question: 8:

Design a Data Structure SpecialStack that supports all the stack operations like push(), pop(), isEmpty(), isFull() and an additional operation getMin() which should return minimum element from the SpecialStack. (Expected complexity  $O(1)$ )