

f

X

Y

in

ig

- C Library - <signal.h>
- C Library - <stdalign.h>
- C Library - <stdarg.h>
- C Library - <stdbool.h>
- C Library - <stddef.h>
- C Library - <stdio.h>
- C Library - <stdlib.h>
- C Library - <string.h> →
- C Library - <tgmath.h>
- C Library - <time.h>
- C Library - <wctype.h>
- C Library - Quick Guide
- C Library - Useful Resources
- C Library - Discussion

C Programming Resources

C Library - <string.h>

tutorialspoint

Learn Business Analytics

Get Certified

< Previous

Quiz

Next >

The **string.h** header defines one variable type, one macro, and various functions for manipulating arrays of characters.

Library Variables

Following is the variable type defined in the header string.h –

Sr.No.	Variable & Description
1	size_t This is the unsigned integral type and is the result of the sizeof keyword.

C Library string.h Macros

Following is the macro defined in the header string.h –

Sr.No.	Macro & Description
1	NULL This macro is the value of a null pointer constant.

C Library string.h Functions

Following are the functions defined in the header string.h –

Sr.No.	Function & Description
1	void *memchr(const void *str, int c, size_t n) Searches for the first occurrence of the character c (an unsigned char) in the first n bytes of the string pointed to, by the argument str.
2	int memcmp(const void *str1, const void *str2, size_t n) Compares the first n bytes of str1 and str2.
3	void *memcpy(void *dest, const void *src, size_t n) Copies n characters from src to dest.
4	void *memmove(void *dest, const void *src, size_t n) Another function to copy n characters from str2 to str1.
5	void *memset(void *str, int c, size_t n) Copies the character c (an unsigned char) to the first n characters of the string pointed to, by the argument str.
6	char *strcat(char *dest, const char *src) Appends the string pointed to, by src to the end of the string pointed to by dest.
7	char *strncat(char *dest, const char *src, size_t n) Appends the string pointed to, by src to the end of the string pointed to, by dest up to n characters long.
8	char *strchr(const char *str, int c) Searches for the first occurrence of the character c (an unsigned char) in the string pointed to, by the argument str.
9	int strcmp(const char *str1, const char *str2) Compares the string pointed to, by str1 to the string pointed to by str2.
10	int strncmp(const char *str1, const char *str2, size_t n) Compares at most the first n bytes of str1 and str2.
11	int strcoll(const char *str1, const char *str2) Compares string str1 to str2. The result is dependent on the LC_COLLATE setting of the location.
12	char *strcpy(char *dest, const char *src) Copies the string pointed to, by src to dest.
13	char *strncpy(char *dest, const char *src, size_t n) Copies up to n characters from the string pointed to, by src to dest.
14	size_t strcspn(const char *str1, const char *str2) Calculates the length of the initial segment of str1 which consists entirely of characters not in str2.
15	char *strerror(int errnum) Searches an internal array for the error number errnum and returns a pointer to an error message string.
16	size_t strlen(const char *str) Computes the length of the string str up to but not including the terminating null character.
17	char *strpbrk(const char *str1, const char *str2) Finds the first character in the string str1 that matches any character specified in str2.
18	char *strrchr(const char *str, int c) Searches for the last occurrence of the character c (an unsigned char) in the string pointed to by the argument str.
19	size_t strspn(const char *str1, const char *str2) Calculates the length of the initial segment of str1 which consists entirely of characters in str2.
20	char *strstr(const char *haystack, const char *needle) Finds the first occurrence of the entire string needle (not including the terminating null character) which appears in the string haystack.
21	char *strtok(char *str, const char *delim) Breaks string str into a series of tokens separated by delim.
22	size_t strxfrm(char *dest, const char *src, size_t n) Transforms the first n characters of the string src into current locale and places them in the string dest .

Print Page

< Previous

Next >

Advertisements

Own now at ₹ 4862/month*

Own now at ₹ 4862/month*

TOP TUTORIALS

Python Tutorial

Java Tutorial

C++ Tutorial

C Programming Tutorial

C# Tutorial

PHP Tutorial

R Tutorial

HTML Tutorial

CSS Tutorial

JavaScript Tutorial

SQL Tutorial

TRENDING TECHNOLOGIES

Cloud Computing Tutorial

Amazon Web Services Tutorial

Microsoft Azure Tutorial

Git Tutorial

Ethical Hacking Tutorial

Docker Tutorial

Kubernetes Tutorial

DSA Tutorial

Spring Boot Tutorial

SDLC Tutorial

Unix Tutorial

CERTIFICATIONS

Business Analytics Certification

Java & Spring Boot Advanced Certification

Data Science Advanced Certification

Cloud Computing And DevOps

Advanced Certification In Business Analytics

Artificial Intelligence And Machine Learning

DevOps Certification

Game Development Certification

Front-End Developer Certification

AWS Certification Training

Python Programming Certification

COMPILERS & EDITORS

Online Java Compiler

Online Python Compiler

Online Go Compiler

Online C Compiler

Online C++ Compiler

Online C# Compiler

Online PHP Compiler

Online MATLAB Compiler

Online Bash Terminal

Online SQL Compiler

Online Html Editor

ABOUT US |

OUR TEAM |

CAREERS |

JOBS |

CONTACT US |

TERMS OF USE |

PRIVACY POLICY |

REFUND POLICY |

COOKIES POLICY |

FAQ'S

tutorialspoint

f

X

Y

in

ig

Google Play

App Store

Tutorials Point is a leading Ed Tech company striving to provide the best learning material on technical and non-technical subjects.

© Copyright 2025. All Rights Reserved.