

DML

Sr. No	List of Practical Experiments
1	Write a program to implement Simple Linear Regression
2	Write a program to implement multiple Linear Regression
3	Write a program to implement K-nearest Neighbors (K-NN)/SVM
4	Write a program to implement Naïve Bayse / DT
5	Write a program to implement K-means clustering.
6	Write a program to implement Hierarchical clustering.
7	Write a program to build ANN.
8	Write a program to build CNN.
9	
10	

Practical 1

Aim: Write a program to implement Simple Linear Regression

Code:

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd

dataset = pd.read_csv("Salary_Data.csv")
X = dataset.iloc[:, :-1].values
y = dataset.iloc[:, -1].values

print(X)
print("\n\n\n")
print(y)

from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 1/4, random_state = 0)

print(X_train)
print("\n\n\n")
print(X_test)
print("\n\n\n")
print(y_train)
print("\n\n\n")
print(y_test)

from sklearn.linear_model import LinearRegression
linear_regression = LinearRegression()
linear_regression.fit(X_train, y_train)

y_train_pred =
linear_regression.predict(X_train)y_test_pred =
linear_regression.predict(X_test)

plt.scatter(X_train, y_train, color = "green", marker = "+", label = "Observed data")
plt.plot(X_train, y_train_pred, color = "red", label = "Predicted data")
plt.xlabel("Years of experience")
plt.ylabel("Salary")
plt.title("Years of experience v/s Salary (Training dataset)")
plt.legend()
plt.show()

plt.scatter(X_test, y_test, color = "green", marker = "+", label = "Observed
```


```
data")plt.plot(X_test, y_test_pred, color = "red", label = "Predicted data")  
plt.xlabel("Years of experience")  
plt.ylabel("Salary")  
plt.title("Years of experience v/s Salary (Testing dataset)")
```


```
plt.legend()  
plt.show()
```

Output:

```
[[ 1.1]  
[ 1.3]  
[ 1.5]  
[ 2. ]  
[ 2.2]  
[ 2.9]  
[ 3. ]  
[ 3.2]  
[ 3.2]  
[ 3.7]  
[ 3.9]  
[ 4. ]  
[ 4. ]  
[ 4.1]  
[ 4.5]  
[ 4.9]  
[ 5.1]  
[ 5.3]
```

```
[[ 5.3]  
[ 7.9]  
[ 2.9]  
[ 5.1]  
[ 3.2]  
[ 4.5]  
[ 8.2]  
[ 6.8]  
[ 1.3]  
[10.5]  
[ 3. ]  
[ 2.2]  
[ 5.9]  
[ 6. ]
```





Practical 2

Aim: Write a program to implement multiple Linear Regression

Code:

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd

dataset = pd.read_csv('/content/50_Startups-2.csv')
x = dataset.iloc[:, :-1].values
y = dataset.iloc[:, -1].values

print(x)

print(y)

from sklearn.compose import ColumnTransformer
from sklearn.preprocessing import OneHotEncoder
ct = ColumnTransformer(transformers=[('encoder', OneHotEncoder(), [3])],
remainder='passthrough')
x = np.array(ct.fit_transform(x))

print(x)

from sklearn.model_selection import train_test_split
x_train, x_test, y_train, y_test = train_test_split(x, y, test_size=0.2, random_state=0)

from sklearn.linear_model import LinearRegression
regressor = LinearRegression()
regressor.fit(x_train, y_train)

y_pred =
regressor.predict(x_test)
```

```
np.set_printoptions(precision=2)
print(np.concatenate((y_pred.reshape(len(y_pred),1), y_test.reshape(len(y_test),1)),1))
```

OUTPUT:-

```

[[165349.2 136897.8 471784.1 'New York']
[162597.7 151377.59 443898.53 'California']
[153441.51 101145.55 407934.54 'Florida']
[144372.41 118671.85 383199.62 'New York']
[142107.34 91391.77 366168.42 'Florida']
[131876.9 99814.71 362861.36 'New York']
[134615.46 147198.87 127716.82 'California']
[130298.13 145530.06 323876.68 'Florida']
[120542.52 148718.95 311613.29 'New York']
[123334.88 108679.17 304981.62 'California']
[101913.08 110594.11 229160.95 'Florida']
[100671.96 91790.61 249744.55 'California']
[93863.75 127320.38 249839.44 'Florida']
[91992.39 135495.07 252664.93 'California']
[119943.24 156547.42 256512.92 'Florida']
[114523.61 122616.84 261776.23 'New York']
[78013.11 121597.55 264346.06 'California']
[94657.16 145077.58 282574.31 'New York']
[91749.16 114175.79 294919.57 'Florida']
[86419.7 153514.11 0.0 'New York']
[76253.86 113867.3 298664.47 'California']
[78389.47 153773.43 299737.29 'New York']
[73004.56 122782.75 302310.26 'Florida']

```

```

[192261.83 191792.06 191050.39 182901.99 166187.94 156991.12 156122.51
155752.6 152211.77 149759.96 146121.95 144259.4 141585.52 134307.35
132602.65 129917.04 126992.93 125370.37 124266.9 122776.86 118474.03
111313.02 110352.25 108733.99 108552.04 107404.34 105733.54 105008.31
103282.38 101004.64 99937.59 97483.56 97427.84 96778.92 96712.8
96479.51 90708.19 89949.14 81229.06 81005.76 78239.91 77798.83
71498.49 69758.98 65200.33 64926.08 49490.75 42559.73 35673.41
14681.4 ]

```

```

[[0.0 0.0 1.0 165349.2 136897.8 471784.1]
[1.0 0.0 0.0 162597.7 151377.59 443898.53]
[0.0 1.0 0.0 153441.51 101145.55 407934.54]
[0.0 0.0 1.0 144372.41 118671.85 383199.62]
[0.0 1.0 0.0 142107.34 91391.77 366168.42]
[0.0 0.0 1.0 131876.9 99814.71 362861.36]
[1.0 0.0 0.0 134615.46 147198.87 127716.82]
[0.0 1.0 0.0 130298.13 145530.06 323876.68]
[0.0 0.0 1.0 120542.52 148718.95 311613.29]
[1.0 0.0 0.0 123334.88 108679.17 304981.62]
[0.0 1.0 0.0 101913.08 110594.11 229160.95]
[1.0 0.0 0.0 100671.96 91790.61 249744.55]
[0.0 1.0 0.0 93863.75 127320.38 249839.44]
[1.0 0.0 0.0 91992.39 135495.07 252664.93]
[0.0 1.0 0.0 119943.24 156547.42 256512.92]
[0.0 0.0 1.0 114523.61 122616.84 261776.23]
[1.0 0.0 0.0 78013.11 121597.55 264346.06]
[0.0 0.0 1.0 94657.16 145077.58 282574.31]

```

```

[[103015.2 103282.38]
[132582.28 144259.4 ]
[132447.74 146121.95]
[ 71976.1 77798.83]
[178537.48 191050.39]
[116161.24 105008.31]
[ 67851.69 81229.06]
[ 98791.73 97483.56]
[113969.44 110352.25]
[167921.07 166187.94]]

```

Practical 3

Aim: Write a program to implement K-nearest Neighbors (K-NN)/SVM

Code:

```
import matplotlib.pyplot as plt
import numpy as np
import pandas as pd

dataset =
pd.read_csv('/content/Social_Network_Ads.csv')
x = dataset.iloc[:, :-1].values
y = dataset.iloc[:, -1].values

print(x)

print(y)

from sklearn.model_selection import train_test_split
x_train, x_test, y_train, y_test = train_test_split(x, y, test_size=0.25, random_state=0)

print(x_train)

print(y_train)

print(x_test)

print(y_test)

from sklearn.preprocessing import
StandardScaler
sc = StandardScaler()
x_train = sc.fit_transform(x_train)
x_test = sc.transform(x_test)

print(x_train)

print(x_test)

from sklearn.svm import SVC
classifier = SVC(kernel='linear', random_state=0)
classifier.fit(x_train, y_train)

print(classifier.predict(sc.transform([[30,200000]])))
```


OUTPUT:-

```
y_pred = classifier.predict(x_test)
print(np.concatenate((y_pred.reshape(len(y_pred),1), y_test.reshape(len(y_test),1)),1))
```

```

from sklearn.metrics import confusion_matrix,
accuracy_scorecm = confusion_matrix(y_test, y_pred)
print(cm)
accuracy_score(y_test,
y_pred)

```

Output:

```

[[ 19 19000]
 [ 35 20000]
 [ 26 43000]
 [ 27 57000]
 [ 19 76000]
 [ 27 58000]
 [ 27 84000]
 [ 32 150000]
 [ 25 33000]
 [ 35 65000]
 [ 26 80000]
 [ 26 52000]
 [ 20 86000]

```

```

[0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 1 1 1 1 1 1 1 1 1 1 1 0 0 0 0 1 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0
0 1 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 1 0
0 0 0 0 0 0 0 0 0 0 0 0 0 1 1 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 0 1 0 1 0 1 0 1 1 0 0 0 1 0 0 0 1 0 1
1 1 0 0 1 1 0 1 1 0 1 1 0 1 0 0 0 0 1 1 0 1 1 0 1 0 1 0 1 0 1 0 0 1 1 0 1 0 0 1
1 0 1 1 0 1 1 0 0 1 0 0 1 1 1 1 1 0 1 1 1 1 0 1 1 0 1 0 1 0 1 1 1 1 1 0 0 0
1 1 0 1 1 1 1 1 0 0 0 1 1 0 0 1 0 1 0 1 1 0 1 0 1 1 0 1 1 0 0 0 1 1 0 1 0
0 1 0 1 0 0 1 1 0 0 1 1 0 1 1 0 0 1 0 1 0 1 1 1 0 1 0 1 1 1 0 1 1 1 1 0 1
1 1 0 1 0 1 0 0 1 1 0 1 1 1 1 1 0 1 1 1 1 1 0 1 1 1 0 1 1]

```

```

[[ 44 39000]
 [ 32 120000]
 [ 38 50000]
 [ 32 135000]
 [ 52 21000]
 [ 53 104000]
 [ 39 42000]
 [ 38 61000]
 [ 36 50000]
 [ 36 63000]
 [ 35 25000]
 [ 35 50000]
 [ 42 73000]
 [ 47 49000]
 [ 50 70000]

```

```

[0 1 0 1 1 1 0 0 0 0 0 0 1 1 1 0 1 0 0 0 1 0 1 0 1 0 0 0 1 1 1 1 0 1 0 1 0 0 1
0 0 1 0 0 0 0 0 0 1 1 1 1 0 0 0 0 1 0 1 0 1 0 0 0 1 0 0 0 0 1 0 0 0 1 0 0 1 0 1
1 1 0 0 1 1 0 0 1 1 0 1 0 0 1 1 0 1 1 1 0 0 0 0 0 0 1 0 0 1 1 1 1 1 0 1 1 0 1 1 0
1 0 0 0 0 0 0 0 1 1 0 0 1 0 0 1 0 0 0 0 1 0 0 1 1 0 1 0 0 0 0 1 0 0 0 1 1 0 0
0 0 1 0 1 0 0 0 0 1 0 0 0 0 1 1 1 0 0 0 0 0 0 0 1 1 1 1 0 1 0 0 0 0 0 0 1 0 0
0 0 0 0 1 1 0 1 0 1 0 0 1 0 0 0 0 1 0 0 0 0 0 0 1 0 0 1 1 0 0 0 0 0 0
0 1 1 0 0 0 0 1 0 0 0 0 1 0 1 0 1 0 0 0 1 0 0 0 1 0 1 0 0 0 0 0 1 1 0 0 0
0 0 1 0 1 1 0 0 0 0 0 1 0 1 0 0 1 0 0 1 0 0 0 0 0 1 1 1 1 0 0 0 0 0 1
0 0 0 0]

```

```

[[ 30 87000]
 [ 38 50000]
 [ 35 75000]
 [ 30 79000]
 [ 35 50000]
 [ 27 20000]
 [ 31 15000]
 [ 36 144000]
 [ 18 68000]
 [ 47 43000]
 [ 30 49000]
 [ 28 55000]
 [ 37 55000]

```

```

[0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 1 0 0 1 0 1 0 1 0 0 0 0 0 1 1 0 0 0 0
0 0 1 0 0 0 0 1 0 0 1 0 1 1 0 0 0 0 1 1 0 0 0 1 0 0 1 0 1 0 1 0 0 0 0 1 0 0 1
0 0 0 0 1 1 1 0 0 0 1 1 0 1 1 0 0 1 0 0 0 1 0 1 1 1]

```

```

[[ 0.58164944 -0.88670699]
 [-0.60673761 1.46173768]
 [-0.01254409 -0.5677824 ]
 [-0.60673761 1.89663484]
 [ 1.37390747 -1.40858358]
 [ 1.47293972 0.99784738]
 [ 0.08648817 -0.79972756]
 [-0.01254409 -0.24885782]
 [-0.21060859 -0.5677824 ]
 [-0.21060859 -0.19087153]
 [-0.30964085 -1.29261101]
 [-0.30964085 -0.5677824 ]
 [ 0.38358493 0.09905991]
 [ 0.8787462 -0.59677555]
 [ 2.06713324 -1.17663843]
 [ 1.07681071 -0.132885241]

```

```

[[-0.80480212 0.50496393]
 [-0.01254409 -0.5677824 ]
 [-0.30964085 0.1570462 ]
 [-0.80480212 0.27301877]
 [-0.30964085 -0.5677824 ]
 [-1.10189888 -1.43757673]
 [-0.70576986 -1.58254245]
 [-0.21060859 2.15757314]
 [-1.99318916 -0.04590581]
 [ 0.8787462 -0.77073441]
 [-0.80480212 -0.59677555]

```

```

[[0 0]
 [0 0]
 [0 0]
 [0 0]
 [0 0]
 [0 0]
 [0 0]
 [1 1]
 [0 0]
 [0 0]
 [0 0]
 [0 0]
 [0 0]

```

```
: from sklearn.metrics import confusion_matrix, accuracy_score  
cm = confusion_matrix(y_test, y_pred)  
print(cm)  
accuracy_score(y_test, y_pred)
```

```
[[66  2]  
 [ 8 24]]
```

```
: 0.9
```

Practical 4

Aim: Write a program to implement Naïve Bayse / DT

Code:

```
import matplotlib.pyplot as
pltimport pandas as pd
import numpy as np

dataset =
pd.read_csv('/content/Social_Network_Ads.csv')x =
dataset.iloc[:, :-1].values
y = dataset.iloc[:, -1].values

print(x)

print(y)

from sklearn.model_selection import train_test_split
x_train, x_test, y_train, y_test = train_test_split(x, y, test_size=0.25, random_state=0)

print(x_train)

print(y_train)

print(x_test)

print(y_test)

from sklearn.preprocessing import
StandardScaler
sc = StandardScaler()
x_train = sc.fit_transform(x_train)
x_test = sc.transform(x_test)

print(x_train)

print(x_test)

from sklearn.neighbors import KNeighborsClassifier
classifier = KNeighborsClassifier(n_neighbors=5, metric='minkowski', p=2)
classifier.fit(x_train, y_train)

print(classifier.predict(sc.transform([[40, 200000]])))

y_pred = classifier.predict(x_test)
print(np.concatenate((y_pred.reshape(len(y_pred),1),
```

ANKIT.J

Roll no -540

```
y_test.reshape(len(y_test),1),1))from sklearn.metrics import confusion_matrix,  
accuracy_score
```

```
cm = confusion_matrix(y_test, y_pred)
print(cm)
accuracy_score(y_test, y_pred)
```

Output:

```
[[ 19 19000]
 [ 35 20000]
 [ 26 43000]
 [ 27 57000]
 [ 19 76000]
 [ 27 58000]
 [ 27 84000]
 [ 32 150000]
 [ 25 33000]
 [ 35 65000]
 [ 26 80000]
 [ 26 520000]
```

```
[0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 1 1 1 1 1 1 1 1 1 1 1 0 0 0 0 1 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0
0 1 0 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 1 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 1 0
0 0 0 0 0 0 0 0 0 0 0 0 0 1 1 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 0 1 0 1 0 1 0 1 1 0 0 0 0 1 0 0 0 0 1 0 1
1 1 0 0 1 1 0 1 1 0 1 1 0 1 0 0 0 0 1 1 0 1 1 0 1 0 1 0 1 0 0 0 1 1 0 1 0 0 0 1
1 0 1 1 0 1 1 0 0 1 0 0 1 1 1 1 1 0 1 1 1 1 0 1 1 0 1 0 1 0 1 0 1 1 1 1 0 0 0 0
1 1 0 1 1 1 1 1 0 0 0 0 1 1 0 0 0 1 0 1 0 1 1 0 1 0 1 1 0 1 1 0 0 0 0 1 1 0 1 0
0 1 0 1 0 0 1 1 0 0 0 1 1 0 1 1 0 0 0 1 0 1 0 1 1 1 0 1 0 1 1 1 0 1 1 1 0 1 0 1
1 1 0 1 0 1 0 0 0 1 1 0 1 1 1 1 1 1 0 0 1 1 1 1 1 0 1 1 1 0 1]
```

```
[[ 44 39000]
 [ 32 120000]
 [ 38 50000]
 [ 32 135000]
 [ 52 21000]
 [ 53 104000]
 [ 39 42000]
 [ 38 61000]
 [ 36 50000]
 [ 36 63000]
 [ 35 25000]
 [ 35 50000]
 [ 42 73000]
 [ 47 49000]
 [ 59 29000]
```

```
[0 1 0 1 1 1 0 0 0 0 0 0 0 1 1 1 0 1 0 0 0 1 0 1 0 1 0 0 0 1 1 1 1 0 1 0 1 0 0 0 1
0 0 1 0 0 0 0 0 0 1 1 1 1 0 0 0 0 1 0 1 0 1 0 0 1 0 0 0 0 1 0 0 0 0 1 1 0 0 1 0 1
1 1 0 0 0 1 1 0 0 0 1 1 0 1 0 0 0 1 1 0 1 1 1 0 0 0 0 0 0 1 0 0 0 1 1 1 1 0 1 1 0 1 1 0
1 0 0 0 0 0 0 0 0 1 1 0 0 0 1 0 0 0 1 0 0 0 0 1 0 1 1 0 1 0 0 0 0 0 1 0 0 0 0 1 1 0 0
0 0 1 0 1 0 0 0 0 1 0 0 0 0 0 1 1 1 0 0 0 0 0 0 0 1 1 1 1 1 0 1 0 0 0 0 0 0 1 0 0
0 0 0 0 0 1 1 0 1 0 1 0 0 0 1 0 0 0 0 0 0 1 0 0 0 0 0 0 1 0 1 1 0 0 0 0 0 0
0 1 1 0 0 0 0 0 1 0 0 0 0 0 1 0 1 0 1 0 0 0 0 1 0 0 0 0 0 1 0 1 0 0 0 0 0 1 1 0 0 0
0 0 1 0 1 1 0 0 0 0 0 0 1 0 1 0 0 1 0 0 0 1 0 1 0 0 0 0 0 0 0 1 1 1 1 0 0 0 0 0 1
0 0 0 0]
```

```
[[ 30 87000]
 [ 38 50000]
 [ 35 75000]
 [ 30 79000]
 [ 35 50000]
 [ 27 20000]
 [ 31 15000]
 [ 36 144000]
 [ 18 68000]
 [ 47 43000]
```

```
[0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 1 0 0 1 0 1 0 1 0 0 0 0 0 1 1 0 0 0 0
0 0 1 0 0 0 0 1 0 0 1 0 1 1 0 0 0 1 1 0 0 1 0 0 1 0 1 0 1 0 0 0 0 1 0 0 1
0 0 0 0 1 1 1 0 0 0 1 1 0 1 1 0 0 1 0 0 0 1 0 1 1 1]
```

```
[[ 0.58164944 -0.88670699]
 [-0.60673761 1.46173768]
 [-0.01254409 -0.5677824 ]
 [-0.60673761 1.89663484]
 [ 1.37390747 -1.40858358]
 [ 1.47293972 0.99784738]
 [ 0.08648817 -0.79972756]
 [-0.01254409 -0.24885782]
 [-0.21060859 -0.5677824 ]
 [-0.21060859 -0.19087153]
 [-0.30964085 -1.29261101]
 [-0.30964085 -0.5677824 ]
```

```
[[-0.80480212 0.50496393]
 [-0.01254409 -0.5677824 ]
 [-0.30964085 0.1570462 ]
 [-0.80480212 0.27301877]
 [-0.30964085 -0.5677824 ]
 [-1.10189888 -1.43757673]
 [-0.70576986 -1.58254245]
 [-0.21060859 2.15757314]
 [-1.99318916 -0.04590581]
 [ 0.8787462 -0.77073441]
 [-0.80480212 -0.59677555]
 [-1.00286662 -0.42281668]
```

```
from sklearn.metrics import confusion_matrix, accuracy_score
cm = confusion_matrix(y_test, y_pred)
print(cm)
accuracy_score(y_test, y_pred)
```

```
[[64  4]
 [ 3 29]]
```

```
0.93
```


Practical 5

Aim: Write a program to implement K-means clustering.

Code:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt

dataset = pd.read_csv('/content/Mall_Customers.csv')
X = dataset.iloc[:, [3,4]].values

print(X)

from sklearn.cluster import AgglomerativeClustering
hc = AgglomerativeClustering(n_clusters=5, affinity='euclidean', linkage='ward')
y_hc = hc.fit_predict(X)

print(y_hc)

plt.scatter(X[y_hc==0,0], X[y_hc==0,1], s=100, c='red', label='Cluster 1')
plt.scatter(X[y_hc==1,0], X[y_hc==1,1], s=100, c='green', label='Cluster 2')
plt.scatter(X[y_hc==2,0], X[y_hc==2,1], s=100, c='blue', label='Cluster 3')
plt.scatter(X[y_hc==3,0], X[y_hc==3,1], s=100, c='cyan', label='Cluster 4')
plt.scatter(X[y_hc==4,0], X[y_hc==4,1], s=100, c='magenta', label='Cluster 5')
plt.title('Clusters of customers')
plt.xlabel('Annual Income (k$)')
plt.ylabel('Spending Score (1-100)')
plt.legend()
plt.show()
```

Output:

```
[ 15 39]
[ 15 81]
[ 16  6]
[ 16 77]
[ 17 40]
[ 17 76]
[ 18  6]
[ 18 94]
[ 19  3]
[ 19 72]
```

[illegible]

Practical 6

Aim: Write a program to implement Hierarchical clustering.

Code:

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd

dataset = pd.read_csv('Mall_Customers.csv')
X = dataset.iloc[:, [3, 4]].values

from sklearn.cluster import KMeans
kmeans = KMeans(n_clusters = 5, init = 'k-means++', random_state = 42)
y_kmeans = kmeans.fit_predict(X)
print(y_kmeans)

plt.scatter(X[y_kmeans == 0, 0], X[y_kmeans == 0, 1], s = 100, c = 'red', label = 'Cluster 1')
plt.scatter(X[y_kmeans == 1, 0], X[y_kmeans == 1, 1], s = 100, c = 'blue', label = 'Cluster 2')
plt.scatter(X[y_kmeans == 2, 0], X[y_kmeans == 2, 1], s = 100, c = 'green', label = 'Cluster 3')
plt.scatter(X[y_kmeans == 3, 0], X[y_kmeans == 3, 1], s = 100, c = 'cyan', label = 'Cluster 4')
plt.scatter(X[y_kmeans == 4, 0], X[y_kmeans == 4, 1], s = 100, c = 'magenta', label = 'Cluster 5')
plt.scatter(kmeans.cluster_centers_[0, 0], kmeans.cluster_centers_[0, 1], s = 300, c = 'yellow', label = 'Centroids')
plt.title('Clusters of customers')
plt.xlabel('Annual Income (k$)')
```

ANKIT.J

Roll no -540

```
plt.ylabel('Spending Score (1-100)')  
plt.legend()  
plt.show()
```

[illegible]

```
import numpy as np
import pandas as pd
import tensorflow as tf

dataset = pd.read_csv('Churn_Modelling.csv')
X = dataset.iloc[:, 3:-1].values
y = dataset.iloc[:, -1].values

print(X)

print(y)

from sklearn.preprocessing import
LabelEncoderle = LabelEncoder()
X[:, 2] = le.fit_transform(X[:, 2])

print(X)

from sklearn.compose import ColumnTransformer
from sklearn.preprocessing import
OneHotEncoder
ct = ColumnTransformer(transformers=[('encoder', OneHotEncoder(), [1])],
remainder='passthrough')
```

```

X = np.array(ct.fit_transform(X))

print(X)

from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.2, random_state = 0)

from sklearn.preprocessing import
StandardScaler
sc = StandardScaler()
X_train = sc.fit_transform(X_train)
X_test = sc.transform(X_test)

ann = tf.keras.models.Sequential()

ann.add(tf.keras.layers.Dense(units=6, activation='relu'))

ann.add(tf.keras.layers.Dense(units=6, activation='relu'))

ann.add(tf.keras.layers.Dense(units=1,
activation='sigmoid'))

ann.compile(optimizer = 'adam', loss = 'binary_crossentropy', metrics =
['accuracy'])
ann.fit(X_train, y_train, batch_size = 32, epochs = 100)

print(ann.predict(sc.transform([[1, 0, 0, 600, 1, 40, 3, 60000, 2, 1, 1, 50000]])) > 0.5)

y_pred = ann.predict(X_test)
y_pred = (y_pred > 0.5)
print(np.concatenate((y_pred.reshape(len(y_pred),1), y_test.reshape(len(y_test),1)),1))

from sklearn.metrics import confusion_matrix,
accuracy_score
cm = confusion_matrix(y_test, y_pred)
print(cm)
accuracy_score(y_test,
y_pred)

```

Output:

```

[[619 'France' 'Female' ... 1 1 101348.88]
 [608 'Spain' 'Female' ... 0 1 112542.58]
 [502 'France' 'Female' ... 1 0 113931.57]
 ...
 [709 'France' 'Female' ... 0 1 42085.58]
 [772 'Germany' 'Male' ... 1 0 92888.52]
 [792 'France' 'Female' ... 1 0 38190.78]]

```

```

[1 0 1 ... 1 1 0]

```

```
[[619 'France' 0 ... 1 1 101348.88]
 [608 'Spain' 0 ... 0 1 112542.58]
 [502 'France' 0 ... 1 0 113931.57]
 ...
 [709 'France' 0 ... 0 1 42085.58]
 [772 'Germany' 1 ... 1 0 92888.52]
 [792 'France' 0 ... 1 0 38190.78]]
```

```
[[1.0 0.0 0.0 ... 1 1 101348.88]
 [0.0 0.0 1.0 ... 0 1 112542.58]
 [1.0 0.0 0.0 ... 1 0 113931.57]
 ...
 [1.0 0.0 0.0 ... 0 1 42085.58]
 [0.0 1.0 0.0 ... 1 0 92888.52]
 [1.0 0.0 0.0 ... 1 0 38190.78]]
```

```
Epoch 1/100
250/250 [=====] - 1s 1ms/step - loss: 0.5750 - accuracy: 0.7490
Epoch 2/100
250/250 [=====] - 0s 1ms/step - loss: 0.4712 - accuracy: 0.7960
Epoch 3/100
250/250 [=====] - 0s 2ms/step - loss: 0.4428 - accuracy: 0.7986
Epoch 4/100
250/250 [=====] - 0s 2ms/step - loss: 0.4296 - accuracy: 0.8075
Epoch 5/100
250/250 [=====] - 0s 2ms/step - loss: 0.4212 - accuracy: 0.8149
Epoch 6/100
250/250 [=====] - 0s 2ms/step - loss: 0.4138 - accuracy: 0.8220
Epoch 7/100
```

```
y_pred = ann.predict(X_test)
y_pred = (y_pred > 0.5)
print(np.concatenate((y_pred.reshape(len(y_pred),1), y_test.reshape(len(y_test),1)),1))
```

```
[[0 0]
 [0 1]
 [0 0]
 ...
 [0 0]
 [0 0]
 [0 0]]
```

```
from sklearn.metrics import confusion_matrix, accuracy_score
cm = confusion_matrix(y_test, y_pred)
print(cm)
accuracy_score(y_test, y_pred)
```

```
[[1499  96]
 [ 186 219]]
```

```
0.859
```

Practical 8

Aim: Write a program to build CNN.

Code:

```
import tensorflow as tf
from keras.preprocessing.image import ImageDataGenerator

train_datagen = ImageDataGenerator(rescale=1./255, shear_range=0.2,
zoom_range=0.2, horizontal_flip=True)
training_set =
train_datagen.flow_from_directory('/content/drive/MyDrive/small_dataset/training_set',
target_size=(64,64), batch_size=32, class_mode='binary')

train_datagen = ImageDataGenerator(rescale=1./255, shear_range=0.2,
zoom_range=0.2, horizontal_flip=True)
test_set =
train_datagen.flow_from_directory('/content/drive/MyDrive/small_dataset/test_set',
target_size=(64,64), batch_size=32, class_mode='binary')

cnn = tf.keras.models.Sequential()

cnn.add(tf.keras.layers.Conv2D(filters=32, kernel_size=3, activation='relu',
input_shape=[64,64,3]))

cnn.add(tf.keras.layers.MaxPool2D(pool_size=2, strides=2))

cnn.add(tf.keras.layers.Conv2D(filters=32, kernel_size=3, activation='relu'))
cnn.add(tf.keras.layers.MaxPool2D(pool_size=2, strides=2))

cnn.add(tf.keras.layers.Flatten())
```


ANKIT.J

Roll no -540

```
cnn.add(tf.keras.layers.Dense(units=128, activation='relu'))
```

```
cnn.add(tf.keras.layers.Dense(units=1,
```

```
activation='sigmoid'))
```

```
cnn.compile(optimizer='adam', loss='binary_crossentropy',  
metrics=['accuracy'])cnn.fit(x=training_set, validation_data=test_set,  
epochs=25)  
  
import numpy as np  
from keras.preprocessing import image  
test_image=image.load_img('/content/drive/MyDrive/small_dataset/single_prediction/cat_or_dog_  
1  
.jpg', target_size=(64,64))  
test_image=image.img_to_array(test_image)  
test_image=np.expand_dims(test_image,  
axis=0)result=cnn.predict(test_image)  
training_set.class_indices  
if result[0][0]==1:  
prediction='dog'  
else:  
prediction='cat'  
  
print(prediction)
```

Output:

```
Epoch 1/25  
1/1 [=====] - 1s 897ms/step - loss: 0.7015 - accuracy: 0.5000 - val_loss: 0.7160 - val_accu  
racy: 0.5000  
Epoch 2/25  
1/1 [=====] - 0s 227ms/step - loss: 0.6286 - accuracy: 0.9000 - val_loss: 0.7793 - val_accu  
racy: 0.5000  
Epoch 3/25  
1/1 [=====] - 0s 224ms/step - loss: 0.6135 - accuracy: 0.5000 - val_loss: 0.7770 - val_accu  
racy: 0.5000  
Epoch 4/25  
1/1 [=====] - 0s 230ms/step - loss: 0.6256 - accuracy: 0.4000 - val_loss: 0.7575 - val_accu  
racy: 0.4000  
Epoch 5/25  
1/1 [=====] - 0s 211ms/step - loss: 0.5565 - accuracy: 0.9000 - val_loss: 0.7845 - val_accu  
racy: 0.4000
```

```
print(prediction)
```

```
dog
```