

SubSentry™ — Geo-Subsidence & Strata Dynamics SCADA

Autonomous Sub-Surface IoT Sensor Grid, Knothe-Budryk Digital Twin & DGMS Statutory Compliance

The Core Mission

To eliminate catastrophic unpredicted underground mine collapses and surface subsidence craters across Coal India Ltd. (BCCL, ECL, SECL) collieries through an intrinsically safe, frugal, real-time edge-IoT sensor mesh.

High-Impact Deliverables

- ▶ **₹8,500 Sensor Nodes:** 95.8% CapEx reduction over imported extensometers.
- ▶ **15-60 Min Early Warning:** Preemptive flash audio-visual evacuation alarms.
- ▶ **Analytical Knothe Engine:** $\$R^2 = 0.964$ AI benchmarked geotechnical profile.
- ▶ **1-Click DGMS Form IV-A:** Statutory audit-proof compliance automation.




Fig 1.1: End-to-End Edge-to-Cloud Telemetry Pipeline Architecture

The Coalfield Crisis: Why Indian Mines Suffer

Bord-and-Pillar Depillaring & Goaf Collapse Hazard in 318 Underground Mines



Blind Geotechnical Failure

Traditional manual prism/total station surveys are conducted only once every 7–14 days. Catastrophic roof falls occur in seconds during active extraction shifts when no surveyor is present.



Prohibitive Foreign Import Cost

Imported borehole extensometers (RST, Geokon) cost **₹3.5L to ₹5.0L per monitoring point** with proprietary locked clouds, making mine-wide sensor grid scaling financially impossible for CIL.



Heavy DGMS Penalties

DGMS Tech Circular No. 02/2019 mandates continuous monitoring during depillaring. Non-compliance triggers immediate mine closure notices, costing ₹10L–₹50L per day in lost coal production.



Target Critical Indian Mining Belts:

BCCL Jharia:

Multi-seam extraction & raging fires.

ECL Raniganj:

Soft shale roof & populated surface.

SECL Korba:

Massive bord & pillar extraction.

WCL Nagpur:

Deep mining water-bearing strata.

The SubSentry™ Hardware MVP & Edge Pipeline

Tested, Verified, and Real-Time Telemetry with Optical UART Isolation

🦴 Edge Sensor Node Architecture

- ▶ **Microcontroller Core:** ATmega328P (16MHz) + ESP32 Dual-Core (240MHz).
- ▶ **6-DOF Tilt Tracking:** MPU6050 Accelerometer/Gyro ($\pm 0.05^\circ$ resolution).
- ▶ **Strata Convergence:** Ultrasonic HC-SR04 ($\pm 3\text{ mm}$ sag resolution).
- ▶ **Hazardous Gas:** MQ-4 Methane (\$200 - 10000 ppm) + DHT11 Ambient.
- ▶ **Signal Conditioning:** 5V-to-3.3V Precision Voltage Divider Protection.

Deterministic UART Packet (9600 Baud):
`$SENTRY,NODE-01,1.24,-0.45,14.20,240,29.4,68.2,OK*4A`



Fig 3.1: 45-Minute Disaster Preemption & Automatic Strobe Alarm Lifecycle

Scientific Geotechnical Modeling & AI Benchmark

Knothe-Budryk Gaussian Theory Cross-Validated with Machine Learning




Fig 4.1: Knothe-Budryk Surface Trough Curve $S(x)$ Over Extraction Goaf

Knothe-Budryk Governing Equation

$$S(x) = \frac{S_{\max}}{2} \left[1 - \text{erf} \left(\frac{\sqrt{\pi}}{R} x \right) \right] \text{ Where } R = \frac{H}{\tan(\beta)}, \beta = 65^\circ \text{ (Influence Radius)}$$

Calculates exact surface vertical depression $S(x)$, tilt $T(x) = dS/dx$, and horizontal tensile strain $\epsilon(x)$ responsible for surface building cracks.

AI Cross-Validation Benchmark

Trained on 5,000 colliery geotechnical vectors against true Knothe profiles:

R^2 Score:
0.964

MAE:
0.032 cm

RMSE:
0.045 cm

Technical, Financial & Operational Feasibility

95.8% Cost Reduction vs Legacy Solutions with Zero Operational Friction

Parameter	Imported Extensometers	SubSentry™ Edge Grid
CapEx / Sensor Point	₹3,50,000 – ₹5,00,000	₹8,500 (95.8% Savings)
Sampling Frequency	Hourly / Manual	Real-Time (500ms)
Installation Time	Specialized Core Drilling	Bolt-Mount (<15 Mins)
DGMS Statutory Report	Manual Paperwork (12h)	1-Click Auto Form IV-A
5-Yr TCO (100 Points)	₹5.30 Crores	₹0.22 Crores




Fig 5.1: 5-Year Colliery Total Cost of Ownership (TCO) Comparison

Who Benefits? (Target Audience & "Kiska Fayed")

Multi-Tier Value Creation Across the Entire Indian Mining Ecosystem




Fig 6.1: 4-Tier Beneficiary & Stakeholder Impact Ecosystem



Underground Miners & Facemen

Direct Life Safety: 15–60 min early evacuation notice prevents fatal entrapment during roof caving; real-time methane alerts prevent asphyxiation.



Mine Managers & Overmen

Operational Ease & Compliance: 1-Click DGMS Form IV-A report generation saves 12+ administrative hours; eliminates false alarm panic.



Coal India Ltd. & Subsidiaries

Asset & Loss Mitigation: Prevents ₹10–₹50 Cr loss of Continuous Miners & Shearers from burial; avoids regulatory mine closure penalties.



Local Mining Villages (Jharia/Raniganj)

Surface Infrastructure Safeguard: Predicts surface sinkholes and cracking before village houses, railways, and highways collapse.

Human-Centric Safety • Zero Unpredicted Mine Tragedies •
Atmanirbhar Bharat

Direct Impact on 3,00,000+ CIL Mining
Workers

Market Size, Viability & Strategic Scalability

₹425+ Crore Indian Domestic Addressable Market (TAM) with High ROI



Market Opportunity

- ▶ **318 Mines:**
Underground coal mines across 8 CIL subsidiaries.
- ▶ **2,500+ Panels:**
Active depillaring and longwall extraction districts.
- ▶ **TAM:** ₹425+ Crores total Indian domestic market for strata monitoring.



Payback & Unit ROI

- ▶ **Payback Period:**
Under **3 Weeks** upon preventing a single 1-day regulatory production halt.
- ▶ **Hardware Unit Margin:** 42% on ₹8,500 BOM.
- ▶ **SaaS Maintenance:**
Annual statutory cloud & calibration retainer.



12-Month Rollout Plan

- ▶ **Phase 1 (M1-M3):**
20-Node pilot in BCCL Jharia colliery.
- ▶ **Phase 2 (M4-M6):**
DGMS statutory certification & CIL ERP link.
- ▶ **Phase 3 (M7-M12):**
Commercial deployment across 50 high-risk mines.



ESG, Carbon & Environmental Impact:

Uncontrolled subsidence fractures overburden strata, releasing high concentrations of trapped coal-bed methane (CH_4) and igniting underground seam fires (e.g., Jharia). SubSentry's early stabilization protects water tables and reduces fugitive greenhouse gas emissions.

Summary: Why SubSentry™ Wins SIH26025

A Complete, Ground-Tested, Mathematically Sound Geotechnical Solution

1. Real MVP

Fully functional hardware (Arduino + ESP32) with live UART data streaming into React 19 SCADA.

2. True Science

Knothe-Budryk mathematical physics engine benchmarked with AI ($R^2 = 0.964$).

3. DGMS Ready

Automated 1-Click Form IV-A reports adhering to CMR 2017 & Circular 02/2019.

4. 95.8% Frugal

₹8,500 indigenous node price democratizes safety across every Indian colliery.

SubSentry™: Protecting Lives, Assets, and the Future of Indian Mining

Zero Casualties • Zero Unpredicted Cave-Ins • 100% Statutory Compliance