Knowledge Assistant & Flashcards — Requirements

Nov 12, 2026 · @Akash Verma

1. Overview

We will build an internal web application with two parts. Employees ask Claude questions about our ERP knowledge base. They also verify that knowledge base through form-wise flashcards, which are scored and tracked.

Goals

- Give 10–15 employees one place to query the knowledge base (KB) in plain language, with answers styled for their role.
- Find errors in the KB by having employees verify flashcards generated from it.
- Measure how well each employee knows each form, and how long they take to understand it.

In scope

- Login, roles and user types
- Chat assistant backed by Claude (Agent SDK) with the KB MCP server
- Weekly flashcard generation, the flashcard player, corrections review, scoring, leaderboard and admin analytics
- Full audit logging

Out of scope (this release)

- Showing answer sources or citations in chat
- Editing the KB from the application (the team updates the KB directly today)
- Mobile apps (the web app must still be usable on a phone browser)

Glossary

Term	Meaning
KB	Knowledge base stored in Neo4j, read through the MCP server
MCP server	Server that exposes KB read tools to Claude

Term	Meaning
Form	An ERP business document or master, such as GRN, Purchase Order or Item Master
Role	Technical, Functional or Product. Decides the answer style (Claude skill)
User type	Admin or General. Decides privileges
Card	One flashcard: a statement about a form at one level, verified by users
Card version	A card's content as generated in one weekly batch

2. Users, roles and permissions

Every user has exactly one role and one user type. The role sets the answer style. The user type sets privileges.


- **REQ-ROLE-01** Roles: Technical, Functional, Product. A general user has exactly one role. It is assigned by an admin.
- **REQ-ROLE-02** Each role maps to one Claude skill: Technical → `/technical`, Functional → `/functional`, Product → `/product`. The role changes only how answers are written. It does not change which KB data a user can see.
- **REQ-ROLE-03** User types: Admin, General.
- **REQ-ROLE-04** Admins are not bound to a role. On each chat they choose which role's answer style to use.
- **REQ-ROLE-05** Admins see all users, all chats and all analytics.

Capability	General	Admin
Chat with the assistant	Yes, own role's style	Yes, any role's style per chat
See own chat history	Yes	Yes
See other users' chats	No	Yes, all
Thumbs up/down on answers	Yes	Yes
Use flashcards (form and level filters)	Yes	Yes

Capability	General	Admin
See the leaderboard (global and per form)	Yes	Yes
Review card corrections	No	Yes
Run or publish flashcard batches	No	Yes
Manage users, roles, scoring settings	No	Yes
See analytics and export	No	Yes
See audit logs	No	Yes

3. Architecture

Everything runs on one EC2 instance under Docker Compose. The only external calls are to Anthropic, for the Claude model, and to the web, for search.



architecture · one EC2, Docker Compose

The browser talks only to Nginx. FastAPI runs the Claude harness, which reaches Neo4j only through the read-only MCP server. All application data is in Postgres.

Layer	Technology
Front end	React with TypeScript (Vite)
Backend	FastAPI (Python), SQLAlchemy, Alembic
AI harness	Claude Agent SDK for Python, with the same engine as Claude Code
Knowledge base	Neo4j in Docker, through the existing MCP server
App database	Postgres in Docker
Hosting	AWS EC2 t4g (ARM), Docker Compose, Nginx

4. Authentication

Users log in with a username and password. Reusing the existing Employee Self Service (ESS) portal login is preferred, but how to connect to it is not yet known.

- **REQ-AUTH-01** Login uses a username and password. There is no self-signup. Accounts are created by an admin or come from ESS.
- **REQ-AUTH-02** ESS integration is behind an adapter, so it can be switched without changing the rest of the app. Options, in order of preference:
  1. Validate credentials against an ESS API.
  2. Validate against the ESS user store directly, read-only.
  3. Fallback: local accounts in Postgres, with passwords hashed using Argon2 or bcrypt.
- **REQ-AUTH-03** Role and user type are always stored in the app's own database, even when the password check is done by ESS.
- **REQ-AUTH-04** Sessions use a short-lived access token plus a refresh token in an HttpOnly, Secure, SameSite cookie. Default idle timeout: 8 hours (proposed).
- **REQ-AUTH-05** After 5 failed attempts in a row, the account is locked for 15 minutes (proposed). Every login attempt is audit-logged.
- **REQ-AUTH-06** An admin can deactivate a user. Deactivation ends that user's sessions immediately. Their history and scores are kept.

- **REQ-AUTH-07** If local accounts are used: an admin can reset a password, and the user must change it at next login.

5. Knowledge assistant (chat)

The chat page works like a familiar chat app. Answers stream back as Claude writes them, and conversations are saved per user.

- **REQ-CHAT-01** The user types a question. The backend sends it to Claude together with the skill for the user's role, and streams the answer back to the browser over Server-Sent Events.
- **REQ-CHAT-02** Conversations have multiple turns. A follow-up message continues the same Claude session, so earlier context is kept.
- **REQ-CHAT-03** If Claude needs clarification, it asks in its reply. The user answers in the next message. There are no pop-up dialogs.
- **REQ-CHAT-04** Sidebar listing the user's own conversations: new chat, rename, delete (soft delete; the record stays in the audit log), and search by title.
- **REQ-CHAT-05** Admins have a role selector on each new chat (Technical, Functional, Product). The selected role is fixed for that conversation and stored with it.
- **REQ-CHAT-06** Admins have an "All chats" view, filterable by user, role, date and feedback. General users never see other users' chats.
- **REQ-CHAT-07** Thumbs up/down on every answer, with an optional comment on thumbs down.
- **REQ-CHAT-08** A Stop button cancels a running answer. The partial answer is saved and marked "stopped".
- **REQ-CHAT-09** Errors are shown clearly: timeout, Claude usage limit reached, MCP server or Neo4j unavailable. The user can retry.
- **REQ-CHAT-10** Answers render as Markdown, including tables and code blocks, with a copy button.
- **REQ-CHAT-11** If all Claude slots are busy, the user sees their position in the queue (see REQ-HARN-07).
- **REQ-CHAT-12** Sources and citations are not shown in this release.

6. Claude harness

FastAPI runs Claude through the Claude Agent SDK for Python. The SDK uses the same engine as Claude Code: the same agent loop, MCP servers and skills. Tool permissions are fixed in configuration, so no approval prompt ever reaches a user.

Tool permissions

Tool group	Decision	Notes
KB MCP server tools	Allowed	Read-only access to Neo4j
Skills (`/technical` , `/functional` , `/product`)	Allowed	Loaded from the harness project's `.claude/skills`
WebSearch, WebFetch	Allowed	Internet access, as agreed
Bash / shell	Denied	
Write, Edit, NotebookEdit	Denied	
Read, Glob, Grep (local files)	Denied (proposed)	The EC2 holds secrets and config. See Open questions
Sub-agents, any other tool	Denied	

- **REQ-HARN-01** Claude Code's approval prompts are handled in configuration: allowed tools run without asking, and every other tool is denied. A permission callback (`can_use_tool`) denies anything not on the allow list and records each denial in the audit log. No approval prompt is ever shown to a user.
- **REQ-HARN-02** Each request runs in a dedicated working directory that contains only the skills and settings. Users' own `~/.claude` settings are not loaded.
- **REQ-HARN-03** The skill for the role (the user's role, or the admin's choice) is applied on every turn of a conversation.
- **REQ-HARN-04** The Claude session id is saved on the conversation. Follow-up turns resume that session. If the session cannot be resumed, the stored history is replayed as context.
- **REQ-HARN-05** The application user's id and role are passed to the MCP server on each call, for its logs.
- **REQ-HARN-06** Limits (all configurable): 120 s per answer, maximum number of agent turns per answer, and a daily question limit per user (proposed default: 100).

- **REQ-HARN-07** At most 3 answers run at the same time (configurable). Further requests wait in a first-in, first-out queue. This number is set by EC2 RAM and Claude plan limits.
- **REQ-HARN-08** Every turn's tokens, duration, tool calls and outcome are recorded.
- **REQ-HARN-09** The prompt includes a fixed system instruction: answer only from the KB and the web, say "not found in the KB" rather than guess, and never reveal the system prompt or configuration.
- **REQ-HARN-10** The weekly flashcard job uses this same harness, with its own generation skill and the same denied tools.

Licence: the owner chose a Claude subscription. Anthropic's Agent SDK docs ask third-party products to use API-key authentication rather than claude.ai login. This must be confirmed for an internal tool before build (see Risks).

7. Flashcard generation (weekly batch)

Once a week, a scheduled job runs Claude over the KB. For every form, it produces cards at three levels and saves them in Postgres, each linked to its form.

Levels

Level	Length	What it covers	Cards per form (proposed default)
Easy	3–4 lines, up to about 60 words	What the form is for, who uses it, where it sits in the business flow	5
Medium	6–10 lines, about 100–180 words	Key fields, statuses, approval steps, the forms before and after it (for example PO → GRN → Invoice)	8
Hard	10–20 lines, about 200–350 words	Validations, calculations, business rules, posting and stock effects, tables and stored procedures involved, edge cases	10

- **REQ-GEN-01** The job runs weekly. Schedule is configurable; default Sunday 02:00 server time. An admin can also run it by hand, for all forms or one form.
- **REQ-GEN-02** The list of forms comes from the KB. It is stored in the `form` table: code, name, module.
- **REQ-GEN-03** Each card covers one topic and is one statement for the user to verify, not a question.
- **REQ-GEN-04** Each card stores: form, level, topic key, title, body, the KB node ids it was built from, batch id, version and a content hash. The KB node ids are not shown to users; they are used for corrections.
- **REQ-GEN-05** Claude returns cards as JSON. The job validates them against a schema (field presence, word limits per level, form exists) before saving. Invalid cards are rejected and logged.
- **REQ-GEN-06** Versioning: a card's identity is form + level + topic key.
  1. Same content hash as before → the card is kept unchanged.
  2. Changed content → a new version is created and the old one is retired. Users can answer the new version.
  3. Topic no longer generated → the card is retired.
  4. Responses always point to the exact version that was shown.
- **REQ-GEN-07** Publishing: new or changed cards start as Draft. Whether an admin must approve them or they publish automatically is an open question. The app supports both, through a setting.
- **REQ-GEN-08** The job also creates control cards: copies of real cards with one fact deliberately changed, used to check for blind clicking (see section 10). They are stored with `is_control = true` and the altered fact recorded.
- **REQ-GEN-09** Every run is logged: start, end, forms processed, cards created, changed, retired and rejected, tokens used, and errors. Admins can see the run history.
- **REQ-GEN-10** If a run fails partway, forms already finished are kept. Re-running processes only the forms that did not finish.

8. Flashcard player

Users pick a form and a level, read one card at a time, and give one of three answers. Time is measured from when the card opens to when it is answered.

Answer options (recommended)

Option	Meaning	Extra input
Known and correct	"I already knew this, and it is right"	None
New to me	"I did not know this; I have read and understood it"	None
Incorrect or incomplete	"I know this area, and the card is wrong"	Required: a reason (Wrong fact, Outdated, Missing important detail, Does not apply to our system) and a correction of at least 15 characters

Why three: "Known and correct" and "New to me" earn the same points, so there is no reason to claim knowledge you lack. "Incorrect" requires a written correction, so it costs effort and cannot be clicked blindly.

- **REQ-CARD-01** Filters: form (search plus list) and level (Easy, Medium, Hard). Both are optional. Unanswered cards come first; within those, the order is random.
- **REQ-CARD-02** Each user answers each card version once. When a new version is published, the user can answer it again.
- **REQ-CARD-03** A progress bar shows answered vs total for the selected filter. An "All done" state appears when nothing is left.
- **REQ-CARD-04** "My answers" lets a user look back at cards they answered and what they chose. Answers cannot be changed.
- **REQ-CARD-05** Timing:
  1. When a card is shown, the server records `opened_at`.
  2. When the user answers, the server records `answered_at`.
  3. The browser also reports periods when the tab was hidden, or idle for more than 60 seconds. These are subtracted to give **active time**.
  4. Active time is capped at 10 minutes. Both raw and active time are stored.
- **REQ-CARD-06** A card closed without an answer (user leaves, logs out or times out) is stored as "abandoned" with its time. It stays unanswered for that user.
- **REQ-CARD-07** Control cards (section 7) look exactly like normal cards.
- **REQ-CARD-08** Keyboard shortcuts 1, 2 and 3 select the answers. The layout must work on phone browsers.

9. Corrections review

Every "Incorrect or incomplete" answer goes to an admin review queue. Confirmed errors are passed to the KB team to fix, so the KB improves each week.

1. A user flags a card. The flag is stored with its reason and correction. The card's flag count goes up by one.
2. When a card reaches 2 flags (configurable), it is marked **Disputed** and hidden from users who have not answered it yet, until it is reviewed.
3. An admin opens the queue. Each item shows: the card, all flags and corrections side by side, and the card's KB node ids.
4. The admin decides:
    - **Confirmed:** the card is wrong. It is retired. Every user who flagged it gets correction points (section 10). An item is added to the KB fix list.
    - **Rejected:** the card is right. It returns to Published. Flaggers get no correction points.
    - **Partly confirmed:** treated as Confirmed for scoring. The admin edits the note for the KB team.
5. The KB team fixes the KB in Neo4j outside this app, then marks the KB fix item as "Fixed in KB". The next weekly batch regenerates the card.

- **REQ-CORR-01** Every review action records the reviewer, the time and a note.
- **REQ-CORR-02** Control cards never enter the review queue. A flag on a control card is auto-confirmed if the user's reason points to the altered fact. Otherwise it is held for an admin to check.
- **REQ-CORR-03** The KB fix list can be exported as CSV.
- **REQ-CORR-04** A user can see the outcome of each of their own flags: Pending, Confirmed or Rejected.

10. Scoring, anti-cheat and leaderboard

Points reward careful reading and real corrections. They cannot be farmed by clicking fast or by claiming knowledge. All values below are proposed defaults that an admin can change.

Points

Event	Points	Condition
Known and correct	Level base: Easy 1, Medium 2, Hard 3	Active time ≥ minimum read time
New to me	Same level base	Active time ≥ minimum read time
Answer faster than minimum read time	0	Recorded as "too fast"
Incorrect: flag submitted	0	Pending review
Incorrect: flag confirmed	5 × level base	Admin confirms
Incorrect: flag rejected	0	
Control card correctly flagged	3 × level base	
Control card marked "Known and correct"	−3 × level base	Blind click detected

Anti-cheat rules

- **REQ-SCORE-01** Minimum read time = the card's word count ÷ 5 words per second, and never less than 4 seconds. Example: a 60-word Easy card needs 12 seconds.
- **REQ-SCORE-02** About 10% of the cards a user is shown are control cards.
- **REQ-SCORE-03** Five "too fast" answers in a row pause the player for 2 minutes and show a warning.
- **REQ-SCORE-04** Points per user per day from "Known" and "New" answers are capped at 200. Correction points have no cap.
- **REQ-SCORE-05** Points are earned only on the first answer to each card version.
- **REQ-SCORE-06** Timing is taken from the server's clock. The browser can only report time to subtract (hidden or idle), never add time.
- **REQ-SCORE-07** Points are stored as an append-only ledger with the rule version used. Admins can recalculate the leaderboard after changing rules.
- **REQ-SCORE-08** Each user has a **reliability score**: control cards caught ÷ control cards seen. Only admins can see it.

Leaderboard

- **REQ-LB-01** All users can see the leaderboard. It has a global view and a per-form view.

- **REQ-LB-02** Columns: rank, name, role, points, cards answered, confirmed corrections.
- **REQ-LB-03** Periods: this week and all time (proposed).
- **REQ-LB-04** Ties are broken by more confirmed corrections, then by who reached the score first.
- **REQ-LB-05** The leaderboard is updated on each answer, or at most 1 minute later.

11. Admin analytics and export

Admins get one analytics area with filters for date range, user, role, form and level. Every table in it can be exported.

Metric	Breakdown	Purpose
Cards answered	User, form, level, week	Activity
Answer mix (Known / New / Incorrect)	User, form, level	What people already know vs are learning
Average and median active time per card	User, form, level	How long it takes to understand
Too-fast rate	User	Rushing
Reliability score (control cards)	User	Honesty of answers
Flag accuracy (confirmed ÷ total flags)	User	Quality of corrections
Form coverage (% of published cards answered)	User × form grid	Who knows which forms
Most-disputed cards and forms	Form, level	Weak areas in the KB
Abandoned cards	User, form	Cards people give up on
Chat usage: questions, thumbs up/down, tokens, average answer time	User, role, day	Assistant quality and cost
Batch runs: cards created, changed, retired, rejected	Run	KB change rate

- **REQ-AN-01** Per-user detail page: all the metrics above for one user, plus their timeline of answers and chats.
- **REQ-AN-02** Export to CSV and Excel (.xlsx) for every table, with the active filters applied.
- **REQ-AN-03** Data is shown as charts where a trend helps (for example weekly activity) and as tables elsewhere.
- **REQ-AN-04** Analytics pages load in under 3 seconds for 15 users and one year of data.

12. Audit logging

Everything is logged, as the owner decided. Logs are append-only and only admins can read them.

- **REQ-AUD-01** Logged events:
  - Login, logout and failed logins
  - Every chat prompt and full answer, with the role used, tokens, duration and every tool call (name and arguments)
  - Denied tool attempts
  - Feedback
  - Every card open, answer, abandonment and timing
  - Flags and review decisions
  - Admin changes: users, roles, settings, scoring rules, publishing
  - Batch runs and exports
- **REQ-AUD-02** Each entry has: time (UTC), user id, IP address, event type, a JSON payload and a request id.
- **REQ-AUD-03** Admin audit viewer with filters (user, event type, date range) and export.
- **REQ-AUD-04** Retention: keep everything; there is no deletion in this release. Disk use is monitored (section 14).

13. Data model (Postgres)

All application data lives in Postgres. The app never writes to Neo4j. This is the logical model; column-level design comes in the build phase.

Entity	Key fields	Notes
user	id, username, display_name, user_type (admin/general), role (technical/functional/product, null for admin), auth_source (ess/local), password_hash (local only), is_active, created_at	One role per general user
conversation	id, user_id, title, role_used, claude_session_id, created_at, deleted_at	role_used is fixed per conversation
message	id, conversation_id, sender (user/assistant), content, status (ok/stopped/error), tokens_in, tokens_out, duration_ms, created_at	
tool_call	id, message_id, tool_name, arguments, allowed, duration_ms	Includes denied attempts
feedback	id, message_id, user_id, value (up/down), comment	
form	id, code, name, module, kb_node_id	Loaded from the KB
card	id, form_id, level, topic_key, is_control, altered_fact	Stable identity: form + level + topic_key
card_version	id, card_id, version, title, body, word_count, kb_node_ids, content_hash, status (draft/published/disputed/retired), batch_id	Responses point here
card_view	id, user_id, card_version_id, opened_at, answered_at, inactive_ms, active_ms, outcome (answered/abandoned)	Server-side timing
card_response	id, card_view_id, answer (known/new/incorrect), reason, correction_text, too_fast	One per user per card version
flag_review	id, card_version_id, reviewer_id, decision (confirmed/rejected/partial), note, decided_at	

Entity	Key fields	Notes
kb_fix_item	id, card_version_id, note, status (open/fixed), fixed_by, fixed_at	Handover to the KB team
points_ledger	id, user_id, event, points, card_version_id, rule_version, created_at	Append-only
scoring_rule_set	version, json_rules, active_from	Section 10 values
batch_run	id, started_at, ended_at, trigger (schedule/manual), counts, tokens, status, error	
setting	key, value	Limits, schedule, thresholds
audit_log	id, ts, user_id, ip, event_type, payload, request_id	Append-only

14. Non-functional requirements

The system serves 10–15 users from one EC2 instance. The current t4g.medium (2 vCPU, 4 GiB RAM, ARM) is likely too small once Claude is running; t4g.large (8 GiB) is recommended.

Memory estimate

This is an estimate, not a measurement. It depends on Neo4j's configuration, the size of the KB, and how many answers run at once.

Component	Estimated RAM
Neo4j (heap + page cache)	1.0–1.5 GiB
Postgres	0.3–0.5 GiB
FastAPI + Nginx	0.2–0.3 GiB
Claude processes, 3 running at once	0.6–1.2 GiB
OS and Docker	0.4–0.5 GiB
Total	**2.5–4.0 GiB**

Performance

- **REQ-NFR-01** First streamed text appears within 10 seconds for 90% of questions (target, to be checked in the proof of concept).
- **REQ-NFR-02** App pages other than chat load in under 2 seconds.

Security

- **REQ-NFR-03** HTTPS only, using a Let's Encrypt or company certificate. Only ports 443 and 22 are open publicly. Neo4j, Postgres and the MCP server are reachable only inside the server.
- **REQ-NFR-04** Secrets (Claude credentials, database passwords, JWT key) are kept in environment files or AWS SSM, never in git.
- **REQ-NFR-05** The Claude harness runs as a non-root OS user that cannot read app secrets. Denied tools are enforced in SDK configuration, not in the prompt.
- **REQ-NFR-06** OWASP Top-10 basics: CSRF protection, input validation, rate limiting on login and chat, and security headers.
- **REQ-NFR-07** Before go-live, a prompt-injection test: try to make Claude run a shell command, read files or reveal its configuration. Every attempt must fail.

Operations

- **REQ-NFR-08** Everything runs under Docker Compose: nginx, react-static, fastapi, postgres, neo4j, mcp-server. The harness runs inside the FastAPI container or a sidecar.
- **REQ-NFR-09** Backups: Postgres dumped daily and kept 30 days; Neo4j dumped weekly; both copied off the server (S3). A restore is tested once before go-live.
- **REQ-NFR-10** Monitoring: container health checks, alerts on disk above 80% and memory above 85%, and on any failed batch run.
- **REQ-NFR-11** Builds and deploys run from CI. Database changes go through Alembic migrations.

Quality

- **REQ-NFR-12** Automated tests cover the backend (pytest) and frontend (Vitest), plus end-to-end tests (Playwright) for login, chat, the card flow and scoring. Scoring rules have unit tests for every row of the points table.
- **REQ-NFR-13** Supported browsers: current Chrome, Edge and Firefox, and mobile Chrome and Safari.

15. Risks

The biggest risk is licensing: running a multi-user app on a single Claude subscription login may not be allowed, and its usage limits are shared by everyone.

Risk	Impact	Mitigation
A Claude subscription login may not be permitted for an app that serves several employees	Blocks go-live or forces a change of plan	Confirm with Anthropic or your account terms before build. The harness keeps credentials in configuration, so moving to an API key or Bedrock is a settings change
Subscription usage limits are shared by every user and the weekly batch	Chat fails during the batch or busy hours	Run the batch overnight. Show a queue and a clear "limit reached" message. Track token use
4 GiB RAM is not enough	Neo4j or Claude killed for lack of memory	Upgrade to t4g.large. Cap concurrent answers at 3
Prompt injection gets Claude to use a denied tool	Server compromise	Deny tools in SDK configuration, non-root user, no secrets readable, test before go-live (REQ-NFR-07)
Generated cards contain KB errors or hallucinations	Users learn wrong facts	Card schema validation, optional admin approval before publishing, the corrections queue
Users game the scores	Analytics become meaningless	Section 10 rules, the reliability score, ledger recalculation
The ESS login cannot be integrated	Separate passwords for users	Use local accounts first; the auth adapter allows switching to ESS later

16. Open questions

The questions in bold block work on a phase. The rest have proposed defaults in this document and can be confirmed later.

- [ ] **Claude licence:** is a Claude subscription login permitted for this internal multi-user app, or do we use an API key or Bedrock? Blocks phase 1.
- [ ] **ESS login:** how can we validate against it (API, LDAP, database)? Who owns it? Blocks phase 2 (local accounts can be used meanwhile).
- [ ] **Forms in the KB:** how is a "form" represented in Neo4j (node label and properties)? Blocks phase 4.
- [ ] Can Claude read local files on the EC2 (Read, Glob, Grep)? Proposed: no.
- [ ] Card publishing: does an admin approve each weekly batch, or does it publish automatically?
- [ ] Cards per form per level: confirm the defaults 5 / 8 / 10.
- [ ] Scoring values and anti-cheat thresholds in section 10: confirm or adjust.
- [ ] Answer options in section 8: confirm the three options and the reason list.
- [ ] Are admins included in the leaderboard?
- [ ] Leaderboard periods: is "this week" plus "all time" enough?
- [ ] Daily question limit per user (proposed: 100) and concurrent answers (proposed: 3).
- [ ] Who on the KB team receives the KB fix list, and how (in-app or CSV)?
- [ ] Domain name and TLS certificate for the app.
- [ ] Does the existing MCP server accept a user id and role on each call (REQ-HARN-05)?

17. Delivery phases and acceptance criteria

There are eight phases, built in order. Each phase is done only when its acceptance criteria pass in the staging environment. Timelines will be estimated after phase 0.

#	Phase	Delivers	Acceptance criteria
0	Decisions and proof of concept	Bold open questions answered; FastAPI → Agent SDK → MCP → Neo4j answer streamed to a test page	One KB question answered end to end; a Bash attempt is denied and logged; time to first text and RAM per Claude process measured

#	Phase	Delivers	Acceptance criteria
1	Project setup	Repository, Docker Compose, Postgres with Alembic, CI, HTTPS	`docker compose up` brings up the whole stack; CI runs tests on every push
2	Login and roles	Login, sessions, user admin, role and user type, audit of logins	General user cannot open admin pages or APIs; lockout after 5 failed attempts works
3	Chat assistant	Streaming chat, history, role skills, admin role selector, feedback, stop, queue, limits	Answer style differs by role; general users see only their own chats; admins see all; timeout and limit errors are shown
4	Flashcard generation	Weekly job, card schema, versioning, control cards, run history, publish setting	A run on 3 forms produces valid cards at all levels; a re-run with no KB change creates no new versions
5	Flashcard player	Filters, three answers, timing, abandoned cards, My answers	Active time excludes hidden-tab time; one scored answer per card version
6	Corrections, scoring, leaderboard	Review queue, KB fix list, points ledger, anti-cheat, leaderboard	Every row of the points table passes a unit test; a control card marked correct deducts points
7	Admin analytics	Metrics in section 11, per-user page, CSV and Excel export	Exported figures match the database; pages load in under 3 seconds
8	Hardening and go-live	Security tests, backups, monitoring, user guide	Prompt-injection tests all fail to break out; a backup is restored successfully; admins sign off