

NATIONAL INSTITUTE OF TECHNOLOGY SRINAGAR
Jammu & Kashmir, India
Department of Computer Science and Engineering

PROJECT REPORT

ON

MEDICAL VISUAL QUESTION ANSWERING FOR CHEST X-RAYS

A knowledge-grounded approach with CheXagent-2-3b: literature review, baseline tests and retrieval-augmented design

Submitted in partial fulfillment of the requirements for the award of the degree of

BACHELOR OF TECHNOLOGY
in
COMPUTER SCIENCE AND ENGINEERING

Submitted by

ANKRIT JARNGAL
Enrollment No. 2023BCSE028

HIRDYANSH
Enrollment No. 2023BCSE036

Under the supervision of

Dr. Snober Mushtaq

Department of Computer Science and Engineering
National Institute of Technology Srinagar, J&K
Hazratbal, Srinagar – 190006, J&K, India



CERTIFICATE

This is to certify that the project titled **MEDICAL VISUAL QUESTION ANSWERING FOR CHEST X-RAYS** has been carried out by **ANKRIT JARNGAL** (Enrollment No. 2023BCSE028) and **HIRDYANSH** (Enrollment No. 2023BCSE036) under the supervision of **Dr. Snober Mushtaq**, in partial fulfillment of the requirements for the award of the degree of Bachelor of Technology in Computer Science and Engineering at the National Institute of Technology Srinagar, Jammu & Kashmir.

Project Supervisor
Dr. Snober Mushtaq
Department of Computer Science and Engineering
NIT Srinagar, J&K

Head of Department
Department of Computer Science and Engineering
NIT Srinagar, J&K

Abstract

Visual question answering (VQA) lets a person ask a free-text question about a medical image and receive a free-text answer. This project studies VQA on chest X-rays with a small open model, CheXagent-2-3b, that runs on a free Colab T4 GPU. We reviewed six papers, kept three that shaped the plan (CheXagent, RULE, Med-Flamingo), and built a pre-registered evaluation: the rules, test sets and success conditions were written down before any model run. We then measured how the model handles perception on its own. Mirroring a chest X-ray changed the model's left/right answer in 78% of 99 question pairs (95% interval 69–85%); on 60 side questions it was right 90% of the time, and on 47 heart-size questions it found 17 of 22 enlarged hearts and called all 25 normal hearts normal. In parallel we designed a knowledge-grounded retrieval pipeline (name the disease, then retrieve from MedlinePlus and medical textbooks) and measured, without any model, how often the corpus holds the gold answer: 29% of gold items on held-out questions with the true disease, 17% with a wrong disease and 3% from the question alone. We then tested the first step of the retrieval design: naming the disease from the X-ray. On 130 chest X-rays with a disease label, the model named the disease correctly 52–56% of the time with two methods, against 22% for always guessing the most common one. The retrieval arms and the baseline and knowledge sets are built and are the next runs. The work makes no clinical-validity claim.

Contents

1 Introduction **1**
1.1 Motivation . . . 1
1.2 Objectives . . . 1
1.3 Scope and standards . . . 1

2 Background **2**
2.1 What a chest X-ray shows . . . 2
2.2 Medical visual question answering . . . 3
2.3 Datasets and model . . . 3

3 Literature review **4**
3.1 Papers that shaped the project . . . 4
3.2 Context papers . . . 4
3.3 Gap and design decisions . . . 5

4 Evaluation method **6**
4.1 Pre-registration . . . 6
4.2 Scoring . . . 6
4.3 Test sets . . . 7

5 Experiments and results to date **7**
5.1 Knowledge test set . . . 7
5.2 Perception tests . . . 8
5.3 Disease naming . . . 8

6 Phase 2: knowledge-grounded retrieval **10**
6.1 Design . . . 10
6.2 Experimental arms . . . 10
6.3 Retrieval check without a model . . . 11

7 Status, limitations and next steps **12**
7.1 Where the work stands . . . 12
7.2 Next steps . . . 12
7.3 Limitations . . . 12

8 Conclusion **13**

A Reproducibility and repository guide **15**

B Glossary **15**

List of Figures

1 A normal frontal (PA) chest X-ray with the main structures labelled. “Dx” and “Sin” are Italian for right and left. Photograph: M. Häggström, Wikimedia Commons, CC0 [11]. 2

2 The task. Yes/no, side and severity questions test perception; knowledge questions test what the model knows about a disease. 3

3 Comparison of the six papers and this project. Highlighted rows shaped the plan; the hollow circle marks the blind rating that is planned but not yet done. 4

4 From literature findings to design decisions. 5

5 Evaluation flow and the test sets. 6

6 Project phases and their status. Phases 1c and 1d are done; Phases 1, 1b and 2 are built and waiting for a model run; Phase 3 is optional. 7

7 Perception tests. Left: share of pairs whose answer changed side when the X-ray was mirrored (a model that ignores the image would score 0%). Middle: left/right accuracy, plain wording, 60 questions (guessing: 50%). Right: heart-size accuracy, plain wording, 47 questions (always answering “no”: 53%). 8

8 Disease naming on 130 chest X-rays. Left: share named correctly by each method, against always answering the most common label. Right: area under the curve for each disease, for the yes/no method (0.5 means no skill). 9

9 The two-step pipeline, and why it is needed: the gold answer depends only on the disease on the image. 10

10 The six experimental arms. 11

11 Left: coverage by query type. Right: coverage by question type with the true disease (all 50 questions). 11

1 Introduction

1.1 Motivation

Chest X-rays are among the most common medical images, and reading them takes training. A system that can answer plain questions about an X-ray ("Is the heart enlarged?", "Which side is the fluid on?", "What causes this disease?") could one day support teaching and report drafting. Recent vision-language models can produce such answers, but how reliable they are, and why, is not well understood. This project is a careful, small-scale investigation of that question, not a clinical tool.

1.2 Objectives

1. Explain what chest X-rays show and what medical VQA asks of a model.
2. Review the literature and keep only the findings that change what we do.
3. Measure how a ready-made chest X-ray model, CheXagent-2-3b, answers questions without any extra training.
4. Design and test a knowledge-grounded retrieval extension, and decide beforehand how success will be judged.
5. Report honestly, including results that went against our expectations.

1.3 Scope and standards

The project follows four standards from the start: plain-language explanations, strict honesty about limits, no claim of clinical validity, and pre-registration (rules fixed before running the model). Everything described here is reproducible from the project repository; Section A lists the main files.

2 Background

2.1 What a chest X-ray shows

A chest X-ray is a shadow picture. X-rays pass easily through air and are stopped by dense tissue, so air-filled lungs appear dark and bone, fluid and the heart appear white. The standard frontal view is the posterior-anterior (PA) film. By convention the patient's right appears on the left of the image, which matters later for left/right questions.




Figure 1. A normal frontal (PA) chest X-ray with the main structures labelled. "Dx" and "Sin" are Italian for right and left. Photograph: M. Häggström, Wikimedia Commons, CC0 [11].

Four findings recur throughout the project (Figure 1):

- **Cardiomegaly**: an enlarged heart, usually judged by a cardiothoracic ratio above 0.5 (heart width over chest width).
- **Pleural effusion**: fluid around the lung, which blunts the sharp angle where the diaphragm meets the chest wall.
- **Pneumothorax**: air outside the lung, seen as a dark area with no lung markings and a visible pleural line.
- **Atelectasis**: partly collapsed lung, which looks whiter and pulls nearby structures toward it.

2.2 Medical visual question answering

In medical VQA the model receives an image and a question and must write an answer (Figure 2). We separate two kinds of difficulty, because they fail in different ways: **perception** (seeing the finding in the picture) and **knowledge** (knowing facts about the disease, such as its cause or treatment).




Figure 2. The task. Yes/no, side and severity questions test perception; knowledge questions test what the model knows about a disease.

2.3 Datasets and model

SLAKE [7] and **VQA-RAD** [8] are radiology VQA datasets with expert-written questions. We use their chest X-ray questions only. SLAKE additionally gives each image a set of labels, which we turn into a disease label for 130 chest images across eight classes (cardiomegaly 29, atelectasis 21, mass 19, nodule 18, pneumonia 17, effusion 13, pneumothorax 10, infiltration 9). The model is **CheXagent-2-3b** [1], a 3.1-billion-parameter vision-language model trained on chest X-ray instruction data. Its training data (CheXinstruct) already includes SLAKE and VQA-RAD, so our tests are close to in-distribution rather than a clean held-out test.

3 Literature review

We reviewed six papers and keep three here because they changed the plan; the other three gave useful context.

3.1 Papers that shaped the project

CheXagent [1] is the only model in our review built end to end for chest X-rays. It was trained on CheXinstruct, a collection of 8.5 million instruction triplets from 32 datasets covering 35 tasks, and outperforms larger general-purpose medical models. Its own results show where it is weakest: fine-grained reasoning such as side and severity reaches only 77–79%, against over 90% on coarse tasks. We chose it as the baseline model, and treat left/right and heart-size questions as the hardest perception cases.

RULE [2] adds retrieval to a medical vision-language model and shows why naive retrieval backfires. Too few or too many retrieved passages hurt, and the model over-trusts retrieved text: among errors introduced by retrieval, 47.4%, 47.4% and 58.7% (IU-Xray, FairVLMed, MIMIC-CXR) were cases where the model had answered correctly without it. RULE retrieves similar case reports, not authoritative knowledge. For us this means: keep retrieved text short, check that retrieval does no harm, and include an arm that supplies only the disease name without any retrieved text.

Med-Flamingo [3] evaluates answers with clinicians and finds that automatic scores can disagree with clinical judgement. We therefore plan a blind 0/1/2 rating of answers and avoid relying on a single automatic score.

3.2 Context papers

PubMedCLIP [4] found that the image encoder matters far more than the text encoder for medical VQA. **LLaVA-Med** [5] shows cheap curriculum tuning of a general model on GPT-4-written instruction data, which carries a hallucination risk because the writer never saw the image. **PMC-VQA** [6] builds questions from figure captions, and even with filtering such questions can often be answered from text alone, a warning for any benchmark of this kind.

	Chest X-ray focus	Free-text answers	Uses retrieval	Clinician / blind rating	Textbook source	what we took from it
CheXagent (2024)	●	●	○	●	○	our baseline model; weakest on left/right and severity (77-79%)
RULE (2024)	○	●	●	○	○	naive retrieval hurts: 47-59% of its errors follow the text
Med-Flamingo (2023)	○	●	○	●	○	automated scores disagree with clinicians: rate blind
LLaVA-Med (2023)	○	●	○	○	○	cheap tuning; GPT-4-written training data
PMC-VQA (2023)	○	●	○	○	○	caption-made questions can be answered from text alone
PubMedCLIP (2023)	○	○	○	○	○	the image encoder matters more than the text encoder
This project	●	●	●	◯	●	**none of the six papers combines these**

Figure 3. Comparison of the six papers and this project. Highlighted rows shaped the plan; the hollow circle marks the blind rating that is planned but not yet done.

3.3 Gap and design decisions

Among the papers reviewed, none combines a chest-X-ray model with retrieval of authoritative knowledge and a careful, pre-registered evaluation. Figure 4 shows how each finding became a concrete decision.




Figure 4. From literature findings to design decisions.

4 Evaluation method

4.1 Pre-registration

Before any run we wrote the rules into `docs/evaluation_protocol.md`: the test sets, the scorer, the statistics and the conditions that would count as success. Changes are recorded as dated amendments rather than silent edits. Figure 5 shows the flow.




Figure 5. Evaluation flow and the test sets.

4.2 Scoring

- **Exact match and loose match** for short answers (yes/no, one word).
- **Item recall** for list-style answers: the share of the gold answer's items that the model's answer covers (scorer version 2, frozen).
- **Constant-answer floor**: the score of a system that ignores the image and always writes the most common gold answer for that question type (leave-one-out). A real system must beat this floor.
- **Statistics**: bootstrap resampled by image, because several questions share one image; exact McNemar test for paired yes/no outcomes; exact sign test for paired scores.

4.3 Test sets

Set	Size	Purpose
Baseline	219	General, left/right and severity questions
Knowledge	130	Symptoms, treatment, cause, prevention, function, why
Side	140	Questions whose answer is a side
Mirror pairs	120	Same question on an image and its mirror
Heart-size	47	"Is the heart enlarged?" wordings
Disease labels	130	Naming the disease from the image

Table 1. Test sets. Five questions were removed from the original 224-question baseline set because they were probably not chest images.

5 Experiments and results to date




Figure 6. Project phases and their status. Phases 1c and 1d are done; Phases 1, 1b and 2 are built and waiting for a model run; Phase 3 is optional.

5.1 Knowledge test set

Of the 130 knowledge questions, 105 are scored (the 25 "function" questions have the same gold answer, "Breathe", and are excluded). They have only 33 distinct gold answers, so the answer is largely fixed by which disease is in the image; this observation motivates the two-step design in Section 6. The constant-answer floor, the score of a system that ignores the image and always writes the most common answer for the question type, is 0.38 item recall on these 105 questions, so a model must beat 0.38 to show that it adds anything.

5.2 Perception tests

The perception notebook (03) was run on a Colab T4 on 13 November 2026 (788 generations). Every notebook contains an **IMAGE CHECK**: the same file path is used with black, white and noise pixels, and the run stops if the output log-probabilities do not change by at least 0.01.

In the **mirror test**, each question was asked on the original image and on its horizontal mirror; a model that reads laterality should change its answer. Of 99 pairs in which a side was named on both images, 77 changed side (78%, 95% interval 69–85%). Accuracy was 82% on the original image and 68% on the mirror (against the mirrored answer). In the **wording test**, six prompt wordings were tried on 60 side questions. Accuracy was 82–95% (plain wording 90%), the share answering "right" was 47–53% for every wording, and the answer depended on the true side for every wording (Fisher $p < 0.001$). In the **heart-size test**, the plain wording found 17 of 22 enlarged hearts and called 25 of 25 normal hearts normal (accuracy 89%, against 53% for always answering "no"; Youden's J 0.77). By the readings fixed in advance, the model uses the image for both properties. The swap rate (78%) sits just under the 80% line of the pre-registered table, with accuracy clearly above 50% on both images, so it is closest to the row "the model does read laterality". Because CheXagent was trained on SLAKE and VQA-RAD, part of this may reflect training exposure rather than general ability.




Figure 7. Perception tests. Left: share of pairs whose answer changed side when the X-ray was mirrored (a model that ignores the image would score 0%). Middle: left/right accuracy, plain wording, 60 questions (guessing: 50%). Right: heart-size accuracy, plain wording, 47 questions (always answering "no": 53%).

5.3 Disease naming

SLAKE's knowledge answers are fixed by the disease on the image, so a retrieval system first needs the model to say which disease it sees. Notebook 04 was run on a Colab T4 on 13 November 2026 on the 130 SLAKE chest X-rays that have a disease label (train 90, validation 20, test 20; eight diseases). Three ways of asking were fixed in advance: an **open** question, **forced** choice of one name from 15 (the 14 ChestX-ray14 names and "No Finding"), and a **yes/no question for each name**, where the name with the highest yes-minus-no score is the prediction. The method used downstream is the one with the best accuracy on the 20 validation images.

Top-choice accuracy was 56% (95% interval 48–64%) for the open question, 36% (28–45%) for forced choice and 52% (44–61%) for yes/no per disease, against 22% for always answering the most common label (cardiomegaly) and 11–13% for shuffled labels. All three are above chance by both pre-registered criteria ($p < 0.001$). On the validation images the yes/no method was

best (55%, against 45% for forced choice and 30% for open), so it is the method used in the retrieval arms. Its score separates the true disease from other images for every disease (area under the curve 0.99 pneumothorax, 0.95 cardiomegaly, 0.89 effusion, 0.86 nodule and mass, 0.82 pneumonia, 0.77 atelectasis, 0.76 infiltration). The weak spots are specific: the yes/no method never predicted pneumonia, and the open question found atelectasis in 1 of 21 images. With 20 validation images the choice of method is noisy, and SLAKE training images are probably in CheXagent's training data.





Figure 8. Disease naming on 130 chest X-rays. Left: share named correctly by each method, against always answering the most common label. Right: area under the curve for each disease, for the yes/no method (0.5 means no skill).

6 Phase 2: knowledge-grounded retrieval

6.1 Design

SLAKE's knowledge questions never name the disease ("What symptoms will the disease on the left bring?"), and the gold answer is effectively a lookup keyed by the disease on the image. The system therefore works in two steps (Figure 9): (a) name the disease from the image, a perception step; (b) retrieve what is known about that disease and let the model answer with the passages in its prompt, a knowledge step.

Retrieval uses our own BM25 implementation over two corpora that are independent of the test data: **MedlinePlus** (US National Library of Medicine, public domain) and the 18 medical textbooks of the MedRAG collection [9]. The textbooks are copyrighted, so they are downloaded at run time into a git-ignored folder and never committed. The retrieval setting (topic lookup plus textbooks, two passages, 700 characters each) was chosen on 16 development questions only and frozen before held-out numbers were computed.



Disease on the image	Question about	Gold answer, on every such image
Pneumonia	cause	Bacterial infection
Pneumonia	treatment	Medical therapy, supportive therapy
Cardiomegaly	cause	Hypertension, dilated cardiomyopathy

Figure 9. The two-step pipeline, and why it is needed: the gold answer depends only on the disease on the image.

6.2 Experimental arms

Six arms (Figure 10) separate the value of knowing the disease from the value of retrieval. Oracle arms (A2–A4) use SLAKE's own disease label, which a real system would not have, so they are upper bounds and never reported as the result. The real system is A6. Amendment 5 requires A6 to beat both the fair baseline A1 and the guess-only arm A5, so a gain that comes only from naming the disease cannot be credited to retrieval.

Arm	Disease named	Retrieved text	Role
● **A1**	none	none	fair baseline, same answer style
● **A2**	none	from the question alone	oracle subset: why the disease matters
● **A3**	true disease (oracle)	none	upper bound: value of knowing the disease
● **A4**	true disease (oracle)	yes	upper bound: value of retrieval
● **A5**	model's own guess	none	real: the guess alone
● **A6**	model's own guess	yes	the system

● oracle: uses SLAKE's own label, an upper bound, never the result ● real: uses only what the model outputs

Figure 10. The six experimental arms.

6.3 Retrieval check without a model

Before spending any GPU time we measured how often the retrieved text contains the gold answer's items (Table 2, Figure 11). "Strict" coverage requires the gold item's words to appear within one sentence.

Retrieval query	Dev (n=16)	Held-out (n=34)	All 50
True disease	0.42	0.29	0.33
Wrong disease	0.16	0.17	0.13
Question only	0.05	0.03	0.04

Table 2. Strict gold-item coverage of the retrieved text. The setting was tuned on the development questions only.




Figure 11. Left: coverage by query type. Right: coverage by question type with the true disease (all 50 questions).

Three readings follow. First, the corpus holds more of the answer when the disease is right, and almost none when only the question is used, which supports the two-step design. Second, coverage is an upper limit on what retrieval can add: even the best case covers about a third of the gold items. Third, it differs by question type (symptoms 67%, cause 44%, treatment 23%, prevention 8%), because generic gold phrases such as "keep healthy" almost never match a source sentence. A router that sends only knowledge questions to retrieval (25 of 219 baseline questions routed, all in the knowledge set) was also checked, to ensure retrieval cannot affect perception questions.

7 Status, limitations and next steps

7.1 Where the work stands

Built and tested: the baseline pipeline, all test sets, the scorers and analysis scripts, the retrieval pipeline and corpora loaders, the five Colab notebooks, and 123 automated tests (using stand-in models to check the plumbing). Run so far: the perception tests (notebook 03), disease naming (notebook 04) and the retrieval check (no model). Still to run: the retrieval arms (notebook 05), and the baseline and knowledge sets (notebooks 01 and 02).

7.2 Next steps

1. Run the retrieval notebook (05) with the yes/no-per-disease method chosen in the disease-naming test.
2. Run notebooks 01 and 02 for the baseline and knowledge sets.
3. Collect blind 0/1/2 ratings of a sample of answers.
4. Consider targeted fine-tuning (Phase 3) only if Phase 2 shows a gap worth closing.

7.3 Limitations

- Zero-shot only, one model, and small test sets (the retrieval check has 50 questions).
- SLAKE's knowledge answers are annotator-written templates, so a high score does not imply clinical knowledge.
- CheXagent's training data includes SLAKE and VQA-RAD, so the tests are not a clean held-out evaluation.
- The disease labels come from SLAKE annotations and cover eight classes only.
- No clinician has reviewed any output. Nothing in this report supports a claim of clinical validity or safety.

8 Conclusion

The literature review gave a clear, narrow question: can retrieved textbook knowledge improve a chest-X-ray model's answers to knowledge questions, without making perception questions worse? We built an evaluation that fixes the rules in advance and a retrieval pipeline that measurably contains the answer more often when the disease is known. The perception tests show that the model's left/right answers follow a mirrored image and that it finds most enlarged hearts. The model also names the disease from the X-ray well above chance, so the first step of the retrieval design is feasible. The next stage is the retrieval arms.

References

[1] Z. Chen, M. Varma, J.-B. Delbrouck, et al. *CheXagent: Towards a Foundation Model for Chest X-Ray Interpretation*. arXiv:2401.12208, 2024.

[2] P. Xia, K. Zhu, H. Li, et al. *RULE: Reliable Multimodal RAG for Factuality in Medical Vision Language Models*. EMNLP, 2024.

[3] M. Moor, Q. Huang, S. Wu, et al. *Med-Flamingo: a Multimodal Medical Few-shot Learner*. Machine Learning for Health (ML4H), PMLR, 2023.

[4] S. Eslami, C. Meinel, G. de Melo. *PubMedCLIP: How Much Does CLIP Benefit Visual Question Answering in the Medical Domain?* Findings of EACL, 2023.

[5] C. Li, C. Wong, S. Zhang, et al. *LLaVA-Med: Training a Large Language-and-Vision Assistant for Biomedicine in One Day*. NeurIPS Datasets and Benchmarks, 2023.

[6] X. Zhang, C. Wu, Z. Zhao, et al. *PMC-VQA: Visual Instruction Tuning for Medical Visual Question Answering*. arXiv:2305.10415, 2023.

[7] B. Liu, L.-M. Zhan, L. Xu, et al. *SLAKE: A Semantically-Labeled Knowledge-Enhanced Dataset for Medical Visual Question Answering*. IEEE ISBI, 2021.

[8] J. J. Lau, S. Gayen, A. Ben Abacha, D. Demner-Fushman. *A dataset of clinically generated visual questions and answers about radiology images*. Scientific Data 5:180251, 2018.

[9] G. Xiong, Q. Jin, Z. Lu, A. Zhang. *Benchmarking Retrieval-Augmented Generation for Medicine*. Findings of ACL, 2024.

[10] S. Robertson, H. Zaragoza. *The Probabilistic Relevance Framework: BM25 and Beyond*. Foundations and Trends in Information Retrieval 3(4), 2009.

[11] M. Häggström. *Normal posteroanterior (PA) chest radiograph (X-ray)*. Wikimedia Commons, CC0.

A Reproducibility and repository guide

Path	Content
`docs/evaluation_protocol.md`	Pre-registered rules and amendments
`docs/phase2_rag_plan.md`	Phase 2 design, arms, frozen settings
`docs/experiment_log.md`	Dated log of decisions and findings
`docs/literature_review.md`	Full review of the six papers
`baseline/`	Model runner, scorers, labels, retrieval code
`notebooks/01-05`	Colab notebooks (baseline, knowledge and side, diagnostics, disease naming, retrieval)
`results/`	Raw outputs of every run
`deliverables/diagrams/`	Mermaid sources of the block diagrams (`scripts/render_diagrams.py`)
`scripts/make_figures.py`	Regenerates the chart and photo figures

Table 3. Where to find things.

B Glossary

Atelectasis
Partial collapse of the lung.

BM25
A classic keyword-based ranking function for finding relevant text passages.

Cardiomegaly
An enlarged heart.

Constant-answer floor
Score of a system that ignores the image and always gives the most common answer.

Item recall
Share of the gold answer's items that an answer covers.

Oracle
An arm that uses the true label; an upper bound, not a real system.

Perception / knowledge
Seeing a finding in the image / knowing facts about the disease.

Pre-registration
Writing down test sets, scoring and success conditions before running the model.

RAG
Retrieval-augmented generation: adding retrieved text to the model's prompt.