Polyspace Bug Finder

Summary Report for Project: PolyspaceProject

Report Author: mabualqu

Polyspace Bug Finder: Summary Report for Project: PolyspaceProject by Report Author: mabualqu

Published 22-Sep-2021 18:27:46

Analysis Author(s): MathWorks Polyspace Version(s): Polyspace Bug Finder 3.6 (R2022a Prerelease)

Project Version(s): 1.0

Result Folder(s):

 $C: \label{linear_control_con$

Table of Contents

Chapter 1. Polyspace Bug Finder Summary	1
	1
Chapter 2. MISRA C:2012 Guidelines	
MISRA C:2012 Guidelines Summary - Violations by Rule	2
MISRA C:2012 Guidelines Summary for Enabled Guidelines	
Chapter 3. Appendix 1 - Configuration Settings	
Polyspace Settings	
Coding Standard Configuration	
Specified Constraints	15
Constraints - User Functions	15
Chapter 4. Appendix 2 - Definitions	16
	16

Chapter 1. Polyspace Bug Finder Summary

Table 1.1. Project Summary


	Count	Reviewed	Unreviewed	Pass/Fail
MISRA C:2012 Guidelines	2	0	2	NA
Total	2	0	2	NA

Table 1.2. Summary By File

File	MISRA C:2012 Guideline s (Reviewed)
$C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihooddd} C: likelihooddddddddddddddddddddddddddddddddddd$	0 (0)
$C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihooddd} C: likelihooddddddddddddddddddddddddddddddddddd$	0 (0)
$C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihooddd} C: likelihooddddddddddddddddddddddddddddddddddd$	0 (0)
$C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihooddd} C: likelihooddddddddddddddddddddddddddddddddddd$	0 (0)
$C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihood} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihoodd} C: \label{likelihooddd} C: likelihooddddddddddddddddddddddddddddddddddd$	0 (0)
$C: linear_continuous_con$	2 (0)

Chapter 2. MISRA C:2012 Guidelines

MISRA C:2012 Guidelines Summary - Violations by Rule



MISRA C:2012 Guidelines Summary for Enabled Guidelines

Guideline	Description	Mode	Total
1.1	The program shall contain no violations of the standard C syntax and constraints, and shall not exceed the implementation's translation limits.	required	0
1.3	There shall be no occurrence of undefined or critical unspecified behaviour.	required	0
2.1	A project shall not contain unreachable code.	required	0
2.2	There shall be no dead code.	required	0
2.7	There should be no unused parameters in functions.	readability	0
3.1	The character sequences /* and // shall not be used within a comment.	required	0
3.2	Line-splicing shall not be used in // comments.	required	0
4.1	Octal and hexadecimal escape sequences shall be terminated.	required	0
5.1	External identifiers shall be distinct.	required	0
5.2	Identifiers declared in the same scope and name space shall be distinct.	required	0
5.4	Macro identifiers shall be distinct.	required	0
5.5	Identifiers shall be distinct from macro names.	required	0
5.6	A typedef name shall be a unique identifier.	required	0
Total			2

Guideline	Description	Mode	Total
5.7	A tag name shall be a unique identifier.	required	0
5.8	Identifiers that define objects or functions with external linkage shall be unique.	required	0
6.1	Bit-fields shall only be declared with an appropriate type.	required	0
6.2	Single-bit named bit fields shall not be of a signed type.	required	0
7.4	A string literal shall not be assigned to an object unless the object's type is "pointer to const-qualified char".	required	0
8.2	Function types shall be in prototype form with named parameters.	required	0
8.3	All declarations of an object or function shall use the same names and type qualifiers.	required	0
8.6	An identifier with external linkage shall have exactly one external definition.	required	0
8.8	The static storage class specifier shall be used in all declarations of objects and functions that have internal linkage.	required	0
8.10	An inline function shall be declared with the static storage class.	required	0
8.12	Within an enumerator list, the value of an implicitly-specified enumeration constant shall be unique.	required	0
9.1	The value of an object with automatic storage duration shall not be read before it has been set.	mandatory	0
9.4	An element of an object shall not be initialized more than once.	required	0
11.1	Conversions shall not be performed between a pointer to a function and any other type.	required	0
11.2	Conversions shall not be performed between a pointer to an incomplete type and any other type.	required	0
11.3	A cast shall not be performed between a pointer to object type and a pointer to a different object type.	required	0
11.6	A cast shall not be performed between pointer to void and an arithmetic type.	required	0
11.7	A cast shall not be performed between pointer to object and a non-integer arithmetic type.	required	0
11.8	A cast shall not remove any const or volatile qualification from the type pointed to by a pointer.	required	0
12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	required	0
12.5	The sizeof operator shall not have an operand which is a function parameter declared as "array of type".	mandatory	0
13.1	Initializer lists shall not contain persistent side effects.	required	0
13.2	The value of an expression and its persistent side effects shall be the same under all permitted evaluation orders.	required	0
13.5	The right hand operand of a logical && or operator shall not contain persistent side effects.	required	0
13.6	The operand of the sizeof operator shall not contain any expression which has potential side effects.	mandatory	0
14.1	A loop counter shall not have essentially floating type.	advisory	0
14.2	A for loop shall be well-formed.	readability	0
14.3	Controlling expressions shall not be invariant.	required	0
15.6	The body of an iteration-statement or a selection-statement shall be a compound-statement.	required	0
Total			2

Guideline	Description	Mode	Total
17.1	The features of <stdarg.h> shall not be used.</stdarg.h>	required	0
17.2	Functions shall not call themselves, either directly or indirectly.	required	0
17.4	All exit paths from a function with non-void return type shall have an explicit return statement with an expression.	mandatory	0
17.6	The declaration of an array parameter shall not contain the static keyword between the [].	mandatory	0
18.1	A pointer resulting from arithmetic on a pointer operand shall address an element of the same array as that pointer operand.	required	0
18.2	Subtraction between pointers shall only be applied to pointers that address elements of the same array.	required	0
18.3	The relational operators >, >=, < and <= shall not be applied to objects of pointer type except where they point into the same object.	required	0
18.6	The address of an object with automatic storage shall not be copied to another object that persists after the first object has cease d to exist.	required	0
18.7	Flexible array members shall not be declared.	required	0
18.8	Variable-length array types shall not be used.	required	0
19.1	An object shall not be assigned or copied to an overlapping object.	mandatory	0
20.2	The ', " or \ characters and the /* or // character sequences shall not occur in a header file name.	required	0
20.3	The #include directive shall be followed by either a <filename> or "filename"sequence.</filename>	required	0
20.4	A macro shall not be defined with the same name as a keyword.	required	0
20.6	Tokens that look like a preprocessing directive shall not occur within a macro argument.	required	0
20.7	Expressions resulting from the expansion of macro parameters shall be enclosed in parentheses.	required	0
20.9	All identifiers used in the controlling expression of #if or #elif preprocessing directives shall be #define'd before evaluation.	required	0
20.11	A macro parameter immediately following a # operator shall not immediately be followed by a ## operator.	required	0
20.12	A macro parameter used as an operand to the # or ## operators, which is itself subject to further macro replacement, shall only be used as an operand to these operators.	required	0
20.13	A line whose first token is # shall be a valid preprocessing directive.	required	0
20.14	All #else, #elif and #endif preprocessor directives shall reside in the same file as the #if, #ifdef or #ifndef directive to which they are related.	required	0
21.1	#define and #undef shall not be used on a reserved identifier or reserved macro name.	required	2
21.2	A reserved identifier or reserved macro name shall not be declared.	required	0
21.3	The memory allocation and deallocation functions of <stdlib.h> shall not be used.</stdlib.h>	required	0
21.4	The standard header file <setjmp.h> shall not be used.</setjmp.h>	required	0
21.5	The standard header file <signal.h> shall not be used.</signal.h>	required	0
21.6	The Standard Library input/output functions shall not be used.	required	0
Total			2

Guideline	Description	Mode	Total
21.7	The Standard Library functions atof, atoi, atol and atoll of <stdlib.h> shall not be used.</stdlib.h>	required	0
21.8	The Standard Library termination functions of <stdlib.h> shall not be used.</stdlib.h>	required	0
21.9	The Standard Library functions bsearch and qsort of <stdlib.h> shall not be used.</stdlib.h>	required	0
21.10	The Standard Library time and date functions shall not be used.	required	0
21.11	The standard header file <tgmath.h> shall not be used.</tgmath.h>	required	0
21.13	Any value passed to a function in <ctype.h> shall be representable as an unsigned char or be the value EOF.</ctype.h>	mandatory	0
21.14	The Standard Library function memcmp shall not be used to compare null terminated strings.	required	0
21.15	The pointer arguments to the Standard Library functions memcpy, memmove and memcmp shall be pointers to qualified or unq ualified versions of compatible types.	required	0
21.16	The pointer arguments to the Standard Library function memcmp shall point to either a pointer type, an essentially signed type, an essentially unsigned type, an essentially Boolean type or an essentially enum type.	required	0
21.17	Use of the string handling functions from <string.h> shall not result in accesses beyond the bounds of the objects referenced by t heir pointer parameters.</string.h>	mandatory	0
21.18	The size_t argument passed to any function in <string.h> shall have an appropriate value.</string.h>	mandatory	0
21.19	The pointers returned by the Standard Library functions localeconv, getenv, setlocale or, strerror shall only be used as if they have pointer to const-qualified type.	mandatory	0
21.20	The pointer returned by the Standard Library functions asctime, ctime, gmtime, localtime, localeconv, getenv, setlocale or strerr or shall not be used following a subsequent call to the same function.	mandatory	0
22.1	All resources obtained dynamically by means of Standard Library functions shall be explicitly released.	required	0
22.2	A block of memory shall only be freed if it was allocated by means of a Standard Library function.	mandatory	0
22.3	The same file shall not be open for read and write access at the same time on different streams.	required	0
22.4	There shall be no attempt to write to a stream which has been opened as read-only.	mandatory	0
22.5	A pointer to a FILE object shall not be dereferenced.	mandatory	0
22.6	The value of a pointer to a FILE shall not be used after the associated stream has been closed.	mandatory	0
22.7	The macro EOF shall only be compared with the unmodified return value from any Standard Library function capable of return ing EOF.	required	0
22.8	The value of errno shall be set to zero prior to a call to an errno-setting-function.	required	0
22.9	The value of errno shall be tested against zero after calling an errno-setting-function.	required	0
22.10	The value of errno shall only be tested when the last function to be called was an errno-setting-function.	required	0
D1.1	Any implementation-defined behaviour on which the output of the program depends shall be documented and understood.	required	0
D2.1	All source files shall compile without any compilation errors.	required	0
D4.1	Run-time failures shall be minimized.	required	0
Total			2

Guideline	Description	Mode	Total
D4.3	Assembly language shall be encapsulated and isolated.	required	0
D4.7	If a function returns error information, then that error information shall be tested.	required	0
D4.10	Precautions shall be taken in order to prevent the contents of a header file being included more than once.	required	0
D4.11	The validity of values passed to library functions shall be checked.	required	0
D4.14	The validity of values received from external sources shall be checked.	required	0
Total			2

Chapter 3. Appendix 1 - Configuration Settings

Polyspace Settings

Option	Value
-author	MathWorks
-boolean-types	boolean_T
-bug-finder	true
-checkers	
-checkers-selection-file	$C: \label{linear_constraints} C: \label{linear_constraints} Is a 26262 \label{linear_constraints} C: \label{linear_constraints} Is a 26262 \label{linear_constraints} C: \label{linear_constraints} Is a 26262 \label{linear_constraints} Is a 26262 \label{linear_constraints} C: \label{linear_constraints} Is a 26262 \label{linear_constraints} Is a 262622 \label{linear_constraints} Is a 2626$
-compiler	generic
-D	main=main_rtwec,restrict=
-data-range-specifications	$C: linear_control_con$
-date	22/09/2021
-disable-checkers	all
-dos	true
-functions-called-in-loop	custom=PreviewCurvature
-functions-to-stub	rtIsNaN,rtIsInf,rtIsNaNF,rtIsInfF
-generate-results-for	all-headers
-I	likelikelikelikelikelikelikelikelikelike
-import-comments	$C: linear_control_con$
-lang	С-СРР
-main-generator	true
-mbd	true
-misra3	from-file
-misra3-agc-mode	true

Option	Value
-prog	PolyspaceProject
-results-dir	C: line:line:line:line:line:line:line:line:
-stub-embedded-coder-lookup-table-functions	true
-target	x86_64
-variables-written-before-loop	none
-variables-written-in-loop	none
-verif-version	1.0

Coding Standard Configuration

Table 3.1. MISRA C:2012 Guidelines Configuration

Guideli ne	Description	Mode	Comment	Enabled
D1.1	Any implementation-defined behaviour on which the output of the program depends shall be documente d and understood.	required	-	yes
D2.1	All source files shall compile without any compilation errors.	required	-	yes
D3.1	All code shall be traceable to documented requirements.	required	Not enforceable	no
D4.1	Run-time failures shall be minimized.	required	-	yes
D4.2	All usage of assembly language should be documented.	advisory	Not enforceable	no
D4.3	Assembly language shall be encapsulated and isolated.	required	-	yes
D4.4	Sections of code should not be "commented out".	advisory	# Not enforceable	no
D4.5	Identifiers in the same name space with overlapping visibility should be typographically unambiguous.	readability	-	no
D4.6	typedefs that indicate size and signedness should be used in place of the basic numerical types.	advisory	-	no
D4.7	If a function returns error information, then that error information shall be tested.	required	-	yes
D4.8	If a pointer to a structure or union is never dereferenced within a translation unit, then the implementati on of the object should be hidden.	advisory	-	no
D4.9	A function should be used in preference to a function-like macro where they are interchangeable.	advisory	-	no
D4.10	Precautions shall be taken in order to prevent the contents of a header file being included more than once .	required	-	yes
D4.11	The validity of values passed to library functions shall be checked.	required	-	yes

Guideli ne	Description	Mode	Comment	Enabled
D4.12	Dynamic memory allocation shall not be used.	required	# Not enforceable	no
D4.13	Functions which are designed to provide operations on a resource should be called in an appropriate seq uence.	advisory	-	no
D4.14	The validity of values received from external sources shall be checked.	required	-	yes
1.1	The program shall contain no violations of the standard C syntax and constraints, and shall not exceed the implementation's translation limits.	required	-	yes
1.2	Language extensions should not be used.	advisory	-	no
1.3	There shall be no occurrence of undefined or critical unspecified behaviour.	required	-	yes
1.4	Emergent language features shall not be used.	required	-	no
2.1	A project shall not contain unreachable code.	required	-	yes
2.2	There shall be no dead code.	required	-	yes
2.3	A project should not contain unused type declarations.	readability	-	no
2.4	A project should not contain unused tag declarations.	readability	-	no
2.5	A project should not contain unused macro declarations.	readability	-	no
2.6	A function should not contain unused label declarations.	readability	-	no
2.7	There should be no unused parameters in functions.	readability	-	yes
3.1	The character sequences /* and // shall not be used within a comment.	required	-	yes
3.2	Line-splicing shall not be used in // comments.	required	-	yes
4.1	Octal and hexadecimal escape sequences shall be terminated.	required	-	yes
4.2	Trigraphs should not be used.	advisory	-	no
5.1	External identifiers shall be distinct.	required	-	yes
5.2	Identifiers declared in the same scope and name space shall be distinct.	required	-	yes
5.3	An identifier declared in an inner scope shall not hide an identifier declared in an outer scope.	advisory	-	no
5.4	Macro identifiers shall be distinct.	required	-	yes
5.5	Identifiers shall be distinct from macro names.	required	-	yes
5.6	A typedef name shall be a unique identifier.	required	-	yes
5.7	A tag name shall be a unique identifier.	required	-	yes
5.8	Identifiers that define objects or functions with external linkage shall be unique.	required		yes
5.9	Identifiers that define objects or functions with internal linkage should be unique.	readability	-	no
6.1	Bit-fields shall only be declared with an appropriate type.	required	-	yes
6.2	Single-bit named bit fields shall not be of a signed type.	required	-	yes

Guideli ne	Description	Mode	Comment	Enabled
7.1	Octal constants shall not be used.	advisory	-	no
7.2	A "u" or "U" suffix shall be applied to all integer constants that are represented in an unsigned type.	readability	-	no
7.3	The lowercase character "l" shall not be used in a literal suffix.	readability	-	no
7.4	A string literal shall not be assigned to an object unless the object's type is "pointer to const-qualified char" .	required	-	yes
8.1	Types shall be explicitly specified.	required	#on for C90	no
8.2	Function types shall be in prototype form with named parameters.	required		yes
8.3	All declarations of an object or function shall use the same names and type qualifiers.	required	-	yes
8.4	A compatible declaration shall be visible when an object or function with external linkage is defined.	advisory	-	no
8.5	An external object or function shall be declared once in one and only one file.	advisory	-	no
8.6	An identifier with external linkage shall have exactly one external definition.	required	-	yes
8.7	Functions and objects should not be defined with external linkage if they are referenced in only one translation unit.	advisory	-	no
8.8	The static storage class specifier shall be used in all declarations of objects and functions that have interna l linkage.	required	-	yes
8.9	An object should be defined at block scope if its identifier only appears in a single function.	advisory	-	no
8.10	An inline function shall be declared with the static storage class.	required	-	yes
8.11	When an array with external linkage is declared, its size should be explicitly specified.	advisory	-	no
8.12	Within an enumerator list, the value of an implicitly-specified enumeration constant shall be unique.	required	-	yes
8.13	A pointer should point to a const-qualified type whenever possible.	advisory	-	no
8.14	The restrict type qualifier shall not be used.	advisory	-	no
9.1	The value of an object with automatic storage duration shall not be read before it has been set.	mandatory	-	yes
9.2	The initializer for an aggregate or union shall be enclosed in braces.	readability	-	no
9.3	Arrays shall not be partially initialized.	readability	-	no
9.4	An element of an object shall not be initialized more than once.	required	-	yes
9.5	Where designated initializers are used to initialize an array object the size of the array shall be specified explicitly.	readability	-	no
10.1	Operands shall not be of an inappropriate essential type.	advisory		no
10.2	Expressions of essentially character type shall not be used inappropriately in addition and subtraction op erations.	advisory	-	no
10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a differe nt essential type category.	advisory	-	no

Guideli ne	Description	Mode	Comment	Enabled
10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the sa me essential type category.	advisory	-	no
10.5	The value of an expression should not be cast to an inappropriate essential type.	advisory	-	no
10.6	The value of a composite expression shall not be assigned to an object with wider essential type.	advisory	-	no
10.7	If a composite expression is used as one operand of an operator in which the usual arithmetic conversions are performed then the other operand shall not have wider essential type.	advisory	-	no
10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type.	advisory	-	no
11.1	Conversions shall not be performed between a pointer to a function and any other type.	required	-	yes
11.2	Conversions shall not be performed between a pointer to an incomplete type and any other type.	required	-	yes
11.3	A cast shall not be performed between a pointer to object type and a pointer to a different object type.	required	-	yes
11.4	A conversion should not be performed between a pointer to object and an integer type.	advisory	-	no
11.5	A conversion should not be performed from pointer to void into pointer to object.	advisory	-	no
11.6	A cast shall not be performed between pointer to void and an arithmetic type.	required	-	yes
11.7	A cast shall not be performed between pointer to object and a non-integer arithmetic type.	required	-	yes
11.8	A cast shall not remove any const or volatile qualification from the type pointed to by a pointer.	required	-	yes
11.9	The macro NULL shall be the only permitted form of integer null pointer constant.	readability	-	no
12.1	The precedence of operators within expressions should be made explicit.	advisory	-	no
12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of t he essential type of the left hand operand.	required	-	yes
12.3	The comma operator should not be used	advisory	-	no
12.4	Evaluation of constant expressions should not lead to unsigned integer wrap-around.	advisory	-	no
12.5	The sizeof operator shall not have an operand which is a function parameter declared as "array of type".	mandatory	-	yes
13.1	Initializer lists shall not contain persistent side effects.	required	-	yes
13.2	The value of an expression and its persistent side effects shall be the same under all permitted evaluation orders.	required	-	yes
13.3	A full expression containing an increment (++) or decrement () operator should have no other potential s ide effects other than that caused by the increment or decrement operator.	readability	-	no
13.4	The result of an assignment operator should not be used.	advisory	-	no
13.5	The right hand operand of a logical && or operator shall not contain persistent side effects.	required	-	yes
13.6	The operand of the sizeof operator shall not contain any expression which has potential side effects.	mandatory	-	yes
14.1	A loop counter shall not have essentially floating type.	advisory	-	yes

Guideli ne	Description	Mode	Comment	Enabled
14.2	A for loop shall be well-formed.	readability	-	yes
14.3	Controlling expressions shall not be invariant.	required	-	yes
14.4	The controlling expression of an if statement and the controlling expression of an iteration-statement shal l have essentially Boolean type.	advisory	-	no
15.1	The goto statement should not be used.	advisory	-	no
15.2	The goto statement shall jump to a label declared later in the same function.	advisory	-	no
15.3	Any label referenced by a goto statement shall be declared in the same block, or in any block enclosing the goto statement.	advisory	-	no
15.4	There should be no more than one break or goto statement used to terminate any iteration statement.	advisory	-	no
15.5	A function should have a single point of exit at the end.	advisory	-	no
15.6	The body of an iteration-statement or a selection-statement shall be a compound-statement.	required	-	yes
15.7	All if else if constructs shall be terminated with an else statement.	readability	-	no
16.1	All switch statements shall be well-formed.	advisory	-	no
16.2	A switch label shall only be used when the most closely-enclosing compound statement is the body of a switch statement.	advisory	-	no
16.3	An unconditional break statement shall terminate every switch-clause.	advisory	-	no
16.4	Every switch statement shall have a default label.	advisory	-	no
16.5	A default label shall appear as either the first or the last switch label of a switch statement.	advisory	-	no
16.6	Every switch statement shall have at least two switch-clauses.	advisory	-	no
16.7	A switch-expression shall not have essentially Boolean type.	advisory	-	no
17.1	The features of <stdarg.h> shall not be used.</stdarg.h>	required	-	yes
17.2	Functions shall not call themselves, either directly or indirectly.	required	-	yes
17.3	A function shall not be declared implicitly.	mandatory	#on for C90	no
17.4	All exit paths from a function with non-void return type shall have an explicit return statement with an expression.	mandatory	-	yes
17.5	The function argument corresponding to a parameter declared to have an array type shall have an appropriate number of elements.	readability	-	no
17.6	The declaration of an array parameter shall not contain the static keyword between the [].	mandatory	-	yes
17.7	The value returned by a function having non-void return type shall be used.	readability	-	no
17.8	A function parameter should not be modified.	readability	-	no
18.1	A pointer resulting from arithmetic on a pointer operand shall address an element of the same array as th at pointer operand.	required	-	yes

Guideli ne	Description	Mode	Comment	Enabled
18.2	Subtraction between pointers shall only be applied to pointers that address elements of the same array.	required	-	yes
18.3	The relational operators >, >=, < and <= shall not be applied to objects of pointer type except where they p oint into the same object.	required	-	yes
18.4	The +, -, += and -= operators should not be applied to an expression of pointer type.	advisory	-	no
18.5	Declarations should contain no more than two levels of pointer nesting.	readability	-	no
18.6	The address of an object with automatic storage shall not be copied to another object that persists after the first object has ceased to exist.	required	-	yes
18.7	Flexible array members shall not be declared.	required	-	yes
18.8	Variable-length array types shall not be used.	required	-	yes
19.1	An object shall not be assigned or copied to an overlapping object.	mandatory	-	yes
19.2	The union keyword should not be used.	advisory	-	no
20.1	#include directives should only be preceded by preprocessor directives or comments.	advisory	-	no
20.2	The ', " or \ characters and the /* or // character sequences shall not occur in a header file name.	required	-	yes
20.3	The #include directive shall be followed by either a <filename> or "filename"sequence.</filename>	required	-	yes
20.4	A macro shall not be defined with the same name as a keyword.	required	-	yes
20.5	#undef should not be used.	readability	-	no
20.6	Tokens that look like a preprocessing directive shall not occur within a macro argument.	required	-	yes
20.7	Expressions resulting from the expansion of macro parameters shall be enclosed in parentheses.	required	-	yes
20.8	The controlling expression of a #if or #elif preprocessing directive shall evaluate to 0 or 1.	advisory	-	no
20.9	All identifiers used in the controlling expression of #if or #elif preprocessing directives shall be #define'd before evaluation.	required	-	yes
20.10	The # and ## preprocessor operators should not be used.	advisory	-	no
20.11	A macro parameter immediately following a # operator shall not immediately be followed by a ## operator.	required	-	yes
20.12	A macro parameter used as an operand to the # or ## operators, which is itself subject to further macro re placement, shall only be used as an operand to these operators.	required	-	yes
20.13	A line whose first token is # shall be a valid preprocessing directive.	required	-	yes
20.14	All #else, #elif and #endif preprocessor directives shall reside in the same file as the #if, #ifdef or #ifndef d irective to which they are related.	required	-	yes
21.1	#define and #undef shall not be used on a reserved identifier or reserved macro name.	required	-	yes
21.2	A reserved identifier or reserved macro name shall not be declared.	required	-	yes
21.3	The memory allocation and deallocation functions of <stdlib.h> shall not be used.</stdlib.h>	required	-	yes

Guideli ne	Description	Mode	Comment	Enabled
21.4	The standard header file <setjmp.h> shall not be used.</setjmp.h>	required	-	yes
21.5	The standard header file <signal.h> shall not be used.</signal.h>	required	-	yes
21.6	The Standard Library input/output functions shall not be used.	required	-	yes
21.7	The Standard Library functions atof, atoi, atol and atoll of <stdlib.h> shall not be used.</stdlib.h>	required	-	yes
21.8	The Standard Library termination functions of <stdlib.h> shall not be used.</stdlib.h>	required	-	yes
21.9	The Standard Library functions bsearch and qsort of <stdlib.h> shall not be used.</stdlib.h>	required	-	yes
21.10	The Standard Library time and date functions shall not be used.	required	-	yes
21.11	The standard header file <tgmath.h> shall not be used.</tgmath.h>	required	-	yes
21.12	The exception handling features of <fenv.h> should not be used.</fenv.h>	advisory	-	no
21.13	Any value passed to a function in <ctype.h> shall be representable as an unsigned char or be the value EO F.</ctype.h>	mandatory	-	yes
21.14	The Standard Library function memcmp shall not be used to compare null terminated strings.	required	-	yes
21.15	The pointer arguments to the Standard Library functions memcpy, memmove and memcmp shall be point ers to qualified or unqualified versions of compatible types.	required	-	yes
21.16	The pointer arguments to the Standard Library function memcmp shall point to either a pointer type, an essentially signed type, an essentially Boolean type or an essentially enum type.	required	_	yes
21.17	Use of the string handling functions from <string.h> shall not result in accesses beyond the bounds of the objects referenced by their pointer parameters.</string.h>	mandatory	-	yes
21.18	The size_t argument passed to any function in <string.h> shall have an appropriate value.</string.h>	mandatory	-	yes
21.19	The pointers returned by the Standard Library functions localeconv, getenv, setlocale or, strerror shall only be used as if they have pointer to const-qualified type.	mandatory	-	yes
21.20	The pointer returned by the Standard Library functions asctime, ctime, gmtime, localtime, localeconv, get env, setlocale or strerror shall not be used following a subsequent call to the same function.	mandatory	_	yes
21.21	The Standard Library function system of <stdlib.h> shall not be used.</stdlib.h>	required	-	no
22.1	All resources obtained dynamically by means of Standard Library functions shall be explicitly released.	required	-	yes
22.2	A block of memory shall only be freed if it was allocated by means of a Standard Library function.	mandatory	-	yes
22.3	The same file shall not be open for read and write access at the same time on different streams.	required	-	yes
22.4	There shall be no attempt to write to a stream which has been opened as read-only.	mandatory	-	yes
22.5	A pointer to a FILE object shall not be dereferenced.	mandatory	-	yes
22.6	The value of a pointer to a FILE shall not be used after the associated stream has been closed.	mandatory	-	yes
22.7	The macro EOF shall only be compared with the unmodified return value from any Standard Library function capable of returning EOF.	required	_	yes

Guideli ne	Description	Mode	Comment	Enabled
22.8	The value of errno shall be set to zero prior to a call to an errno-setting-function.	required	-	yes
22.9	The value of errno shall be tested against zero after calling an errno-setting-function.	required	-	yes
22.10	The value of errno shall only be tested when the last function to be called was an errno-setting-function.	required	-	yes

Specified Constraints

Constraints - User Functions

Table 3.2. File: C:\ Users\ mabualqu\ hlf2\ ISO_06_08_SwU\ WPs\ ISO_6_8_5_2_Impl\ slprj\ ert\ PreviewCurvature\ PreviewCurvature.c

Name	Туре	Main Gener ator Called	Init Mode	Init Range	Initialize P ointer	# Allocated O bjects	Init Allocated	Global Assert	Assert Range	Comment
PreviewCurvature.* arg1	const float64		INIT	minmax				unsupported	unsupported	
PreviewCurvature.* arg2	const float32		INIT	minmax				unsupported	unsupported	
PreviewCurvature.* arg3	const float32		INIT	minmax				unsupported	unsupported	
PreviewCurvature.* arg4	const float32		INIT	minmax				unsupported	unsupported	
PreviewCurvature.* arg5	const float32		INIT	minmax				unsupported	unsupported	
PreviewCurvature.* arg6	float64		INIT	minmax				unsupported	unsupported	
PreviewCurvature.* arg7	float64		INIT	minmax				unsupported	unsupported	
PreviewCurvature.* arg8	float64		INIT	minmax				unsupported	unsupported	
PreviewCurvature.arg1	float64 const *		INIT		Not NULL	MULTI	1			
PreviewCurvature.arg2	float32 const *		INIT		Not NULL	MULTI	1			
PreviewCurvature.arg3	float32 const *		INIT		Not NULL	MULTI	1			
PreviewCurvature.arg4	float32 const *		INIT		Not NULL	MULTI	1			
PreviewCurvature.arg5	float32 const *		INIT		Not NULL	MULTI	1			
PreviewCurvature.arg6	float64 *		INIT		Not NULL	MULTI	31			
PreviewCurvature.arg7	float64 *		INIT		Not NULL	MULTI	1			
PreviewCurvature.arg8	float64 *		INIT		Not NULL	MULTI	1			

Chapter 4. Appendix 2 - Definitions

Table 4.1. Abbreviations

Abbreviation	Definition
NA	Not Available