

## Assignment 3

|         |                                                                                                                |
|---------|----------------------------------------------------------------------------------------------------------------|
| Team ID | 1                                                                                                              |
| Members | Ankur Gupta (20252651008)<br>Kartik Karnwal (20252651028)<br>Kirti Gautam (20252651029)<br>Pintu (20252651038) |

### 1 Task 1

Partner: **TextRelay** — external SMS gateway used by the **Notifications** service. Operation: **sendSMS**, backing **Notifications.send** from Assignment 2.

SOAP fits here because TextRelay is a telecom provider we don't own: it enforces a strict WSDL so malformed messages never reach a real phone, WS-Security signs the credential inside the envelope rather than relying on transport alone, and it needs a synchronous, all-or-nothing acknowledgement (**sent** or a fault) rather than a best-effort REST call. CampusEats' own services stay REST since we control both ends and don't need that contract weight.

### 2 Task 4

```
POST /sms HTTP/1.1
Host: api.textrelay.example
Content-Type: text/xml; charset=utf-8
SOAPAction: "urn:textrelay:sendSMS"

<soap:Envelope> ... </soap:Envelope>
```

### 3 Task 5

Either a direct link from TextRelay (**textrelay.example/Notifications.wsdl**), or a lookup in CampusEats' internal partner catalogue for “who sends SMS?” — the modern stand-in for UDDI; no live registry server is run.

|               |                                                                          |
|---------------|--------------------------------------------------------------------------|
| business      | TextRelay Communications Pvt. Ltd.                                       |
| service       | Notifications                                                            |
| endpoint      | <b>https://api.textrelay.example/sms</b>                                 |
| spec (tModel) | speaks <b>urn:textrelay</b> — Notifications WSDL ( <b>partner.wsdl</b> ) |

### 4 Task 6

- TextRelay fault: **INVALID\_DESTINATION** (“Invalid destination number”)
- CampusEats **Notifications.send** error: “**invalid user**”
- The student-facing app never sees **INVALID\_DESTINATION** or TextRelay's namespace — only the contract's own error code.