7. From a given vertex in a weighted connected graph, find shortest paths to other vertices using **Dijkstra's algorithm**. Write the program in Java.

```
import java.util.*;
public class DijkstraDemo
{
 static int dist [] = new int[20];        /* Array to store Min Distance */
 static int visited [] = new int[20];  /* Array to keep track of visited nodes */
 static int path[] = new int[20];      /* Array to keep track of shortest path from source node
                                          to all other nodes */
 static int source;
 public static void main(String [] args)
 {
    int u,v,n;
    int w[][] = new int[20][20]; /* 2D-array to read the values of weighted graph */
    int i,j;

    Scanner in = new Scanner(System.in);

    System.out.println("Enter the no of nodes");
    n = in.nextInt();

    System.out.println("Enter the weight matrix");
    for(i=1;i<=n;i++)
    {
     for(j=1;j<=n;j++)
      {
       w[i][j] = in.nextInt();
      }
    }

    System.out.println("Enter the source vertex");
    source = in.nextInt();
    /* Initially set all the nodes as unvisited */
    for(i=1;i<=n;i++)
    {
      visited[i]=0;
    }
    /* Set the source node as visited */
     visited[source] = 1;

    for(i=1;i<=n;i++)
    {
       dist[i] = w[source][i];
    }
    /* Initially set the shortest path from source node to all other nodes is through source */
    for(i=1;i<=n;i++)
```

```
0  3 999 7 999
3 0 4 2 999
999 4 0 6 6
7 2 6 0 4
999 999 6 4 0
```

```
    {
       path[i] = source;
    }
     /* Set the shortest path to the source node as -1 */
     path[source] = -1;

    for(i=1;i<n;i++)
    {
      u = minDistance(n);
      visited[u] = 1;
      v = 1;

      while(v<=n)
      {
        if((dist[u] + w[u][v]<dist[v]) && visited[v]==0)
        {
          dist[v] = dist[u] + w[u][v];
          path[v] = u;
        }
        v++;
      } end of while loop
    }  end of for loop
    printShortest(n);
}
 /* Method to find next closest node to the souce node */
 public static int minDistance(int n)
 {
     int i,minDist,minIndex=0;
     minDist = 999;

     for(i=1;i<=n;i++)
     {
      if(dist[i] < minDist && visited[i] == 0)
      {
         minDist = dist[i];
         minIndex = i;
      }
     }
     return minIndex;
 }
 /* Method to print shortest distance from source node to all other nodes*/
 public static void  printShortest(int n)
 {
   int i;

   for(i=1;i<=n;i++)
```

u=2 u=4 visited[2]=1,visited[1]=1
visited= 1 1 0 0 0 visited=1 1 0 1 0

w= 0 3 999 7 999
3 0 4 2 999
7 2 6 0 4

dist = 0 3 999 7 999
dist= 0 3 7 5 999
dist= 0 3 7 5 9

path[3]=2
path[5]=4
path =-1 1 1 1 1
-1 1 2 2 1
-1 1 2 2 4

dist= 0 3 999 7 999
0 3 7 5 999

visited=1 1 0 0 0

mindist=3
minIndex=2

mindist=7 mindist=5
minIndex=3 minindex=4

```
    {
       if(i!=source)
       {
        System.out.println("The shortest distance from node " + source + " to " + i +"=" + dist[i]);
        System.out.print("The shortest path from node " + source+ " to " + i +" is: ");
        System.out.print(source);
        printPath(path,i);
        System.out.println();
       }
    }
  }
 /*Method to print shortest path */
 public static void printPath(int path[],int j)
 {
    if(path[j]== -1)
     return ;

    printPath(path,path[j]);
    System.out.print("--->"+ j +" ");
  }
}
```

-1 1 2 2 4

printpath(path,2)

printpath(path,1)

printpath(path,1)