

MCM

MCM is matrix chain multiplication. Given a sequence of matrices, find the most efficient way to multiply these matrices together. The problem is not actually to perform the multiplications but merely to decide in which order the multiplications are to be performed.

Matrix-Chain-Order (p)

```

1  n ← length[p] - 1
2  for i = 1 to n
3      do m[i, j] ← 0
4  for i = 2 to n
5      do for l = 1 to n - i + 1
6          do j = i + l - 1
7              m[i, j] ← ∞
8              for k = i to j - 1
9                  do q ← m[i, k] + m[k + 1, j] + p[i - 1] * p[k] * p[j]
10                     if q < m[i, j]
11                         then m[i, j] ← q
12                            s[i, j] ← k
13  return m and s

```

~~return m and s~~

LCS

Longest common subsequence

Given two sequences, find the length of longest subsequence present in both of them.

A subsequence is a sequence that appears in the same relative order, but not necessarily contiguous.

Eg - abcdefg ← sequence


subsequences → abc, abg, abd, aeg, ---

So a string of length n has 2^n different possible subsequences.

There are 2 methods of LCS

- recursion
- dynamic programming

Matrix Chain Multiplication U-2



$$A_1 \cdot A_2 \cdot A_3 \cdot A_4$$

$$\begin{array}{cccc} 5 \times 4 & 4 \times 6 & 6 \times 2 & 2 \times 2 \\ p_0 \ p_1 & p_1 \ p_2 & p_2 \ p_3 & p_3 \ p_4 \end{array}$$

$$M[i, j] = \begin{cases} i=j, & 0 \\ \min_{i \leq k \leq j} M[i, k] + M[k+1, j] + p_{i-1} p_k p_j \end{cases}$$

	1	2	3	4
1	0	120		
2	X	0	48	
3	X	X	0	84
4	X	X	X	0

$$i=1 \quad j=2 \quad k=1$$

$$M[1, 2] = 0 + 0 + 5 \times 4 \times 6 = 120$$

$$i=2 \quad j=3 \quad k=2$$

$$M[2, 3] = 0 + 0 + 4 \times 2 \times 6 = 48$$

$$i=3 \quad j=4 \quad k=3$$

$$M[3, 4] = 0 + 0 + 6 \times 2 \times 2 = 24$$

and so on - - -

→ Verification of $M[1,4]$ at $k=3$

$$M[1,3] + M[4,4] \rightarrow 0$$

↓

$k=1$ $M[1,1] + M[2,3]$

0 ✓

$$A_1 \cdot (A_2 \cdot A_3) \cdot A_4$$

$$4 \times 6 \times 2$$

$$- 42$$

$$4 \times 2$$

$$- 40$$

$$5 \times 4 \times 2$$

$$5 \times 2$$

$$5 \times 2 + 7$$

$$- 70$$

$$\underline{158}$$

Longest Common Subsequence LCS

⇒ Algo to find LCS using recursion.

int LCS(i, j)

{

if ($A[i] == '10'$ || $B[i] == '10'$)

return 0;

else if ($A[i] == B[i]$)

return 1 + LCS(i+1, j+1);

else

return Max (LCS(i+1, j), LCS(i, j+1));

}


g -

String 1

0	1	2
b	d	v

String 2

0	1	2	3	4
a	b	c	d	v



	0	1	2	3	4
0	2	2	1		
1	1	1	1	1	
2	0	0	0		0

~~Longest Common Subsequence~~

LCS = 2

⇒ Algo using dynamic programming

if $(A[i] == B[j])$

$$LCS[i, j] = 1 + LCS[i-1, j-1]$$

else

$$LCS[i, j] = \text{Max} [LCS(i-1, j), \text{ ~~max~~ } LCS(i, j-1)]$$

Eg - String 1

b	d
---	---

String 2

a	b	c	d
---	---	---	---

		a b c d				
		0	1	2	3	4
0		0	0	0	0	0
b	1	0	0	1	1	1
d	2	0	0	1	1	2

Greedy Algorithm

Activity selection problem

- Sort the activity in ascending order of their finishing time.
- Select the first activity
- Select the new activity if its starting time is greater or equal to the finishing time of previously selected activity.
- Repeat step 3 till all the activities are examined.

Algorithm -

$n \leftarrow \text{length}[s]$

$A \leftarrow \{1\}$

$j \leftarrow 1$

for $i = 2$ to n

do if $s_i \geq f_j$

then $A \leftarrow A \cup \{i\}$

$j \leftarrow i$

return A

Example - $S = \{A_1, A_2, A_3, A_4, A_5, A_6, A_7, A_8\}$

$S_i = \{1, 2, 3, 4, 8, 9, 9, 11\}$

$f_i = \{3, 5, 4, 7, 10, 9, 11, 12\}$

Step 1 - Arrange them in increasing order of finishing time -

Activity	A_1	A_3	A_2	A_4	A_6	A_5	A_7	A_8
Start Time	1	3	2	4	9	8	9	11
Finish Time	3	4	5	7	9	10	11	12

$i, j \rightarrow i$

starting time of $j \geq 1 \neq 3$ j shifts
 finishing time of i $3 \geq 3$ i shifts
 $3 \neq 4$ j shifts

and so on ---

selected activity	A_1	A_3	A_4	A_6	A_7	A_8
start	1	3	4	9	9	11
finish	3	4	7	9	11	12

Huffman code.

Data can be encoded efficiently using Huffman codes. It is widely used and very effective technique for compressing data.

Eg - B C C A B B D D A E C C B B A E D D
C C

ii Fixed length code.

A - 65 - 01000001 - 8 bit
B - 66 - 01000010
C - 67 - 01000011
D - 68 - 01000100
E - 69 - 01000101

Char	Count	code
A	3	000
B	5	001
C	6	010
D	4	011
E	2	100

20

msg size - $20 \times 3 = 60$

code size - $5 \times 3 = 15$

char - $5 \times 8 = 40$
115

iii

Variable length code

Char	Count	Code
A	3	1001
B	5	10
C	6	11
D	4	01
E	2	000

$$A \rightarrow 3 \times 3 = 9$$

$$B \rightarrow 5 \times 2 = 10$$


$$C \rightarrow 6 \times 2 = 12$$

$$D \rightarrow 4 \times 2 = 8$$

$$E \rightarrow 2 \times 3 = 6$$

$$\hline 45$$

Optimal message pattern tree



msg size - 45

code size - 12

char - 40

$$\hline 97$$

Algorithm -

HUFFMAN (C)

- 1 $n \leftarrow |C|$
- 2 $Q \leftarrow C$
- 3 for $i = 1$ to $n - 1$
- 4 do allocate a new node z
- 5 $\text{left}(z) \leftarrow x \leftarrow \text{Extract_Min}(Q)$
- 6 $\text{right}(z) \leftarrow y \leftarrow \text{Extract_Min}(Q)$
- 7 $f(z) \leftarrow f(x) + f(y)$
- 8 $\text{Insert}(Q, z)$
- 9 return $\text{Extract_Min}(Q)$

Eg -

Char	Count	Code
a	45	0
b	13	101
c	12	100
d	16	111
e	9	1101
f	5	1100

$$a \rightarrow 45 \times 1 = 45$$

$$b \rightarrow 39$$

$$c \rightarrow 36$$

$$d \rightarrow 48$$

$$e \rightarrow 36$$





$$f \rightarrow 20$$

$$\underline{\underline{224}}$$

msg size - 224
code size - 100
char - $\frac{40}{364}$

Task
This

f:5 e:9 c:12 b:13 d:16 a:45



Task Scheduling Problem


This is the problem of optimally scheduling unit time tasks on a single processor, where each task has a deadline and some profit.

Eg -

Task	T_1	T_2	T_3	T_4	T_5	T_6
Profit	50	40	30	10	20	1
Deadline	2	2	3	4	1	5

Arrange profit in descending order.

Task	T_1	T_2	T_3	T_5	T_4	T_6
Profit	50	40	30	20	10	1
Deadline	2	2	3	1	4	5




~~Task~~


Travelling Salesman Problem

In this a salesman needs to visit 'n' cities in such a manner that all cities must be visited at once and in the end he returns to the city from where he started with minimum cost.


Eg -




	1	2	3	4	5	6	7	8
1	0	5	0	6	0	(4) ¹	0	7
2	5	0	(2) ⁶	4	3	0	0	0
3	0	2	0	(1) ³	0	0	0	0
4	(6) ⁸	4	1	0	7	0	0	0
5	0	(3) ⁵	0	7	0	0	6	4
6	4	0	0	0	0	0	(3) ⁷	0
7	0	0	0	0	6	3	0	(2) ²
8	7	0	0	0	(4) ⁴	0	2	0



Total = 25



	1	2	3	4
1	0	10	15	20
2	5	0	9	10
3	6	13	0	12
4	8	8	9	0



$$\text{Min } \{35, 45, 43\} = 35$$

$\{1, 2, 4, 3\}$

$$g(i, S) = \min \{ c_{ij} + g(j, S - \{i\}) \}$$

$$S = \{1, 2, 3, 4\}$$

$$10 + 25 = 35$$


$$/$$

$$c_{ij}$$

Graph Coloring

In graph coloring we have to color the vertices of a graph such that no 2 adjacent vertices must have same color.


Eg - We have given a simple graph and a set of 3 colors let say Red, Blue, Green.





Colors - R, B, G

1	2	3	4
R	G	R	G
R	G	R	B

There are so many solution possible for this graph. We can find all the solutions using backtracking





Solutions 1

R G R G
R G R B
R G B G
R B R G
R B R B

And so on many more solutions
can be obtained.

N - Queen Problem

N - Queens problem is to place n - queens in such a manner on an $n \times n$ chessboard that no two queens attack each other by being in the same row, column, or diagonal.

Eg - We have 4 queens to be placed in 4×4 chessboard.


	1	2	3	4
1	Q_1	x		
2	x	x	Q_2	
3	x	x	x	x
4				

	1	2	3	4
1		Q_1		
2	x	x	x	Q_2
3	Q_3	x	x	x
4	x	x	Q_4	x



1	2	3	4
Q_3	Q_1	Q_4	Q_2

There can be more than 1 solution possible. We can use backtracking method to generate next node and stop if next node violates the rule.



Number of nodes possible

$$= 1 + 4 + 4 \times 3 + 4 \times 3 \times 2 + 4 \times 3 \times 2 \times 1$$

= 65

$$= 1 + \sum_{i=1}^n \left[\prod_{j=0}^{i-1} (4-j) \right]$$

Algorithm -

place (k, i)
{

for (j=1 to k-1)
{

if ((x[j] = i) or (Abs (x[j] - i) =
Abs [j - k]))

then

return false

}

return true;

}

NQueens (k, n)

{

for (i=1 to n)
{

if (place (k, i))
{

x[k] = i;

if (k == n)

then

print ($a[1:n]$)

else

N Queens ($k+1, n$)

}


#

Hamiltonian Cycle

Hamiltonian Path -

Given a graph $G = (V, E)$ we have to find the Hamiltonian path.

Eg -



Path - 4, 3, 1, 2, 5

or


5, 2, 1, 3, 4.

Visiting each vertex ^{only} ~~at least~~ once ~~with~~ is called Hamiltonian path.

Hamiltonian cycle - Visiting ~~at~~ each vertex only once with some starting and ending vertex is called Hamiltonian cycle.

Hamiltonian using backtracking

Eg -




We have to create an adjacent matrix having ~~rows~~ rows and column equal to number of nodes.

	a	b	c	d	e	f
a	0	1	1	1	0	0
b	1	0	1	0	1	0
c	1	1	0	1	1	0
d	1	0	1	0	1	1
e	0	1	1	1	0	1
f	0	0	0	1	1	0

Conditions for construction of cycle

- no repetition of value
- if we are inserting $x[k]$ it must be connected to $x[k-1]$
- last node and first node must have a edge in between.



1	2	3	4	5	6
a	b	c	e	f	d

1	2	3	4	5	6
a	b	e	f	d	c

And so on more solutions can be obtained.

Algorithm -

NextVertex(k)

do

$$x[k] = (x[k] + 1) \text{Mod}(n + 1)$$

if $(x[k] = 0)$

return;

~~if (G(x[k-1], x[k]) != 0)~~

if (G(x[k-1], x[k]) != 0)
{

for (j = 1 to k-1)
{

if (x[j] == x[k])

break;

if (j == k)

if (k < n or (k == n &&

G(x[n], x[1]) != 0))

return;

}

}

}

while (true);

}

Hamiltonian (k)

{

do

{

NextVertex(k);

if (x[k] == 0)

return;

else if (k == n)

print (x[1:n]);

else

Hamiltonian (k+1);

}

while (true);

}