

# Essentials of Information Technology

PC-CS-305

Collection API & Generics

## Topic & Structure of the lesson



- Using varargs , overloading varargs methods
- Using String ,StringBuffer and String Builder class
- Collection Framework using Interface and Implementation
- Interfaces List, Set, Queue, Map.
- Implementation of Set interface using HashSet, TreeSet and LinkedHashSet.

## Topic & Structure of the lesson



- Implementation of List interface using ArrayList and LinkedList.
- Implementation of Map interface using HashMap and TreeMap.
- Using Generics

PC-CS-305: Essentials of Information Technology

## Varargs



Creation of methods, that take variable number of arguments is called varargs and it short form for variable length arguments.

A variable length argument is specified by three periods (...)

### *Signature of a method using varargs*

static void vaTest (int ...v) ,v is operated as an array

PC-CS-305: Essentials of Information Technology

## Variable length Argument Prior JDK 5.0



```
class PassArray {
    static void vaTest(int v[]){
        System.out.println("Number of args: "+v.length);
        System.out.println("Contents: ");
        for(int x: v)
            System.out.println(x+" ");
        System.out.println();
    }
    public static void main(String[] args) {
        int n1[] = {10};
        int n2[] = {1,2,3};
        int n3[] = {};
        vaTest(n1);
        vaTest(n2);
        vaTest(n3);
    }
}
```

PC-CS-305: Essentials of Information Technology

## Varargs



```
class VarArgs {
    void vaTest(int ...v){
        System.out.println("Number of args: "+v.length);
        System.out.println("Contents: ");
        for(int x: v)
            System.out.println(x+" ");
        System.out.println();
    }

    public static void main(String[] args)
    {
        VarArgs a= new VarArgs();

        a.vaTest();
        a.vaTest(1);
        a.vaTest(1,2,3);
    }
}
```

PC-CS-305: Essentials of Information Technology

## Note



A method can have normal parameters along with variable length parameters, however the variable length parameter must be last parameter declared by the method.

```
int doit(int a, int b, double c, int ...vals)
```

PC-CS-305: Essentials of Information Technology

## Overloading Varargs Methods



```
class VarArgs2 {  
    static void vaTest(int ...v){  
        for(int x: v)  
            System.out.println(x + " ");  
        System.out.println();  
    }  
    static void vaTest(boolean a,boolean ...v){  
        for(boolean x: v)  
            System.out.println(x + " ");  
        System.out.println();  
    }  
    public static void main(String[] args) {  
        vaTest(1,2,3);  
        vaTest(true,false);  
        vaTest(true,false,false);  
    }  
}
```

PC-CS-305: Essentials of Information Technology

## 5 Golden Rules



1. Primitive Widening > Boxing > Varargs.
2. Widening and Boxing (WB) not allowed.
3. Boxing and Widening (BW) allowed.

<http://www.coderanch.com/t/417622/Programmer-Certification-SCJP/certification/Golden-Rules-widening-boxing-varargs>

PC-CS-305: Essentials of Information Technology

## 5 Golden Rules



4. While overloading, Widening + vararg **and** Boxing + vararg can only be used in a mutually exclusive manner i.e. not together.
5. Widening between wrapper classes not allowed

PC-CS-305: Essentials of Information Technology

## Examples



Overloaded methods	Invoked by saying	Called method
doX(Integer i) & doX(long l)	doX(5)	long (by Rule 1)
doX(int...i) & doX(Integer i)	doX(5)	Integer (by Rule 1)
doX(Long l) & doX(int...i)	doX(5)	int...i (Rule 2 & 1)
doX(Long l) & doX(Integer...i)	doX(5)	Integer...i (R. 2&1)
doX(Object o) & doX(Long l)	doX(5)	Object o (Rule 2&3)
doX(Object o) & doX(int...i)	doX(5)	Object o (Rule 3&1)
doX(Object o) & doX(long l)	doX(5)	long l (Rule 3&1)
doX(long...l) & doX(Integer...i)	doX(5)	ambiguous (Rule 4)
doX(long...l) & doX(Integer i)	doX(5)	Integer (Rule 1)
doX(Long l)	Integer i; doX(i)	error (Rule 5)
doX(Long l) & doX(long...l)	Integer i; doX(i)	long...l (Rule 5 & 1)

PC-CS-305: Essentials of Information Technology

## Collection API



- A *collection* — is simply an object that groups multiple elements into a single unit.
- They can dynamically grow and shrink, which is their advantage over arrays.

PC-CS-305: Essentials of Information Technology

## Collection Framework



All collection framework contain the following

### *Interface*

These are the abstract data types that represent collection.

### *Implementation*


These are the concrete implementation of collection interface

PC-CS-305: Essentials of Information Technology

## Interfaces



The core collection interfaces encapsulate different types of collections, These interfaces allow collections to be manipulated independently of the details of their representation.



A Set is a special kind of Collection.

A SortedSet is a special kind of Set.

PC-CS-305: Essentials of Information Technology

## Interfaces



The Java platform doesn't provide any direct implementations of Collection interface but provides implementations of more specific sub interfaces, such as Set and List.

***Set*** — a collection that cannot contain duplicate elements. This interface models the mathematical set abstraction and is used to represent Sets.

PC-CS-305: Essentials of Information Technology

## Interfaces



***List*** — an ordered collection (sometimes called a *sequence*). Lists can contain duplicate elements. The user of a List generally has precise control over where in the list each element is inserted and can access elements by their integer index (position).

***Queue*** — a collection used to hold multiple elements prior to processing. Besides basic Collection operations, a Queue provides additional insertion, extraction, and inspection operations.

PC-CS-305: Essentials of Information Technology



## Interfaces



***Map*** — an object that maps keys to values. A Map cannot contain duplicate keys: each key can map to at most one value; duplicate values are allowed.

***SortedSet*** — a Set that maintains its elements in ascending order. Sorted sets are used for naturally ordered sets.

PC-CS-305: Essentials of Information Technology

## Interfaces



***SortedMap*** — a Map that maintains its mappings in ascending key order.

PC-CS-305: Essentials of Information Technology

## Implementation




The classes that implement these interfaces are listed below:

<b><i>Set</i></b>	HashSet	LinkedHashSet	
<b><i>List</i></b>	Vector	ArrayList	LinkedList
<b><i>Map</i></b>	HashMap	HashTable	LinkedHashMap
<b><i>SortedSet</i></b>	TreeSet		
<b><i>SortedMap</i></b>	TreeMap		
<b><i>Queue</i></b>	LinkedList	PriorityQueue	


PC-CS-305: Essentials of Information Technology

## Implementation



PC-CS-305: Essentials of Information Technology

## Implementation



PC-CS-305: Essentials of Information Technology

## Array List



- The ArrayList class extends AbstractList and implements the List interface.
- ArrayList supports dynamic arrays that can grow as needed.
- An ArrayList is a variable-length array of object references.

PC-CS-305: Essentials of Information Technology

## Array List



- Since this implementation use an array to store the elements of the list, so access to an element using an index is very fast, but insertion and deletion are not.
- Example ArrayListDemo.java

PC-CS-305: Essentials of Information Technology

## Linked List



- The LinkedList class extends AbstractSequentialList and implements the List interface.
- This implementation is not synchronized ,if multiple threads access a list concurrently, and at least one of the threads modifies the list structurally, it must be synchronized externally.

PC-CS-305: Essentials of Information Technology

## Linked List



- LinkedList is implemented using doubly linked list so access to an element requires the list to be traversed using the links.
- This implementation of List interface produce the slowest access to an element in the middle of list by means of an index.

PC-CS-305: Essentials of Information Technology

## Linked List



- This implementation of the List interface provides for the fastest insertion of a new element into the middle of the list.
- The LinkedList is implemented using a doubly linked list; an insertion requires only the updating of the links at the point of insertion. Therefore, the LinkedList allows for fast insertions and deletions.

PC-CS-305: Essentials of Information Technology

## Linked List



- The LinkedList class provides methods such as addFirst, addLast, getFirst, getLast, removeFirst and removeLast that facilitate the implementation of stacks and queues.
- *Example* LinkedListDemo.java

PC-CS-305: Essentials of Information Technology

## Vector



```
public class Vector extends AbstractList  
                        implements List.
```

Vector is synchronized.

PC-CS-305: Essentials of Information Technology

## Vector Constructors



### ***Vector( )***

The first form creates a default vector, which has an initial size of 10.

### ***Vector(int initialCapacity)***

Constructs an empty vector with the specified initial capacity and with its capacity increment equal to zero.

PC-CS-305: Essentials of Information Technology

## Vector



### ***Vector(int initialCapacity, int capacityIncrement)***

Constructs an empty vector with the specified initial capacity and capacity increment.

PC-CS-305: Essentials of Information Technology

## Vectors



Vector use an array to store the elements of the list; so access to any element using an index is very fast.

**Example** VectorDemo.java

## Hash Set



HashSet extends AbstractSet and implements the Set interface.

Each element must be unique.

Duplicate elements must not replace old elements.



## Hash Set



- Hash set does not guarantee the order of its elements, because the process of hashing doesn't usually lend itself to the creation of sorted sets.
- This class permit the null elements.

PC-CS-305: Essentials of Information Technology

## Hash Set



- Accessing an element is fast as compared to TreeSet.
- This implementation is not synchronized.
- Example HashSetDemo.java

PC-CS-305: Essentials of Information Technology

## Linked Hash Set



- `LinkedHashSet` implements `Set` and extends `HashSet`.
- Maintains a linked list of the entries in the set, in the order in which they were inserted.
- In other words it allow elements to be accessed in the order that they were added.

PC-CS-305: Essentials of Information Technology

## Linked Hash Set



- When cycling through a `LinkedHashSet` using an iterator, the elements will be returned in the order in which they were inserted.
- This implementation is not synchronized.
- *Example* `LinkedHashSetDemo.java`

PC-CS-305: Essentials of Information Technology

## Tree Set



- Duplicate elements are not accepted.
- TreeSet provides an implementation of the SortedSet interface that uses a tree for storage.
- This class guarantees that the sorted set will be in ascending element order.

PC-CS-305: Essentials of Information Technology

## Tree Set



- This implementation provides guaranteed  $\log(n)$  time cost for the basic operations .
- Access and retrieval times are quite fast, which makes TreeSet an excellent choice when storing large amounts of sorted information that must be found quickly.
- This implementation is not synchronized.

PC-CS-305: Essentials of Information Technology

## Tree Set



- The entries can be sorted using the Comparable interface.
- The elements are ordered using their natural ordering or by a Comparator provided at set creation time, depending on which constructor is used.
- Example TreeSetDemo.java

PC-CS-305: Essentials of Information Technology

## HashMap



HashMap implements Map and extends AbstractMap.

A hash map does not guarantee the order of its elements, therefore, the order in which elements are added to a hash map is not necessarily the order in which they are read by an iterator.

The HashMap class is roughly equivalent to Hashtable, except that it is unsynchronized and permits nulls.

PC-CS-305: Essentials of Information Technology

## Hash Map



- HashMap lets you have null values as well as one null key

Example HashMapDemo.java

PC-CS-305: Essentials of Information Technology

## Tree Map



TreeMap implements SortedMap and extends  
AbstractMap.

- A TreeMap provides an efficient means of storing key/value pairs in sorted order.
- Entries are sorted using Comparator or the Comparable interface.

PC-CS-305: Essentials of Information Technology

## Tree Map



- This implementation is not synchronized.
- Duplicate entries replace old entries.

Example TreeMapDemo.java

PC-CS-305: Essentials of Information Technology

## Hash Table



- Like HashMap, Hashtable stores key/value pairs in a hash table.
- When using a Hashtable, you specify an object that is used as a key, and the value that you want linked to that key. The key is then hashed, and the resulting hash code is used as the index at which the value is stored within the table.

PC-CS-305: Essentials of Information Technology

## Hash Table



- A hash table can only store objects that override the `hashCode( )` and `equals( )` methods that are defined by `Object`.
- The `hashCode( )` method must compute and return the hash code for the object.
- `Hashtable` is synchronized

PC-CS-305: Essentials of Information Technology

## Hash Table



- `Hashtable` doesn't let you have anything that's null.
- As of the Java 2 platform v1.2, this class has been retrofitted to implement `Map`, so that it becomes a part of Java's collection framework.
- Example `HTDemo.java`

PC-CS-305: Essentials of Information Technology

## LinkedHashMap



- LinkedHashMap implements Map and extends HashMap.
- This implementation differs from HashMap in that it maintains a doubly-linked list running through all of its entries.

PC-CS-305: Essentials of Information Technology

## Priority Queue



- This class is new with Java 5.
- This class implements the Queue interface.
- Since the LinkedList class has been enhanced to implement the Queue interface, basic queues can be handled with a LinkedList.

PC-CS-305: Essentials of Information Technology



## Priority Queue



- PriorityQueue create a "priority-in, priority out" queue as opposed to a typical FIFO queue.
- A PriorityQueue's elements are ordered either by natural ordering (in which case the elements that are sorted first will be accessed first) or according to a Comparator.

PC-CS-305: Essentials of Information Technology

## Priority Queue



- In either case, the elements' ordering represents their relative priority.
- Queues have a few methods not found in other collection interfaces:  
peek(), poll(), and offer().

PC-CS-305: Essentials of Information Technology

## Summary



Class	Map	Set	List	Ordered	Sorted
HashMap	x			No	No
HashTable	x			No	No
TreeMap	x			Sorted	By <i>natural order</i> or custom comparison rules
LinkedHashMap	x			By insertion order or last access order	No
HashSet		x		No	No
TreeSet		x		Sorted	By <i>natural order</i> or custom comparison rules
LinkedHashSet		x		By insertion order	No
ArrayList			x	By index	No
Vector			x	By index	No
LinkedList			x	By index	No
PriorityQueue				Sorted	By to-do order

PC-CS-

## Summary



Key Interface Methods	List	Set	Map	Descriptions
boolean <b>add</b> (element) boolean <b>add</b> (index, element)	X X	X		Add an element. For Lists, optionally add the element at an index point.
boolean <b>contains</b> (object) boolean <b>containsKey</b> (object key) boolean <b>containsValue</b> (object value)	X	X	X X	Search a collection for an object (or, optionally for Maps a key), return the result as a boolean.
object <b>get</b> (index) object <b>get</b> (key)	X		X	Get an object from a collection, via an index or a key.
int <b>indexOf</b> (object)	X			Get the location of an object in a List.
Iterator <b>iterator</b> ()	X	X		Get an Iterator for a List or a Set.
Set <b>keySet</b> ()			X	Return a Set containing a Map's keys.
<b>put</b> (key, value)			X	Add a key/value pair to a Map.
<b>remove</b> (index) <b>remove</b> (object) <b>remove</b> (key)	X X	X	X	Remove an element via an index, or via the element's value, or via a key.
int <b>size</b> ()	X	X	X	Return the number of elements in a collection.
Object[] <b>toArray</b> () T[] <b>toArray</b> (T[])	X	X		Return an array containing the elements of the collection.

PC-CS-305: Essentials of Information Technology

## Sorting Collections



Sorting and searching topics have been added to the exam for Java 5.

### *Sorting Collections*

ArrayList doesn't give you any way to sort its contents, but the java.util.Collections class does:

PC-CS-305: Essentials of Information Technology

## Example



```
import java.util.*;
class TestSort1 {
    public static void main(String[] args) {
        ArrayList<String> stuff = new ArrayList<String>(); // #1
        stuff.add("Denver");
        stuff.add("Boulder");
        stuff.add("Vail");
        stuff.add("Aspen");
        stuff.add("Telluride");
        System.out.println("unsorted " + stuff);
        Collections.sort(stuff); // #2
        System.out.println("sorted " + stuff);}}}
```

PC-CS-305: Essentials of Information Technology

## Defining Ordering



- Suppose a collection has objects that you want to sort in a certain order, but either the class of the objects does not implement the Comparable interface or the order in which you want to sort the objects is other than the natural order.
- In that case use comparator, an object of a class that implements the Comparator interface.

PC-CS-305: Essentials of Information Technology

## Using Comparator



- Like the Comparable interface, the Comparator interface consists of a single method:

`int compare(T o1, T o2)`

*Example* OrderingTest.java

PC-CS-305: Essentials of Information Technology

## Generics



- Generics means parameterized types.
- Parameterized types are important as they enable to create classes, interfaces, and methods in which the type of data upon which they operate is specified as parameter.
- Using Generics its possible to create a single class that automatically works with different types of data.

PC-CS-305: Essentials of Information Technology

## Generics



- The class, interface or methods that operate on a parameterized type is called generic.
- **Example** Gen, GenDemo

PC-CS-305: Essentials of Information Technology

## Generics



Generics eliminate the process to explicitly cast to translate between Object and type of data being operated upon.

### *Generics work only with Objects*

When declaring an instance of generic type, the type argument passed to the type parameter must be a class type.

```
Gen<int> strOb=new Gen<int>(53);  
// Error cannot use primitive.
```

PC-CS-305: Essentials of Information Technology

## Generics



### *Generic Types differ based on their Arguments*

Reference of one specific version of generic type is not type compatible with another version of same generic type.

```
iOb=strOb; //wrong  
Even though iOb and strOb are of type Gen<T>
```

PC-CS-305: Essentials of Information Technology

## Generics



*Generic class can also be declared with more than one type parameter*

Example TwoGen , SimpGen

PC-CS-305: Essentials of Information Technology

## Polymorphism & Generics



Polymorphism applies to the "base" type of the collection:

```
List<Integer> myList = new ArrayList<Integer>();
```

But what about this?

```
List<Parent> myList = new ArrayList<Child>();
```

```
List<Number> numbers = new ArrayList<Integer>();
```

Is this possible?

PC-CS-305: Essentials of Information Technology

## Polymorphism & Generics



- No, here—the type of the variable declaration must match the type you pass to the actual object type.
- If you declare `List<Foo> foo` then whatever you assign to the `foo` reference **MUST** be of the generic type `<Foo>`, Not a subtype of `<Foo>`, Not a supertype of `<Foo>`, Just `<Foo>`.

PC-CS-305: Essentials of Information Technology

## Polymorphism & Generics



`List myList = new ArrayList();` // old-style, non-generic is almost identical to

`List<Object> myList = new ArrayList<Object>();`  
// holds ANY object type

Declaring a List with a type parameter of `<Object>` makes a collection that works in almost the same way as the original pre-Java 5

PC-CS-305: Essentials of Information Technology



## Summary of Main Teaching Points



PC-CS-305: Essentials of Information Technology

## Question and Answer Session



# Q & A

PC-CS-305: Essentials of Information Technology