

## DBMS LAB5

Anmol Keswani\_ECS\_D6-68

**Aim:** To Implement of Data Insertion, View Creation, and Multi-Table Join Operations in SQL

**Q1. Insert new player Michale Clark with player ID 300311 in the table player.**

```
MySQL localhost:3306 ssl surabhi09_match SQL > INSERT INTO Player (PLAYERID, FNAME, LNAME)
-> VALUES (300311, 'Michale', 'Clark');
Query OK, 1 row affected (0.0564 sec)
```

**Q2. Insert new player Sam from India , Ahemdabad with player ID 406317 in the table player.**

```
MySQL localhost:3306 ssl mahek01 SQL > INSERT INTO Player (PLAYERID, FNAME, COUNTRY, BPLACE)
-> VALUES(406317, 'Sam', 'INDIA', 'Ahmedabad');
Query OK, 1 row affected (0.0048 sec)
```

**Q3. Creating View for Batsman.**

CREATE VIEW Batsman (PID,FName,LName,Country,MID,Score)

AS SELECT PlayerID,FName,LName,Country,MatchID,NRuns

FROM Player,Batting

WHERE PlayerID=PID;

```
MySQL localhost:3306 ssl mahek01 SQL > CREATE VIEW Batsman (PID,FName,LName,Country,MID,Score)
-> AS SELECT PlayerID,FName,LName,Country,MatchID,NRuns
-> FROM Player,Batting
-> WHERE PlayerID=PID;
Query OK, 0 rows affected (0.0143 sec)
```

select \* from Batsman;

```
MySQL localhost:3306 ssl mahek01 SQL > select * from Batsman;
```

| PID   | FName     | LName       | Country   | MID  | Score |
|-------|-----------|-------------|-----------|------|-------|
| 23001 | Yuvraj    | Singh       | India     | 2755 | 0     |
| 25001 | MS        | Dhoni       | India     | 2755 | 71    |
| 91001 | Sanath    | Jayasuriya  | Sri Lanka | 2755 | 60    |
| 94002 | Chaminda  | Vaas        | Sri Lanka | 2755 | 17    |
| 92002 | Muthiah   | Murlitharan | Sri Lanka | 2755 | 1     |
| 89001 | Sachin    | Tendulkar   | India     | 2689 | 91    |
| 23001 | Yuvraj    | Singh       | India     | 2689 | 38    |
| 25001 | MS        | Dhoni       | India     | 2689 | 36    |
| 99002 | Adam      | Gilchrist   | Australia | 2689 | 2     |
| 95001 | Ricky     | Ponting     | Australia | 2689 | 1     |
| 24001 | Andrew    | Symonds     | Australia | 2689 | 42    |
| 99001 | Breet     | Lee         | Australia | 2689 | 7     |
| 27001 | Praveen   | Kumar       | India     | 2689 | 7     |
| 27001 | Praveen   | Kumar       | India     | 2755 | 2     |
| 98002 | Harbhajan | Singh       | India     | 2689 | 3     |
| 98002 | Harbhajan | Singh       | India     | 2755 | 2     |

16 rows in set (0.0021 sec)

#### Q4. Creating View for Bowling.

```
CREATE VIEW Bowling2689 (PID,FName,LName,Country,NOvers,NWickets)
AS SELECT PlayerID,FName,LName,Country,NOvers,NWickets
FROM Player,Bowling
WHERE PlayerID=PID
AND MatchID=2689;
```

```
MySQL localhost:3306 ssl mahek01 SQL > CREATE VIEW Bowling2689 (PID,FName,LName,Country,NOvers,NWickets)
-> AS SELECT PlayerID,FName,LName,Country,NOvers,NWickets
-> FROM Player,Bowling
-> WHERE PlayerID=PID
-> AND MatchID=2689;
Query OK, 0 rows affected (0.0043 sec)
```

select \* from Bowling2689;

```
MySQL localhost:3306 ssl mahek01 SQL > select * from Bowling2689;
+-----+-----+-----+-----+-----+-----+
| PID   | FName | LName | Country | NOvers | NWickets |
+-----+-----+-----+-----+-----+-----+
| 99001 | Breet | Lee   | Australia | 10    | 1        |
| 24001 | Andrew | Symonds | Australia | 3      | 1        |
| 23001 | Yuvraj | Singh | India    | 3      | 0        |
| 98002 | Harbhajan | Singh | India    | 10     | 1        |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.0013 sec)
```

#### Q5. Find name of all players who have scored 60 or more runs.

```
MySQL localhost:3306 ssl surabhi09_match SQL > SELECT DISTINCT p.FNAME
-> FROM Player p
-> JOIN Batting b ON p.PLAYERID = b.PID
-> WHERE b.NRuns >= 60;
+-----+
| FNAME |
+-----+
| MS    |
| Sanath |
| Sachin |
+-----+
3 rows in set (0.0007 sec)
```

#### Q6. Find the names of bowlers that have not taken any wickets in ODI match 2689 .

```
MySQL localhost:3306 ssl mahek01 SQL > SELECT DISTINCT p.FNAME
-> FROM PLAYER p
-> JOIN Bowling b ON p.PLAYERID = b.PID
-> WHERE b.MATCHID = 2689
-> AND b.NWickets = 0;
+-----+
| FNAME |
+-----+
| Yuvraj |
+-----+
1 row in set (0.0009 sec)
```

**Q7. Define a view NPlayer for obtaining the names of the countries & number of players from each country.**

```
MySQL localhost:3306 ssl mahek01 SQL > CREATE VIEW NPlayer AS
-> SELECT COUNTRY , COUNT(*) AS NUMBERofplayer
-> FROM Player
-> GROUP BY COUNTRY;
Query OK, 0 rows affected (0.0060 sec)
```

SELECT \* FROM NPlayer ;

```
MySQL localhost:3306 ssl mahek01 SQL > SELECT * FROM NPlayer;
+-----+-----+
| COUNTRY | NUMBERofplayer |
+-----+-----+
| India   | 10              |
| Australia | 5              |
| West Indies | 1              |
| Sri Lanka | 3              |
| Pakistan | 2              |
| Zimbabwe | 1              |
| South Africa | 4              |
| New Zealand | 2              |
| England | 1              |
+-----+-----+
9 rows in set (0.0012 sec)
```